

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
AND SUBDIVISION OF SECTIONS 20 AND 35,  
**TOWNSHIP 32 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***Stephan L. Barott, Cadastral Surveyor,  
(Forest Service, U.S. Department of Agriculture)***

Under Special Instructions dated, August 6, 2001, approved August 7, 2001,  
which provided for the surveys included under Group No. 1995,  
and Assignment Instructions dated March 21, 2002

***Survey commenced April 17, 2002***

***Survey completed November 9, 2002***

## T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and subdivision of sections 20 and 35, township 32 south, range 7 west, Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1881, W. H. Byars, U.S. Deputy Surveyor, surveyed the south boundary (Seventh Standard Parallel South) and the subdivisional lines of the township.</p> <p>In 1969-70, John M. Jelley, Rollin D. Aanrud, and Lynn M. Roseberry, Cadastral Surveyors, resurveyed a portion of the south boundary (Seventh Standard Parallel South) of the township.</p> <p>In 1975, Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, resurveyed a portion of the south boundary (Seventh Standard Parallel South) of the township.</p> <p>In 1978, Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, resurveyed a portion of the subdivisional lines of the township, and remonumented certain original corner points.</p> <p>In 1990, Terrence O. Nickerson, Cadastral Surveyor, and Gordon L. Caster, Surveying Technician, resurveyed a portion of the subdivisional lines of the township.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated August 6, 2001, for Group No. 1995, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.</p>
------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET

The geographic position (NAD 1927) of the cor. of secs. 26, 27, 34, and 35, T. 32 S., R. 7 W., as determined from a direct tie to Bureau of Land Management Geodetic Control Station No. EC 71084 established in 1988, and shown on the official plat of survey accepted April 28, 1993, is as follows:

Latitude: 42° 45' 14.78" N.      Longitude: 123° 30' 18.56" W.

The geographic position (NAD 1927) of the cor. of secs. 16, 17, 20, and 21, T. 32 S., R. 7 W., as determined from a tie to Oregon Department of Transportation Control Station "AZAL" is as follows:

Latitude: 42° 46' 57.70" N.      Longitude: 123° 32' 35.58" W.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon**

---

(Restoring the 1881 survey by W. H. Byars, the 1978 resurvey by Lynn M. Roseberry and Rollin D. Aanrud, the 1969-70 resurvey by John M. Jelley, Rollin D. Aanrud, and Lynn Roseberry and the 1990 resurvey by Terrence O. Nickerson and Gordon L. Caster)

From the ¼ sec. cor. of secs. 35 and 36, reestablished at proportionate measurement by Ronald A. Brandt, Registered Land Surveyor No. 841, recorded survey No. M83-29 and C.S. file 58/125N in 1980. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, from which the remains of bearing trees mkd. by Brandt

A madrone stump, 18 ins. diam., bears East, 0.1 ft. dist. to face, with scribe marks 1/4 PS841 BT visible on an open blaze.

A fir stump, 18 ins. diam., bears S. 36¼° W., 18.0 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by person(s) unknown, reported by Brandt

A fir stump, 19 ins. diam., bears S. 85½° E., 35.2 ft. dist., with no marks visible.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET

A fir stump, 17 ins. diam., bears S. 82° E.,  
33.6 ft. dist., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins.  
in the ground, directly over the iron pipe, with brass cap mkd.

T 32 S R 7 W  
1/4  
S 35 | S 36

2002

from which new bearing trees

A fir, 9 ins. diam., bears N. 20½° E., 30.2 ft. dist.,  
mkd. 1/4 S36 BT.

A fir, 9 ins. diam., bears N. 80¼° W., 16.7 ft. dist.,  
mkd. 1/4 S35 BT.

Deposit a magnet, in a white plastic case, at the base of the  
stainless steel post.

From this point, an unrecorded iron pipe, 1 in. diam., firmly  
set, projecting 4 ins. above ground, bears S. 89¼° W.,  
2.9 ft. dist.

From this same point, the standard cor. of secs. 35 and 36, on  
the S. bdy. of the Tp., bears S. 0° 20' 00" E.,  
2547.81 ft. dist.; monumented with an iron post, 2½ in. diam,  
firmly set, projecting 2 ins. above the ground, with brass cap  
mkd.

SC  
T 32 S R 7 W  
S 35 | S 36

1969

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 36½° E.,  
10.4 ft. dist., with no scribe marks visible. (Record,  
N. 30° E., 9.2 ft.)

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEEET	<p>A decayed fir stump, 26 ins. diam., bears S. 10° E., 13.4 ft. dist., with no scribe marks visible. (Record, 12.5 ft.)</p> <p>and bearing trees mkd. by Larson, reported by Roseberry and Aanrud</p> <p>A fir, 25 ins. diam., bears N. 28° E., 15.2 ft. dist., with a healed blaze. (Record, N. 32° E.)</p> <p>A live oak, 20 ins. diam., bears S. 1° E., 32.0 ft. dist., with a healed blaze.</p> <p>A fir, 26 ins. diam., bears N. 33° W., 17.8 ft. dist., with a healed blaze.</p> <p>N. 0° 20' 30" W., bet. secs. 35 and 36.</p> <p>Ascend moderate SW. slope, through logging slash and moderate undergrowth.</p> <p>1273.83 Point for the N 1/16 sec. cor. of secs. 35 and 36, no permanent monument set.</p> <p>2547.66 The cor. of secs. 25, 26, 35, and 36, perpetuated by the Douglas County Surveyor's Office in 1968, and recorded in C.S. file 54/36; monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">County Surveyors Office</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T 32 S</td> <td style="padding: 2px 10px;">R 7 W</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S 26</td> <td style="padding: 2px 10px;">S 25</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S 35</td> <td style="padding: 2px 10px;">S 36</td> </tr> </table> <p style="text-align: center;">1968</p> <p>from which the remaining original bearing trees</p> <p>A pine, 23 ins. diam., bears N. 45° E., 33.0 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 44 ins. diam., bears N. 14½° W., 13.2 ft. dist., with no scribe marks visible. (Record, N. 20° W., 11.2 ft. dist.)</p>	T 32 S	R 7 W	S 26	S 25	S 35	S 36
T 32 S	R 7 W						
S 26	S 25						
S 35	S 36						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

F E E T	<p>and the remains of bearing trees mkd. by the County Surveyor's Office</p> <p style="padding-left: 40px;">A fir stump, 18 ins. diam., bears S. 50° E., 52.8 ft. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A dead madrone, 20 ins. diam., bears S. 33¼° W., 76.4 ft. dist., with a healed blaze.</p> <p>From this point, an iron pipe, reported by the County Surveyors Office, 1 in. diam., firmly set, projecting 6 ins. above ground, bears S. 15° W., 0.8 ft. dist.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 87° 18' 00" W., bet. secs. 26 and 35.</p> <p>Ascend moderate SE. slope, through scattered timber and dense undergrowth.</p> <p>420 Gravel road, 14 ft. wide, bears N. 30° E. and S. 30° W.</p> <p>1207.67 Point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 7 W</p> <p style="text-align: center;">E 1/16     <u>S 26</u></p> <p style="text-align: center;">                 S 35</p> <p style="text-align: center;">                 2002</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 54 ins. diam., bears S. 83¼° W., 12.6 ft. dist., mkd. E1/16 S35 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 3½° W., 18.6 ft. dist., mkd. E1/16 S26 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Ascend moderate SE. slope, through light timber and light undergrowth, marking and blazing the true line.</p> <p>1350 Ridge, bears N. 20° E. and S. 20° W.; descend steep SW. slope.</p> <p>1770 Cat road, 8 ft. wide, bears N. 30° E. and S. 30° W.; leave timber.</p> <p>2415.34 The ¼ sec. cor. of secs. 26 and 35, perpetuated by the Douglas County Surveyor's Office in 1968, and recorded in C.S. file 54/36; monumented with an iron post, 1½ in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">County Surveyors Office</p> <p style="text-align: center;">T 32 S R 7 W</p> <p style="text-align: center;">                 S 26</p>
---------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

F E E T	<p style="text-align: center;">1/4 ——— S 35 1968</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 8° W., 19.8 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 61½° E., 17.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 59° E., 25.6 ft. dist., with a healed blaze.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 89° 12' 00" W., beginning new measurement.</p> <p>Descend steep W. slope, through dense brush.</p> <p>300 Panther Creek, 3 ft. wide, course S.; ascend steep E. slope, through dense brush.</p> <p>810 Gravel road, 18 ft. wide, bears N. and S.</p> <p>1358.35 Point for the W 1/16 sec. cor. of secs. 26 and 35, no permanent monument set.</p> <p>Ascend broken S. slope along N. edge of timber.</p> <p>2716.70 The cor. of secs. 26, 27, 34, and 35, monumented with an aluminum post, 2½ ins. diam., firmly set, flush with the ground, with aluminum cap, oriented to the west, mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 32 S</td> <td style="padding: 0 5px;">R 7 W</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> </table> <p style="margin: 5px 0 0 0;">1983 RLS 1654</p> </div> <p>from which the remains of bearing trees mkd. by Ronald A. Quimby, Registered Land Surveyor No. 1654, in 1983, and reported by Nickerson and Caster</p> <p style="padding-left: 40px;">A live oak snag, 8 ft. tall, 6 ins. diam., bears N. 36½° E., 5.9 ft. dist., with scribe marks T32S R7W S26 BT visible on partially opened face. (Record, N. 34° E.)</p> <p style="padding-left: 40px;">A sawed madrone stump, 6 ft. tall, 10 ins. diam., bears S. 69½° E., 39.9 ft. dist., with scribe marks T32S R7W S35 BT visible on partially opened face. (Record, S. 70° E.)</p>	T 32 S	R 7 W	S 27	S 26	S 34	S 35
T 32 S	R 7 W						
S 27	S 26						
S 34	S 35						

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p style="margin-left: 40px;">A fir stump, 31 ins. diam., bears S. 81¼° W., 85.4 ft. dist., with a partially healed blaze. (Record, S. 83° W., 84.8 ft. dist.)</p> <p style="margin-left: 40px;">A madrone, 10 ins. diam., bears N. 62° W., 37.9 ft. dist., with a healed blaze. (Record, N. 64° W., 38.3 ft. dist.)</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 37½° E., 115.0 ft. dist., mkd. T32S R7W S35 BT.</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 71084 bears N. 12° 44' 30" W., 112.31 ft. dist.; (mean bearing and sea level distance), monumented with an aluminum post, set flush with the ground in concrete, with an aluminum cap mkd. DEPT OF INTERIOR CONTROL SURVEY STATION EC 71084 1988 and a triangle.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p>
------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon**

FEET

T 32 S	R 7 W
S 20	S 21
S 29	S 28

1978

from which the remains of the original bearing trees

A madrone stump, 10 ins. diam., bears S. 10° E., 22.1 ft. dist., with no scribe marks visible. (Record 24.4 ft.)

A pine stump, size indeterminate, bears S. 25° W., 55.4 ft. dist., with fragmentary scribe marks visible on a detached face lying loose on the ground alongside.

and the remains of bearing trees mkd. by Price, reported by Roseberry and Aanrud

A pine snag, 27 ins. diam., bears N. 53° E., 62.0 ft. dist., with scribe marks RS 33 BT visible on partially opened blaze.

A madrone stump, 12 ins. diam., bears S. 74° E., 16.1 ft. dist., with no scribe marks visible. (Record, S. 66½° W.)

A pine stump, size indeterminate, bears N. 62° W., 66.7 ft. dist., with no scribe marks visible.

and the remains of bearing trees mkd. by the County Surveyors Office, reported by Roseberry and Aanrud

A root hole, bears S. 66½° W., 15.8 ft. dist.

A madrone, 10 ins. diam., bears N. 78° W., 7.9 ft. dist., with a healed blaze.

and bearing trees mkd. by Roseberry and Aanrud

A fir, 14 ins. diam., bears S. 8¼° E., 52.1 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 60½° W., 26.1 ft. dist., with fragmentary scribe marks visible on an opened blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	and bearing trees marked by person(s) unknown
	A fir, 11 ins. diam., bears N. 49½° E., 18.6 ft. dist., with scribe mark 7 visible on partially opened blaze and "Roseburg Lumber Co." BT tag.
	A fir, 16 ins. diam., bears S. 28½° E., 28.2 ft. dist., with a healed blaze and "Roseburg Lumber Co." BT tag.
	N. 0° 30' 30" E., bet. secs. 20 and 21.
	Ascend over moderate SW. slope, through scattered timber and moderate undergrowth, marking and blazing the true line.
800	Top of spur, slopes W., descend along NW. slope.
1150	Draw, drains W., ascend S. slope.
1320	Cat road, 8 ft. wide, bears N. 45° E. and S. 45° W.
1560	Top of spur, slopes NW.
1670	Dry draw, drains SW.
2330	Draw, drains S. 30° W., ascend over moderate SW. slope
2611.30	The ¼ sec. cor. of secs. 20 and 21, perpetuated by the Douglas County Surveyor's Office, recorded in C.S. file 54/36 in 1967; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd.
	County Surveyors Office
	T 32 S R 7 W
	S 20 <sup>1/4</sup> S 21
	1967
	from which the remains of an original bearing tree
	A sawed pine stump, 35 ins. diam., bears S. 79¼° W., 51.1 ft. dist., with illegible fragmentary scribe marks visible on decayed open face. (Record, S. 78° W., 51.5 ft.)
	and bearing trees mkd. by the County Surveyor's Office

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 18 ins. diam., bears S. 52½° E., 18.5 ft. dist., with a healed double blaze.</p> <p>A fir, 15 ins. diam., bears N. 81½° W., 12.8 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 15' 00" E., beginning new measurement.</p> <p>Over broken SW. slope, through moderate timber and moderate undergrowth, marking and blazing the true line.</p>
1297.83	<p>Point for the N 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 7 W N 1/16 S 20   S 21</p> <p>2002</p> </div> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 49½° E., 43.4 ft. dist., mkd. N1/16 S21 BT.</p> <p>A fir, 13 ins. diam., bears N. 42° W., 12.4 ft. dist., mkd. N1/16 S20 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Over broken SW. slope, through moderate timber and moderate undergrowth, discontinue marking and blazing.</p>
2595.66	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>County Surveyors Office</p> <p>T 32 S R 7 W S 17   S 16 ----- S 20   S 21</p> <p>1967</p> </div> <p>from which the original bearing trees</p> <p>A live oak, 7 ins. diam., bears N. 16½° E., 20.5 ft. dist., with no scribe marks visible on an open face.</p> <p>A pine, 29 ins. diam., bears S. 41° E., 37.0 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

F E E T	<p>A live oak, 5 ins. diam., bears S. 6° W., 12.5 ft. dist., with no scribe marks visible on a decayed open face.</p> <p>A pine, 24 ins. diam., bears N. 57° W., 21.8 ft. dist., with no scribe marks visible on a decayed open face.</p> <p>and bearing trees mkd. by the County Surveyor's Office, reported by Roseberry and Aanrud</p> <p>A fir, 27 ins. diam., bears N. 48° E., 25.7 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 1° W., 26.7 ft. dist., with a healed blaze.</p> <p>A fir, 35 ins. diam., bears N. 7° W., 36.0 ft. dist., with a healed blaze.</p> <p>From this point, Oregon Department of Transportation Control Station "AZAL" bears N. 85° 36' 00" E., 78,497.01 ft. dist. (mean bearing and sea level distance); monumented with an ORDOT Primary GPS brass disk, 4 ins. diam., firmly set in a concrete collar, 8 ins. diam., 1 in. below the surface of the ground, mkd. AZAL 1989 and a triangle.</p> <hr/> <p>From the ¼ sec. cor. of secs. 17 and 20, perpetuated by the Douglas County Surveyor's Office in 1967, and recorded in C.S. file 54/36; monumented with iron pipe, 1¼ ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">County Surveyors Office</p> <p style="text-align: center;">T 32 S R 7 W S 17 1/4 <u>        </u> S 20</p> <p style="text-align: center;">1967</p> <p>from which the remaining original bearing tree</p> <p>A fir, 29 ins. diam., bears N. 42° E., 12.9 ft. dist., with a healed double blaze; rescribed by the County Surveyor's Office in 1967. (Record, N. 45° E., 12.5 ft.)</p> <p>and a bearing tree mkd. by the County Surveyor's Office</p> <p>A fir, 13 ins. diam., bears S. 14° W., 22.2 ft. dist., with a healed double blaze.</p> <p>From this point, the cor. of secs. 16, 17, 20, and 21, bears S. 88° 18' 30" E., 2533.06 ft. dist., hereinbefore described.</p> <p>S. 89° 33' 30" W., bet. secs. 17 and 20.</p> <p>Ascend steep E. slope, through scattered timber and dense undergrowth, marking and blazing the true line.</p> <p>1240 Spur slopes SW.; descend moderate SW. slope along timber edge.</p>
---------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET											
2015	Dry draw, drains SW.; ascend gentle SE. slope.										
2716.35	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 32 S</td> <td>R 7 W</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1978</td> </tr> </table>	T 32 S	R 7 W	S 18	S 17			S 19	S 20	1978	
T 32 S	R 7 W										
S 18	S 17										
S 19	S 20										
1978											
	from which the remains of the original bearing trees										
	<p style="margin-left: 40px;">A root hole, bears S. 37° W., 59.4 ft. dist., with down and decayed fir alongside, size indeterminate, with no scribe marks visible.</p>										
	<p style="margin-left: 40px;">A fir, 46 ins. diam., bears N. 55° W., 86.8 ft. dist., with axe marks visible on burned bark blaze. (Record 89.1 ft.)</p>										
	and a bearing tree mkd. by person(s) unknown reported by Roseberry and Aanrud										
	<p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 14¼° E., 42.2 ft. dist., with a healed double blaze. (Record, N. 17° E., 38.3 ft.)</p>										
	and bearing trees mkd. by Roseberry and Aanrud										
	<p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 28½° E., 34.3 ft. dist., with a healed blaze. (Record N. 31½° E.)</p>										
	<p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 80¼° E., 45.5 ft. dist., with a healed blaze.</p>										
	<p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 50½° W., 33.0 ft. dist., with a healed blaze.</p>										
	<p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 38½° W., 15.2 ft. dist., with a healed blaze.</p>										
	<hr/> <p><b>Subdivision of Section 20, T. 32 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/>										
	From the ¼ sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, 24 ins. below ground in fill slope of BLM gravel road no. 32-7-20, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 32 S</td> <td>R 7 W</td> </tr> <tr> <td>1/4</td> <td>S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td></td> <td>S 29</td> </tr> <tr> <td colspan="2" style="text-align: center;">1978</td> </tr> </table>	T 32 S	R 7 W	1/4	S 20				S 29	1978	
T 32 S	R 7 W										
1/4	S 20										
	S 29										
1978											

Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>from which bearing trees mkd. by Roseberry and Aanrud</p> <p>A fir, 21 ins. diam., bears N. 36½° E., 28.4 ft. dist., with a healed blaze.</p>

Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A pine, 29 ins. diam., bears S. 9° E., 40.6 ft. dist., with a healed blaze.</p> <p>N. 1° 02' 30" E., on the N. and S. center line of sec. 20.</p> <p>Ascend through moderate brush.</p>
50	BLM gravel road No. 32-7-20, 20 ft. wide, bears N. 30° E. and S. 30° W.
185	Same road, 20 ft. wide, bears N. 30° W. and S. 30° E; descend over steep, broken N. slope.
1560	Douglas County Road No. 27 (Cow Creek Road), 30 ft. wide, bears NW. and SE.
1700	Left bank of Cow Creek, 55 ft. wide, course N. 40° W.
1755	Right bank of Cow Creek; ascend steep SW. slope through dense brush.
1920	Railroad tracks, bear N. 55° W. and S. 55° E.; ascend steep S. slope through light timber and moderate undergrowth.
2584.01	<p>Point for the center ¼ sec. cor. of sec. 20, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, cemented in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 7 W C 1/4 S 20</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">A white oak, 10 ins. diam., bears N. 18½° E., 38.9 ft. dist., mkd. C1/4 S20 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 76¼° E., 90.6 ft. dist., mkd. C1/4 S20 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
2615	Creek, 1 ft. wide, course S. 25° E.; ascend over nearly level land, through light brush.
3325	BLM gravel road No. 32-7-20.1, 12 ft. wide, bears NW. and SE.; enter heavy brush.
3903.95	<p>Point for the center N 1/16 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad   \quad \text{S } 20 \\ \text{C} \end{array}</math> <p>2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 26¼° E., 37.9 ft. dist., mkd. CN1/16 S20 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 88½° E., 4.4 ft. dist., mkd. X BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Descend moderate NW. slope, through light timber and moderate undergrowth, marking and blazing the true line.</p>
4085	Dry draw, drains SW.; ascend moderate SE. slope, through light timber and heavy undergrowth.
5223.89	<p>The ¼ sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the ¼ sec. cor. of secs. 20 and 21.</p> <p>N. 89° 19' 00" W., on the E. and W. center line of sec. 20.</p> <p>Descend over moderate SW. slope, through scattered timber and moderate undergrowth.</p>
1284.30	<p>Point for the center E 1/16 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p><u>E 1/16</u> C                      C S 20 2002</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 25¾° E., 29.9 ft. dist., mkd. CE1/16 S20 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 77¾° W., 36.3 ft. dist., mkd. CE1/16 S20 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Ascend over moderate SE. slope, through moderate timber and light undergrowth, marking and blazing the true line.</p>
1435	Spur, slopes S.; descend over moderate SE. slope.
1605	BLM gravel road no. 32-7-20.1, 12 ft. wide, bears NW. and SE.
1770	Creek, 2 ft. wide, course S. 10° W.; ascend along broken S. slope.
2550	Creek, 1 ft. wide, course S. 5° E.; ascend along broken S. slope.
2568.60	The center ¼ sec. cor. of sec. 20.  Ascend over gradual SE. slope, through scattered timber and light undergrowth.
3055	Spur slopes S.; descend over steep SW. slope.
3360	Creek, 2 ft. wide, course SE.; ascend over steep SE. slope.
4355	Spur, slopes SW.; descend over gradual SW. slope.
4515	Dry draw, drains SW.; ascend over gradual SE. slope.
4870	Spur, slopes SW.; descend over gradual SW. slope.
4980	Dry draw, drains SW.; ascend over gradual SE. slope.

Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
5149.33	<p>The ¼ sec. cor. of secs. 19 and 20, monumented with the remains of the original pine corner tree, rotted and broken off at ground level, perpetuated by Douglas. J. Theno, Registered Engineer No. 2968, recorded in C. S. file No. 41/289 in 1954, and further perpetuated by the Douglas County Surveyor's Office, recorded in C. S. file No. 60/17 in 1978, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed pine stump, 43 ins. diam., bears N. 33¼° E., 53.5 ft. dist., with no scribe marks visible. (Record N. 30° E., 49.5 ft.)</p> <p style="padding-left: 40px;">A root hole, bears S. 30° W., 5.3 ft. dist.</p> <p>and the remains of bearing trees mkd. by Theno</p> <p style="padding-left: 40px;">A madrone clump with decayed center, size indeterminate, bears S. 51½° E., 14.4 ft. dist., with no scribe marks visible.</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears N. 28° W., 20.5 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 41¼° E., 38.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 76° W., 18.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Remove the rotted remains of the corner tree and set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 7 W 1/4 S 19 S 20</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, a point established by Theno, perpetuated by the Douglas County Surveyor's Office in 1978, monumented with an iron pipe, 1 in. diam., firmly set, flush with the ground, with brass cap mkd. DOUGLAS COUNTY SURVEYOR W.C. 1/4 S19 S20 T32S R7W 1978 2.5 FT. TO COR, and an arrow pointing to the cor., bears N. 57° 28' 00" W., 2.5 ft. dist.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 20 and 21.</p> <p>N. 88° 49' 00" W., on the E. and W. center line of the NE¼ of sec. 20.</p>

Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEEET	Ascend over gradual SE. slope, through moderate timber and moderate undergrowth, marking and blazing the true line.						
295	Spur, slopes SW.; descend over SW. slope.						
1130	Dry creek bed, 2 ft. wide, drains SW.; over broken S. slope.						
2550.74	The center N 1/16 sec. cor. of sec. 20.						
	<hr/> <p>From the E 1/16 sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S 20</td> </tr> <tr> <td style="text-align: center;">E 1/16</td> <td style="text-align: center;">—————</td> </tr> <tr> <td></td> <td style="text-align: center;">S 29</td> </tr> </table> <p>1978</p> </div> <p>from which bearing trees mkd. by Roseberry and Aanrud</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 25° W., 19.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 33° W., 16.5 ft. dist., with a healed blaze.</p> <p>N. 0° 46' 30" E., on the N. and S. center line of the SE¼ of sec. 20.</p> <p>Descend steep, rocky slope, through scattered timber and dense undergrowth, marking and blazing the true line.</p>		S 20	E 1/16	—————		S 29
	S 20						
E 1/16	—————						
	S 29						
285	Bottom of steep, rocky slope.						
310	Left bank of Cow Creek, 55 ft. wide, course NW.						

**Subdivision of Section 20,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
420	Right bank of Cow Creek; ascend steep SW. slope through scattered timber and dense undergrowth.
670	Railroad tracks, bear NW. and SE.
935	Douglas County Road No. 27 (Cow Creek Road), 30 ft. wide, bears NW. and SE.
1080	Dry draw, drains S. 75° W.; ascend over SW. slope.
1200	Top of spur, slopes S. 70° W.; descend over NE. slope.
1410	Dry draw, drains S. 50° W.; ascend over SW. slope.
1770	BLM gravel road no. 32-7-20.1, 12 ft. wide, bears NW. and SE.; ascend through moderate timber.
2045	Top of spur, slopes S. 70° W.; descend over NW. slope.
2360	Dry draw, drains S. 70° W.; ascend over SW. slope.
2450	Dirt road, 12 ft. wide, bears N. 65° E. and S. 50° W.
2596.97	The center E 1/16 sec. cor. of sec. 20.
<hr/> <p><b>Subdivision of Section 35, T. 32 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/>	
<p>From the standard ¼ sec. cor. of sec. 35, on the S. bdy. of the Tp., perpetuated by James M. McIntosh, Registered Land Surveyor No. 2103, recorded survey No. M138-51 in 2001; monumented with an aluminum pipe, 1¼ ins. diam., firmly set, projecting 4 ins. above the ground, with an aluminum cap mkd.</p>	
<p>T 32 S R 7 W 1/4 S 35</p> <hr style="width: 20%; margin: auto;"/>	
<p>2001</p>	
<p>from which bearing trees mkd. by Roseberry and Aanrud</p>	
<p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 11° E., 78.9 ft. dist., with a healed blaze. (Record N. 10° E.)</p>	
<p style="padding-left: 40px;">A madrone, 20 ins. diam., bears N. 30½° W., 8.9 ft. dist., with scribe marks 35 SC BT visible on partially opened blaze.</p>	
<p>N. 1° 47' 30" E., on the N. and S. center line of sec. 35.</p>	
<p>Ascend over moderate SW. slope, through moderate timber and dense undergrowth.</p>	
1281.38	Point for the center S 1/16 sec. cor. of sec. 35.
<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">           C            S 1/16   S 35            C            2002         </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 1¼° E., 26.6 ft. dist., mkd. X BT.</p>
	<p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 57¼° W., 47.9 ft. dist., mkd. CS1/16 S35 BT.</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Continue ascent over moderate SE. slope, through scattered timber and moderate undergrowth, marking and blazing the true line.</p>
<p>2215</p>	<p>Ridge, bears N. 40° E. and S. 40° W.; descend along steep W. slope, through scattered timber and dense undergrowth.</p>
<p>2562.76</p>	<p>Point for the center ¼ sec. cor. of sec. 35, at intersection with the E. and W. centerline.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">           T 32 S R 7 W            C 1/4 S 35            2002         </p>

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>from which</p> <p>A fir, 7 ins. diam., bears N. 9½° E., 10.6 ft. dist., mkd. C1/4 S35 BT.</p> <p>A fir, 8 ins. diam., bears S. 5¼° E., 3.2 ft. dist., mkd. C1/4 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Continue descent along steep W. slope, through an old clearcut and dense brush.</p>
3863.96	<p>Point for the center N 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p> <math display="block">\begin{array}{c} C \\ N\ 1/16 \quad   \quad S\ 35 \\ C \end{array}</math> </p> <p>2002</p> </div> <p>from which</p> <p>A fir, 11 ins. diam., bears N. 34¾° E., 31.7 ft. dist., mkd. CN1/16 S35 BT.</p> <p>A fir, 7 ins. diam., bears S. 84° E., 38.4 ft. dist., mkd. X BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Corner falls in the cut bank of an old logging road, 15 ft. wide, bears N. 60° W. and S. 60° E.</p> <p>Continue descent along steep W. slope, through scattered timber and dense undergrowth.</p>
5165.16	<p>The ¼ sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the ¼ sec. cor. of secs. 35 and 36.</p> <p>N. 88° 37' 30" W., on the E. and W. center line of sec. 35.</p> <p>Descend over moderate SW. slope, through logging slash and dense brush.</p>
30	<p>BLM gravel road no. 32-7-36, 20 ft. wide, bears N. 60° W. and S. 60° E.</p>
1255.08	<p>Point for the center E 1/16 sec. cor. of sec. 35, no permanent monument set.</p>
1390	<p>Creek, 1 ft. wide, course S.; ascend over moderate SE. slope, through heavy timber and moderate undergrowth.</p>

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
2145	Ridge, bears S. 50° W.; descend along steep SW. slope.
2490	Cat road, 8 ft. wide, bears N. and S.
2510.16	The center ¼ sec. cor. of sec. 35.
	Continue descent along steep SW. slope, through moderate timber and moderate undergrowth, marking and blazing the true line.
2985	Dry draw, drains S. 65° W.
3170	Old logging road, 15 ft. wide, bears N. 30° E. and S. 30° W.
3370	Old logging road, 15 ft. wide, bears N. 20° W. and S. 20° E.
3580	Panther Creek, 3 ft. wide, course S. 25° W.; ascend moderate SE. slope, through moderate timber and dense undergrowth.
3650	Old logging road, 15 ft. wide, bears N. 20° E. and S. 20° W.
3835	Creek, 1 ft. wide, course S. 55° E.
3840.40	Point for the center W 1/16 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{C} \qquad \qquad \text{C} \\ \text{S } 35 \\ 2002 \end{array}</math> </div>
	from which
	<div style="text-align: center;"> <p>A fir, 6 ins. diam., bears S. 29½° E., 24.2 ft. dist., mkd. <span style="margin-left: 150px;">X</span> <span style="float: right;">BT.</span></p> </div>

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 9 ins. diam., bears S. 47½° W., 29.7 ft. dist., mkd. CW1/16 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Continue ascent over moderate SE. slope, through moderate timber and dense undergrowth, discontinue marking and blazing.</p>
4435	BLM gravel road no. 32-7-35, 18 ft. wide, bears N. 30° E. and S. 25° W.
5170.64	<p>The ¼ sec. cor. of secs. 34 and 35, monumented with an aluminum post, 2½ ins. diam., firmly set, 6 ins. below ground level, on the edge of an old cat road, with an aluminum cap mkd.</p> <p style="text-align: center;">T 32 S R 7 W</p> <p style="text-align: center;">1/4 S 34   S 35</p> <p style="text-align: center;">1983 RLS 1654</p> <p>from which a bearing tree mkd. by Quimby, reported by Nickerson and Caster</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 89° E., 19.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 10½° W., 67.4 ft. dist., mkd. 1/4 S34 BT.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 35.</p> <p>S. 87° 58' 30" E., on the calculated E. and W. center line of the NE¼ of sec. 35.</p> <p>Ascend steep SW. slope, through an old clearcut and dense brush field, marking and blazing the true line.</p>
850	Ridge, bears S. 30° W.; descend steep SE. slope.
1231.29	Point for the NE 1/16 sec. cor. of sec. 35, at its calculated position.

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 35</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 12° E., 94.8 ft. dist., mkd. NE1/16 S35 BT.</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears N. 81° W., 54.3 ft. dist., mkd. NE1/16 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>N. 0° 44' 00" E., on the calculated N. and S. center line of the NE¼ of sec. 35.</p> <p>Ascend steep SW. slope, through moderate timber and light undergrowth, marking and blazing the true line.</p>
1287.28	<p>The E 1/16 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 35.</p> <p>N. 88° 45' 30" W., on the E. and W. center line of the SW¼ of sec. 35.</p> <p>Ascend moderate SE. slope, through moderate timber and moderate undergrowth, marking and blazing the true line.</p>
370	<p>Spur, slopes S. 10° W.; descend steep, rocky SW. slope.</p>
950	<p>Panther Creek, 3 ft. wide, course S. 10° W.; ascend moderate SE. slope.</p>
1340	<p>BLM gravel road no. 32-7-34, 18 ft. wide, bears N. and S.</p>
1840	<p>Spur, slopes S. 45° W.; descend moderate SW. slope, through moderate timber and moderate undergrowth.</p>
2190	<p>Dry draw, drains S. 30° W.; ascend along moderate S. slope.</p>
2580	<p>Spur, slopes S. 44° W.; descend along moderate S. slope.</p>

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
2632.88	<p>The S 1/16 sec. cor. of secs. 34 and 35, monumented with an aluminum post, 2½ ins. diam., firmly set, 2 ins. below ground level, with an aluminum cap, all marks obliterated, from which bearing trees mkd. by Quimby, reported by Nickerson and Caster</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 59° E., 34.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 43° W., 21.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Remove the damaged aluminum post monument, and in its place set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 7 W</p> <p style="margin-left: 40px;">S 1/16</p> <p style="margin-left: 40px;">S 34   S 35</p> <p>2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and buried the aluminum post alongside.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 35.</p> <p>N. 1° 10' 30" E., on the calculated N. and S. center line of the NW¼ of sec. 35.</p> <p>Descend NE. slope, through logging slash and moderate brush, marking and blazing the true line.</p>
5	Creek, 1 ft. wide, course S. 55° E.; ascend S. slope.
310	Leave new clearcut; enter old clearcut.
1294.31	<p>Point for the NW 1/16 sec. cor. of sec. 35, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>NW 1/16 S 35</p> <p>2002</p> </div>

Subdivision of Section 35,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 12¼° W., 6.0 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 68¼° W., 16.4 ft. dist., mkd. NW1/16 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <hr/> <p>S. 88° 55' 00" E., on the calculated E. and W. center line of the NW¼ of sec. 35.</p> <p>Descend steep SE. slope, through moderate timber and dense undergrowth, marking and blazing the true line.</p>
155	Creek, 3 ft. wide, course S. 20° E.; ascend along moderate S. slope and leave timber.
430	Spur, slopes S. 35° W.; descend along moderate S. slope.
570	Dry draw, drains S. 25° E.; ascend moderate SW. slope.
640	Spur, slopes S. 10° W.; descend moderate SE. slope.
860	Panther Creek, 3 ft. wide, course S. 55° W.; ascend steep SW. slope.
1344.29	The center N 1/16 sec. cor. of sec. 35.
	<hr/> <p><b>GENERAL DESCRIPTION</b></p> <p>The lands included in this survey are located approximately six miles west of the town of Glendale, Oregon. Access is gained by way of the Douglas County Road No. 27 (Cow Creek Road) and BLM system roads. Elevations range from 1200 feet above sea level to 2500 feet above sea level.</p> <p>The soil in the area is composed of generally rocky clay. The area is drained by Panther Creek in section 35, which flows into Cow Creek, and by Cow Creek itself in section 20. Timber in the area consists of fir, pine, cedar, oak, and madrone, with undergrowth of ceanothus, manzanita, poison oak, and blackberries.</p>

## T. 32 S., R. 7 W., Willamette Meridian, Oregon

FEET

There were no mineral deposits or mining activity noted along the lines surveyed. The lands have been used primarily for timber production, and farming and ranching activities.

The mean magnetic declination, as shown on the United States Geological Survey 7½ minute quadrangle, RABBIT MOUNTAIN, OREGON, Provisional Edition, published in 1990, is 18° East.