

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF
CERTAIN CORNER POINTS
ON THE EAST BOUNDARY,

TOWNSHIP 25 SOUTH, RANGES 8 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 22, 2002,
approved February 22, 2002,
which provided for the rehabilitation included under Group No. 2000,
and Assignment Instructions dated June 18, 2003

Survey commenced June 18, 2003

Survey completed June 18, 2003

**Rehabilitation of Certain Corner Points on the East Boundary,
T. 25 S., R. 8 W., Willamette Meridian, Oregon**


FEET

This cor. is located in the SW. cor. of a clear-cut, with timber edges bearing North and East.

The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:

Latitude: 43° 25' 18.7" N.; Longitude: 123° 35' 07.1" W.

The witness cor. to the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



from which the remains of bearing trees mkd. by Beck and Jelley

A fir snag, 79 ins. diam., bears N. 61¼° E., 102.4 ft. dist., with a healed blaze. (Record, N. 61° E., 103.0 ft.)

A fir snag, 33 ins. diam., bears S. 46¼° W., 171.9 ft. dist., with no marks visible. (Record, S. 47° W., 172.3 ft.)

and new bearing trees

A fir, 16 ins. diam., bears N. 76¼° E., 84.6 ft. dist., mkd. X BT.

A fir, 25 ins. diam., bears N. 78¼° W., 154.7 ft. dist., mkd. X BT.

The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:

Latitude: 43° 25' 31.2" N.; Longitude: 123° 35' 07.2" W.
