

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF THE CENTER SOUTH
1/16 SECTION CORNER OF SECTION 9,
TOWNSHIP 29 SOUTH, RANGE 3 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 22, 2002,
approved February 22, 2002, which provided for the
rehabilitation included under Group No. 2000,
and Assignment Instructions dated April 23, 2003

Survey commenced April 23, 2003

Survey completed April 23, 2003

T. 29 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes describe the rehabilitation of the center south 1/16 section corner of section 9, township 29 south, range 3 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated February 22, 2002, under Group No. 2000.

The rehabilitation of the center south 1/16 section corner of section 9, was made at the request of the Roseburg District Manager, for the administrative purposes of the Bureau of Land Management.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The mean magnetic declination, as taken from U.S. Geological Survey quadrangle map, "WHITEROCK, OREG.", Provisional Edition, dated 1987, is 18½° East.

**Rehabilitation of the Center South 1/16
Section Corner of Section 9,
T. 29 S., R. 3 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by John M. Jelley
and Lynn M. Roseberry, Cadastral Surveyors, in 1966-67)

The center S 1/16 sec. cor. of sec. 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ \text{S } 1/16 \quad | \quad \text{S } 9 \\ \text{C} \\ 1966 \end{array}$$

from which a bearing tree mkd. by Jelley and Roseberry

A fir, 11 ins. diam., bears N. 22° E., 9.9 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 16 ins. diam., bears S. 42° E., 23.4 ft. dist., mkd. CS 1/16 S9 BT.

Corner is located 13.0 ft. East of Weaver Creek, 6 ft. wide, course S. 25° W.

Rehabilitation of the Center South 1/16
Section Corner of Section 9,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

FEET	<p>The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR Global Positioning System (GPS), utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:</p> <p>Latitude: 43° 03' 39.39" N.; Longitude: 123° 04' 09.71" W.</p> <hr/>
------	---