

T. 29 S., R. 8 W., Willamette Meridian, Oregon

F E E T

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES
AND
SUBDIVISION OF SECTION 29
TOWNSHIP 29 SOUTH, RANGE 8 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated August 23, 2004, approved August 24, 2004,
which provided for the surveys included under Group No. 2097,
and Assignment Instructions dated August 27, 2004

Survey commenced September 1, 2004

Survey completed September 30, 2004

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 29, township 29 south, range 8 west, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1855, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the subdivisional lines.</p> <p>In 1856, A.J. Burnett, U.S. Deputy Surveyor, surveyed Donation Land Claims.</p> <p>In 1965, Donald R. Beck, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 31.</p> <p>In 2001, A. Bert Skeesick, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 32.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the <u>Special Instructions</u> dated August 23, 2004, for Group No. 2097, Oregon.</p> <p>The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) static measurement techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO), version 1.61. The GPS portion of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys using Global Positioning System Methods" version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.</p> <p>An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement</p>
------	---

T. 29 S., R. 8 W., Willamette Meridian, Oregon

F E E T

Management (CMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS)) of the corner of sections 19, 20, 29, and 30, as determined from a tie to National Geodetic Survey stations "OBEC CONS COOP CORS ARP" and CAPE BLANCO CORS ARP", is as follows:

Latitude: 43° 01' 32.45" N. Longitude: 123° 40' 53.25" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Dennis Hathorn)

Beginning at the 1/4 sec. cor. of secs. 28 and 29, perpetuated by A.R. Evans, Oregon Registered Mining Engineer No. 2741, in 1953, and remonumented by the Douglas County Surveyor's Office in 1967, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 300240, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 29 S R 8 W

1/4 S29 | S28

1967

from which the remains of an original bearing tree

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>A decayed cedar stump, 23 ins. diam., bears N. 11° W., 8.6 ft. dist., with no marks visible. (Record, N. 5° W.)</p>
	<p>and the remains of bearing trees mkd. by Evans</p>
	<p>A fir, 20 ins. diam., bears N. 28¼° E., 8.2 ft. dist., with a healed blaze.</p>
	<p>A fallen hemlock, 8 ins. diam., bears N. 78½° W., 11.0 ft. dist., with no marks visible.</p>
	<p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p>
	<p>A fir, 15 ins. diam., bears S. 46½° W., 45.4 ft. dist., with a healed blaze.</p>
	<p>N. 0° 02' 15" W., bet. secs. 28 and 29.</p>
	<p>Descend broken NW. slope; begin posting and blazing.</p>
20	<p>Tom Taylor Creek, 1 ft. wide, course S. 85° W.; asc. broken SW. slope.</p>
140	<p>Dirt road, 8 ft. wide, bears East and West.</p>
475	<p>Spur, slopes N. 62° W.; thence over broken W. slope.</p>
1330.62	<p>Point for the N 1/16 sec. cor. of secs. 28 and 29, occupied by a steel fencepost, firmly set, projecting 24 ins. above ground, established without authority in 1976 by the Federal Highway Administration for the Bureau of Land Management. This monument is not accepted as the true cor. location and is removed.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T 29 S R 8 W N 1/16 S 29 S 28 2004 </p>
	<p>from which a bearing tree mkd. by the Federal Highway Administration</p>
	<p>A fir, 18 ins. diam., bears N. 87¼° W., 31.3 ft. dist., with a healed blaze. (Mag-nail driven at the base on right side center.)</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET					
	<p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 24¼° E., 22.4 ft. dist., mkd. N 1/16 S28 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Discontinue posting and blazing.</p>				
1450	<p>Seasonal creek, 2 ft. wide, course N. 72° W.; asc. broken SW. slope.</p>				
2661.24	<p>The cor. of secs. 20, 21, 28, and 29, perpetuated by the Douglas County Surveyor's Office in 1923, remonumented by the Douglas County Surveyor's Office in 1958, and rehabilitated by the Douglas County Surveyor's Office in 1997, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 300300, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS</p> <p>T 29 S R 8 W</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px 10px;">S20</td> <td style="padding: 2px 10px;">S21</td> </tr> <tr> <td style="padding: 2px 10px;">S29</td> <td style="padding: 2px 10px;">S28</td> </tr> </table> <p>OFFICE 1958</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 20° E., 34.9 ft. dist., with a healed blaze. (Record, N. 22° E., 33.0 ft.)</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 28½° E., 28.0 ft. dist., with no marks visible. (Record, S. 27° E., 31.7 ft.)</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1923</p> <p style="padding-left: 40px;">A roothole, bears S. 72° E., 46.2 ft. dist., with fallen chinquapin trunk, 30 ins. diam., lying alongside, no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 32 ins. diam., bears S. 49½° W., 41.9 ft. dist., with a healed blaze.</p>	S20	S21	S29	S28
S20	S21				
S29	S28				

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1958

A fir, 30 ins. diam., bears S. $19\frac{1}{4}^{\circ}$ E., 14.3 ft. dist., with a healed blaze.

A dead chinquapin, 18 ins. diam., bears S. $67\frac{1}{4}^{\circ}$ W., 12.0 ft. dist., with a healed double blaze.

A double trunk madrone, 26 ins. diam., bears N. 83° W., 28.8 ft. dist., with scribe marks T29S R8W visible in the bark of southerly trunk and decayed blaze on northerly trunk with no marks visible.

and a bearing tree mkd. by the Douglas County Surveyor's Office in 1997

A cedar, 11 ins. diam., bears S. $46\frac{1}{4}^{\circ}$ W., 38.5 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.

From the cor. of secs. 29, 30, 31, and 32, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 29 S	R 8 W
S30	S29
S31	S32
1965	

from which the remains of the original bearing trees

An oak, 21 ins. diam., bears S. $76\frac{1}{4}^{\circ}$ E., 68.6 ft. dist., with no scribe marks visible on partially healed blaze.

A sawed fir stump, 48 ins. diam., bears S. $8\frac{1}{4}^{\circ}$ W., 116.8 ft. dist., with a healed blaze.

and remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1923

A fir stump, 27 ins. diam., bears S. 46° E., 28.4 ft. dist., with no marks visible.

and a bearing tree mkd. by the Douglas County Surveyors Office in 1958

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 17 ins. diam., bears N. 57¼° E., 13.5 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by Beck</p> <p>A fir, 20 ins. diam., bears S. 4½° W., 93.0 ft. dist., with a healed blaze.</p> <p>A fir, 27 ins. diam., bears N. 65° W., 84.5 ft. dist., with a healed double blaze.</p> <p>N. 0° 04' 13" W., bet. secs. 29 and 30.</p> <p>Over level farmland.</p>
500	Buck Springs Road, chip sealed, 16 ft. wide, bears N. 22½° E. and S. 22½° W.
1325.12	Point for the S 1/16 sec. cor. of secs. 29 and 30. Not monumented.
2155	Creek, 6 ft. wide, course N. 76° W.
2650.24	Point for the 1/4 sec. cor. of secs. 29 and 30 at proportionate dist.; there is no remaining evidence of the original cor.
	Corner location falls in cultivated pasture; no monument was set at landowners' request.
3010	Creek, 4 ft. wide, course N. 52° W.
4655	State Highway No. 42, paved, 55 ft. wide, bears N. 39½° E. and S. 39½° W.
5300.48	<p>The cor. of secs. 19, 20, 29, and 30, perpetuated by the Douglas County Surveyor's Office, in 1923, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 200300, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 2 ins. above ground, from which the remains of an original bearing tree</p> <p>A sawed decayed stump, size and species indeterminate, bears N. 40½° E., 872.1 ft. dist., with no marks visible. (Record, N. 40° E., 877.1 ft.)</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>A pine, 45 ins. diam., bears N. 32° E., 538.3 ft. dist., with a healed blaze.</p> <p>A fir, 28 ins. diam., bears S. 36¾° E., 685.6 ft. dist., with a healed blaze.</p> <p>At the corner point in the center of the iron pipe</p> <p>Drive an aluminum rod, 36 ins. long, ¼ in. diam., 30 ins. in the ground (driving the iron pipe below ground surface), with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 29 S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="padding: 0 5px;">S 19</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 20</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 30</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 5px;">S 29</td> </tr> </table> <p>2004</p> </div> <p>Corner falls at intersection of fences extending East, South, and West.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 89° 36' 21" W., bet. secs. 20 and 29.</p> <p>Descend gentle W. slope, along unmaintained woven wire fence.</p> <p>1314.16 The E 1/16 sec. cor. of secs. 20 and 29, established by Eugene A. Bloom, Oregon Professional Land Surveyor No. 492, in 1984, recorded in the Douglas County Surveyors Office, Map File No. M98-14, and is accepted as the cor., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap mkd. AA SURVEYING SERVICE INC.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over the existing rebar, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 29 S</td> <td style="padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="padding: 0 5px;">E1/16</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 20</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 29</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">2004</td> </tr> </table> </div> <p>from which a bearing tree mkd. by the Federal Highway Administration as an accessory for the E 1/16 sec. cor. of</p>	T 29 S	R 8 W	S 19	S 20	S 30	S 29	T 29 S	R 8 W	E1/16	S 20		S 29		2004
T 29 S	R 8 W														
S 19	S 20														
S 30	S 29														
T 29 S	R 8 W														
E1/16	S 20														
	S 29														
	2004														

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>secs. 20 and 29, established without authority in 1976 for the Bureau of Land Management.</p> <p>A fir, 22 ins. diam., bears S. $9\frac{1}{4}^{\circ}$ W., 26.7 ft. dist., with a healed blaze. (Mag-nail driven at the base on right side center.)</p> <p>and a new bearing tree</p> <p>A fir, 8 ins. diam., bears N. $64\frac{3}{4}^{\circ}$ E., 26.3 ft. dist., mkd. E 1/16 S20 BT.</p> <p>Corner is located 0.8 ft. N. of woven wire fence extending East and West.</p> <hr/> <p>S. $89^{\circ} 36' 53''$ W., beginning new measurement</p> <p>Continue desc. gentle W. slope; begin posting and blazing.</p>
1314.12	<p>The 1/4 sec. cor. of secs. 20 and 29, reestablished by the Douglas County Surveyor's Office in 1923, at proportionate measurement, and perpetuated by the Douglas County Surveyor's Office in 1965. There is no remaining evidence of the original cor., therefore this point is accepted as the cor., monumented with a steel shaft, 1 in. diam., firmly set, projecting 2 ins. above ground, from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1923</p> <p>A decayed pine stump, size indeterminate, bears N. 63° E., 149.7 ft. dist., with no marks visible.</p> <p>A fir, 33 ins. diam., bears S. $76\frac{3}{4}^{\circ}$ E., 75.1 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office in 1965</p> <p>A fir, 26 ins. diam., bears N. 48° E., 14.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, over the existing steel shaft, with brass cap mkd.</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET

T 29 S R 8 W
 S 20
 1/4 —————
 S 29
 2004

Corner is located at the intersection of fences extending East, South, and West.

From this point, the cor. of secs. 19, 20, 29, and 30 bears S. 89° 42' 09" W., 2630.63 ft. dist., hereinbefore described.

No intermediate survey monuments on the W½ of the line bet. secs. 20 and 29 were searched for.

**Subdivision of Section 29,
 T. 29 S., R. 8 W., Willamette Meridian, Oregon**

From the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron pipe, 1 in. diam., firmly set, buried 3 ins. below the broken paved surface of Burma Road, with aluminum cap mkd.

T 29 S R 8 W
 S 29
 1/4 —————
 S 32
 2001

from which the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1939

A sawed fir stump, 32 ins. diam., bears N. 6¼° E., 55.9 ft. dist., with no marks visible.

A decayed madrone stump, size indeterminate, bears S. 38° E., 118.8 ft. dist., with no marks visible.

and bearing trees mkd. by the Douglas County Surveyors Office in 1958


A cedar, 21 ins. diam., bears N. 11¼° E., 52.9 ft. dist., with a healed double blaze.

A fir, 14 ins. diam., bears S. 66½° E., 56.9 ft. dist., with a healed double blaze.

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	and an accessory reported by Skeesick
	The NW. cor. of a frame house, 20 X 50 ft., bears
	S. ½° W., 164.3 ft. dist., long side bears South.
	N. 0° 02' 18" W., on the N. and S. centerline of sec. 29.
	Descend broken NW. slope.
740	Graveled road, 16 ft. wide, bears S. 69½° E. and N. 69½° W.
1310.15	Point for the center S 1/16 sec. cor. of sec. 29, occupied by a steel fencepost, firmly set, projecting 27 ins. above ground, established without authority in 1976 by the Federal Highway Administration for the Bureau of Land Management. This monument is not accepted as the true cor. location and is removed.
	Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 29 S R 8 W C S 1/16 S 29 C 2004</p>
	from which a bearing tree mkd. by the Federal Highway Administration
	A fir, 35 ins. diam., bears S. 11½° W., 24.7 ft. dist., with a healed blaze. (Mag-nail driven at the base on right side center.)
	and a new bearing tree
	A fir, 8 ins. diam., bears S. 82° E., 15.2 ft. dist., mkd. CS 1/16 S29 BT.
	Deposit a magnet, in a white plastic case, at the base of the iron post and drive the steel fencepost alongside. Corner is located 1.4 ft. S. of cor. of fence extending North.
	Continue desc. broken NW. slope, along woven wire fence; begin posting and blazing.
1895	Spring branch, 1 ft. wide, course N. 80° W.; asc. broken SW. slope.
2145	Spur, slopes N. 70° W.; desc. broken NW. slope.

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
2611.30	<p>Point selected for the witness cor. to the center 1/4 sec. cor. of sec. 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>WC T 29 S R 8 W C 1/4 S 29 2004</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 12° E., 58.8 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 87¼° E., 17.8 ft. dist., mkd. X BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p>
2620.30	<p>True point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. centerline, falls on cutbank of creek; impracticable to monument.</p> <p>Corner is located at the intersection of fences extending North, South, and N. 70° W.</p>
2625	Creek, 2 ft. wide, course S. 75° W.; asc. broken SW. slope.
2880	Spur, slopes N. 80° W.; desc. gentle NW. slope.
3947.04	Point for the center N 1/16 sec. cor. of sec. 29. Not monumented.
5273.78	<p>The 1/4 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>S. 89° 46' 22" W., on the E. and W. centerline of sec. 29.</p> <p>Descend broken W. slope.</p> <p>130 Graveled road, 16 ft. wide, bears S. 35¼° E. and N. 35¼° W.</p> <p>865 Graveled road, 16 ft. wide, bears N. 63½° E. and S. 63½° W.</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
1314.26	Point for the center E 1/16 sec. cor. of sec. 29. Not monumented.
2628.52	The center 1/4 sec. cor. of sec. 29.
3943.25	Point for the center W 1/16 sec. cor. of sec. 29. Not monumented. Point falls 1.6 ft. East of fences extending North and South, approximately 35 ft. North of the intersection of fences extending North, South, East, and West.
4495	Burma Road, paved, 22 ft. wide, bears North and South.
5257.98	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/> From the N 1/16 sec. cor. of secs. 28 and 29.
	S. 89° 41' 48" W., on the calculated E. and W. centerline of the NE¼ of sec. 29.
	Descend gentle W. slope; begin posting and blazing.
1240	Graveled road, 10 ft. wide, bears N. 40° E. and S. 40° W.
1314.21	Point for the NE 1/16 sec. cor. of sec. 29 at its calculated position.
	Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 29 S R 8 W NE 1/16 . S 29 2004</p>
	from which a bearing tree mkd. by the Federal Highway Administration in 1976
	<p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 54½° E., 14.3 ft. dist., with a healed blaze. (Mag-nail driven at the base on right side center.)</p>
	and a new bearing tree
	<p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 49° E., 35.9 ft. dist., mkd. NE 1/16 S29 BT.</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>From this point, a steel fencepost, firmly set, projecting 30 ins. above ground, bears N. 87° 29' 07" W., 8.53 ft. dist., established without authority in 1976 by the Federal Highway Administration for the Bureau of Land Management, and is not accepted as the true cor. location.</p> <hr/> <p>N. 0° 02' 18" W., on the calculated N. and S. centerline of the NE¼ of sec. 29.</p> <p>Descend broken N. slope; continue posting and blazing.</p> <p>265 Spring branch, 2 ft. wide, course N. 60° W.; continue over broken W. slope.</p>
1328.54	<p>The E 1/16 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 29 and 32 monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 8 W</p> <p>S 29</p> <hr style="width: 50px; margin: 0 auto;"/> <p>W1/16</p> <p>S 32</p> <p>2001</p> </div> <p>from which bearing trees mkd. by Skeesick</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 72½° E., 23.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 26½° E., 16.1 ft. dist., with scribe marks X BT visible on a partially healed blaze.</p> <p>N. 0° 04' 10" W., on the calculated N. and S. centerline of the SW¼ of sec. 29.</p> <p>Descend gentle NW. slope, along woven wire fence; begin posting and blazing.</p> <p>1246 Corner of fences extending South and N. 81½° W. bears West, 2.6 ft. dist.</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
1260	Burma Road, paved, 22 ft. wide, bears S. 66° E. and N. 72° W.
1296	Corner of fence extending North, bears West, 2.2 ft. dist.
1332.63	Point for the SW 1/16 sec. cor. of sec. 29 at its calculated position.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 29 S R 8 W SW 1/16 . S 29 2004</p>
	from which
	A fir, 17 ins. diam., bears S. 20° E., 140.7 ft. dist., mkd. SW 1/16 S29 BT.
	A fir, 13 ins. diam., bears S. 23¼° W., 107.0 ft. dist., mkd. SW 1/16 S29 BT.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Corner is located 2.3 ft. East of woven wire fence and 17.9 ft. South of SW. cor. of wood frame shed, 16 X 32 ft., long side bears N. 1¾° E.
	<hr/> N. 89° 26' 42" E., on the calculated E. and W. centerline of the SW¼ of sec. 29.
	Over level farmland; continue posting and blazing.
30.70	End of wood fence, extending S. 42° E., bears South, 31.1 ft. dist.
60.20	SW. corner of wood frame house, 24 X 38 ft., bears North, 1.1 ft. dist.; long side bears N. 0¾° W.
69.20	Intersect W. end of wood frame porch, 8 X 15 ft., at a point from which the SW. cor. of porch, bears S. 0¾° E., 6.5 ft. dist., long side bears N. 89¼° E.
84.20	Intersect E. end of same wood frame porch, at a point from which the SE. cor. of same porch, bears S. 0¾° E., 5.9 ft. dist., long

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	side bears S. 89¼° W., and SE. cor. of same wood frame house bears N. 0¼° W., 2.1 ft. dist.
146.70	Intersect woven wire fence at a point from which the cor. of fences, extending N. 2° E., East and West, bears S. 2° W., 41.0 ft. dist.
381.40	Intersect woven wire fence at a point from which the cor. of fences, extending N. 5½° E. and West, bears S. 5½° W., 46.4 ft. dist.
402.60	Intersect woven wire fence at a point from which the cor. of fence, extending North, bears South, 46.8 ft. dist.
421.70	Center of 250 gallon propane tank, bears South, 21.0 ft. dist.
453.90	Intersect W. side of wood frame house, 32 X 45 ft., at a point from which the SW. cor. of house, bears S. 7° E., 17.9 ft. dist., long side bears N. 83° E.
499.40	Intersect E. side of same wood frame house, at a point from which the SE. cor. of house, bears S. 7° E., 11.6 ft. dist., long side bears S. 83° W.
535.30	NE. cor. of wellhouse, 6 X 6½ ft., bears South, 19.8 ft. dist., long side bears S. 81½° W.
630	Thompson Creek, 2 ft. wide, course N. 60° W.; asc. broken NW. slope.
1314.15	The center S 1/16 sec. cor. of sec. 29.
	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in rolling hills and broad, flat creek bottoms, approx. 1.0 mile southerly from the community of Camas Valley, Oregon.</p> <p>The elevation ranges from approx. 1100 feet above sea level near the 1/4 sec. cor. of secs. 29 and 30 to approx. 1400 feet above sea level near the cor. of secs. 20, 21, 28, and 29.</p> <p>The area is drained by Thompson Creek and Tom Taylor Canyon, which flow westerly to Jim Belieu Creek and then southeasterly to join with the Middle Fork of the Coquille River.</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>The soil is generally composed of rocky clay.</p> <p>Access to the survey was made by graveled roads branching from Burma Road.</p> <p>The mean magnetic declination for the area surveyed is 18° East, as shown on the "CAMAS VALLEY, OREGON" 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1990.</p>
------	---