

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE SUBDIVISIONAL LINES  
AND SUBDIVISION OF SECTION 9,  
TOWNSHIP 24 SOUTH, RANGE 7 WEST,  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

Under Special Instructions dated January 13, 2003, approved  
January 13, 2003, which provided for the surveys included under  
Group No. 2037, and Assignment Instructions dated February 3, 2003

***Survey commenced February 3, 2003***

***Survey completed March 20, 2003***

## T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 9, township 24 south, range 7 west, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1857, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.</p> <p>In 1893-1894, Williams R. Whipple, U.S. Deputy Surveyor, retraced certain lines and completed the survey of the subdivisional lines.</p> <p>In 1963, C. Albert White, Cadastral Surveyor, and Donald R. Beck, Surveying Technician, resurveyed a portion of the subdivisional lines and subdivided section 5.</p> <p>In 1975-1976, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 17.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated January 13, 2003, for Group No. 2037, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.</p> <p>An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management for Windows, (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.</p>
------	--

## T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET

The geographic position (NAD 1983 (91)) of the 1/4 section corner of sections 9 and 16, as determined by a tie to National Geodetic Survey HARN stations "T 739" and "WELK", is as follows:  
Latitude: 43° 29' 26.86" N. Longitude: 123° 32' 05.95" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

(Restoring the 1857 survey by Dennis Hathorn,  
the 1893-94 survey by Williams R. Whipple, and  
the 1963 resurvey by C. Albert White and Donald R. Beck)

Beginning at the cor. of secs. 9, 10, 15, and 16, perpetuated by the Douglas County Surveyors Office in 1956, and further perpetuated by Bruce A. Shaner, Oregon Professional Land Surveyor No. 430, in 1996, recorded in the Douglas County Surveyors Office, Map File No. M125-20 and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 400500, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS  
T24S R7W  
SEC 9 | 10  
COR ———  
16 | 15  
1956  
OFFICE

from which the remains of an original bearing tree

A roothole bears S. 55° E., 24.4 ft. dist., with fallen fir trunk, 56 ins. diam., lying alongside, no marks visible.

and remains of bearing trees mkd. by the Douglas County Surveyors office

A fir, 25 ins. diam., bears N. 36° E., 33.3 ft. dist., with a healed blaze.

A roothole bears S. 89° W., 24.0 ft. dist., with fallen cedar trunk, size indeterminate, lying alongside, no marks visible.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 24 ins. diam., bears N. 1½° W., 33.2 ft. dist., with a healed blaze.</p>
	<p>and remains of bearing trees mkd. by Shaner</p>
	<p>A fir, 14 ins. diam., bears S. 32° E., 30.3 ft. dist., with a healed blaze.</p>
	<p>A roothole bears S. 60° W., 24.3 ft. dist., with fallen trunk, 9 ins. diam., lying alongside, species indeterminate, with a healed blaze.</p>
	<p>N. 0° 07' 12" W., bet. secs. 9 and 10, posting and blazing.</p>
	<p>Ascend SW. slope.</p>
825	<p>Spur, slopes S. 42° E.; desc. broken NE. slope.</p>
1360	<p>Spring branch, 1 ft. wide, course East; asc. broken E. slope.</p>
2590	<p>Spur, slopes East; desc. broken NW. slope.</p>
2672.88	<p>The 1/4 sec. cor. of secs. 9 and 10, perpetuated by the Douglas County Surveyors Office, in 1957, and further perpetuated by Leslie D. Roberts, Oregon Professional Land Surveyor No. 1039, in 1996, recorded in the Douglas County Surveyors Office, Map File No. M123-73, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 400540, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 24 S 1/4 S   S 9   10 R 7 W 1957</p>
	<p>from which the remains of an original bearing tree</p>
	<p>A decayed fir stump, size indeterminate, bears N. 25¾° E., 10.6 ft. dist., no marks visible. (Record, N. 23° E.)</p>
	<p>and remains of bearing trees mkd. by the Douglas County Surveyors Office</p>
	<p>A decayed hemlock stump, size indeterminate, bears S. 70° E., 32.8 ft. dist., no marks visible.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET											
	<p>A fir, 25 ins. diam., bears S. 21° W., 56.9 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by Roberts</p> <p>A fir, 7 ins. diam., bears N. 87° E., 18.4 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 12' 04" E., beginning new measurement.</p> <p>Continue desc. broken NW. slope, posting and blazing.</p>										
570	Graveled road, 12 ft. wide, bears N. 30° E. and S. 30° W.										
810	Graveled road, 12 ft. wide, bears S. 62° E. and N. 62° W.										
1680	Spur, slopes N. 53° W.; continue desc. broken NW. slope.										
2030	Graveled road, 16 ft. wide, bears S. 80° E. and N. 80° W.										
2325	Slope changes to steep NE. slope.										
2672.85	<p>The cor. of secs. 3, 4, 9, and 10, perpetuated by the Douglas County Surveyors Office, in 1957, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 400600, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 24 S</td> </tr> <tr> <td style="text-align: center;">S 4</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 9</td> <td style="text-align: center;">S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">R 7 W</td> </tr> </table> <p>OFFICE 1957</p> </div> <p>from which the remains of the original bearing trees</p> <p>A fir, 36 ins. diam., bears N. 55° E., 14.5 ft. dist., with a healed blaze.</p> <p>A decayed fir stob, size indeterminate, 6 ft. high, bears S. 69¾° W., 12.3 ft. dist., with scribe marks BT visible on decayed blaze. (Record, S. 60° W., 13.2 ft.)</p> <p>A roothole bears N. 39¾° W., 34.3 ft. dist., with fallen fir trunk, size indeterminate, lying downhill, no marks visible. (Record, N. 34° W.)</p>	T 24 S		S 4	S 3	-----		S 9	S10	R 7 W	
T 24 S											
S 4	S 3										
-----											
S 9	S10										
R 7 W											

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	and bearing trees mkd. by the Douglas County Surveyors Office
	A hemlock, 15 ins. diam., bears S. 73½° E., 26.0 ft. dist., with a healed double blaze.
	A fir, 26 ins. diam., bears S. 30° W., 28.2 ft. dist., with a healed double blaze.
	and a new bearing tree
	A hemlock, 5 ins. diam., bears N. 36¼° W., 39.4 ft. dist., mkd. X BT.
	<hr/>
	From the cor. of secs. 9, 10, 15, and 16, hereinbefore described.
	N. 89° 34' 09" W., bet. secs. 9 and 16, posting and blazing.
	Ascend NE. slope.
40	Ridge, bears N. 20° W. and S. 20° W.; desc. broken SW. slope.
2200	Spring branch, 1 ft. wide, course S. 50° W.
2320	Creek, 2 ft. wide, course S. 14° W.; asc. SE. slope.
2440	Wire fence, bears N. 88° E. and S. 88° W.
2654.30	The 1/4 sec. cor. of secs. 9 and 16, perpetuated by the Douglas County Surveyors Office in 1956, from evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 340500, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS T24S R7W S 9 1/4 16 1956 OFFICE
	from which the remaining bearing tree mkd. by the Douglas County Surveyors Office
	A cedar, 43 ins. diam., bears N. 88½° W., 15.2 ft. dist., with a healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>and new bearing tree</p> <p>A fir, 20 ins. diam., bears N. 4½° E., 27.5 ft. dist., mkd. 1/4 S9 BT. (MAG-NAIL driven into left side of tree)</p> <p>Corner lies 2.3 ft. North of wire fence, bears E. and W.</p> <p>From this point, the National Geodetic Survey HARN station "T 739", determined by NAVSTAR Global Positioning System, utilizing static, carrier phase receivers, bears S. 80° 47' 20" E., 58,131.40 ft. dist. (mean bearing and sea level dist.), monumented with a stainless steel rod, ¾ in. diam., firmly set, buried 3 ins. below ground surface in an aluminum monument well, 0.8 ft. East of westerly right-of-way fence.</p> <hr/> <p>N. 89° 01' 39" W., beginning new measurement, posting and blazing.</p>
244.74	<p>From this point, the NE. cor. of Tax Lot 200, T. 24 S., R. 7 W., Sec. 16, bears South, 0.92 ft. dist., established by B. Osburn Shaw, Oregon Professional Land Surveyor No. 431, in 1972, recorded in the Douglas County Surveyors Office, Map File No. M46-60, monumented with a rebar, ½ in. diam., firmly set, projecting 4 ins. above ground, bent over, in center of dirt road, 8 ft. wide, which bears N. 48° E. and S. 48° W.</p>
1138	<p>Wire fence, bears S. 88° E. and N. 88° W.</p>
1180	<p>Spring branch, 2 ft. wide, course S. 4° W., asc. steep E. slope.</p>
1325.72	<p>Point for the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 7 W S 9 W 1/16 S 16 2003</p> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 34½° E., 12.3 ft. dist., mkd. W 1/16 S9 BT.</p> <p>A fir, 11 ins. diam., bears S. 4¾° E., 15.6 ft. dist., mkd. W 1/16 S16 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET																
	<p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>From this point, a steel pin, ½ in. diam., firmly set, projecting 18 ins. above ground, bears N. 4° 33' 15" E., 2.11 ft. dist., set by person(s) unknown, and is not utilized in this survey.</p> <p>Discontinue posting and blazing.</p>															
2139	Wire fence, bears N. 88° E. and S. 88° W.															
2157	Ridge, bears N. 15° E. and S. 15° W.; desc. broken W. slope.															
2651.44	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p>															
	<p style="text-align: center;">COUNTY SURVEYORS  <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center;">T 24 S</td> <td></td> <td style="text-align: center;">S 9</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black;"></td> </tr> <tr> <td style="text-align: center;">S17</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S16</td> </tr> <tr> <td colspan="3" style="text-align: center;">R 7 W</td> </tr> </table> <p style="text-align: center;">OFFICE 1957</p> </p>	T 24 S		S 9	S 8		S 9				S17		S16	R 7 W		
T 24 S		S 9														
S 8		S 9														
S17		S16														
R 7 W																
	<p>from which the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1957, reported by Jelley</p> <p style="padding-left: 40px;">A roothole bears N. 64¼° E., 20.9 ft. dist., with fallen oak trunk, size indeterminate, lying alongside, no marks visible. (Record, N. 52¼° E., 24.4 ft.)</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 80° E., 8.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 12¼° W., 25.4 ft. dist., with fallen fir trunk, 23 ins. diam., lying alongside, no marks visible. (Record, S. 17¼° W., 23.1 ft.)</p> <p style="padding-left: 40px;">A roothole bears N. 28¼° W., 34.6 ft. dist., with fallen fir trunk, 18 ins. diam., lying alongside, no marks visible. (Record, N. 25½° W., 36.3 ft.)</p> <p>and a bearing tree mkd. by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 1998, recorded in the Douglas County Surveyors Office, Map File No. M128-73, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 300500</p>															

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A fir, 12 ins. diam., bears N. <math>36\frac{1}{4}^{\circ}</math> E., 29.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by Ken W. Hoffine, Oregon Professional Land Surveyor No. 2291, in 2001, recorded in the Douglas County Surveyors Office, Map File No. M138-42, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 300500</p> <p style="text-align: center;">A fir, 27 ins. diam., bears N. <math>5\frac{1}{4}^{\circ}</math> E., 44.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p style="text-align: center;">A fir, 18 ins. diam., bears N. <math>85\frac{1}{2}^{\circ}</math> W., 71.7 ft. dist., mkd. T24S R7W S8 BT.</p> <hr/> <p>N. <math>0^{\circ} 06' 06''</math> E., bet. secs. 8 and 9.</p> <p>Over broken W. slope.</p> <p>1325.70 The S <math>\frac{1}{16}</math> sec. cor. of secs. 8 and 9, monumented with an iron post, <math>1\frac{1}{4}</math> ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T24S</td> <td style="padding: 0 5px;">R7W</td> </tr> <tr> <td style="padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">  <math>\frac{1}{16}</math></td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">SOUTH COR</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1979</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1960</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="text-align: center;">A decayed fir stump, size indeterminate, bears S. <math>45^{\circ}</math> W., 20.5 ft. dist., no marks visible.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyors Office, in 1960, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 300520, reported by White and Beck</p> <p style="text-align: center;">A fir, 22 ins. diam., bears S. <math>72^{\circ}</math> E., 7.0 ft. dist., with a healed blaze. (Record, 6.6 ft. dist.)</p>	T24S	R7W	S 8	S 9		$\frac{1}{16}$	SOUTH COR		1979		1960	
T24S	R7W												
S 8	S 9												
	$\frac{1}{16}$												
SOUTH COR													
1979													
1960													

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir stump, 18 ins. diam., bears N. 62½° W., 10.6 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p style="text-align: center;">A fir, 13 ins. diam., bears S. 0¼° E., 30.6 ft. dist., mkd. X BT.</p> <p>N. 0° 00' 39" E., <u>beginning new measurement</u>, posting and blazing.</p> <p>Descend steep N. slope.</p>
1328.17	<p>The 1/4 sec. cor. of secs. 8 and 9, perpetuated by the Douglas County Surveyors Office, in 1974, recorded in the Douglas County Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 300540, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T24S R7W S 8   S 9 1/4 1974</p> <p>from which the remains of an original bearing tree</p> <p style="text-align: center;">A decayed fir stump, 50 ins. diam., bears East, 19.8 ft. dist., with fragmentary scribe marks visible on opened blaze.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="text-align: center;">A decayed fir stump, size indeterminate, bears N. 88° W., 16.6 ft. dist., no marks visible.</p> <p style="text-align: center;">A decayed cedar stump, 15 ins. diam., bears N. 17° W., 27.9 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p style="text-align: center;">A fir, 9 ins. diam., bears N. 1° E., 17.4 ft. dist., mkd. 1/4 S9 BT.</p> <p style="text-align: center;">A fir, 5 ins. diam., bears N. 82¾° W., 18.3 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	N. 0° 15' 15" E., beginning new measurement, posting and blazing.
	Descend broken N. slope.
160	Spring branch, 2 ft. wide, course West; asc. SE. slope.
520	Spur, slopes N. 70° W.; desc. N. slope.
550	Dirt road, 20 ft. wide, bears S. 75° E., N. 75° W.
1020	Spring branch, 1 ft. wide, course N. 70° W.; asc. SW. slope.
1331.35	Point for the N 1/16 sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T24S   R7W   N 1/16     S  8       S  9       2003           </pre>
	from which
	A cedar, 17 ins. diam., bears N. 5½° E., 43.5 ft. dist., mkd. N 1/16 S9 BT.
	A fir, 9 ins. diam., bears N. 80½° E., 37.5 ft. dist., mkd. N 1/16 S9 BT.
	Deposit a magnet, in a white plastic case, at the base of the iron post.
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, bears S. 10° 50' 47" W., 0.53 ft. dist., established without authority during a 1979 Bureau of Land Management administrative survey, recorded in the Douglas County Surveyors Office, Map Files No. M80-76, and M134-70. This position is not used in this survey.
	Discontinue posting and blazing; continue over rolling W. slope.
2662.70	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>T 24 S R 7 W</p> <p>S 5 S 4</p> <p>S 8 S 9</p> <p>1963</p>
	<p>from which the remains of bearing trees mkd. by White and Beck</p> <p>A decayed fir stump, 16 ins. diam., bears N. 44½° E., 100.5 ft. dist., with scribe marks S9 BT visible on a decayed blaze. (Record, 101.6 ft.)</p> <p>A decayed fir stump, size indeterminate, bears N. 69¼° W., 133.3 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 22 ins. diam., bears N. 27¾° E., 126.8 ft. dist., mkd. T24S R7W S4 BT.</p> <p>A black walnut, 32 ins. diam., bears S. 41¾° E., 120.9 ft. dist., mkd. T24S R7W S9 BT.</p> <p>A fir, 19 ins. diam., bears N. 68¾° W., 199.8 ft. dist., mkd. T24S R7W S5 BT.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10, hereinbefore described.</p> <p>N. 89° 34' 48" W., bet. secs. 4 and 9, posting and blazing.</p> <p>Ascend steep NE. slope.</p>
185	Spur, slopes N. 10° W.; asc. broken NE. slope.
1140	Ridge and graveled road, 16 ft. wide, bears S. 15° E. and N. 15° W.; desc. broken SW. slope.
2540	Spring branch, 1 ft. wide, course N. 57° W.
2636.48	The 1/4 sec. cor. of secs. 4 and 9, perpetuated by the Douglas County Surveyors Office, in 1957, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 340600, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">COUNTY SURVEYORS T 24 S S 4 1/4 ●●●●● S 9 R 7 W OFFICE 1957</p> <p>from which the remains of the original bearing trees.</p> <p style="padding-left: 40px;">A decayed hemlock stump, 24 ins. diam., bears N. 66¼° E., 14.0 ft. dist., with a healed blaze. (Record, fir, N. 62° E., 15.2 ft.)</p> <p style="padding-left: 40px;">A cedar, 47 ins. diam., bears South, 32.7 ft. dist., with a healed blaze. (Record, 31.7 ft.)</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 58¼° W., 16.8 ft. dist., mkd. 1/4 S4 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 02' 19" W., beginning new measurement, continuing posting and blazing.</p> <p>Descend broken N. slope.</p> <p>1108 Graveled road, 15 ft. wide, bears S. 7° E. and N. 7° W.</p> <p>1328.07 The witness point bet. secs. 4 and 9, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T24S R7W S 4 ●●●●● S 9 W C 1960</p> <p>from which the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1960, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 7 W., Point Identifier No. 320600, reported by White and Beck</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 20° E., 33.0 ft. dist., with a healed blaze.</p>
------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, 18 ins. diam., bears N. 30½° W., 48.2 ft. dist., no marks visible. (Record, hemlock)</p> <p>and new bearing tree</p> <p>A fir, 7 ins. diam., bears N. 24° E., 15.8 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 44' 59" W., beginning new measurement, continuing posting and blazing.</p>
0.60	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9 determined at midpoint longitudinally bet. the 1/4 sec. cor. of secs. 4 and 9 and the cor. of secs. 4, 5, 8, and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 S R 7 W S 4 W 1/16 ●●●● S 9</p> </div> <p style="text-align: center;">2003</p> <p>from which</p> <p>A hemlock, 14 ins. diam., bears S. 10° E., 48.7 ft. dist., mkd. W 1/16 S9 BT.</p> <p>A fir, 16 ins. diam., bears N. 66° W., 5.6 ft. dist., mkd. W 1/16 S4 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p>
60	<p>Creek, 4 ft. wide, course N. 12° E.; asc. broken NE. slope.</p>
664.18	<p>The W-W 1/64 sec. cor. of secs. 4 and 9, established by Leslie D. Roberts, Oregon Professional Land Surveyor No. 1039, in 1980, and is accepted as the corner, recorded in the Douglas County Surveyors Office, Map File No. M84-57, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	PLS 1039 S 4 ●●●● S 9 W W 1/64 T24S R7W 1980
	from which bearing trees mkd. by Roberts
	A fir, 25 ins. diam., bears N. 77° E., 27.2 ft. dist., with a healed double blaze.
	A fir, 10 ins. diam., bears S. 2° E., 29.1 ft. dist., with a healed double blaze.
	_____
	S. 89° 44' 59" W., beginning new measurement.
40	Spur, slopes N. °10 E.; desc. NW. slope.
664.91	The cor. of secs. 4, 5, 8, and 9, hereinbefore described.
	_____
	<b>Subdivision of Section 9, T. 24 S., R. 7 W., Willamette Meridian, Oregon</b>
	_____
	From the 1/4 sec. cor. of secs. 9 and 16, hereinbefore described.
	N. 0° 13' 29" E., on the N. and S. centerline of sec. 9.
	Ascend broken S. slope.
185	Dirt road, 16 ft. wide, bears N. 88° E. and S. 88° W.
670	Dirt road, 16 ft. wide, bears S. 21° E. and N. 21° W.
860	Graveled road, 16 ft. wide, bears S. 84° E. and N. 84° W.
1337.91	Point for the center S 1/16 sec. cor. of sec. 9, not monumented.
1948	Graveled road, 16 ft. wide, bears N. 85° E. and S. 85° W.
1950	Ridge, bears East and West; desc. broken NW. slope.
2675.82	Point for the center 1/4 sec. cor. of sec. 9 at the intersection with the E. and W. centerline.

Subdivision of Section 9,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 7 W C 1/4 + S 9 2003</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 21¾° E., 16.4 ft. dist., mkd. C 1/4 S9 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 83° W., 14.9 ft. dist., mkd. C 1/4 S9 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
3170	Graveled road, 16 ft. wide, bears S. 85° E. and N. 85° W.
4010.47	Point for the center N 1/16 sec. cor. of sec. 9, not monumented.
5345.12	The 1/4 sec. cor. of secs. 4 and 9, hereinbefore described.
	<hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10, hereinbefore described. N. 89° 30' 10" W., on the E. and W. centerline of sec. 9. Descend broken NW. slope.</p>
2637.92	The center 1/4 sec. cor. of sec. 9, hereinbefore described.
3720	Graveled road, 16 ft. wide, bears N. 67° E. and S. 67° W.
3967.28	Point for the center W 1/16 sec. cor. of sec. 9, not monumented.
4940	Graveled road, 16 ft. wide, bears N. 7° E. and S. 7° W.
5296.64	The 1/4 sec. cor. of secs. 8 and 9, hereinbefore described.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 9 and 16, hereinbefore described.</p> <p>N. 0° 08' 27" E., on the calculated N. and S. centerline of the SW¼ of sec. 9, posting and blazing.</p>

Subdivision of Section 9,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	Ascend broken SE. slope.
4	Wire fence, bears East and West.
990	Spring branch, 1 ft. wide, course S. 34° E.; asc. SW. slope.
1331.81	Point for the SW 1/16 sec. cor. of sec. 9, at its calculated position.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 24 S R 7 W SW 1/16 + S 9 2003
	from which
	A fir, 13 ins. diam., bears S. 14½° E., 27.2 ft. dist., mkd. SW 1/16 S9 BT.
	A fir, 20 ins. diam., bears N. 65° W., 32.5 ft. dist., mkd. SW 1/16 S9 BT.
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	_____
	N. 89° 17' 31" W., on the calculated E. and W. centerline of the SW¼ of sec. 9, posting and blazing.
635	Dirt road, 16 ft. wide, bears N. 40° E. and S. 40° W.
660	Spur, slopes N. 40° E.; desc. NW. slope.
1326.47	The S 1/16 sec. cor. of secs. 8 and 9, hereinbefore described.
	_____
	From the W 1/16 sec. cor. of secs. 4 and 9, hereinbefore described.
	S. 0° 14' 21" W., on the N. and S. centerline of the NW¼ of sec. 9, posting and blazing.
	Descend SW. slope.

**Subdivision of Section 9,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
165	Creek, 2 ft. wide, course N. 80° W.; asc. NW. slope.
930	Creek, 4 ft. wide, course N. 35° W.
1347.52	<p>The NW 1/16 sec. cor. of sec. 9, established by David A. Edwards, Oregon Registered Land Surveyor No. 2339, in 2000, recorded in the Douglas County Surveyors Office, Map File No. M134-70, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap mkd. D A EDWARDS LS2339, from which bearing trees mkd. by Edwards</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 85¼° E., 18.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. ¼° E., 7.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>Memo: In spite of the fact that Edwards used an erroneous position for the 1/4 sec. cor. of secs. 4 and 9 when subdividing sec. 9, the magnitude of his error is small and most of his corner positions are not monumented. Therefore this monumented position is accepted as the corner point.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, directly over the rebar, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 7 W NW 1/16 + S 9 2003</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <hr/> <p>N. 89° 33' 12" W., on the E. and W. centerline of the NW¼ of sec. 9, posting and blazing.</p> <p>Ascend broken NE. slope.</p>
210	Spur, slopes N. 40° W.; desc. SW. slope.
1328.88	The N 1/16 sec. cor. of secs. 8 and 9, hereinbefore described.

Subdivision of Section 9,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

FEET

**GENERAL DESCRIPTION**

The lands included in the foregoing survey are located in mountainous terrain, about 13.0 miles northwesterly from the community of Sutherlin, Oregon. The survey lies approximately 1 mile southwesterly of Bullock Road.

The elevation ranges from about 600 feet above sea level near the W 1/16 section corner of sections 4 and 9 to about 1540 feet above sea level near the 1/4 section corner of sections 9 and 10.

The northerly portion of section 9 is drained by tributaries of McGee Creek, which flows northerly into the Umpqua River. The southerly portion of section 9 is drained by a minor tributary of the Umpqua River.

Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

The soil is generally composed of rocky clay, with numerous basalt outcroppings and bluffs, and steep, crumbling rock slopes.

Access to the survey was made by graveled roads branching from Bullock Road.

The mean magnetic declination for the area surveyed is 18° East, as shown on the "KELLOGG, OREGON" 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1990.

---