

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND
SUBDIVISION OF SECTIONS 23 AND 27
TOWNSHIP 29 SOUTH, RANGE 9 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated March 24, 2003, approved March 31, 2003,
which provided for the surveys included under Group No. 2043,
and Assignment Instructions dated April 23, 2003

Survey commenced May 6, 2003

Survey completed June 26, 2003

T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 23 and 27, township 29 south, range 9 west, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines as shown on the official plat of survey approved July 7, 1856.

In 1907, William M. Porter, U.S. Deputy Surveyor, resurveyed a portion of the subdivisional lines and completed the survey of the subdivisional lines as shown on the official plat of survey approved March 19, 1909, and amended April 29, 1909.

In 1966, John M. Jelley, Cadastral Surveyor, resurveyed a portion of the east boundary and subdivisional lines, and remonumented certain original corner points, as shown on the official plat of survey accepted January 23, 1969.

In 1989-90, Wayne L. Rogers, Cadastral Surveyor, and Garry L. Moore, Surveying Technician, resurveyed a portion of the subdivisional lines and subdivided section 35 as shown on the official plat of survey accepted April 29, 1993.

In 2002, A. Bert Skeesick, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 13 as shown on the official plat of survey accepted October 22, 2004.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 23, 2003, for Group No. 2043, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) static measurement techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed and adjusted (by least squares analysis) using Trimble Geomatics Office (TGO) software, version 1.60. The GPS portion of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys using Global Positioning System Methods", Version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.

T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

An analysis of the unadjusted conventional field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management (CMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS)), as determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.02 feet, 95% confidence level, utilizing dual frequency, carrier phase GPS receivers, and National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP", is as follows:

The corner of sections 22, 23, 26 and 27:

Latitude: 43° 01' 31.70" N. Longitude: 123° 44' 30.29" W.

The ¼ section corner of sections 14 and 23:

Latitude: 43° 02' 23.76" N. Longitude: 123° 43' 55.11" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>(Restoring the 1855 survey by Dennis Hathorn, the 1966 resurvey by John M. Jelley, and the 1990 resurvey by Wayne L. Rogers and Garry L. Moore)</p> <hr/> <p>Beginning at the S 1/16 sec. cor. of secs. 23 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting ½ in. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S23 S24 1966</p> </div> <p>from which a bearing tree mkd. by Jelley</p> <p style="text-align: center;">An oak, 17 ins. diam., bears S. 47½° W., 322.1 ft. dist., with healed blaze. (Record, S. 46½° W.)</p> <p>No additional accessories available within limits.</p> <p>N. 0° 04' 29" E., bet. secs. 23 and 24.</p> <p>Descend gentle NE. slope, along wire fence.</p>
1318.39	<p>The ¼ sec. cor. of secs. 23 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R9W 1/4 S23 S24 1966</p> </div> <p>from which the bearing tree mkd. by Jelley</p> <p style="text-align: center;">A fir, 19 ins. diam., bears S. 30½° E., 162.4 ft. dist., with a healed blaze.</p> <p>No additional accessories available within limits.</p> <hr/> <p>N. 0° 15' 19" W., beginning new measurement.</p> <p>Ascend gentle S. slope, along wire fence.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET																			
1329.71	<p>The N 1/16 sec. cor. of secs. 23 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <table border="0"> <tr> <td>S23</td> <td> </td> <td>S24</td> </tr> <tr> <td colspan="3">1966</td> </tr> </table> </div> <p>from which the bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 17° E., 19.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 69° W., 39.6 ft. dist., with no marks visible.</p> <p>Corner is located 0.8 ft. SE. of the corner of woven wire fences extending N. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 14' 40" W., beginning new measurement, posting and blazing.</p> <p>Ascend gentle SW. slope.</p>	S23		S24	1966														
S23		S24																	
1966																			
1331.48	<p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 7 ins. above ground, (with an iron pipe, ¾ in. diam., projecting 9 ins. above ground alongside) with brass cap mkd.</p> <div style="text-align: center;"> <p>DOUGLAS COUNTY SURVEYORS OFFICE</p> <table border="0"> <tr> <td></td> <td>T29S</td> <td>R9W</td> </tr> <tr> <td>COR</td> <td>14</td> <td> 13</td> </tr> <tr> <td></td> <td colspan="2">-----</td> </tr> <tr> <td>SECS</td> <td>23</td> <td> 24</td> </tr> <tr> <td></td> <td colspan="2">BLM 1966</td> </tr> <tr> <td></td> <td colspan="2">1957</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole bears N. 80° E., 44.2 ft. dist., with decayed trunk, size indeterminate, lying alongside, with no marks visible.</p> <p style="padding-left: 40px;">A root hole bears S. 50° E., 38.9 ft. dist., with decayed trunk, size indeterminate, lying alongside, with no marks visible.</p>		T29S	R9W	COR	14	13		-----		SECS	23	24		BLM 1966			1957	
	T29S	R9W																	
COR	14	13																	

SECS	23	24																	
	BLM 1966																		
	1957																		

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET

A root hole bears S. 50° W., 73.9 ft. dist., with decayed trunk, size indeterminate, lying alongside, with no marks visible.

A root hole bears N. 23° W., 23.1 ft. dist., with decayed trunk, size indeterminate, lying alongside, with no marks visible.

and bearing trees mkd. by the Douglas County Surveyor's Office, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 600400, reported by Jelley

A cedar, 29 ins. diam., bears N. 9° E., 57.8 ft. dist., with a healed blaze.

A fir, 31 ins. diam., bears S. 60° E., 27.1 ft. dist., with a healed double blaze.

A fir, 29 ins. diam., bears S. 67° W., 22.8 ft. dist., with a healed double blaze. (Record, S. 73° W.)

A fir, 21 ins. diam., bears N. 56° W., 62.7 ft. dist., with a healed double blaze.

Corner is located N. 83° E., 0.8 ft. dist., of a fence corner, fences extend south and west.

From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T29S	R9W
S27	S26
S34	S35
BLM 1966 1959	

from which the remains of the original bearing trees

A fir stump, size indeterminate, bears S. 45° W., 11.9 ft. dist., with no marks visible.

A fir stump, 36 ins. diam., bears N. 14° W., 27.7 ft. dist., with scribe mark T visible on an opened blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 500200, reported by Rogers and Moore</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 62½° E., 88.4 ft. dist., with a healed double blaze. (Record, N. 61¼° E.)</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears S. 57° E., 29.2 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir snag, 14 ins. diam., bears S. 51¼° W., 23.8 ft. dist., with a healed double blaze. (Record, S. 57° W.)</p> <p>and the bearing trees mkd. by Rogers and Moore</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 0¼° W., 46.6 ft. dist., with a healed blaze. (Record, S. 2° W., 47.5 ft.)</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 80° W., 35.0 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 52¼° E., 37.6 ft. dist., mkd. T29S R9W S35 BT.</p> <p>Corner is located 0.5 ft. S. of the cor. of barbed wire fences extending N., E., and W.</p> <p>N. 0° 16' 53" E., bet. secs. 26 and 27.</p> <p>Ascend gentle SW. slope.</p>
1100	Graveled road, 20 ft. wide, bears E. and W.
1330.80	The S 1/16 sec. cor. of secs. 26 and 27, established by George E. Laney, Oregon Professional Land Surveyor No. 1623, in 1975, recorded in the Douglas County Surveyor's Office, Map File No. 85-20, and is accepted as a careful and faithful establishment of the cor. position; monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with alum. cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>G.E. LANEY</p> <p>S 1/16 S27 S26</p> <p>LS 1623</p>
	<p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 41¼° E., 14.6 ft. dist., mkd. S 1/16 S26 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 28½° W., 17.4 ft. dist., mkd. S 1/16 S27 BT.</p> <p>From the cor., a point established by person(s) unknown, monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 4 ins. above ground, with no cap, bears N. 39° 45' 10" W., 4.70 ft. dist. This point is not utilized in this survey.</p> <p>From this same cor, a fence cor. bears S. 68½° E., 1.5 ft. dist., with barbed wire fences extending S., E., and N. 20° W.</p> <p>Also from this same cor, another fence cor. bears N. 21° W., 8.1 ft. dist., with woven wire fences extending N., W., and S. 20° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 16' 34" E., beginning new measurement, posting and blazing.</p> <p>Ascend broken SE. slope, along woven wire fence.</p>
692.36	An iron pipe, ¾ in. diam., firmly set, projecting 8 ins. above ground, with alum. cap mkd. GEORGE E LANEY LS 1623 102, established by George E. Laney, Oregon Professional Land Surveyor No. 1623, in 1981, and recorded in the Douglas County Surveyor's Office, Map File No. 88-39. This point is accepted as a witness point marking the line bet. secs. 26 and 27.
1140	Creek, 3 ft. wide, course S. 64° E.
1330.72	The ¼ sec. cor. of secs. 26 and 27, perpetuated by the Douglas County Surveyor's Office in 1920, 1959, and 1963, and remonumented by the Douglas County Surveyor's Office in 1981, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 500240; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 7 ins. above ground, (alongside of which is an

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>iron pipe, 1 in. diam., firmly set projecting 6 ins. from the ground) with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T29S R9W 1/4 S27 S26 1981</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A burnt cedar stump, 31 ins. diam., bears S. $56\frac{3}{4}^{\circ}$ E., 20.4 ft. dist., with no marks visible. (Record, S. 60° E., 19.1 ft.)</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1959</p> <p style="padding-left: 40px;">A fir stump, 35 ins. diam., bears S. $6\frac{1}{4}^{\circ}$ E., 48.2 ft. dist., with no marks visible.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office in 1963</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. $5\frac{3}{4}^{\circ}$ W., 67.7 ft. dist., with a healed double blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1981</p> <p style="padding-left: 40px;">A fir stump, 21 ins. diam., bears N. $74\frac{1}{4}^{\circ}$ E., 49.1 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. $40\frac{1}{2}^{\circ}$ W., 62.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. $79\frac{1}{2}^{\circ}$ E., 35.6 ft. dist., mkd. 1/4 S26 BT.</p> <p>Corner is located 4.2 ft. E. of woven wire fence extending N. and S.</p> <p style="text-align: center;">_____</p> <p>N. $0^{\circ} 00' 57''$ W., beginning new measurement, posting and blazing.</p> <p>Ascend broken SE. slope, along woven wire fence.</p>
------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
985	Graveled road, 15 ft. wide, bears E. and W.
1615	Spur, slopes S. 76° E.; desc. broken NE. slope.
2658.13	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T29S R9W S22 S23 ----- S27 S26 BLM 1966 1959
	<p>from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1959, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 500300, reported by Jelley</p> <p style="padding-left: 40px;">A sawed fir stump, 31 ins. diam., bears S. 31½° W., 27.7 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A hemlock snag, 17 ins. diam., bears N. 32° W., 32.0 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A sawed fir stump with tin cap, 38 ins. diam., bears N. 76½° E., 9.9 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 88¼° E., 21.0 ft. dist., with scribe marks S23 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 27° W., 43.5 ft. dist., with scribe marks S22 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears N. 3¼° W., 26.3 ft. dist., with scribe marks S23 BT visible on a partially healed blaze.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 23 and 26, monumented by Jelley with an iron post, 2½ ins. diam., top half bent over and missing cap, with bottom half still vertical and firmly set in</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>the ground. There is no remaining evidence of the bearing trees mkd. by Jelley.</p> <p>I remove the damaged monument and in its place set a stainless steel post, 28 ins. long, 2½ ins. diam., 30 ins. in the ground, buried 2 ins. below surface, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R9W S 23 E 1/16 <u> </u> S 26 2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 23 ins. diam., bears N. 40½° E., 177.0 ft. dist., mkd. E 1/16 S23 BT.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 37¾° E., 228.1 ft. dist., mkd. E 1/16 S26 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base, and the original iron post alongside the stainless steel post.</p> <p>N. 89° 41' 09" W., bet. secs. 23 and 26.</p> <p>Over level pasture.</p>
890	Leave pasture; desc. W. slope.
995	Holmes Creek, 2 ft. wide, course S.; asc. E. slope.
1310.64	<p>The ¼ sec. cor. of secs. 23 and 26, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, (alongside of which is an axle, 1 in. diam., firmly set, projecting 4 ins. above ground) with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R9W S 23 1/4 <u> </u> S 26 1966</p> </div> <p>from which the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1920, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 540300, reported by Jelley</p> <p style="padding-left: 40px;">A sawed fir stump, 58 ins. diam., bears S. 31½° W., 61.4 ft. dist., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1959, reported by Jelley
	A sawed fir stump, 34 ins. diam., bears S. 29½° W., 146.5 ft. dist., with a healed double blaze.
	A fir, 13 ins. diam., bears N. 27° W., 112.2 ft. dist., with a healed blaze.
	and a new bearing tree
	A fir, 10 ins. diam., bears S. 27¼° W., 42.3 ft. dist., mkd. 1/4 S26 BT.

	N. 89° 25' 09" W., beginning new measurement, posting and blazing.
	Over level ground, along wire fence.
400	Spring branch, 4 ft. wide, course S. 66° E.; asc. broken E. slope.
1125	Graveled road, 16 ft. wide, bears S. 12° E. and N. 12° W.
1820	Spur, slopes N.; desc. broken W. slope.
2570	Spring branch, 2 ft. wide, course S. 20° E.
2665.29	The cor. of secs. 22, 23, 26, and 27, hereinbefore described.

	From the cor. of secs. 13, 14, 23, and 24, hereinbefore described.
	N. 89° 42' 50" W., bet. secs. 14 and 23, posting and blazing.
	Descend broken NW. slope, along wire fence.
530	Ravine, drains N. 28° E.; asc. broken NE. slope.
1115	Spur, slopes N.; desc. broken NW. slope.
1332.23	The E 1/16 sec. cor. of secs. 14 and 23, remonumented by the Douglas County Surveyor's Office in 1976, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 560400, and perpetuated by Gary T. Smither, Oregon Professional Land Surveyor No. 2485, in 2000, recorded in the Douglas County Surveyor's Office, Map

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>File No. 135-53; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 3 ins above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS CO SURVEYOR T29S R9W S 14 E 1/16 <u> </u> S 23 1976</p> <p>from which the remains of a bearing tree mkd. by Jelley</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 60° E., 27.1 ft. dist., with fallen trunk lying alongside, no marks visible.</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A sawed, decayed stump, 15 ins. diam., bears N. 68½° E., 78.0 ft. dist., with no scribe marks visible on a partially healed blaze.</p> <p>and the bearing trees mkd. by Smither</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 33° E., 12.0 ft. dist., with scribe marks X BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 71¼° W., 20.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 42' 25" W., beginning new measurement, continue posting and blazing.</p>
325	Ravine, drains N. 13° E.; asc. broken NE. slope.
1070	Spur, slopes N. 20° W., and graveled road, 10 ft. wide, bears S. 17° E. and N. 17° W.; desc. broken W. slope.
1332.77	<p>The ¼ sec. cor. of secs. 14 and 23, perpetuated by Gary T. Smither, Oregon Professional Land Surveyor No. 2485, in 2000, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 540400, and recorded in the Douglas County Surveyor's Office, Map File No. 135-53, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 3 ins above ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET

COUNTY SURVEYORS OFFICE

T29S R9W
S 14 DCSO
————— 1976
S 23
BLM 1966
1959

from which the remains of an original bearing tree

A decayed oak stump, size indeterminate, bears S. $39\frac{1}{2}^{\circ}$ W., 103.6 ft. dist., with no marks visible. (Record, S. 45° W., 105.6 ft.)

and a bearing tree mkd. by the Douglas County Surveyor's Office, reported by Jelley

A fir, 22 ins. diam., bears N. 27° E., 47.9 ft. dist., with healed double blazes.

and the remains of a bearing tree mkd. by Jelley

A fallen, decayed fir, size indeterminate, bears S. 8° W., 114.2 ft. dist., with no marks visible.

and the bearing trees mkd. by Smither

A fir, 21 ins. diam., bears N. $25\frac{3}{4}^{\circ}$ E., 30.3 ft. dist., with scribe marks $\frac{1}{4}$ S14 BT visible on a partially healed blaze.

A fir, 8 ins. diam., bears N. 63° E., 13.6 ft. dist., with scribe marks $\frac{1}{4}$ S14 BT visible on a partially healed blaze.

A fir, 13 ins. diam., bears N. $62\frac{3}{4}^{\circ}$ W., 17.0 ft. dist., with scribe marks $\frac{1}{4}$ S14 BT visible on a partially healed blaze.

and a new bearing tree

A fir, 6 ins. diam., bears S. $16\frac{3}{4}^{\circ}$ W., 11.6 ft. dist., mkd. $\frac{1}{4}$ S23 BT.

From the cor. of secs. 22, 23, 26, and 27, hereinbefore described.

N. $89^{\circ} 47' 18''$ W., bet. secs. 22 and 27, posting and blazing.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2646.93	<p>Ascend broken NE. slope.</p> <p>The ¼ sec. cor. of secs. 22 and 27, remonumented by the Douglas County Surveyor's Office in 1959, and perpetuated by the Douglas County Surveyor's Office in 1965 and 1996, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 440300, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 17 ins. above ground, with the original stone alongside, showing 4 x 10 x 4 ins. above ground and fragmentary chisel marks visible on N. face, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S R9W S 22 1/4 _____ S 27 1959</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir stump, 28 ins. diam., bears S. 44° E., 9.3 ft. dist., with no marks visible. (Record, 8.6 ft.)</p> <p style="padding-left: 40px;">A sawed fir stump, 24 ins. diam., bears N. 22° W., 9.3 ft. dist., with no marks visible. (Record, 10.6 ft.)</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1959</p> <p style="padding-left: 40px;">A sawed fir stump, 20 ins. diam., bears N. 23¾° W., 44.5 ft. dist., with no marks visible.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office in 1965</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 9½° W., 33.2 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by the Douglas County Surveyor's Office in 1996</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 36¾° E., 13.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 49° E., 72.0 ft. dist., with a healed double blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEEET	<p>A madrone, 9 ins. diam., bears N. 25° W., 40.7 ft. dist., with scribe marks 1/4 S22 BT visible on a partially healed blaze.</p> <hr/> <p style="text-align: center;">Subdivision of Section 23, T. 29 S., R. 3 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 23 and 26, hereinbefore described. N. 0° 33' 29" W., on the N. and S. centerline of sec. 23, posting and blazing.</p> <p>Ascend gentle SE. slope, along wire fence.</p> <p>1323.23 Point for the center S 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> C S 1/16 S 23 C 2003 </pre> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 21 ins. diam., bears S. 84½° E., 36.1 ft. dist., mkd. CS 1/16 S23 BT.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 35¼° W., 37.5 ft. dist., mkd. CS 1/16 S23 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Corner is located N. 18° W., 7.5 ft. dist., from a fence corner, with woven wire fences extending N. and S.</p> <p>From this point, an iron pipe, ¾ in diam., firmly set, projecting 2 ins. above ground, with no cap, bears S. 20° 45' 21" E., 6.25 ft. dist., established without authority by a 1980 Bureau of Land Management administrative survey. This point is not accepted as the true cor. position; I remove the iron pipe and bury it alongside the stainless steel post.</p> <p>Discontinue posting and blazing.</p>
-------	--

Subdivision of Section 23,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	Descend broken E. slope.
1980	Graveled road, 16 ft. wide, bears N. 23° E. and S. 23° W.
2615	Graveled road, 16 ft. wide, bears N. 22° W. and S. 22° E.
2646.46	Point for the center ¼ sec. cor. of sec. 23, at intersection with the E. and W. centerline. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T29S R9W C 1/4 . S 23 2003</div> from which <div style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 25¾° W., 49.7 ft. dist., mkd. C 1/4 S23 BT.</div> <div style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 4¾° W., 38.7 ft. dist., mkd. C 1/4 S23 BT.</div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Corner is located 11.0 ft. E. and 30.0 ft. N. of a gravel road, 16 ft. wide, bears N. 20° W. and S. 20° E. Ascend gentle W. slope.
3972.30	Point for the center N 1/16 sec. cor. of sec. 23, not monumented.
5298.14	The ¼ sec. cor. of secs. 14 and 23, hereinbefore described. <hr style="width: 50%; margin-left: 0;"/> From the ¼ sec. cor. of secs. 23 and 24, hereinbefore described. N. 89° 30' 04" W., on the E. and W. centerline of sec. 23. Over broken S. slope.
1325	Wire fence, bears N. and S.
1325.58	Point for the center E 1/16 sec. cor. of sec. 23.

Subdivision of Section 23,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} E \ 1/16 \\ C \ \hline S \ 23 \\ C \end{array}$ <p>2003</p> <p>from which</p> <p>A fir, 16 ins. diam., bears N. 42¼° E., 19.2 ft. dist., mkd. CE 1/16 S23 BT.</p> <p>A fir, 24 ins. diam., bears S. 10° W., 40.5 ft. dist., mkd. CE 1/16 S23 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Corner is located 0.5 ft. W. of a fence cor., with woven wire fences extending N. and S.</p> <p>From this point, an iron pipe, ¾ in diam., firmly set, projecting 2 ins. above ground, with no cap, bears N. 23° 01' 22" E., 2.13 ft. dist., established without authority by a 1980 Bureau of Land Management administrative survey. This point is not accepted as the true cor. position; I remove the iron pipe and bury it alongside the stainless steel post.</p>
1600	Graveled road, 16 ft. wide, bears N. and S.; desc. broken SW. slope.
2651.16	The center ¼ sec. cor. of sec. 23, hereinbefore described. Ascend broken E. slope.
3205	Dirt road, 12 ft. wide, bears N. 21° W. and S. 21° E.
4310	Dirt road, 12 ft. wide, bears N. 70° E. and S. 70° W.
4765	Graveled road, 16 ft. wide, bears N. 3° W. and S. 3° E.
5295	Wire fence, bears N. and S.
5298.20	The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

Subdivision of Section 23,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S R9W S22 S23 1/4 BLM1966 1959</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 50° W., 7.9 ft. dist., with fragmentary axe marks visible. (1966 record, 73.9 ft.; 1855 record, 7.9 ft.)</p> <p>and the bearing trees mkd. by the Douglas County Surveyor's Office, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 500340, reported by Jelley</p> <p style="padding-left: 40px;">A cedar, 32 ins. diam., bears N. 26° E., 94.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 28° W., 70.6 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 76° E., 28.2 ft. dist., with scribe marks 1/4 S BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 26° W., 17.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>Corner is located 2.0 ft. W. of a fence cor. with woven wire fences extending N. and S.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 23, hereinbefore described.</p> <p>S. 89° 36' 09" E., on the computed E. and W. centerline of the SE¼ of sec. 23, posting and blazing.</p> <p>Descend E. slope, along wire fence.</p> <p>70 Holmes Creek, 8 ft. wide, course S.; asc. broken W. slope.</p>

Subdivision of Section 23,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
1318.11	<p>Point for the SE 1/16 sec. cor. of sec. 23, at the calculated intersection with the N. and S. centerline of the SE¼ of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S23</p> <p style="text-align: center;">2003</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 26¼° W., 63.1 ft. dist., mkd. SE 1/16 S23 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 52¼° W., 33.7 ft. dist., mkd. SE 1/16 S23 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the iron post.</p> <p>Corner is located N. 10° W., 2.1 ft. dist., from a fence corner with woven wire fences extending N. and W.</p> <p>From the cor., an iron pipe, ¾ in diam., firmly set, projecting 3 ins. above ground, with no cap, bears S. 11° 27' 07" E., 2.85 ft. dist., established without authority by a 1980 Bureau of Land Management administrative survey. This point is not accepted as the true cor. position, I remove the iron pipe and bury it alongside the iron post.</p> <hr/> <p>N. 0° 13' 56" W., on the computed N. and S. centerline of the SE¼ of sec. 23, posting and blazing.</p> <p>Over level ground, along wire fence.</p>
180	Descend broken NE. slope.
1260	Spring branch, 1 ft. wide, course S. 55° E.; asc. broken SW. slope.
1320.79	<p>The center E 1/16 sec. cor. of sec. 23, hereinbefore described.</p> <hr/> <p>N. 0° 23' 52" W., on the computed N. and S. centerline of the NE¼ of sec. 23, posting and blazing.</p> <p>Ascend broken SW. slope, along wire fence.</p>

Subdivision of Section 23,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
410	Spur, slopes S. 40° W.; desc. broken NW. slope.
600	Ravine, drains S. 22° W.; asc. broken SE. slope.
1327.77	<p>Point for the NE 1/16 sec. cor. of sec. 23, at the calculated intersection with the E. and W. centerline of the NE¼ of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S23</p> <p style="text-align: center;">2003</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 5½° W., 20.5 ft. dist., mkd. NE 1/16 S23 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 85° W., 17.5 ft. dist., mkd. NE 1/16 S23 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Corner is located S. 7° W., 1.1 ft. dist., from a fence corner with woven wire fences extending S. and E.</p> <p>From the cor., an iron pipe, ¼ in. diam., firmly set, projecting 7 ins. above ground, with no cap, bears N. 1° 10' 10" E., 0.60 ft. dist., established without authority by a 1980 Bureau of Land Management administrative survey. This point is not accepted as the true cor. position; I remove the iron pipe and bury it alongside the stainless steel post.</p> <hr/> <p>S. 89° 35' 13" E., on the computed E. and W. centerline of the NE¼ of sec. 23, posting and blazing.</p> <p>Ascend SW. slope, along wire fence.</p>
95	Spur, slopes S. 50° W.; desc. broken SE. slope.
295	Ravine, drains S. 30° W.; asc. broken W. slope.
595	Spur, slopes S. 35° W.; desc. broken SE. slope.
1020	Ravine, drains S. 40° W.; asc. broken NW. slope.

Subdivision of Section 23,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEEET	The N 1/16 sec. cor. of secs. 23 and 24, hereinbefore described.
1328.78	<p style="text-align: center;">Subdivision of Section 27, T. 29 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 27 and 34, remonumented by the Douglas County Surveyor's Office in 1959, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 440200, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S R9W S 27 1/4 _____ S 34 1959</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole bears S. 20° W., 15.2 ft. dist., with fallen trunk, size indeterminate, lying alongside, with scribe marks BT visible on partially opened blaze.</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears N. 58° W., 5.3 ft. dist., with no marks visible.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears S. 65¼° W., 29.4 ft. dist., with a healed double blaze.</p> <p>Corner is located S. 15° E., 3.2 ft. dist., from a fence corner with woven wire fences extending N., E., and W.</p> <p>N. 0° 00' 35" W., on the N. and S. centerline of sec. 27, posting and blazing.</p> <p>Descend broken NE. slope, along wire fence.</p>
3	Wire fence, bears E. and W.
1314.28	<p>Point for the center S 1/16 sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 27,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<div style="text-align: center;"> <p>T29S R9W</p> <p> C</p> <p>S 1/16 S 27</p> <p> C</p> <p> 2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 35° E., 19.2 ft. dist., mkd. CS 1/16 S27 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 61° W., 48.7 ft. dist., mkd. CS 1/16 S27 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From the cor., a fence cor. bears N. 2° W., 21.1 ft. dist., with woven wire fences extending S. and E.</p> <p>Discontinue posting and blazing.</p>
2628.56	<p>Point for the center ¼ sec. cor. of sec. 27 at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T29S R9W</p> <p> C 1/4 S 27</p> <p> 2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 83¼° E., 43.7 ft. dist., mkd. C 1/4 S27 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 47½° W., 12.9 ft. dist., mkd. C 1/4 S27 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
5334.42	<p>The ¼ sec. cor. of secs. 22 and 27, hereinbefore described.</p> <hr/>

Subdivision of Section 27,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>From the ¼ sec. cor. of secs. 26 and 27, hereinbefore described. S. 89° 10' 43" W., on the E. and W. centerline of sec. 27.</p>
2647.77	<p>The center ¼ sec. cor. of sec. 27, hereinbefore described.</p>
5285.97	<p>The ¼ sec. cor. of secs. 27 and 28, remonumented by the Douglas County Surveyor's Office in 1959, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 09 W., Point Identifier No. 400240, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 24 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S R9W S28 S27 1/4 1959</p>
	<p>from which the remains of an original bearing tree A sawed fir stump, 48 ins. diam., bears S. 45° W., 3.3 ft. dist., with a healed blaze.</p>
	<p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office A sawed fir stump, 18 ins. diam., bears S. 35° E., 41.0 ft. dist., with a healed double blaze.</p>
	<p>and new bearing trees A fir, 6 ins. diam., bears N. 38° E., 24.5 ft. dist., mkd. 1/4 S27 BT. A fir, 8 ins. diam., bears S. 1¼° W., 14.3 ft. dist., mkd. 1/4 S28 BT.</p>
	<hr/> <p>From the S 1/16 sec. cor. of secs. 26 and 27, hereinbefore described. S. 89° 31' 58" W., on the E. and W. centerline of the SE¼ of sec. 27, posting and blazing. Ascend broken NE. slope, along wire fence.</p>
135	<p>Graveled road, 14 ft. wide, bears N. 30° W. and S. 30° E.</p>

Subdivision of Section 27,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
855	Dirt road, 10 ft. wide, bears N. 55° W. and S. 55° E.
1130	Spur, slopes S. 55° E.; desc. broken SW. slope.
2641.11	The center S 1/16 sec. cor. of sec. 27, hereinbefore described.
	<hr/> <p>GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in rolling hills and broad, flat, creek bottoms, approximately three miles west-southwesterly of the community of Camas Valley, Oregon.</p> <p>The elevation ranges from approximately 1,200 feet above sea level near the 1/4 section corner of sections 23 and 26 to approximately 2,200 feet above sea level near the 1/4 section corner of sections 27 and 28.</p> <p>The area is drained by Bingham and Holmes Creeks, which flow together in section 26, then southeasterly to the Middle Fork of the Coquille River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>The soil is generally composed of rocky clay.</p> <p>Access to the survey was made by graveled roads branching from SW. Denn Road.</p> <p>The mean magnetic declination for the area surveyed is 18° East, as shown on the "CAMAS VALLEY, OREGON" 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1990.</p>