

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION
OF THE EAST AND WEST BOUNDARIES,
AND A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTIONS 13 AND 19,

TOWNSHIP 23 SOUTH, RANGE 4 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated July 24, 2006, approved
July 27, 2006, which provided for the surveys included under
Group No. 2147, and Assignment Instructions dated August 10, 2006,
and August 30, 2006.

Survey commenced August 14, 2006

Survey completed November 2, 2006

T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the east and west boundary, a portion of the subdivisional lines, and the subdivision of sections 13 and 19, Township 23 South, Range 4 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this resurvey is as follows:</p> <p>In 1851, James Freeman, U.S. Deputy Surveyor, surveyed the north and west boundary.</p> <p>In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the south boundary and a portion of the subdivisional lines.</p> <p>In 1882, James P. Currin, U.S. Deputy Surveyor, surveyed a portion of the west boundary of T. 23 S., R. 3 W.</p> <p>In 1884, William P. Wright, U.S. Deputy Surveyor, completed the survey of the subdivisional lines.</p> <p>In 1963, C. Albert White and Donald R. Beck, Cadastral Surveyors, resurveyed a portion of the subdivisional lines and remonumented certain original corner points.</p> <p>In 1971, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.</p> <p>In 1976, James E. Jelley, Cadastral Surveyor, resurveyed portions of the south boundary and subdivisional lines.</p> <p>In 1981-82, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 14.</p> <p>In 1991-92, Dale T. Bedell, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 20.</p> <p>In 2000-01, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of north boundary and subdivisional lines and subdivided sections 3, 9, 11, 15 and 33.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated July 24, 2006, for Group No. 2147, Oregon.</p> <p>The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis. The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of the Agriculture, Forest Service.</p>
------	--

T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements and carried forward by means of sustained angulation using conventional survey techniques. Directions along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch X ¼ inch magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations "DCSO CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows:

The ¼ section corner of sections 13 and 18 on the east boundary of the township.

Latitude: 43° 34' 10.49" N. Longitude: 123° 06' 26.41" W.

The corner of sections 19, 24, 25, and 30 on the west boundary of the township.

Latitude: 43° 32' 52.81" N. Longitude: 123° 13' 38.31" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1855-56 survey by Harvey Gordon and
Charles T. Gardner and the 1882 survey by James P. Currin)

Beginning at the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., perpetuated by Marion D. Hale, for Weyerhaeuser Timber Company, in 1957, further perpetuated at the original position of the original corner tree no longer in existence by Vernon Ray Tracy, of the Douglas County Surveyor's Office, in 1965, and further perpetuated by the Lane County Surveyor's Office, in 2003, recorded in the Douglas County Surveyor's Office, Record of Government Corners Renewed, Point Identifier No. 700400, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<pre> T 23 S R4 S 13 S 18 R3 W --- --- W S 24 S 19 1965 </pre>
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole bears N. 79½° E., 9.3 ft. dist., with uprooted sawed fir stump, 32 ins. diam., lying alongside, with no marks visible. (Record, S. 50° E., 7.9 ft.)</p> <p>and the remains of bearing trees mkd. by Hale</p> <p style="padding-left: 40px;">A sawed fir stump, 56 ins. diam., bears S. 88¼° E., 38.5 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed and decayed hemlock stump, 19 ins. diam., bears S. 34° W., 34.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A roothole bears N. 74¼° W., 25.9 ft. dist., with uprooted fir stump, 63 ins. diam., lying alongside, with no marks visible.</p> <p>and the remains of bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A decayed hemlock stump, 18 ins. diam., bears N. 66¼° E., 42.3 ft. dist., with scribe marks BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A decayed hemlock stump, 20 ins. diam., bears S. 4¼° E., 40.2 ft. dist., with scribe marks 23S 3W BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 23 ins. diam., bears S. 66¼° W., 17.8 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Lane County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 49½° E., 16.1 ft. dist., with scribe marks S BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 17 ins. diam., bears S. 46½° E., 61.8 ft. dist., with scribe marks CS BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 39¼° W., 8.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>N. 0° 0' 02" E., bet. secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>Descend over broken NE. slope, posting and blazing.</p>
130	Creek, 4 ft. wide, course East, asc. over SE. slope.
1375	Ridge, bears N. 60° E. and S. 60° W., desc. over NW. slope.
2160	Bottom of descent, slopes N. 45° E.; asc. over SE. slope.

Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
2580	Graveled road, 12 ft. wide, bears N. 65° E. and S. 65° W.
2731.42	<p>The ¼ sec. cor. of secs. 13 and 18, perpetuated by Glen McChesney, for Weyerhaeuser Timber Company, in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 23 S., R. 4 W., Point Identifier No. 700440, determined at record dist. from the original NE. bearing tree and record bearing from McChesney's SW. bearing tree, reported by the Douglas County Surveyor's Office, in 1997, alongside of which is the uprooted original fir corner tree, 56 ins. diam., with fragmentary scribing visible, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 45 ins. diam., bears N. 6½° E., 19.8 ft. dist., with no marks visible. (Record, N. 10° E.)</p> <p>and the remains of bearing trees mkd. by McChesney</p> <p style="padding-left: 40px;">A sawed fir stump, 58 ins. diam., bears N. 23° E., 38.6 ft. dist., with no marks visible, and a W nail in the face.</p> <p style="padding-left: 40px;">A sawed fir stump, 48 ins. diam., bears S. 46° W., 30.9 ft. dist., with a healed blaze, and a W nail in the healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 23 S</p> <p style="margin-left: 40px;">1/4</p> <p>R 4 W R 3 W</p> <p>S 13 S 18</p> <p style="margin-left: 40px;">2006</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 11½ E., 30.5 ft. dist., mkd. 1/4 S18 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 84° W., 21.2 ft. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 17' 22" E., beginning new measurement.</p> <p>Ascend over gentle E. slope, continue posting and blazing.</p>
1950	Spur, slopes N. 50° E., desc. over NW. slope.
2674.83	The corner of secs. 7, 12, 13, and 18, perpetuated by Glen McChesney, for Weyerhaeuser Timber Company, in 1958, further perpetuated by Vernon Ray Tracy, of the Douglas County Surveyor's Office, in 1965, recorded in the Douglas County Surveyors Record of Government Corners Renewed, Point Identifier

**Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

No. 700500, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 23 S	
R 4 W	R 3 W
S 12	S 7
S 13	S 18
1965	

from which the remains of the original bearing trees

A sawed fir stump, 53 ins. diam., bears N. 50° E., 12.5 ft. dist., with a healed blaze.

A sawed cedar stump, 39 ins. diam., bears S. 55° E., 7.9 ft. dist., with a healed blaze.

A burnt cedar snag, 26 ins. diam., bears N. 50° W., 29.7 ft. dist., no marks visible.

and the remains of bearing trees mkd. by McChesney

A fir stump, 52 ins. diam., bears N. 4¾° E., 52.7 ft. dist., with no marks visible, and a W nail in the face.

A cedar, 22 ins. diam., bears S. 49¾° W., 32.9 ft. dist., with no marks visible. We blaze and scribe it X BT.

and a bearing tree mkd. by Tracy

A hemlock, 29 ins. diam., bears N. 25¾° W., 69.3 ft. dist., with a healed double blaze.

and new bearing trees

A fir, 10 ins. diam., bears N. 47° E., 27.6 ft. dist., mkd. T23S R3W S7 BT.

A fir, 13 ins. diam., bears S. 88¾° E., 16.1 ft. dist., mkd. T23S R3W S18 BT.

**Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1851 survey by James E. Freeman, the 1963 remonumentation by C. Albert White and Donald R. Beck, and the 1991-92 resurvey by Dale T. Bedell)

From the cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET

T 23 S	
R 5 W	R 4 W
S 24	S 19
S 25	S 30
1963	
1976	

from which the remains of original bearing trees

A roothole bears N. $26\frac{1}{2}^{\circ}$ E., 25.7 ft. dist., with fallen yew trunk, 12 ins. diam., lying alongside, with no marks visible.

A decayed fir stump, size indeterminate, bears N. $44\frac{1}{2}^{\circ}$ W., 41.6 ft. dist., with no marks visible.

and the remains of an original line tree reported by White and Beck, not utilized as an Angle Point

A decayed fir stump, 55 ins. diam., bears North, 19.8 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by White and Beck

A yew, 11 ins. diam., bears N. $43\frac{1}{4}^{\circ}$ E., 35.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

A yew snag, 16 ins. diam., bears S. 68° W., 16.5 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by White and Beck, reported by Jelley in 1976

A sawed fir stump, 31 ins. diam., bears N. 53° W., 29.0 ft. dist., with a healed blaze.

and bearing trees mkd. by Jelley in 1976

A fir, 20 ins. diam., bears N. 89° E., 8.3 ft. dist., with a healed blaze.

A fir, 22 ins. diam., bears S. $21\frac{1}{4}^{\circ}$ E., 5.9 ft. dist., with a healed blaze.

and new accessories

An iron rod, $\frac{5}{8}$ in. diam., 30 ins. long, driven 29 ins. in the ground for a reference monument, bears S. $43^{\circ} 11' 31''$ W., 10.00 ft. dist., with aluminum cap mkd. RM T23S R5W 10.0 FT TO COR S25 2006, and an arrow pointing to the corner.

An iron rod, $\frac{5}{8}$ in. diam., 30 ins. long, driven 29 ins. in the ground for a reference monument, bears N. $44^{\circ} 22' 35''$ W., 7.90 ft. dist., with aluminum cap mkd. RM T23S R5W 7.9 FT TO COR S24 2006, and an arrow pointing to the corner.

**Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	N. 0° 33' 07" W., bet. secs. 19 and 24, on the W. bdy. of the Tp.
	Descend over broken N. and NW. slope, posting and blazing.
1830	Creek 2 ft. wide, course N. 45° W., asc. over SW. sloe.
2025	Spur, slopes N. 40° W., desc. over NW. slope.
2110	Rock bluff, edge bears S. 80° E. and N. 80° W.
2235	Dirt road, 8 ft. wide, bears N. 45° E. and S. 40° W.
2325	Adams Creek, 5 ft. wide, course S. 45° W., asc. over SE. slope.
2628.15	<p>The ¼ sec. cor. of secs. 19 and 24, perpetuated by Oscar F. Thiel, of the Douglas County Surveyor's Office, in 1927, further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, further perpetuated by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 2002, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 100340, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above the ground, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A madrone sprout, 9 ins. diam., bears S. 21° E., 6.6 ft. dist., with no marks visible. (Record, S. 35° E.)</p> <p style="padding-left: 40px;">A decayed fir stump, 25 ins. diam., bears N. 20° W., 26.4 ft. dist., with axe marks visible.</p> <p>and bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A yew, 10 ins. diam., bears N. 12¼° E., 85.3 ft. dist., with scribe marks 1/4 S19 CS BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 60° W., 12.9 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Smalley</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 12¼° E., 20.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 84° W., 17.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Cement a brass cap, 3 ins. diam., with 3½ in. stem, on top of iron pipe, mkd.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>T 23 S 1/4 R 5 W R 4 W S 24 S 19 2006</p> <hr style="width: 30%; margin: 10px auto;"/>
935	<p>N. 0° 18' 57" E., beginning new measurement. Ascend over broken SE. slope, continue posting and blazing. Spur, slopes S. 35° W., desc. over NW. slope.</p>
1324.12	<p>Point for the N 1/16 sec. cor. of secs. 19 and 24. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 23 S R5W R4W N 1/16 S 24 S 19 2006</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 48¾° E., 30.4 ft. dist., mkd. N 1/16 S19 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 65° W., 35.0 ft. dist., mkd. N 1/16 S24 BT.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post. Discontinue posting and blazing Descend over broken NW. slope.</p>
1335	<p>Barbed wire fence, 5 strand, bears E. and W.</p>
2648.24	<p>The corner of secs. 13, 18, 19, and 24, perpetuated by Gene E. Johnson, Oregon Professional Engineer No. 3561, in 1954, from original evidence no longer in existence, remonumented by Milo E. Godfrey, Deputy County Surveyor, in 1963, further perpetuated by Vernon Ray Tracy, of the Douglas County Surveyor's Office, in 1965, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 100400, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p>
	<p>COUNTY SURVEYORS OFFICE T 23 S R S 13 S 18 R 5 4 W S 24 S 19 W 1963</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of bearing trees mkd. by Johnson, reported by Bedell</p> <p>A decayed fir stump, size indeterminate, bears S. 75° W., 20.5 ft. dist., with no marks visible.</p> <p>A fir, 50 ins. diam., bears N. 60° W., 46.9 ft. dist., with scribe marks T23S R5W S13 visible on the bark.</p> <p>and bearing trees mkd. by Godfrey, reported by Bedell</p> <p>A cedar, 45 ins. diam., bears N. 61° E., 222.4 ft. dist., with a healed blaze.</p> <p>A fir, 51 ins. diam., bears S. 7½° E., 198.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Tracy, reported by Bedell</p> <p>A fir, 60 ins. diam., bears S. 17° W., 180.2 ft. dist., with a healed blaze.</p> <p>Corner falls beneath a barbed wire fence, with fences extending N. and S. Iron post is alongside a wood post, 12 ins. diam., impossible to occupy without destroying wood post.</p>
	<hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/>
	<p>(Restoring the 1884 survey by William P. Wright, the 1885 survey by Harvey Gordon and Charles T. Gardener, the 1976 and 1982 resurveys by James E. Jelley, and the 1991-92 resurvey by Dale T. Bedell)</p> <hr/>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., herein before described.</p> <p>N. 88° 16' 13" W., bet. secs. 13 and 24.</p> <p>Descend over NE. slope, posting and blazing.</p>
160	Creek 2 ft. wide, course N. 5° E., asc. over SE. slope.
245	Spur, slopes N. 50° E., desc. over W. slope.
295	Carlson Creek 3 ft. wide, course N. 40° E., asc. over E. slope.
2767.05	<p>The ¼ sec. cor. of secs. 13 and 24, perpetuated by Marion D. Hale, Oregon Professional Land Surveyor No. 243, in 1957, further perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, date unknown, filed in 1965, further perpetuated by Vernon Ray Tracy, of the Douglas County Surveyor's Office, in 1965, further perpetuated by Donald Le Roy Branch, Oregon Professional Land Surveyor No. 1137, in 1987, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 640400, monumented with an iron post, 1¼ ins.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	COUNTY SURVEYOR OFFICE T 23 S S 13 1/4 ——— S 24 R 4 W 1965
	from which the remains of an original bearing tree
	A fir snag, 17 ins. diam., bears N. 55° E., 15.8 ft. dist., with scribe marks BT visible on a partially opened blaze.
	and the remains of a bearing tree mkd. by Hale
	A sawed fir stump, 32 ins. diam., bears N. 2¼° W., 14.0 ft. dist., with no marks visible.
	and the remains of a bearing tree mkd. by Tracy
	A sawed fir stump, 23 ins. diam., bears N. 21¼° E., 27.4 ft. dist., with scribe marks 1/4 S13 CS BT visible on an open blaze.
	and a bearing tree mkd. by Branch
	A double trunked hemlock, 28 ins. diam., bears S. 24¼° W., 8.1 ft. dist., with a healed blaze.
	and a new bearing tree
	A fir, 10 ins. diam., bears N. 83½° E., 23.1 ft. dist., mkd. 1/4 S13 BT.

	N. 89° 05' 44" W., beginning new measurement.
	Descend over broken SW. slope, continue posting and blazing.
1480	Spring branch 1 ft. wide, course N. 25° W., continue desc. over NW. slope.
1830	Spring branch 2 ft. wide, course N. 70° W., continue desc. over NW. slope.
1925	Abandoned dirt road, 10 ft. wide, bears S. 10° E. and N. 10° W.
2070	Abandoned dirt road, 10 ft. wide, bears N. 5° E. and S. 5° W.
2582.79	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2½ ins. diam., flush with the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET									
	<table border="1"> <tr> <td>T 23 S</td> <td>R 4 W</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1971</td> </tr> </table>	T 23 S	R 4 W	S 14	S 13	S 23	S 24	1971	
T 23 S	R 4 W								
S 14	S 13								
S 23	S 24								
1971									
	<p>from which the remains of bearing trees mkd. by Wilford N. Haines, Registered Professional Land Surveyor No. 239, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 600400, reported by Jelley in 1981-82</p> <p>A tin-capped, sawed fir stump, 22 ins. diam., bears N. 9½° E., 38.0 ft. dist., with scribe marks T23S R4W1 visible on the bark.</p> <p>A sawed and decayed fir stump, 24 ins. diam., bears S. 17¼° E., 28.1 ft. dist., with no marks visible.</p> <p>A tin-capped, sawed fir stump, 23 ins. diam., bears S. 55° W., 63.0 ft. dist., with no marks visible.</p> <p>A tin-capped, sawed and decayed fir stump, 13 ins. diam., bears N. 74½° W., 8.6 ft. dist., with no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 7 ins. diam., bears N. 12¾° E., 12.6 ft. dist., mkd. T23S R4W S13 BT.</p> <p>A fir, 10 ins. diam., bears S. 62¾° E., 5.8 ft. dist., mkd. T23S R4W S24 BT.</p> <p>A fir, 6 ins. diam., bears S. 33¾° W., 29.9 ft. dist., mkd. T23S R4W S23 BT.</p> <p>A fir, 10 ins. diam., bears N. 23° W., 7.4 ft. dist., mkd. T23S R4W S14 BT.</p> <hr/> <p>N. 0° 37' 26" E., bet. secs. 13 and 14.</p> <p>Descend over broken W. slope, posting and blazing.</p> <p>130 Creek 3 ft. wide, course N. 65° W., asc. over W. slope.</p> <p>220 Spur, slopes W., desc. over W. slope.</p> <p>1317.54 The S 1/16 sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1"> <tr> <td>S 1/16</td> <td></td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td colspan="2" style="text-align: center;">1971</td> </tr> </table> </p> <p>from which the remains of bearing trees mkd. by Jelley in 1971</p>	S 1/16		S 14	S 13	1971			
S 1/16									
S 14	S 13								
1971									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A roothole bears N. 46° E., 21.1 ft. dist., with fallen decayed fir trunk, 13 ins. diam., lying alongside, with no marks visible.</p> <p>A fir, 14 ins. diam., bears S. 43½° W., 5.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 20 ins. diam., bears S. 78¼° E., 33.4 ft. dist., mkd. S 1/16 S13 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 46' 29" E., beginning new measurement.</p> <p>Descend over broken NW. slope, continue posting and blazing.</p>
1317.95	<p>The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S R 4 W 1/4 S 14 S 13 1971</p> </div> <p>from which a bearing tree mkd. by Jelley in 1971</p> <p>A fir, 19 ins. diam., bears N. 55¼° E., 15.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Jelley in 1971, reported by Jelley in 1981-82</p> <p>A fir, 15 ins. diam., bears S. 46° W., 14.2 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 46' 39" E., beginning new measurement.</p> <p>Descend over broken NW. slope, continue posting and blazing.</p>
1319.21	<p>The N 1/16 sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N 1/16 S 14 S 13 1971</p> </div> <p>from which the remains of bearing trees mkd. by Jelley in 1971</p> <p>A fir, 19 ins. diam., bears N. 84° E., 9.9 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 22 ins. diam., bears N. 59° W., 12.2 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 8¼° E., 25.3 ft. dist., mkd. X BT.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of Tp., hereinbefore described.</p> <p>N. 89° 48' 25" W., between secs. 12 and 13.</p> <p>Descend over broken NW. slope, posting and blazing.</p>
1318.68	<p>The E 1/16 sec. cor. of secs. 12 and 13, established by Wilford N. Haines, Registered Professional Land Surveyor No. 239, in 1963, recorded in the Douglas County Surveyor's Office, Map File No. M26-80, and is accepted as the corner, monumented with a "T" iron, 1 in. diam., firmly set, projecting 9 ins. above the ground, with no cap, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A hemlock, 26 ins. diam., bears N. 78¼° E., 25.6 ft. dist., with scribe marks 1/16 S12 visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 19 ins. diam., bears N. 88° W., 22.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the "T" iron, with brass cap mkd.</p> <p>Note: Talked w/Tim Moore Rsbj BLM BC should be marked for</p> <div style="text-align: center; padding-left: 40px;"> <p>E 1/16</p> <p>S 13</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 24</p> <p>2006</p> </div> <p>Sections 12 & 13 not 13 & 24 4/8/2008 JC DCSO</p>
1323.87	<p>from which a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 11 ins. diam., bears S. 42° W., 46.4 ft. dist., mkd. E 1/16 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 52' 04" W., beginning new measurement.</p> <p>Continue desc. over broken NW. slope, posting and blazing.</p> <p>The ¼ sec. cor. of secs. 12 and 13, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1961, further perpetuated by Vernon Ray Tracy, of the Douglas County Surveyor's Office, in 1965, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 640500, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above the ground, with no cap, from which the remains of an original bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, size indeterminate, bears S. 14° W., 11.2 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Haines</p> <p>A decayed fir stump, size indeterminate, bears S. 13½° E., 61.1 ft. dist., with no marks visible.</p> <p>A sawed cedar stump, 30 ins. diam., bears N. 25½° W., 48.1 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Tracy</p> <p>A sawed fir stump, 22 ins. diam., bears S. 61½° W., 38.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4W S 12 1/4 ——— S 13 2006</p> <p>from which new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 35½° E., 41.0 ft. dist., mkd. 1/4 S12 BT.</p> <p>A fir, 14 ins. diam., bears S. 78° E., 79.3 ft. dist., mkd. 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the ¼ sec. cor. of secs. 19 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 19 1/4 ——— S 30 T23S R4W 1976</p> <p>from which the remains of a bearing tree mkd. by Oscar F. Thiel, Registered Professional Land Surveyor No. 4, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 140300, reported by Jelley in 1976</p> <p>A broken decayed fir stump, 30 ins. diam., bears S. 82½° W., 19.5 ft. dist., with fragmentary scribe marks visible on an opened blaze.</p> <p>and bearing trees mkd. by Jelley in 1976</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET																		
	<p>A fir, 25 ins. diam., bears N. 59° E., 7.3 ft. dist., with a healed blaze.</p> <p>A fir, 24 ins. diam., bears S. 60° W., 57.4 ft. dist., with a healed blaze.</p> <p>N. 89° 50' 45" W., between secs. 19 and 30.</p> <p>Descend over broken NW. slope, posting and blazing.</p>																	
1330	Ravine, drains N. 30° W., asc. over NE. slope.																	
1580	Dirt road, 8 ft. wide, bears S. 60° E. and N. 60° W.																	
2774.08	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.																	
	<hr/> <p>From the ¼ sec. cor. of secs. 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4</p> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">S 19</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S 20</td> </tr> <tr> <td style="padding: 0 10px;">T23S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">R4W</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 10px;">1976</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A decayed fir stump, 28 ins. diam., bears N. 46½° E., 26.3 ft. dist., with no marks visible. (Record, N. 50° E., 24.4 ft. dist.)</p> <p>A decayed fir stump, 44 ins. diam., bears S. 20° W., 2.0 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by Jelley in 1976</p> <p>A fir, 17 ins. diam., bears N. 35¼° E., 17.8 ft. dist., with a healed double blaze.</p> <p>A fir, 21 ins. diam., bears N. 35¼° W., 17.2 ft. dist., with a healed double blaze.</p> <p>N. 1° 38' 17" W., bet. secs. 19 and 20.</p> <p>Descend over N. slope, posting and blazing.</p> <tr> <td data-bbox="201 1583 375 1631">615</td> <td data-bbox="375 1583 1450 1631">Creek, 2 ft. wide, course N. 20° W., asc. over SW. slope.</td> </tr> <tr> <td data-bbox="201 1631 375 1680">1495</td> <td data-bbox="375 1631 1450 1680">Spur, slopes S. 60° W., desc. over NW. slope.</td> </tr> <tr> <td data-bbox="201 1680 375 1728">2485</td> <td data-bbox="375 1680 1450 1728">Adams Creek, 1 ft. wide, course N. 50° W., asc. over SE. slope.</td> </tr> <tr> <td data-bbox="201 1728 375 1961">2667.31</td> <td data-bbox="375 1728 1450 1961">The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, (alongside of which is an axle, 1¼ ins. diam., splines up, firmly set, projecting 5 ins. above the ground, origin unknown), with brass cap mkd.</td> </tr>	S 19		S 20	T23S		R4W	1976			615	Creek, 2 ft. wide, course N. 20° W., asc. over SW. slope.	1495	Spur, slopes S. 60° W., desc. over NW. slope.	2485	Adams Creek, 1 ft. wide, course N. 50° W., asc. over SE. slope.	2667.31	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, (alongside of which is an axle, 1¼ ins. diam., splines up, firmly set, projecting 5 ins. above the ground, origin unknown), with brass cap mkd.
S 19		S 20																
T23S		R4W																
1976																		
615	Creek, 2 ft. wide, course N. 20° W., asc. over SW. slope.																	
1495	Spur, slopes S. 60° W., desc. over NW. slope.																	
2485	Adams Creek, 1 ft. wide, course N. 50° W., asc. over SE. slope.																	
2667.31	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, (alongside of which is an axle, 1¼ ins. diam., splines up, firmly set, projecting 5 ins. above the ground, origin unknown), with brass cap mkd.																	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 23 S</td> <td style="padding: 0 5px;">R 4 W</td> </tr> <tr> <td style="padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1976</td> </tr> </table> </div> <p>from which the remains of the original bearing trees, rescribed by James W. Byron, of the Douglas County Surveyor's Office, in 1959, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 200400 reported by Jelley in 1976</p> <p style="margin-left: 40px;">A sawed fir stump, 40 ins. diam., bears N. 47° E., 54.8 ft. dist., with scribe marks T23S R4W S17 CS visible on a partially healed blaze.</p> <p style="margin-left: 40px;">A decayed fir snag, 14 ins. diam., bears S. 69¼° E., 48.2 ft. dist., with scribe marks R4W S20 CS visible on partially healed blaze.</p> <p style="margin-left: 40px;">A sawed and decayed fir stump, 45 ins. diam., bears S. 59° W., 25.1 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A fir, 31 ins. diam., bears N. 69° W., 31.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Vernon Ray Tracy, of the Douglas County Surveyor's Office, in 1965, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 200400, reported by Jelley in 1976</p> <p style="margin-left: 40px;">A cedar, 32 ins. diam., bears N. 3½° E., 260.7 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S. 84¼° W., 80.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and bearing trees mkd. by Jelley in 1976</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 27¼° E., 31.7 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 55¼° E., 21.5 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears S. 4° W., 13.2 ft. dist., with a healed blaze.</p> <p>Corner is located at cor. of barbed wire fences extending N. and W.</p> <hr style="width: 60%; margin-left: 0;"/> <p style="margin-left: 40px;">N. 89° 42' 16" W., between secs. 18 and 19.</p> <p style="margin-left: 40px;">Descend over broken SW. slope, posting and blazing.</p>	T 23 S	R 4 W	S 18	S 17	S 19	S 20	1976	
T 23 S	R 4 W								
S 18	S 17								
S 19	S 20								
1976									
1915	<p style="margin-left: 40px;">Spur, slopes S., continue desc. over SW. slope.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET 2683.83	<p>Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T23S R4W S 18 1/4 ——— S 19 2006</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 69¼° E., 43.6 ft. dist., mkd. 1/4 S18 BT.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 39¼° E., 15.7 ft. dist., mkd. 1/4 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located N. 31° W., 15.2 ft. dist. from a fence cor., with barbed wire fences extending E. and S.</p> <p>Discontinue posting and blazing.</p> <p>Continue descending over W. slope.</p>
5370.34	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <div style="text-align: center; margin-left: 100px;"> <p>Subdivision of Section 13, T. 23 S., R. 4 W., Willamette Meridian, Oregon</p> </div> <hr style="width: 80%; margin: 10px auto;"/> <p>From the ¼ sec. cor. of secs. 13 and 24, hereinbefore described.</p> <p>N. 1° 28' 15" E., on the N. and S. centerline of sec. 13.</p> <p>Descend over broken NE. slope.</p>
2663.06	<p>Point for the center ½ sec. cor. of sec. 13, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T 23 S R 4 W C 1/4 S 13 2006</p> </div> <p>from which</p>

Subdivision of Section 13,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 16 ins. diam., bears N. 62½° E., 6.5 ft. dist., mkd. C 1/4 S13 BT.</p> <p>A fir, 16 ins. diam., bears S. 17¼° E., 6.8 ft. dist., mkd. C 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Descend over broken NW. slope.</p>
3070	Creek 2 ft. wide, course S. 40° W., asc. over SW. slope.
3996.81	<p>The center N 1/16 sec. cor. of sec. 13, established by Leslie D. Roberts, Oregon Professional Land Surveyor No. 1039, in 1997, recorded in the Douglas County Surveyor's Office, Map File No. M127-75, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with yellow plastic cap mkd. ROBERTS SURV. INC., from which bearing trees mkd. by Roberts</p> <p>A cedar, 38 ins. diam., bears S. 82½° E., 17.9 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 7¼° W., 13.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16 S 13 C 2006</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 1° 26' 20" E., beginning new measurement.</p> <p>Descend over W. slope, posting and blazing.</p>
1335.12	<p>The ¼ sec. cor. of secs. 12 and 13, hereinbefore described.</p> <hr/> <p>From the ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 41' 47" W., on the E. and W. centerline of sec. 13.</p> <p>Ascend over an E. slope, changing to desc. over broken NW. slope.</p>
2697.16	<p>The center ¼ sec. cor. of sec. 13, hereinbefore described.</p> <p>Continue descending over broken NW. slope.</p>

Subdivision of Section 13,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET 5315.55	<p>The ¼ sec. cor. of secs. 13 and 14, hereinbefore described.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 13, hereinbefore described.</p> <p>S. 89° 59' 33" W., on the E. and W. centerline of the NW¼ of sec. 13.</p> <p>Descend over broken NW. slope, posting and blazing.</p>
2634.53	<p>The N 1/16 sec. cor. of secs. 13 and 14, hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 19 T. 23 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 19 and 30, hereinbefore described.</p> <p>N. 1° 03' 42" W., on the N. and S. centerline of sec. 19.</p> <p>Descend over NE. slope, posting and blazing.</p>
610	<p>Creek, 2 ft. wide, course N. 70° W., asc. over W. slope.</p>
2612.91	<p>Point for the center ¼ sec. cor. of sec. 19, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W C 1/4 S 19 2006</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 6¼° E., 3.8 ft. dist., mkd. C 1/4 S19 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 67¾° E., 9.3 ft. dist., mkd. C 1/4 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <p>Descend over NW. slope.</p>
3870	<p>Adams Creek, 5 ft. wide, course S. 75° W., asc. over SW. slope.</p>
3941.82	<p>Point for the center N 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 30 ins. base, to top, with brass cap mkd.</p>

Subdivision of Section 19,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>C N 1/16 S 19 C 2006</p>
	<p>from which</p> <p style="padding-left: 40px;">An alder, 11 ins. diam., bears S. 39° E., 5.3 ft. dist., mkd. C N 1/16 S19 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 54¼° W., 15.4 ft. dist., mkd. C N 1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend over broken SW. slope, posting and blazing.</p>
5270.73	<p>The ¼ sec. cor. of secs. 18 and 19, hereinbefore described.</p> <hr/> <p>From the ¼ sec. cor. of secs. 19 and 20, hereinbefore described. N. 89° 31' 13" W., on the E. and W. centerline of sec. 19.</p> <p>Ascend over broken NE. slope, posting and blazing.</p>
315	<p>Spur, slopes N., desc. over NW. slope.</p>
1035	<p>Spur, slopes N. 5° W., desc. over NW. slope.</p>
1480	<p>Dirt road, 8 ft. wide, bears N. 65° E. and S. 65° W.</p>
2655	<p>Dirt road, 8 ft. wide, bears N. 40° E. and S. 40° W.</p>
2711.22	<p>The center ¼ sec. cor. of sec. 19, hereinbefore described.</p> <p>Discontinue posting and blazing.</p> <p>Descend over NW. slope.</p>
5461.96	<p>The ¼ sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 19, hereinbefore described. N. 89° 36' 41" W., on the E. and W. centerline of the NW¼ of sec. 19.</p> <p>Ascend over broken SE. slope, posting and blazing.</p>
430	<p>Spur, slopes S., desc. over SW. slope.</p>
2718.62	<p>The N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/>

T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	GENERAL DESCRIPTION
	<p>The lands included in the foregoing resurvey are located in Douglas County, approximately 10 miles southeast of the town of Yoncalla, Oregon. The terrain is mountainous. Elevations range from approximately 650 feet above sea level, near the E 1/16 section corner of sections 4 and 9, to about 1650 feet above sea level, near the corner of sections 1, 2, 11, and 12.</p> <p>The area is drained by numerous small and seasonal drainages flowing into Elk Creek. The timber consists of fir, cedar, hemlock, alder, maple, oak, chinquapin, pine, ash, yew, and madrone. The undergrowth is mainly scotch broom, salal, Oregon grape, manzanita, arrowwood, poison oak, vine maple, ferns, and young timber.</p> <p>Access is by logging roads branching from Douglas County Road No. 7, "Elk Head Road".</p> <p>No mineral deposits were noted along the lines resurveyed. The lands are used primarily for timber production.</p>