

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
AND CERTAIN LINES OF DONATION LAND CLAIM NO. 38,
AND THE SUBDIVISION OF SECTIONS 34 AND 35
TOWNSHIP 32 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Richard J. Dieckmann, Cadastral Surveyor

Under Special Instructions dated July 15, 2005, approved July 19, 2005,
which provided for the surveys included under Group No. 2125,
and Assignment Instructions dated July 24, 2006.

Survey commenced July 26, 2006

Survey completed February 12, 2007

T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and certain lines of Donation Land Claim (DLC) No. 38, and the subdivision of sections 34 and 35, Township 32 South, Range 6 West, Willamette meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1855, Wells Lake and George W. Hyde, U.S. Deputy Surveyors, surveyed the north boundary (Seventh Standard Parallel South) for T. 33 S., R. 6 W. In the same year they also resurveyed this north boundary for the south boundary of T. 32 S., R. 6 W., making the corners along this boundary equal in control, and surveyed a portion of the subdivisional lines.

In 1856, J. A. Burnett, Deputy Surveyor, surveyed DLC No. 38.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1966-67, Rollin D. Aanrud, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 15.

In 1976, Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, resurveyed a portion of the subdivisional lines.

In 1980, Rollin D. Aanrud, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1986-89, Mark D. Dixon and Henry E. Hartley, Cadastral Surveyors, resurveyed and correctively resurveyed portions of the subdivisional lines.

In 2005, Francis J. Simon, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 21, concurrently under this same Group.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 15, 2005, for Group No. 2125, Oregon.

The directions of the lines are based on the true meridian as determined by direct GPS observation. They were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

The survey was performed using a combination of Global Positioning System (GPS) satellite techniques and terrestrial measured distances and directions. The GPS measurements utilized dual frequency carrier phase receivers NAVSTAR Global Positioning System static data and NGS Online Positioning User Service (OPUS) with NSRS CORS stations.

Terrestrial measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted data assured a closure not

T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET

exceeding 1:4000 in error. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Lines which represent Bureau of Land Management (BLM) property boundaries were blazed, painted, and tagged with BLM boundary signs.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983(CORS96)) of the ¼ section corner of section 35 only, on the south boundary of the township, as determined by a conventional tie to a temporary point, established utilizing NAVSTAR GPS static data and NGS Online Positioning User Service (OPUS) with NSRS CORS stations, "CAPE MENDOCINO 1", "KALMATH FALLS 1", and "APPLETON", is as follows:

Latitude: 42° 44' 22.32" N. Longitude: 123° 22' 38.12" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

(Restoring the survey by Wells Lake and George W. Hyde in 1855)

Beginning at the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., perpetuated by George J. Wenderoth, Douglas County Deputy Surveyor, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 47/7, further perpetuated by the Douglas County Surveyor's Office, in 1967, recorded per file C.S. 54/53, further perpetuated by John E. Hollingsworth, Registered Land Surveyor No. 691, in 1988, recorded per files C.S. 63/62-2D and M107-16, and utilized by various Oregon Professional Surveyors; monumented with an iron pipe, 1 in. diam. firmly set, projecting 10 ins. above the ground, with a plastic yellow cap set inside the top, mkd. OREGON STATE PARKS from which an original bearing tree

A Douglas fir, 54 ins. diam., bears N. 57¼° W.,
9.2 ft. dist., with a healed blaze. (Record, N. 40° W.)

and a bearing tree mkd. by Wenderoth

A Douglas fir snag, 18 ins. diam., bears N. 59° E.,
66.1 ft. dist., with fragmentary scribe marks visible on
a rotting blaze.

and bearing trees mkd. by the Douglas County Surveyor's Office

A Douglas fir, 28 ins. diam., bears N. 82¼° E.,
37.9 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A Douglas fir, 37 ins. diam., bears N. 35½° W., 34.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W S 35 S 36</p> <p style="text-align: center;">T 33 S R 6 W S2 2006</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, the standard cor. of secs. 1 and 2 on the N. bdy. of T. 33 S., R. 6 W., bears N. 89° 35' 03" E., 200.23 ft. dist., perpetuated by George J. Wenderoth, Douglas County Deputy Surveyor, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 47/7, further perpetuated by John E. Hollingsworth, Registered Land Surveyor No. 691, in 1988, recorded per files C.S. 63/62-2E and M107-16, utilized by various Oregon Professional Surveyors, monumented with an iron pipe, 1 in. diam., firmly set, projecting 14 ins. above the ground, with a plastic yellow cap set inside the top, mkd. OREGON STATE PARKS, from which the remains of the original bearing trees</p> <p style="text-align: center;">A decayed Douglas fir stump, of indeterminate size, bears S. 75° E., 21.8 ft. dist., no marks visible.</p> <p style="text-align: center;">A decayed Douglas fir stump, of indeterminate size, bears S. 33° W., 13.2 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Wenderoth</p> <p style="text-align: center;">A broken off Douglas fir snag, 15 ins. diam., bears N. 83½° E., 77.0 ft. dist., with fragmentary scribe marks visible on a rotting blaze.</p> <p style="text-align: center;">A maple, 17 ins. diam., bears S. 10¼° W., 56.1 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Hollingsworth</p> <p style="text-align: center;">A Douglas fir, 15 ins. diam., bears S. 78¼° E., 22.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET					
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 33 S</td> <td style="padding: 0 5px;">R 6 W</td> </tr> </table> <p style="text-align: center;">SC 2006</p>	S 2	S 1	T 33 S	R 6 W
S 2	S 1				
T 33 S	R 6 W				
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Also from the corner of secs. 35 and 36 only, the standard ¼ sec. cor. of sec. 2, on the N. bdy. of T. 33 S., R. 6 W., bears, N. 89° 39' 53" W., 2450.78 ft. dist, reestablished by proportionate measurement, by John E. Hollingsworth, Registered Land Surveyor No. 691, in 1988, recorded in the Douglas County Surveyor's Office per files C.S. 63/62-2B and M107-16, utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron post 1¼ ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap 2½ ins. diam., mkd.</p> <p style="text-align: center;">OREGON STATE PARKS T 32 S R 6 W</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">1/4 S 2</td> </tr> <tr> <td style="padding: 0 5px;">T 33 S R 6 W</td> </tr> </table> 1988 LS 691 </p> <p>From this corner, a point established as the ¼ sec. cor. of sec. 2 by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/294C and M49-21, bears N. 38° 03' E., 2.60 ft. dist., monumented with an iron rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, and was not used for control in this survey, from which bearing trees mkd. by Brandt</p> <p style="margin-left: 40px;">A Douglas fir, 18 ins. diam., bears S. 45° E., 29.1 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A sawed Douglas fir stump, 19 ins. diam., bears S. 25¼° W., 18.7 ft. dist., with a healed blaze.</p> <p>N. 0° 14' 48" W., bet. secs. 35 and 36.</p>	1/4 S 2	T 33 S R 6 W		
1/4 S 2					
T 33 S R 6 W					
160	A ravine, 3 ft. wide, drains West.				
1323.15	From this point, a point established by person(s) unknown, bears West, 3.84 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a 3½ ins. square post, firmly set, projecting 2.5 ft. above the ground, on the Northwest side of the iron rod, approximately 8 ins. away.				
2585	The top of a ridge, 10 ft. wide, bears E. and W.				
2650.65	Point for the ¼ sec. cor. of secs. 35 and 36 at proportionate distance, there is no remaining evidence of the original cor.				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W 1/4 S 35 S 36 2006</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 89° E., 67.5 ft. dist., mkd. X at breast height, BT at the base.</p> <p style="padding-left: 40px;">An incense cedar, 4 ins. diam., bears S. 74° W., 71.5 ft. dist., mkd. X at breast height, BT at the base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
2935	The Southern edge of pavement of Interstate Highway No. 5 Northbound, bears N. 42° E. and S. 42° W.
3095	The Southern edge of pavement of Interstate Highway No. 5 Southbound, bears N. 42° E. and S. 42° W.
3160	The Northern edge of pavement of Interstate Highway No. 5 Southbound, bears N. 42° E. and S. 42° W.
3270	The left bank of Cow Creek, 35 ft. wide, course S. 40° W.
3820	The right bank of Cow Creek, course S. 20° E.
3940	The left bank of Cow Creek, course S. 20° E.
4715	The left bank of Cow Creek, course S. 31° W.
4840	The right bank of Cow Creek, course S. 31° W.
5301.30	<p>The cor. of secs. 25, 26, 35, and 36, reestablished by proportionate measurement by Henry W. Lawrence, Registered Engineer No. 1543, in 1953, recorded in the Douglas County Surveyor's Office per file C.S. 41/128, further perpetuated by George J. Wenderoth, Douglas County Deputy Surveyor, in 1955, recorded per files C.S. 46/141 and M 7-19, and further perpetuated by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1977, recorded in the Douglas County Surveyor's Office per files C.S. 58/125 and M66-26, and utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original, therefore this position is accepted as the cor.; monumented with an iron rod, 1 in. diam., firmly set, projecting 3 ins. above the ground, from which bearing trees mkd. by Brandt</p> <p style="padding-left: 40px;">A black cottonwood, 25 ins. diam., bears S. 59° W., 57.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A black cottonwood, 19 ins. diam., bears N. 60° W., 56.5 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEEET

A black cottonwood, 22 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ E., 39.2 ft. dist., no marks visible on a partially healed blaze.

A black cottonwood, 13 ins. diam., bears S. $32\frac{1}{4}^{\circ}$ E., 120.6 ft. dist., with no marks visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 32 S	R 6 W
S 26	S 25
S 35	S 36
2006	

Deposit a magnet in a white plastic case at the base of the stainless steel post.

The cor. is located in a fence line, bears N. and S.

From this corner, a point established as a witness cor. by Lawrence and perpetuated by Wenderoth, bears N. $0^{\circ} 08' 00''$ W., 330.30 ft. dist., this point now functions as a reference monument, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, upper 12 ins. bent to the North and flush with the ground, from which a bearing tree mkd. by Lawrence

A black oak, 39 ins. diam., bears S. 58° W., 20.5 ft. dist., with a cut out blaze that has partially healed over.

Also from the cor. of secs. 25, 26, 35, and 36, the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, bears N. $89^{\circ} 38' 05''$ W., 2629.69 ft. dist., perpetuated from original evidence, no longer in existence, by W. F. Briggs, in 1873, and filed in the Douglas County Surveyor's Office per Vol. 0 P. 107, and further perpetuated by the Douglas County Surveyor's Office in 1953 and 2005, per files C.S. 45/249 and M9-19, and C.S. 67/10-19 respectively, and utilized by various Oregon Professional Surveyors, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, buried 8 ins. below the ground, with a brass cap $2\frac{1}{2}$ ins. diam., mkd.

COUNTY SURVEYORS

1/4 S

SEC 26

SEC 35

1953

OFFICE

from which a bearing tree mkd. by Briggs

A white oak, 26 ins. diam., bears N. $30\frac{3}{4}^{\circ}$ W., 293.7 ft. dist., mkd. with a healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>and a bearing tree mkd by the Douglas County Surveyor's Office in 1953</p> <p style="padding-left: 40px;">A white oak, 27 ins. diam., bears S. 45¼° E., 102.2 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office in 2005</p> <p style="padding-left: 40px;">A white oak, 24 ins. diam., bears S. 63½° W., 46.0 ft. dist., with scribe marks 1/4 S35 CS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.</p> <hr/> <p>From the ¼ sec. cor. of secs. 34 and 35, restored by person(s) unknown, recovered by J. Elmer Nelson, Registered Engineer No. 126, in 1949, recorded in the Douglas County Surveyor's Office per file Volume 9, page 15, utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original cor.; therefore this position is accepted as the cor.; monumented with an iron pipe, ¾ in. diam., firmly set, flush with the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 6 W</p> <p>1/4</p> <p>S 34 S 35</p> <p>2006</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 62° E., 127.1 ft. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A white oak, 12 ins. diam., bears N. 43° W., 64.3 ft. dist., mkd. 1/4 S34 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The corner is located in a fence line, bears N. and S.</p> <p>N. 0° 15' 13" W., bet. secs. 34 and 35.</p>
54.73	From this point, a point established by person(s) unknown, bears West, 0.39 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 ins. above the ground.
85	The center line of pavement of Douglas County Road No. 12 (Azalea-Glendale Road), 21 ft. wide, bears N. 69° E. and S. 69° W.
119.38	From this point, a point established by person(s) unknown, bears West, 1.28 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET					
914.29	From this point, a point established by person(s) unknown, bears West, 11.77 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground.				
918.91	A point established by Max Hull, Registered Land Surveyor No. 901, recorded in the Douglas County Surveyor's Office per files C.S. 55/288 R.M. 2-58, in 1973, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with a plastic yellow cap mkd. HULL RS 901.				
1328.86	Point for the N 1/16 sec. cor. of secs. 34 and 35, no permanent monument established.				
2166.69	Intersect the N. bdy. of DLC No. 38, from which the NW. corner of the claim, bears N. 89° 53' 29" W., 1049.51 ft. dist., hereinafter described.				
2657.72	The cor. of secs. 26, 27, 34, and 35, perpetuated by Milo E. Godfrey, Douglas County Deputy Surveyor, in 1964, recorded in the Douglas County Surveyor's Office per file C.S. 49/91; monumented with an iron post, 1½ ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.				
<p>COUNTY SURVEYORS OFFICE</p> <p>T 32 S</p> <table border="1" style="margin: auto;"> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table> <p>R 6 W</p> <p>1964</p>		S 27	S 26	S 34	S 35
S 27	S 26				
S 34	S 35				
from which the remains of an original bearing tree					
<p style="padding-left: 40px;">A root hole with a dead and downed rotting black oak of indeterminate size lying nearby, bears N. 85° W., 82.5 ft. dist., with a visible scar on a rotted healed blaze.</p>					
and bearing trees mkd. by Godfrey					
<p style="padding-left: 40px;">A Douglas fir, 21 ins. diam., bears N. 3° E., 17.0 ft. dist., mkd. with a healed blaze.</p>					
<p style="padding-left: 40px;">A Douglas fir, 24 ins. diam., bears S. 48° E., 9.0 ft. dist., mkd. with a healed blaze.</p>					
<p style="padding-left: 40px;">A Douglas fir, 18 ins. diam., bears S. 45° W., 2.1 ft. dist., mkd. with a healed blaze.</p>					
<p style="padding-left: 40px;">A Douglas fir, 15 ins. diam., bears N. 21° W., 11.4 ft. dist., mkd. with a healed blaze.</p>					
<hr/>					
From the ¼ sec. cor. of secs. 26 and 35.					
S. 89° 51' 47" W., bet. secs. 26 and 35.					

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
1311.93	<p>The W 1/16 sec. cor. of secs. 26 and 35, established by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1977, recorded in the Douglas County Surveyor's Office per files C.S. 58/125-2C and M66-26, and is accepted as the cor.; monumented with an iron rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees mkd. by Brandt</p> <p style="padding-left: 40px;">A sawed Douglas fir stump, 25 ins. diam., bears N. 7½° E., 17.2 ft. dist., with scribe marks 1/16 S26 PS841 BT visible on open blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 23 ins. diam., bears S. 21¾° W., 25.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{S } 26 \\ \text{W } 1/16 \text{ ---} \\ \text{S } 35 \\ 2006 \end{array}$ </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A Douglas fir, 8 ins. diam., bears N. 33¼° W., 31.8 ft. dist., mkd. W1/16 S26 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 51' 59" W., beginning new measurement.</p>
1312.32	<p>The cor. of secs. 26, 27, 34, and 35.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 89° 47' 35" W., bet. secs. 27 and 34.</p>
1324.22	<p>Point for the E 1/16 sec. cor. of secs. 27 and 34. No permanent monument established.</p>
2648.44	<p>The ¼ sec. cor of secs. 27 and 34, established by proportionate measurement, by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 42/327, and utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original cor.; therefore this position is accepted as the cor.; monumented with an iron pipe, 1¼ ins. diam. firmly set, projecting 10 ins. above the ground, from which bearing trees mkd. by Lawrence</p> <p style="padding-left: 40px;">A Douglas fir, 32 ins. diam., bears N. 21¼° E., 42.1 ft. dist., with visible bark scribes 1/4S at breast height and BT near the base.</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 23° W., 29.2 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W S 27 1/4 ——— S 34 2007</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A Douglas fir, 24 ins. diam., bears S. 30¾° W., 32.8 ft. dist., mkd. 1/4 S34 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' 53" W., beginning new measurement.</p>
1324.09	<p>The W 1/16 sec. cor. of secs. 27 and 34, established by Richard G. Templin, Registered Land Surveyor No. 2359, in 1990, recorded in the Douglas County Surveyor's Office per files C.S. 63/103-1 and M109-77, and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above the ground, with a chewed plastic faded yellow cap, from which bearing trees mkd. by Templin</p> <p style="padding-left: 40px;">A broken top Douglas fir snag, 7 ins. diam., bears N. 78¾° E., 12.7 ft. dist., with scribe marks W1/16 S27 visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 14 ins. diam., bears S. 25° E., 9.2 ft. dist., with healed upper and lower blazes.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 51' 41" W., beginning new measurement</p>
970	<p>The center line of pavement of Windy Creek Road, 22 ft. wide, bears N. 20° E. and S. 20° W.</p>
1325.64	<p>The corner of sections 27, 28, 33, and 34, perpetuated from original evidence no longer in existence, by J. W. Cole, in 1923, recorded in the Douglas County Surveyor's Office per files C.S. 7/5B and Volume 3, page 162, further perpetuated by the Douglas County Surveyor's Office in 1967, per file C.S. 54/53, utilized by various Oregon Professional Surveyors, monumented with an axel, 2 ins. diam. projecting 3 ins. above the ground, from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1967</p> <p style="padding-left: 40px;">A decayed ponderosa pine stump, 36 ins. diam., bears North, 160.0 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A Douglas fir, 31 ins. diam., bears S. 27¾° E., 13.7 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET

An ash, 15 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 36.9 ft. dist., with a healed blaze

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, directly over the inverted axel, with brass cap mkd.

T 32 S	R 6 W
S 28	S 27
S 33	S 34
2006	

from which new bearing trees

A grand fir, 5 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., 21.7 ft. dist., mkd. X at breast height and BT at the base.

A maple, 9 ins. diam., bears N. $17\frac{3}{4}^{\circ}$ W., 36.8 ft. dist., mkd. T32S R6W S28 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, perpetuated from original evidence, no longer in existence, by the Douglas County Surveyor's Office, in 1949, 1958, and 2006, recorded per files C.S. 43/134, 49/91, and 67/14-35 respectively, and utilized by various Oregon Professional Surveyors, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with a $2\frac{1}{2}$ ins. diam. brass cap mkd.

T 32 S	
	1/4
R 6 W	S 34
S 33	
2006	

from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1949

A sawed white oak stump, 13 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ W., 44.8 ft. dist., no marks visible.

and a bearing tree mkd. by the Douglas County Surveyor's Office in 1958



A white oak, 17 ins. diam., bears S. $89\frac{3}{4}^{\circ}$ W., 107.6 ft. dist., with a healed upper and lower blazes.

and bearing trees mkd. by the Douglas County Surveyor's Office in 2006

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

F E E T	<p>A ponderosa pine, 12 ins. diam., bears S. 19½° E., 24.8 ft. dist., with scribe marks 1/4 S34 visible on open upper blaze and CSBT visible on open lower blaze.</p> <p>A madrone, 12 ins. diam., bears N. 73° W., 33.0 ft. dist., with scribe marks 1/4 S33 visible on open upper blaze and CSBT visible on open lower blaze.</p> <p>The corner is located 1 ft. N. of corner of fences extending E., S., and W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of Certain Lines of Donation Land Claim No. 38, T. 32 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the 1856 survey by J. A. Burnett)</p> <hr/> <p>From the Northern most NE. exterior cor. of DLC No. 38, reportedly perpetuated by F. C. Frear and N. Richardson in 1942, recorded in the Douglas County Surveyor's Office's old corner book, page 172, further perpetuated by the Douglas County Surveyor's Office in 1953 and 2005, recorded per files C.S. 45/249 and M9-19, and C.S. 67/10-20 respectively, and utilized by various Oregon Professional Surveyors, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above the ground, from which the original bearing tree</p> <p style="padding-left: 40px;">A white oak, 36 ins. diam., bears S. 80° W., 333.3 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office in 1953</p> <p style="padding-left: 40px;">A white oak, 15 ins. diam., bears S. 84½° W., 48.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A white oak, 19 ins. diam., bears N. 15° W., 92.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set an iron rod, 63 ins, long, 5/8 in. diam., 51 ins. in the ground, directly inside the center of the iron pipe, with an aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 32 S R 6 W</p> <div style="display: inline-block; border-left: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">DLC 38</div> <div style="display: inline-block; vertical-align: middle; margin-left: 5px;">S35</div> <p style="margin-top: 5px;">2006</p> </div> <p>N. 89° 53' 29" W., on the N. bdy. of DLC No. 38.</p> <p>190.97 A point established by Max H. Hull, Registered Land Surveyor No. 901, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/288 and R.M. 2-58, monumented with an</p>
---------	---

Dependent Resurvey of Certain Lines of
 Donation Land Claim No. 38,
 T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with a plastic yellow cap mkd. HULL RS 901.
250	The center line of pavement of Douglas County Road No. 12 (Azalea-Glendale Road), 22 ft. wide, bears N. 20° E. and S. 62° W., in a curve.
330.20	From this point, a point established by Max H. Hull, Registered Land Surveyor No. 901, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/288 and R.M. 2-58, bears South, 0.24 ft. dist., monumented with an iron rod, 5/8 in. diam., disturbed from its original placement, leaning to the Southeast, and projecting 9 ins. above the ground.
1170.53	<p>Point for the crossing closing corner at intersection with the calculated N. and S. center line of the NW¼ of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>from which</p> <p style="padding-left: 40px;">A Douglas fir, 6 ins. diam., bears N. 35° E., 50.6 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A Douglas fir, 26 ins. diam., bears N. 74° W., 45.3 ft. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
1370.44	<p>A point established by Max H. Hull, Registered Land Surveyor No. 901, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/288 and R.M. 2-58, monumented with an iron rod, 5/8 in. diam., firmly set, top 1 in. below the ground surface, with a broken plastic yellow cap with remaining marks ULL RS 901 visible. This point is accepted as marking the N. bdy. of DLC No. 38 and is identified as Witness Point No. 1.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam. onto the iron rod, with aluminum cap mkd.</p> <div style="text-align: center;">  </div>

Dependent Resurvey of Certain Lines of
 Donation Land Claim No. 38,
 T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
2119.89	From this point, the center of a buried cylindrical concrete structure 18 ins. diam., flush with the ground, with an exposed, removable lid, bears North, 7.1 ft. dist.
2481.94	Intersect the line bet. secs. 34 and 35, from which the cor. of secs. 26, 27, 34, and 35, bears N. 0° 15' 13" W., 491.03 ft. dist., hereinbefore described.
3531.45	<p>The NW. corner of DLC No. 38, perpetuated from original evidence no longer in existence, by Max H. Hull, Registered Land Surveyor No. 901, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/288 and R.M. 2-43, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with a plastic yellow cap mkd. HULL RS 901, from which bearing trees mkd. by Hull</p> <p style="padding-left: 40px;">A red cedar, 7 ins. diam., bears N. 27¾° E., 7.9 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 14 ins. diam., bears S. 74¾° W., 12.4 ft. dist., with a healed upper and lower blazes.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, directly over the iron rod, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 6 W</p> <p>S 34</p> <div style="border-left: 1px solid black; border-top: 1px solid black; width: 100px; height: 40px; margin-left: auto; margin-right: auto;"> <p style="text-align: center; margin: 0;">DLC 38</p> </div> <p>2006</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>S. 0° 10' 42" E., on the W. bdy. of DLC No. 38.</p>
844.98	From this point, a point established by person(s) unknown, bears East, 7.12 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above the ground.
2161.55	<p>Point for the crossing closing corner at intersection with the E. and W. center line of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 34 DLC 38</p> <p>C ——— C</p> <div style="border-left: 1px solid black; border-right: 1px solid black; width: 100px; height: 40px; margin-left: auto; margin-right: auto;"> <p style="text-align: center; margin: 0;">CCC</p> </div> <p>2007</p> </div> <p>from which</p>

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 38,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A white oak, 17 ins. diam., bears S. 59° W., 40.0 ft. dist., mkd. X at breast height and BT at the base.</p> <p>A Douglas fir, 9 ins. diam., bears N. 39½° W., 21.7 ft. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established by person(s) unknown, bears N. 62° 01' W., 12.16 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 14 ins. above the ground.</p>
2555	The center line of pavement of Douglas County Road No. 12 (Azalea-Glendale Road), 21 ft. wide, bears N. 58° E. and S. 58° W.
2860	The center line of a seasonal drainage, 26 ft. wide, drains S. 64° W.
3002.40	<p>Point for the SW. cor. of DLC No. 38 at proportionate position, determined by the Grant Boundary method of adjustment, between the original Northwest cor. of DLC 38 and the reestablished Southeast corner of DLC No. 38, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W</p> <div style="text-align: center;"> </div> <p>from which</p> <p>A utility pole, No. PPL E1683, bears N. 5° E., 457.7 ft. dist.</p> <p>A utility pole, No. PPL E1681, bears N. 68½° W., 444.9 ft. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 49' 18" E., on the S. bdy. of Donation Land Claim No. 38.</p>
3665.22	Intersect the N. and S. center line of sec. 35, from which the ¼ sec. cor. of sec. 35, bears S. 0° 02' 24" E., 1816.55 ft. dist., hereinafter described.
3790	The center line of pavement of Douglas County Road No. 313 (Glendale Valley Road), 40 ft. wide, bears N. 62° E. and S. 62° W.

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 38,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET					
5047.99	<p>Point for the SE. cor. of DLC No. 38 at proportionate position, determined by the Grant Boundary method of adjustment, between P.O.C. marker STA 455 + 97.75 for the Old Pacific Highway and the Eastern most Northeast exterior cor. of DLC No. 38, from record information filed in the Douglas County Surveyor's Office per C.S. 45/249 and M9-19, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 6 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">DLC 38</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td colspan="2" style="text-align: center; padding-top: 5px;">2007</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A Douglas fir, 5 ins. diam., bears S. 50° W., 356.6 ft. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, the P.O.C. marker STA 455 + 97.75 for the Old Pacific Highway, set by person(s) unknown, perpetuated by the Douglas County Surveyor's Office in 1953 and 2005, recorded per files C.S. 45/249 and M9-19, and C.S. 67/10-21 respectively, bears, S. 87° 35' 00" W., 261.80 ft. dist., monumented with an iron rod, ¾ in. diam., firmly set, projecting 5 ins. above the ground. This point now functions as a reference monument, from which bearing trees mkd. for the reference monument by the Douglas County Surveyor's Office in 2005</p> <p style="padding-left: 40px;">A Douglas fir, 23 ins. diam., bears N. 80° E., 10.1 ft. dist., with fragmentary scribe marks visible on partially healed upper and lower blazes.</p> <p style="padding-left: 40px;">A grand fir, 9 ins. diam., bears S. 65° E., 22.5 ft. dist., with scribe marks RMCS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.</p> <p style="padding-left: 40px;">A madrone, 10 ins. diam., bears S. 2¾° E., 11.2 ft. dist., with scribe marks RMCS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.</p> <p style="padding-left: 40px;">A madrone, 11 ins. diam., bears S. 83¾° W., 28.6 ft. dist., with scribe marks RMCS visible on partially healed upper blaze and scribe marks BT visible on partially healed lower blaze.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., onto the rod, with aluminum cap mkd.</p>	DLC 38	S 35	2007	
DLC 38	S 35				
2007					

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 38,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET

RM
DLC 38
261.8 FT
----->
TO COR

From this reference monument, a 4 ins. square wooden post painted white and marked SHRW and P.O.C. 455+97.75, bears NE., 0.4 ft. dist.

Also from the SE. cor. of DLC No. 38., the Eastern most NE. exterior cor. of DLC No. 38, bears N. 1° 22' 54" W., 2179.10 ft. dist. perpetuated from original evidence, no longer in existence, by the Douglas County Surveyor's Office, in 1953 and 2005, per files C.S. 45/249 and M9-19, and C.S. 67/10-29 respectively. This point was determined from the accessories established by the Douglas County Surveyor's Office. The point falls in a drainage ditch, where no permanent monument has been established, from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1953

A maple, 43 ins. diam., bears N. 82° W., 63.8 ft. dist., with a healed blaze.

and bearing trees and an accessory mkd. by the Douglas County Surveyor's Office in 2005

A maple, 15 ins. diam., bears N. 12¾° E., 57.1 ft. dist., with scribe marks ENE DLC38 CSBT visible on open blaze.

A maple, 11 ins. diam., bears N. 53½° W., 107.7 ft. dist., with scribe marks ENE DLC38 CSBT visible on open blaze.

An iron post, 1½ ins. diam., firmly set, projecting 6 ins. above the ground, bears N. 56° 25' E., 7.7 ft. dist., with a 2½ ins. diam. brass cap mkd. DOUGLAS CO. SURVEYORS OFFICE BO 1 WEST - 5 FT TO ENE DLC38 2005 and an arrow pointing to the corner.

**Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

From the ¼ sec. cor. of sec. 34 only, on the S. bdy. of the Tp., established by proportionate measurement, by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 42/327, there is no remaining evidence of the original corner; this position was verified and is accepted as the cor.; monumented with a severed iron pipe, 1½ ins. diam., firmly set, projecting 1 in. above the ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 29 ins. in the ground, top 1 in. below surface, directly over the iron pipe, with brass cap mkd.

Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	T 32 S R 6 W <u>1/4 S 34</u> T 33 S R 6 W 2006
	<p>from which</p> <p style="padding-left: 40px;">An ash, 17 ins. diam., bears N. 21¼° E., 148.8 ft. dist., not marked at the request of the landowner.</p> <p style="padding-left: 40px;">A utility pole, No. PPL E4469, bears S. 60¼° W., 218.2 ft. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established as the ¼ sec. cor. of sec. 34 by Raymond R. Wytcherley, Registered Land Surveyor No. 2724, in 2001, recorded in the Douglas County Surveyor's Office per files C.S. 65/38-3(A&E) and M137-18, bears S. 41° 30' W., 4.0 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, buried 10 ins. below the ground, with plastic yellow cap mkd. WYTCHERLEY LS 2724, and was not used for control in this resurvey.</p> <p>Also from the ¼ sec. cor. of sec. 34 only, a point reestablished by proportionate measurement for the standard ¼ sec. cor. of sec. 3, on the N. bdy. of T. 33 S., R. 6 W., by Gerald V. Nygren, Registered Land Surveyor No. 1035, in 1994, recorded in the Douglas County Surveyor's Office per files C.S. 63/134-10 and M121-31, bears S. 88° 46' 43" E., 196.09 ft. dist., there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, buried 8 ins. below the ground, with a plastic yellow cap mkd. NYGEN LS 1035.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 43 ins. in the ground, top 15 ins. below surface, directly over the iron rod, with brass cap mkd.</p>
	<hr style="width: 10%; margin: 0 auto;"/> 1/4 S 3 T 33 S R 6 W SC 2006
	<p>from which</p> <p style="padding-left: 40px;">A utility pole, No. E3993, bears S. 30° E., 644.1 ft. dist.</p> <p style="padding-left: 40px;">A utility pole, No. E4468, bears S. 35¼° W., 604.1 ft. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET									
	<p>From the standard $\frac{1}{4}$ sec. cor. of sec. 3, T. 33 S., R. 6 W., a point established as this same cor. by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/294C and M49-21, bears N. $1^{\circ} 39' E.$, 2.3 ft. dist., monumented with an iron rod, 1 in. diam., buried 12 ins. below the ground, and was not used for control in this survey.</p> <p>Also from the $\frac{1}{4}$ sec. cor. of sec. 34 only, the standard sec. cor. of secs. 3 and 4, on the N. bdy. of T. 33 S., R. 6 W., reestablished by proportionate measurement, by Raymond R. Wytcherley, Registered Land Surveyor No. 2724, in 2001, recorded in the Douglas County Surveyor's Office per files C.S. 65/38-3(A&E) and M137-18, bears N. $89^{\circ} 44' 50'' W.$, 2453.28 ft. dist., there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, buried 7 ins. below the ground, with plastic yellow cap mkd. WYTCHERLEY LS 2724, from which accessories reported by Wytcherley</p> <p style="padding-left: 40px;">A "T" iron fence post, bears N. $65\frac{1}{2}^{\circ} E.$, 81.2 ft. dist.</p> <p style="padding-left: 40px;">A "T" iron fence post, bears S. $8\frac{3}{4}^{\circ} W.$, 132.2 ft. dist.</p> <p style="padding-left: 40px;">A "T" iron fence post, bears N. $3\frac{1}{4}^{\circ} W.$, 29.6 ft. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 43 ins. in the ground, top 15 ins. below surface, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 5px;">S 4</td> <td style="padding: 5px;">S 3</td> </tr> <tr> <td style="padding: 5px;">T 33 S</td> <td style="padding: 5px;">R 6 W</td> </tr> <tr> <td colspan="2" style="padding: 5px;">SC</td> </tr> <tr> <td colspan="2" style="padding: 5px;">2006</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From the standard sec. cor. of secs. 3 and 4, T. 33 S., R. 6 W., a point established as this same cor. by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1973, recorded in the Douglas County Surveyor's Office per files C.S. 55/294C and M49-21, bears N. $1^{\circ} 31' W.$, 1.40 ft. dist., monumented with an iron rod, 1 in. diam., buried 12 ins. below the ground, and was not used for control in this survey.</p> <p>N. $0^{\circ} 10' 42'' E.$, on the N. and S. center line of sec. 34.</p>	S 4	S 3	T 33 S	R 6 W	SC		2006	
S 4	S 3								
T 33 S	R 6 W								
SC									
2006									
590	<p>The center line of pavement of Douglas County Road No. 12 (Azalea-Glendale Road), 23 ft. wide, bears N. $46^{\circ} E.$ and S. $62^{\circ} W.$, in a curve.</p>								
1315.19	<p>From this point, a point established by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 42/327, bears East,</p>								

Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	1.5 ft. dist, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 8 ins. above the ground, and was not used for control in this survey.
2623.84	<p>The center $\frac{1}{4}$ sec. cor. of sec. 34, established by Raymond R. Wytcherley, Registered Land Surveyor No. 2724, in 2001, recorded in the Douglas County Surveyor's Office per files C.S. 65/38-3C and M137-18, and is accepted as the cor.; monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 4 ins. above the ground, with a plastic yellow cap mkd. WYTCHERLEY LS 2724, from which bearing trees mkd. by Wytcherley</p> <p style="padding-left: 40px;">A Douglas fir, 16 ins. diam., bears N. $78\frac{1}{4}^{\circ}$ E., 13.5 ft. dist., with scribe marks $C\frac{1}{4}$ visible on partially healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 13 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 13.6 ft. dist., with no visible scribe marks on a partially healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 14 ins. diam., bears S. $43\frac{1}{4}^{\circ}$ W., 30.0 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 9 ins. diam., bears N. $20\frac{1}{4}^{\circ}$ W., 48.4 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W C $\frac{1}{4}$ S 34 2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established as the center $\frac{1}{4}$ sec. cor. by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 42/327, bears N. $13^{\circ} 41' W.$, 3.3 ft. dist, monumented with a bent iron pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 8 ins. above the ground, and was not used for control in this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 12' 41'' E.$, beginning new measurement.</p>
1324.59	<p>The center N $\frac{1}{16}$ sec. cor. of sec. 34, established by Raymond R. Wytcherley, Registered Land Surveyor No. 2724, in 2001, recorded in the Douglas County Surveyor's Office per files C.S. 65/38-3D and M137-18, and is accepted as the cor.; monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 3 ins. above the ground, with a plastic yellow cap mkd. WYTCHERLEY LS 2724, from which bearing trees mkd. by Wytcherley</p>

Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A madrone, 10 ins. diam., bears S. 67¼° E., 14.2 ft. dist., with scribe marks CN1/16 BT visible on partially healed blaze.</p> <p>A madrone, 11 ins. diam., bears S. 20° W., 10.5 ft. dist., with scribe marks CN1/16 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;"> C N 1/16 S 34 C 2007 </p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established as the center N 1/16 sec. cor. by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 42/327, bears N. 19° 52' W., 1.4 ft. dist, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, and was not used for control in this survey, from which a bearing tree mkd. by Lawrence</p> <p style="text-align: center;"> A Douglas fir, 24 ins. diam., bears S. 86½° W., 7.0 ft. dist., with visible bark scribes 1/16S at breast height and 15BT43 near the base. </p> <hr/> <p>N. 0° 14' 35" E., beginning new measurement.</p>
1324.62	<p>The ¼ sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the ¼ sec. cor. of secs. 34 and 35.</p> <p>N. 89° 36' 45" W., on the E. and W. center line of sec. 34.</p>
190	<p>The center line of pavement of Douglas County Road No. 12 (Azalea-Glendale Road), 21 ft. wide, bears N. 70° E. and S. 70° W.</p>
269.52	<p>From this point, a point established by person(s) unknown, bears South, 0.97 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground.</p>
1052.49	<p>The crossing closing corner on the W. bdy. of DLC No. 38.</p>
1335.52	<p>Point for the center E 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	$\frac{E\ 1/16}{C\ \frac{\quad}{C}}$ S 34 2007
	from which
	A Douglas fir, 15 ins. diam., bears N. $0\frac{1}{2}^{\circ}$ E., 49.0 ft. dist., mkd. CE1/16 S34 BT.
	A Douglas fir, 12 ins. diam., bears N. $68\frac{1}{4}^{\circ}$ W., 51.0 ft. dist., mkd. CE1/16 S34 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
2671.04	The center $\frac{1}{4}$ of sec. 34.

	N. $89^{\circ} 37' 28''$ W., beginning new measurement.
1326.41	From this point, a point established as the center W 1/16 sec. cor. by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S. 42/327, bears South, 4.43 ft. dist, monumented with an iron pipe, $1\frac{1}{4}$ ins. diam. firmly set, projecting 4 ins. above the ground, and was not used for control in this survey.
2650.64	The $\frac{1}{4}$ cor. of secs. 33 and 34.

	From the center E 1/16 sec. cor. of sec. 34.
	N. $0^{\circ} 00' 49''$ W., on the calculated N. and S. center line of the NE $\frac{1}{4}$ of sec. 34.
1326.71	Point for the NE 1/16 sec. cor. of sec. 34 at its calculated position.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	NE 1/16 S 34 2007
	from which
	A Douglas fir, 8 ins. diam., bears N. 14° E., 13.6 ft. dist., mkd. NE1/16 S34 BT.
	A white oak, 8 ins. diam., bears S. $60\frac{1}{4}^{\circ}$ E., 7.5 ft. dist., mkd. NE1/16 S34 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this corner, a point established as the NE 1/16 sec. cor. by Henry W. Lawrence, Registered Engineer No. 1543, in 1955, recorded in the Douglas County Surveyor's Office per file C.S.

**Subdivision of Section 34,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEEET	<p>42/327, bears N. 31° 05' W., 8.1 ft. dist.; monumented with an iron pipe, 1 in. diam. firmly set, projecting 5 ins. above the ground, and was not used for control in this survey, from which a bearing tree mkd. by Lawrence</p> <p style="text-align: center;">A black oak, 11 ins. diam., bears N. 20½° W., 5.0 ft. dist., with a healed blaze.</p> <hr/> <p>N. 89° 42' 10" W., on the calculated E. and W. centerline of the NE¼ of sec. 34.</p>
1330.23	<p>The center N 1/16 sec. cor. of sec. 34.</p> <hr/> <p style="text-align: center;">Subdivision of Section 35, T. 32 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of sec. 35 only, on the S. bdy. of the Tp., reestablished by proportionate measurement, by Mark A. Heimberger, Registered Land Surveyor No. 2287, in 2006, recorded in the Douglas County Surveyor's Office per file M151-65, there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with a plastic yellow cap mkd. PLS 2287 LANDMARK, from which bearing trees and accessories mkd. by Heimberger</p> <p style="text-align: center;">An iron rod 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears North, 40.0 ft. dist., with a plastic yellow cap mkd. PLS 2287 LANDMARK.</p> <p style="text-align: center;">A Douglas fir, 22 ins. diam., bears N. 69¾° E., 64.5 ft. dist., with scribe marks S1/4 S35 BT visible on open blaze.</p> <p style="text-align: center;">An iron rod 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears East, 40.0 ft. dist., with a plastic yellow cap mkd. PLS 2287 LANDMARK.</p> <p style="text-align: center;">A Douglas fir, 14 ins. diam., bears N. 35¾° W., 57.2 ft. dist., with scribe marks S1/4 S35 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., directly over the iron rod, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W <u>1/4 S 35</u> T 33 S R 6 W 2006</p>

**Subdivision of Section 35,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established as the ¼ sec. cor. of sec. 35 by Robert M. Thompson, Registered Engineer No. 3683, in 1971, recorded in the Douglas County Surveyor's Office per files C.S. 55/236 and M44-38, bears N. 27° 05' W., 9.5 ft. dist.; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 15 ins. above the ground, and was not used for control in this survey, from which bearing trees mkd. by Thompson</p> <p style="padding-left: 40px;">A Douglas fir, 20 ins. diam., bears N. 75½° E., 51.6 ft. dist., with a healed upper and lower blazes.</p> <p style="padding-left: 40px;">A sawed Douglas fir stump, 20 ins. diam., bears S. 10° W., 40.0 ft. dist., with a partially healed blaze.</p> <p>Also from the ¼ sec. cor. of sec. 35 only, the standard ¼ sec. cor. of sec. 2, on the N. bdy. of T. 33 S., R. 6 W., bears S. 89° 44' 05" E., 198.65 ft. dist., hereinbefore described.</p> <p>N. 0° 02' 24" W., on the N-S centerline of sec. 35.</p>
639.34	<p>From this point, a point established by Robert M. Thompson, Registered Engineer No. 3683, in 1971, recorded in the Douglas County Surveyor's Office per files C.S. 55/236 and M44-38, bears West, 3.89 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, and was not used for control in this survey.</p>
1675.86	<p>From this point, a point established by Robert M. Thompson, Registered Engineer No. 3683, in 1971, recorded in the Douglas County Surveyor's Office per files C.S. 55/236 and M44-38, bears West, 4.63 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground, and was not used for control in this survey.</p>
1740	<p>The center line of pavement of Douglas County Road No. 313 (Glendale Valley Road), 40 ft. wide, bears N. 62° E. and S. 62° W.</p>
1816.55	<p>Intersect the S. bdy. of DLC No. 38, from which the SE. cor. of DLC No. 38, bears N. 89° 49' 18" E., 1382.77 ft. dist., hereinbefore described.</p>
2637.13	<p>Point for the center ¼ sec. cor. of sec. 35 at intersection with the E. and W. center line. This point falls in the riparian area for Cow Creek and no permanent monument was established.</p>
3067.13	<p>Point selected for a witness cor. to the center ¼ sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, top 6 ins. below surface, with brass cap mkd.</p>

Subdivision of Section 35,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	WC T 32 S R 6 W C 1/4 ↓ S 35 ↓ 2006
	from which A white oak, 23 ins. diam., bears N. 66½° W., 120.5 ft. dist., unmarked. A utility pole, No. PPL E4029, bears N. 36½° E., 77.1 ft. dist.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
3969.95	Point for the center N 1/16 sec. cor. of sec. 35. No permanent monument established.
5085	The center line of pavement of Douglas County Road No. 12 (Azalea-Glendale Road), 22 ft. wide, bears N. 52° E. and S. 74° W., in a curve.
5302.77	The ¼ sec. cor. of secs. 26 and 35.
	<hr/> From the ¼ sec. cor. of secs. 35 and 36. N. 89° 57' 42" W., on the E. and W. center line of sec. 35.
1375	The center line of pavement of Junction Road (Old Pacific Highway), 36 ft. wide, bears N. 10° E. and S., in a curve.
2639.50	The true point for the center ¼ sec. cor. of sec. 35
2909.50	Point selected for a Witness Point on the E. and W. center line of sec. 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.
	WP C ——— C S 35 2006
	from which An incense cedar, 15 ins. diam., bears S. 31¼° W., 75.0 ft. dist., unmarked. A maple, 23 ins. diam., bears N. 27¾° W., 105.2 ft. dist., unmarked.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Subdivision of Section 35,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

FEET	
3946.83	Point for the center W 1/16 sec. cor. of sec. 35. No permanent monument established.
5254.16	The ¼ sec. cor. of secs. 34 and 35. <hr/>
	From the crossing closing corner on the N. and S. center line of the NW¼ of sec. 35, on the N. bdy. of DLC No. 38, hereinbefore described.
	N. 0° 08' 33" W., on the calculated N. and S. center line of the NW¼ of sec. 35.
496.58	The W 1/16 sec. cor. of secs. 26 and 35. <hr/>
	GENERAL DESCRIPTION
	The lands included in this survey are located approximately one mile East of the town of Glendale, Oregon. Access is gained by the way of U.S. Interstate Highway No. 5, county roads, and private roads. Elevations range from about 1400 feet above mean sea level on the valley floor of the SW¼ of section 34, to about 2520 feet above mean sea level in the NE¼ of section 34.
	The soil in the area is generally composed of rocky clay. The area is drained by Cow Creek. Timber consists of fir, cedar, oak, chinquapin, alder, maple, and madrone, with undergrowth of poison oak, blackberries, fern, salal, Oregon grape, evergreen huckleberry, and native grasses.
	The valley floor is used for grazing and the surrounding hills are used for timber harvest.