

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
THE REHABILITATION OF THE  
1/4 SECTION CORNER  
BETWEEN SECTIONS 19 AND 30

**TOWNSHIP 29 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***Timothy J. Moore, Cadastral Surveyor***

Under Special Instructions dated February 22, 2002,  
approved February 22, 2002,  
which provided for the surveys included under Group No. 2000,  
and Assignment Instructions dated April 23, 2006.

***Corner Rehabilitation commenced April 24, 2006***

***Corner Rehabilitation completed April 24, 2006***

**T. 29 S., R. 7 W., Willamette Meridian, Oregon**

The following field notes describe the rehabilitation of the  $\frac{1}{4}$  section corner of sections 19 and 30, Township 29 South, Range 7 West, of the Willamette Meridian, Oregon, as provided for in the Special Instructions dated February 22, 2002, under Group No. 2000.

The rehabilitation of the  $\frac{1}{4}$  section corner of sections 19 and 30, was made at the request of the Roseburg District Manager, for the administrative purpose of the Bureau of Land Management.

Each new bearing tree has a  $2\frac{1}{2}$  inch X  $\frac{1}{4}$  inch magnetic nail (Mag-Nail) driven at level elevation with the monument right side-center.

The mean magnetic declination as taken from the U.S. Geological Survey Quadrangle map, "TENMILE, OREGON", Provisional Edition, dated 1990, is  $18^{\circ}$  East.

---

**Rehabilitation of the 1/4 Section Corner of Sections 19 and 30,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

---

(Rehabilitating a corner established by  
Nathaniel Ford, U.S. Deputy Surveyor, in 1854,  
Reestablished by Fed Mensch U.S. Cadastral Engineer, in 1924,  
and Perpetuated by Daniel E. Weller and Dale T. Bedell,  
Cadastral Surveyors, in 1989)

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. (cap is rotated  $180^{\circ}$ )

S19  
1/4           
S30  
1924

from which the remains of a bearing tree mkd. by Mensch

A sawed fir stump, 23 ins. diam., bears N.  $10^{\circ}$  W., 5.3 ft. dist., with a healed blaze and tin cap.

from which the remains of a bearing tree mkd. by Weller and Bedell

A stump hole, bears N.  $72\frac{1}{2}^{\circ}$  W., 6.9 ft. dist., a blown down, 21 ins. diam. fir, lying along side with a healed blaze.

and the remains of bearing trees marked by Gregory D. Lang, Oregon Professional Land Surveyor No. 2295, recorded in the Douglas County Surveyors Office, Records of Government Corners Renewed, T. 29 S., R. 7 W., Point Identifier 140300.

A stump hole, bears S.  $31\frac{1}{2}^{\circ}$  E., 27.6 ft. dist., with a blown down, 8 ins. diam. fir, lying along side, mkd. 1/4 S 30 BT.

A stump hole, bears S.  $88\frac{1}{2}^{\circ}$  E., 89.8 ft. dist., with a blown down, 12 ins. diam. fir, lying along side, mkd. 1/4 S 19 BT.

Rehabilitation of the 1/4 Section Corner of Sections 19 and 30,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

A fir, 27 ins. diam., bears N.  $53\frac{3}{4}^{\circ}$  W., 126.0 ft. dist., mkd. 1/4 S  
19 BT. This tree has been girdled by a cable; it was use as a tail  
hold for a logging operation.

and new bearing trees

A fir, 5 ins. diam., bears N.  $58^{\circ}$  W., 13.1 ft. dist., mkd. X BT.

A fir, 7 ins. diam., bears S.  $67^{\circ}$  E., 9.1 ft. dist., mkd. 1/14 S30  
BT.

This corner is located in an area where the timber was just harvested.

---