

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY AND SUBDIVISIONAL LINES, AND  
THE SUBDIVISION OF SECTION 35,  
**TOWNSHIP 20 SOUTH, RANGE 6 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

Under Special Instructions dated April 14, 2003, approved April 14, 2003,  
which provided for the surveys included under Group No. 2048,  
and Assignment Instructions dated May 21, 2003.

***Survey commenced June 30, 2003***

***Survey completed July 29, 2003***

## T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of section 35, Township 20 South, Range 6 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1872, John H. McClung, U.S. Deputy Surveyor, surveyed the north, south, and west boundaries, and subdivisional lines, as shown on the official plat of survey approved January 23, 1873.</p> <p>In 1884, William P. Wright, U.S. Deputy Surveyor, retraced portions of the north boundary and completed the subdivision of T. 21 S., R. 6 W., as shown on the official plat of survey approved February 25, 1885.</p> <p>In 1962, Norman J. McDonald, Surveying Technician, resurveyed a portion of the north boundary and subdivisional lines of T. 21 S., R. 6 W., and subdivided section 1, as shown on the official plat of survey accepted September 26, 1963. Suspended May 22, 1991, suspension lifted November 21, 1994.</p> <p>In 1984-85, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the north boundary and subdivisional lines of T. 21 S., R. 6 W., as shown on the official plat of survey accepted February 20, 1987.</p> <p>In 1989, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted March 23, 1993.</p> <p>In 1991, Wayne L. Rogers, Cadastral Surveyor, correctively resurveyed a portion of the north boundary and correctively surveyed a portion of the subdivision of section lines of section 1, T. 21 S., R. 6 W., as shown on the official plat of survey accepted April 29, 1994.</p> <p>In 1997, Wayne L. Rogers, Cadastral Surveyor, resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted July 1, 1999.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and Special Instructions dated April 14, 2003, for Group No. 2048, Oregon.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p>
------	---

## T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET

The direction of lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

The survey was performed using a combination of Global Positioning System (GPS) satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.30 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The unadjusted data assured a closure not exceeding 1:4000 in error. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic position (NAD 1983 (CORS 96)) of the ¼ corner of sections 26 and 35, as determined by a tie to the station "DODSON BUTTE CORS ARP", is as follows:

Latitude: 43° 47' 40.65" N.      Longitude: 123° 22' 44.85" W.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

---

(Restoring the 1872 survey by John H. McClung, the  
1962 resurvey by Norman J. McDonald, and the  
1984-85 resurvey by Wayne L. Rogers)

---

Beginning at the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T20S	R6W
S35	S36

S2  
T21S    R6W  
1984

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, 36 ins. diam., bears S. 45° E., 25.1 ft. dist., with scribe marks BT visible on an opened blaze.</p> <p>and the remains of the bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1958, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 600100</p> <p style="padding-left: 40px;">A fir stump, 21 ins. diam., bears N. 54° E., 44.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed stump, size indeterminate, bears N. 62° E., 17.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 68½° W., 11.9 ft. dist., with a healed blaze.</p> <p>and the remains of the bearing trees mkd. by McDonald</p> <p style="padding-left: 40px;">A fir stump, 20 ins. diam., bears N. 52° E., 48.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 72½° W., 21.8 ft. dist., with a healed blaze.</p> <p>and a new accessory</p> <p style="padding-left: 40px;">An aluminum rod, 72 ins. long, ¼ in. diam., driven 72 ins. in the ground as a reference monument, bears N. 51° 30' E., 22.7 ft. dist., with aluminum cap mkd. RM T20S R6W S36 22.7FT TO COR 2003, and an arrow pointing to the cor.</p> <p>S. 89° 55' 13" W., on the S. bdy. of sec. 35 and the Tp., posting and blazing the true line.</p> <p>Descend NW. slope.</p>
1340	Redford Creek, 6 ft. wide, course S. 75° W.; asc. SE. slope.
1640	Graveled road, 15 ft. wide, bears N. 60° E. and S. 50° W.
1925	Spur, slopes S.; desc. SW. slope.
2115	Smith Creek Road, paved, 26 ft. wide, bears S. 48° E. and N. 48° W.
2715.52	The ¼ sec. cor. of sec. 35 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">T20S    R6W 1/4    S35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1984</p> <p>from which the bearing trees mkd. by Rogers</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 26¼° E., 28.8 ft. dist., with a healed blaze. (Record, N. 28° E., 29.7 ft.)</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears N. 39¼° W., 16.5 ft. dist., with a healed blaze. (Record, N. 35½° W.)</p> <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin: auto;"/> <p>S. 89° 53' 15" W., beginning new measurement.</p>
2476.46	<p>The closing cor. of secs. 2 and 3, T. 21 S., R. 6 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T20S    R6W S 35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 3   S 2 CC</p> <p style="text-align: center;">T21S    R6W 1984</p> <p>from which the remaining bearing tree mkd. by Rogers</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 29° E., 60.8 ft. dist., with a healed blaze. (Record, S. 31½° E., 61.4 ft.)</p> <p>From the corner, the original closing cor. of secs. 2 and 3, T. 21 S., R. 6 W., bears S. 0° 26' 08" E., 3.05 ft. dist., perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1961, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 504100, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE</p> <p style="text-align: center;">T20S S 35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 3   S 2 CC</p> <p style="text-align: center;">T21S    R6W 1961</p> <p>from which the remains of the original bearing trees</p>

Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET

A decayed fir stump, size indeterminate, bears S.  $61\frac{1}{4}^{\circ}$  E., 63.6 ft. dist., no marks visible. (Record, S.  $60^{\circ}$  E., 62.0 ft.)

A decayed fir stump, size indeterminate, bears N.  $60\frac{1}{4}^{\circ}$  W., 39.1 ft. dist., no marks visible. (Record, N.  $59^{\circ}$  W., 31.7 ft.)

and bearing trees mkd. by Godfrey

A fir, 16 ins. diam., bears S.  $19^{\circ}$  E., 110.2 ft. dist., with a healed blaze.

A double trunk cedar, 64 ins. diam., bears S.  $73^{\circ}$  W., 151.8 ft. dist., with a healed blaze.

Also from the corner, a point established by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in an unrecorded survey, bears S.  $31^{\circ} 10' 58''$  E., 4.90 ft. dist., monumented with an iron "T" post, 1 x 1 ins., firmly set, projecting 4 ins. above ground, with aluminum washer mkd.

WILFORD N HAINES  
239  
SURVEY  
.  
POINT  
DRAIN ORE

from which a bearing tree mkd. by Haines

A fir, 29 ins. diam., bears N.  $71^{\circ}$  E., 104.3 ft. dist., with a healed blaze.

S.  $89^{\circ} 54' 40''$  W., beginning new measurement.

238.27 The cor. of secs. 34 and 35 only, monumented with an iron post,  $1\frac{1}{4}$  ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T20S | R6W  
34 | 35  
3  
T21S R6W  
1954

from which the remains of the original bearing trees

A fir stump, 48 ins. diam., bears N.  $32^{\circ}$  E., 52.1 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the South Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 56 ins. diam., bears S. 41° W., 23.1 ft. dist., with a healed blaze.</p>
	<p>A fir stump, 38 ins. diam., bears N. 47¼° W., 20.7 ft. dist., no marks visible on an opened blaze. (Record, N. 49° W., 19.8 ft.)</p>
	<p>and bearing trees mkd. by Ben B. Irving, Douglas County Surveyor, in 1954, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 500100</p>
	<p>A cedar, 18 ins. diam., bears S. 82° E., 48.2 ft. dist., with a healed blaze.</p>
	<p>A cedar, 42 ins. diam., bears N. 41° W., 67.3 ft. dist., with a healed blaze.</p>
	<p>and a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1961, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 500100</p>
	<p>A fir, 20 ins. diam., bears N. 32° E., 58.1 ft. dist., with a healed blaze.</p>
	<hr/> <p align="center"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 S., R. 6 W., Willamette Meridian, Oregon</b></p> <hr/>
	<p align="center">(Restoring the 1872 survey by John H. McClung and the 1989 and 1997 resurveys by Wayne L. Rogers)</p> <hr/>
	<p>From the cor. of secs. 35 and 36 only, hereinbefore described.</p>
	<p>N. 0° 23' 14" E., bet. secs. 35 and 36, posting and blazing.</p>
	<p>Descend broken N. slope.</p>
780	<p>Redford Creek, 6 ft. wide, course S. 50° W.; asc. SE. slope.</p>
2590.70	<p>The ¼ sec. cor. of secs. 35 and 36, reestablished by David Wellman, Oregon Professional Land Surveyor No. 2163, in 1994, filed in the Douglas County Surveyor's Office, Map File No. 120-55, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 600140. There is no remaining evidence of the original cor.; therefore this position is accepted as the cor., monumented with an iron pipe, ¾ in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

F E E T	<p style="text-align: center;">T20S R6W 1/4 S35   S36 PLS2163 1994</p> <p>from which the remains of the bearing trees mkd. by Wellman</p> <p>A sawed fir stump, 24 ins. diam., bears N. 44¼° E., 28.1 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.</p> <p>A sawed fir stump, 11 ins. diam., bears S. 61° E., 35.8 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.</p> <p>A fir, 13 ins. diam., bears S. 31¼° W., 28.5 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.</p> <p>A fir, 14 ins. diam., bears N. 46° W., 23.8 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze.</p> <p>From the corner, a point established by person(s) unknown, bears S. 10° E., 3.4 ft. dist., monumented with an iron pipe, ¾ in. diam, firmly set projecting 4 ins. from the ground. This position is not utilized during the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 23' 08" E., beginning new measurement, posting and blazing.</p> <p>260 Spur, slopes W.; desc. broken NW. slope.</p> <p>2110 Summit Creek, 5 ft. wide, course S. 60° W.; asc. S. slope.</p> <p>2235 Summit Creek Road, gravel, 16 ft. wide, bears N. 80° E. and S. 80° W.</p> <p>2590.70 The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T20S R6W S26   S25 ----- S35   S36 1961</p> <p>from which the remains of an original bearing tree</p>
---------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed stump, size indeterminate, bears S. 40° E., 13.2 ft. dist., with decayed trunk lying alongside and scribe marks S36 visible on a partially opened blaze.</p> <p>and the remains of a reference tree mkd. by the Weyerhaeuser Company in 1957, reported by Rogers</p> <p>A fir stump, 40 ins. diam., bears N. 30½° E., 35.6 ft. dist., 34.3 ft. dist. to "W" nail in face.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1961, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 600200</p> <p>A fir, 28 ins. diam., bears S. 22° E., 53.5 ft. dist., with a healed double blaze.</p> <p>A fir, 21 ins. diam., bears S. 78½° W., 28.0 ft. dist., with a healed blaze.</p> <p>A fir, 32 ins. diam., bears N. 47½° W., 29.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Rogers</p> <p>A fir, 14 ins. diam., bears N. 59¼° W., 17.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p>
	<hr/> <p>From the cor. of secs. 34 and 35 only, hereinbefore described.</p> <p>N. 0° 14' 31" W., bet. secs. 34 and 35.</p> <p>Over level creek bottom.</p>
305	Smith River, 20 ft. wide, course N. 77° W.
855	Smith River Road, paved, 30 ft. wide, bears S. 34° E. and N. 34° W.
1343.62	<p>Point for the S 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an iron rod, 30 ins. long, ¾ in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">T20S R6W S 1/16 S34   S35 2003</p> <p>from which</p> <p>An aluminum rod, 72 ins. long, 3/4 in. diam., driven 72 ins. in the ground as a reference monument, bears N. 46° 50' E., 33.6 ft. dist., with aluminum cap mkd. RM T20S R6W S1/16 S35 33.6FT TO COR 2003, and an arrow pointing to the cor.</p> <p>An aluminum rod, 72 ins. long, 3/4 in. diam., driven 72 ins. in the ground as a reference monument, bears N. 23° 05' E., 23.7 ft. dist., with aluminum cap mkd. RM T20S R6W S1/16 S34 23.7FT TO COR 2003, and an arrow pointing to the cor.</p> <p>Corner is located on S. edge of graveled road.</p> <p>Begin posting and blazing.</p> <p>Ascend SE. slope.</p>
1355	Graveled road, 16 ft. wide, bears N. 40° E. and S. 40° W.
2687.24	<p>The 1/4 sec. cor. of secs. 34 and 35, reestablished by Ben B. Irving, Douglas County Surveyor, in 1954, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 500140. There is no remaining evidence of the original cor.; therefore this position is accepted as the corner, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS T20S R6W S34   S35 1/4 S 1954 OFFICE</p> <p>from which bearing trees mkd. by Irving</p> <p>A fir, 15 ins. diam., bears N. 78 3/4° E., 61.8 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 24 ins. diam., bears N. 52½° W., 34.9 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 14' 30" W., beginning new measurement, posting and blazing.</p> <p>735 Graveled road, 16 ft. wide, bears S. 35° E. and N. 35° W.</p> <p>2195 Graveled road, 16 ft. wide, bears N. 45° E. and S. 45° W.</p> <p>2687.89 The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>COUNTY SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T20S</td> <td style="padding: 0 10px;">R6W WM</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">27</td> <td style="padding: 0 10px;">26</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">34</td> <td style="padding: 0 10px;">35</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1954</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">OFFICE</td> </tr> </table> </div> <p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A fir snag, size indeterminate, bears N. 59° E., 13.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir snag, size indeterminate, bears N. 30° W., 2.6 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Ben B. Irving, Douglas County Surveyor, in 1954, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 500200, reported by Rogers</p> <p style="padding-left: 40px;">A fir, 39 ins. diam., bears N. 25° E., 59.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A tin-capped, sawed fir stump, 23 ins. diam., bears S. 28¾° E., 43.6 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 38 ins. diam., bears S. 19½° W., 81.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 49 ins. diam., bears N. 22° W., 31.0 ft. dist., with a healed blaze and scribe marks BT visible on bark blaze.</p> <p>and a bearing tree mkd. by Rogers</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears N. 69° E., 23.8 ft. dist., with scribe marks 6W S26 BT visible on a partially healed blaze.</p>	T20S	R6W WM	27	26	34	35	1954		OFFICE	
T20S	R6W WM										
27	26										
34	35										
1954											
OFFICE											

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEEET	<p>and new bearing trees</p> <p style="padding-left: 40px;">A chinquapin, 7 ins. diam., bears S. 33¾° E., 23.3 ft. dist., mkd. T20S R6W S35 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 62¾° W., 40.2 ft. dist., mkd. T20S R6W S34 BT.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 35, T. 20 S., R. 6 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the ¼ sec. cor. of sec. 35 only on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 32' 14" W., on the N. and S. centerline of sec. 35, posting and blazing.</p> <p>Ascend gentle S. slope.</p> <p>200 Smith River Road, paved, 24 ft. wide, bears S. 75° E. and N. 75°W.</p> <p>1319.38 Point for the center S 1/16 sec. cor. of sec. 35; discontinue posting and blazing.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T20S    R6W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 80px;"> </p> <p style="margin-left: 80px;">S 1/16    S 23</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;">2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 28¾° E., 19.0 ft. dist., mkd. CS 1/16 S35 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 68¾° W., 5.4 ft. dist., mkd. CS 1/16 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>1725 Ridge, bears N. 60° E. and S. 60° W.; desc. broken NW. slope.</p>
-------	---

Subdivision of Section 35,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	
2638.76	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 35, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20S R6W C 1/4 . S 35 2003</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. <math>56\frac{3}{4}^{\circ}</math> E., 4.8 ft. dist., mkd. C 1/4 S35 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. <math>25^{\circ}</math> W., 20.3 ft. dist., mkd. C 1/4 S35 BT.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
2660	Spur, slopes N. $30^{\circ}$ W., desc. broken N. slope.
3280	Summit Creek, 6 ft. wide, course S. $65^{\circ}$ W.; asc. broken SE. slope.
3420	Summit Creek Road, gravel, 20 ft. wide, bears N. $68^{\circ}$ E. and S. $68^{\circ}$ W.
4880	Spur, slopes N. $50^{\circ}$ E., desc. broken NW. slope.
4950	Draw bottom, drains N. $40^{\circ}$ W.; asc. broken W. slope.
5292.97	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 20 S., R. 06 W., Point Identifier No. 540200, monumented with an iron post, <math>1\frac{1}{4}</math> ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T20S R6W S 26 1/4 ——— S 35 1962</p> <p>from which the remains of an original bearing tree</p>

Subdivision of Section 35,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	
	<p>A decayed stump, size indeterminate, bears N. 20° W., 9.2 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Godfrey</p> <p>A fir, 39 ins. diam., bears N. 18¾° E., 25.0 ft. dist., with a healed blaze.</p> <p>A fir, 27 ins. diam., bears S. 42¾° E., 12.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 43 ins. diam., bears S. 83¾° W., 5.7 ft. dist., with scribe marks S BT visible on the bark.</p> <hr/> <p>From the ¼ sec. cor. of secs. 35 and 36, hereinbefore described.</p> <p>N. 89° 04' 51" W., on the E. and W. centerline of sec. 35.</p> <p>Descend broken NW. slope.</p>
2757.78	The center ¼ sec. cor. of sec. 35, hereinbefore described.
5459.14	The ¼ sec. cor. of secs. 34 and 35, hereinbefore described.
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 35, hereinbefore described.</p> <p>N. 89° 35' 49" W., on the E. and W. centerline of the SW¼ of sec. 35, posting and blazing.</p> <p>Ascend broken S. slope.</p>
1630	Ridge, bears N. 45° E. and S. 45° W.; desc. steep NW. slope.
2490	Summit Creek, 5 ft. wide, course S. 15° W.; continue over level creek bottom.
2580	Wire fence, bears North and South.
2707.94	The S 1/16 sec. cor. of secs. 34 and 35, hereinbefore described.
	<hr/>

## T. 20 S., R. 6 W., Willamette Meridian, Oregon

FEET	GENERAL DESCRIPTION
	<p>The lands included in the foregoing survey are located in rolling hills and broad, flat creek bottoms, approximately 9.5 miles north-northwesterly from the community of Drain, Oregon.</p> <p>The elevation ranges from approximately 800 feet above sea level near the corner of sections 34 and 35 only to approximately 1380 feet above sea level near the ¼ section corner of sections 26 and 35.</p> <p>The area is drained by Redford and Summit Creeks, which flow southwesterly to Smith River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>The soil is generally composed of rocky clay.</p> <p>Access to the survey was made by graveled roads branching from Smith River Road.</p> <p>The mean magnetic declination for the area surveyed is 19° East, as shown on the "BEAVER CREEK, OREG." 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1984.</p>