

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

WEST BOUNDARY (OFFSET MERIDIAN)

AND SUBDIVISIONAL LINES

AND THE SUBDIVISION OF SECTION 7,

**TOWNSHIP 23 SOUTH, RANGE 4 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

***Robert H. Browning, Surveying Technician***

Under Special Instructions dated June 28, 2007, approved July 2, 2007,

which provided for the surveys included under Group No. 2172,

and Assignment Instructions dated July 18, 2007.

***Survey commenced July 31, 2007***

***Survey completed November 26, 2007***

## T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the west boundary (offset meridian) and subdivisional lines and subdivision of section 7, Township 23 South, Range 4 West, Willamette Meridian, Oregon.

The history of federal surveys that pertain to this survey is as follows:

In 1851, James E. Freeman, U.S. Deputy Surveyor, surveyed the west boundary of the township (Offset Meridian).

In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines.

In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1976, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the south boundary and subdivisional lines.

In 1991-92, Dale T. Bedell, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 20.

The history of private surveys that pertain to this survey is as follows:

In 1960, Wilford N. Haines, Oregon Professional Land Surveyor No. 239, resurveyed a portion of the subdivisional lines, recorded in the Douglas County Surveyors Office, CS File No. 51/102-1.

In 1963, Wilford N. Haines, Oregon Professional Land Surveyor No. 239, resurveyed a portion of the subdivisional lines and subdivided section 7, recorded in the Douglas County Surveyors Office, Map File No. M26-38.

In 1999, Ken W. Hoffine, Oregon Professional Land Surveyor No. 2291, resurveyed a portion of the west boundary and further subdivided section 7, recorded in the Douglas County Surveyors Office, Map File No. M133-2.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 28, 2007, for Group No. 2172, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.

**T. 23 S., R. 4 W., Willamette Meridian, Oregon**

F E E T

The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.05 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic position (NAD 1983 (CORS 96)) of the ¼ section corner of sections 7 and 8 as determined by a tie to a GPS occupation of a temporary hub, utilizing dual frequency, carrier phase GPS receivers, as calculated by the National Geodetic Survey's Online Positioning Users Service, which held as fixed National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO" and "DODSON BUTTE", is as follows:

Latitude: 43° 35' 03.20" N.      Longitude: 123° 12' 25.31" W.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

---

**Dependent Resurvey of a Portion of the West Boundary  
(Offset Meridian),  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

---

(Restoring the 1851 survey by James E. Freeman)

---

Beginning at the cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYOR  
T 23 S  
R S 12 | S 7 R  
5 ——— | ——— 4  
W S 13 | S 18 W  
1979

**Dependent Resurvey of a Portion of the West Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEEET	<p>from which the remains of original bearing trees</p> <p>A sawed fir stump, 20 ins. diam., bears N. 20° E., 16.7 ft. dist., with no marks visible on an open blaze. (Record, 28 ins. diam., 19.1 ft.)</p> <p>A sawed cedar stump, 16 ins. diam., bears S. 79° W., 12.5 ft. dist., with a healed blaze. (Record, fir, S. 84° W.)</p> <p>A sawed fir stump, 30 ins. diam., bears N. 68½° W., 25.9 ft. dist., with fragmentary scribe marks visible on an open blaze. (Record, N. 65° W., 27.1 ft.)</p> <p>and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1959, reported by Bedell</p> <p>A cedar snag, 12 ins. diam., bears N. 78½° W., 33.0 ft. dist., with scribe marks T23S R5W S12 CS visible on an open blaze.</p> <p>and the remains of bearing trees mkd. by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965, reported by Bedell</p> <p>A fir, 24 ins. diam., bears S. 22° E., 103.0 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears S. 22½° W., 50.5 ft. dist., with a healed blaze. (Record, S. 24° W., 51.5 ft.)</p> <p>A fir, 26 ins. diam., bears N. 33° W., 42.9 ft. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by Larry E. Monrean, Deputy County Surveyor, in 1979, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 100500, not reported by Bedell</p> <p>A fir, 16 ins. diam., bears N. 71¼° E., 116.3 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Bedell</p> <p>A pine, 10 ins. diam., bears N. 36° E., 13.5 ft. dist., with a healed blaze.</p> <p>N. 0° 28' 55" E., bet. secs. 7 and 12, on the W. bdy. of the Tp. Descend over broken NW. slope, posting and blazing.</p>
460	Adams Creek, 4 ft. wide, course N. 65° E., asc. over SE. slope.

Dependent Resurvey of a Portion of the West Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET 1327.32	<p>The S 1/16 sec. cor. of secs. 7 and 12, established by Hoffine in 1999, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>LONE ROCK TIMBER</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T23S</td> <td style="padding: 0 5px;">R5W</td> <td style="padding: 0 5px;">S 1/16</td> <td style="padding: 0 5px;">T23S</td> </tr> <tr> <td style="padding: 0 5px;">S 12</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">R4W</td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 5px 0;">1999</td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 5px 0;">PLS 2291</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Hoffine</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 2¾° E., 34.6 ft. dist., with scribe marks BT visible on the bark.</p> <p style="margin-left: 40px;">An oak snag, 16 ins. diam., bears N. 52¼° W., 52.9 ft. dist., with scribe marks S 1/16 S12 BT visible on an open blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 85° W., 4.0 ft. dist., mkd. S 1/16 S12 BT.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 28' 07" E., beginning new measurement.</p> <p>Ascend over SE. slope.</p>	T23S	R5W	S 1/16	T23S	S 12		S 7	R4W	1999				PLS 2291			
T23S	R5W	S 1/16	T23S														
S 12		S 7	R4W														
1999																	
PLS 2291																	
1327.30	<p>The ¼ sec. cor. of secs. 7 and 12, perpetuated by Haines in 1963, further perpetuated by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965, further perpetuated by Hoffine in 1999, further perpetuated by Stephen J. Flause and John Pike, Douglas County Surveyors Office, in 2007, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 100540, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 18 ins. above the ground, from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A fir snag, 31 ins. diam., bears N. 85° E., 25.7 ft. dist., with no marks visible on an opened blaze.</p> <p>and bearing tree mkd. by Hoffine</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 61¼° W., 23.3 ft. dist., with a healed blaze.</p>																

**Dependent Resurvey of a Portion of the West Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

and bearing trees mkd. by Flause and Pike

A fir, 9 ins. diam., bears N.  $48\frac{1}{2}^{\circ}$  E., 20.4 ft. dist., with scribe marks 1/4 S7 CS BT visible on a partially healed double blaze.

A cedar, 12 ins. diam., bears S.  $58^{\circ}$  W., 32.9 ft. dist., with scribe marks 1/4 S12 CS BT visible on a partially healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, directly over the "T" shaped iron rod, in a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. to top, with brass cap mkd.

T 23 S  
R 5 W    R 4 W  
1/4  
|  
S 12    S 7  
2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

---

(Restoring the 1855 survey by Harvey Gordon and  
Charles T. Gardner, the 1884 survey by William P. Wright,  
and the 1976 resurvey by James E. Jelley)

---

From the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

1/4  
S 17    S 16  
|  
T 23 S    R 4 W  
1976

from which the remains of bearing trees mkd. by Jelley

A decayed fir stump, size indeterminate, bears S.  $14\frac{1}{4}^{\circ}$  E., 16.5 ft. dist., with no marks visible.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 21 ins. diam., bears N. 40½° W., 13.5 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears N. 54¼° E., 41.2 ft. dist., mkd. 1/4 S16 BT.</p> <p>N. 0° 20' 10" W., bet. secs. 16 and 17.</p> <p>Ascend over broken SE. slope, posting and blazing.</p>												
115	<p>Spur, slopes N. 85° E., desc. over NE. slope.</p>												
2633.64	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 23 S</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 17</td> <td style="text-align: center;">S 16</td> </tr> <tr> <td colspan="2" style="text-align: center;">R 4 W</td> </tr> <tr> <td colspan="2" style="text-align: center;">1958</td> </tr> </table> </div> <p>from which the remaining bearing tree mkd. by Arthur Boyer, County Surveyor, in 1937-38, reported by Jelley</p> <p>A fir, 34 ins. diam., bears N. 20½° W., 47.8 ft. dist., with a healed double blaze.</p> <p>and the remains of a bearing tree mkd. by James W. Byron, Douglas County Surveyors Office, in 1957, reported by Jelley</p> <p>A sawed fir stump, 24 ins. diam., bears N. 77° E., 40.9 ft. dist., with no marks visible.</p> <p>and a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, reported by Jelley</p> <p>A fir, 21 ins. diam., bears S. 77° W., 22.4 ft. dist., with a healed double blaze.</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 30¼° E., 34.0 ft. dist., mkd. T23S R4W S9 BT.</p> <p>A fir, 8 ins. diam., bears S. 64¼° E., 55.0 ft. dist., mkd. T23S R4W S16 BT.</p>	T 23 S		S 8	S 9	-----		S 17	S 16	R 4 W		1958	
T 23 S													
S 8	S 9												
-----													
S 17	S 16												
R 4 W													
1958													

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Discontinue posting and blazing.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 20, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, (with a "T" shaped iron rod, 1 in. diam., firmly set alongside, projecting 2 ins. above the ground, with 1 in. diam. brass disk mkd. SURVEY POINT WILFORD N HAINES 239 DRAIN ORE affixed to top), with brass cap mkd.</p> <div style="text-align: center;"> <p>S 17  <math>\frac{1}{4}</math> ———  S 20  T 23 S    R 4 W  1976</p> </div> <p>from which the remains of bearing trees mkd. by Haines in 1960, reported by Bedell</p> <p style="padding-left: 40px;">A sawed fir stump, 20 ins. diam., bears S. <math>35^{\circ}</math> E., 17.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. <math>46\frac{1}{2}^{\circ}</math> W., 8.3 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Bedell</p> <p style="padding-left: 40px;">A sawed fir stump, 21 ins. diam., bears S. <math>64^{\circ}</math> W., 17.8 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. <math>14\frac{1}{4}^{\circ}</math> E., 28.4 ft. dist., mkd. X BT.</p> <p>N. <math>88^{\circ} 33' 05''</math> W., bet. secs. 17 and 20.</p> <p>Descend over westerly slope, posting and blazing.</p>
105	Graveled road, 15 ft. wide, bears S. $5^{\circ}$ E. and N. $5^{\circ}$ W.
2652.12	<p>The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 2 ins. above the ground (with an axle, <math>1\frac{3}{4}</math> ins. diam., firmly set, projecting 6 ins. above the ground, alongside), with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S    R 4 W  S 18   S 17  ——— ———  S 19   S 20  1976</p> </div> <p>from which the remains of the original bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 52 ins. diam., bears N. 47° E., 54.8 ft. dist., with scribe marks T23S R4W S17 CS BT visible on an open blaze.</p> <p>A fir snag, 13 ins. diam., bears S. 69¾° E., 48.2 ft. dist., with scribe marks T23S R4W S20 CS visible on an open blaze.</p> <p>A sawed fir stump, 46 ins. diam., bears S. 59° W., 25.1 ft. dist., with no marks visible.</p> <p>A fir, 30 ins. diam., bears N. 69° W., 31.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 200400, reported by Jelley</p> <p>A cedar, 33 ins. diam., bears N. 3½° E., 260.7 ft. dist., with a healed blaze.</p> <p>A fir, 27 ins. diam., bears S. 84¾° W., 80.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and bearing trees mkd. by Jelley</p> <p>A fir, 16 ins. diam., bears N. 27¾° E., 31.7 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears S. 55¾° E., 21.4 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears S. 4° W., 13.2 ft. dist., with a healed blaze.</p> <p>Corner is located 1.0 ft. E. of a fence cor. with 5 strand barbed wire fences extending North and West.</p> <hr/> <p>N. 0° 05' 41" E., bet. secs. 17 and 18.</p> <p>Ascend over SW. slope, continue posting and blazing.</p>
2667.13	<p>The ¼ sec. cor. of secs. 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEEET	$\begin{array}{c} 1/4 \\ S\ 18 \quad   \quad S\ 17 \\ T\ 23\ S \quad   \quad R\ 4\ W \\ 1976 \end{array}$
2662.97	<p>from which bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears N. <math>22\frac{1}{4}^{\circ}</math> E., 38.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. <math>38\frac{1}{2}^{\circ}</math> W., 32.7 ft. dist., with a healed blaze. (Record, N. <math>40\frac{1}{2}^{\circ}</math> W.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>0^{\circ} 08' 16''</math> E., beginning new measurement.</p> <p>Descend over broken NE. slope, continue posting and blazing.</p> <p>The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, <math>1\frac{1}{2}</math> ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <math display="block">\begin{array}{c} T\ 23\ S \quad R\ 4\ W \\ S\ 7 \quad   \quad S\ 8 \\ \hline S\ 18 \quad   \quad S\ 17 \\ SEC\ COR \\ 1959 \end{array}</math> </div> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 72 ins. diam., bears S. <math>36^{\circ}</math> E., 58.5 ft. dist., with fragmentary scribe marks visible on the bark. (Record, 60.7 ft.)</p> <p>and the remains of a bearing tree mkd. by James W. Byron, Douglas County Surveyors Office, in 1959, reported by Jelley</p> <p style="padding-left: 40px;">A sawed fir stump, 21 ins. diam., bears S. <math>66\frac{3}{4}^{\circ}</math> W., 70.3 ft. dist., with a healed double blaze.</p> <p>and the remains of a bearing trees mkd. by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965, not Byron as reported by Jelley, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 200500</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. <math>22^{\circ}</math> E., 73.3 ft. dist., with a healed double blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 23 ins. diam., bears N. 70¾° W., 21.1 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears S. 25° W., 21.2 ft. dist., mkd. T23S R4W S18 BT.</p> <p>Discontinue posting and blazing.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. 89° 00' 49" W., bet. secs. 8 and 17.</p> <p>Ascend over NE. slope, posting and blazing.</p>
2628.30	<p>The ¼ sec. cor. of secs. 8 and 17, established by Haines in 1963, by proportionate measurement, there is no remaining evidence of the original corner, therefore this position is accepted as the cor., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 11 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p>A fir, 40 ins. diam., bears S. 33¾° E., 25.2 ft. dist., with a healed blaze.</p> <p>A sawed cedar stump, 20 ins. diam., bears N. 39¾° W., 22.4 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S    R 4 W</p> <p>          S 8</p> <p>          1/4 —————</p> <p>          S 17</p> <p>          2007</p> </div> <p>from which a new bearing tree</p> <p>A fir, 8 ins. diam., bears N. 40° W., 17.2 ft. dist., mkd. 1/4 S8 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89° 04' 36" W., beginning new measurement.</p> <p>Ascend over NE. slope, continue posting and blazing.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1395	Ridge, bears N. 10° W. and S. 10° E., desc. over W. slope.
2623.70	The cor. of secs. 7, 8, 17, and 18, hereinbefore described.
	S. 89° 34' 50" W., bet. secs. 7 and 18.
	Descend over W. slope, continue posting and blazing.
2651.28	The ¼ sec. cor. of secs. 7 and 18, perpetuated by James W. Byron, Douglas County Surveyors Office, in 1959, further perpetuated by the Douglas County Surveyors Office in 1979, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 23 S., R. 4 W. Point Identifier No. 140500, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 23 S R 4 W S 7 1/4 COR ——— S 18 1959
	from which the remains of the original bearing trees
	A sawed fir stump, 44 ins. diam., bears S. 66° W., 10.6 ft. dist., with no marks visible.
	A sawed fir stump, 68 ins. diam., bears N. 35° W., 81.9 ft. dist., with no marks visible. (Record, 79.2 ft.)
	and the remains of bearing trees mkd. by Byron
	A fir, 27 ins. diam., bears North, 25.8 ft. dist., with a healed double blaze.
	A sawed fir stump, 29 ins. diam., bears S. 29° E., 26.9 ft. dist., with no marks visible.
	and the remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1979
	A fir snag, 26 ins. diam., bears N. 12½° W., 138.2 ft. dist., with a healed double blaze.
	and a new bearing tree
	A fir, 7 ins. diam., bears S. 74° E., 28.4 ft. dist., mkd. 1/4 S18 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located in an unmaintained barbed wire fence, with fences extending East and West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 46' 49" W., beginning new measurement.</p> <p>Descend over broken SW. slope, continue posting and blazing.</p>
545	Graveled road, 15 ft. wide, bears N. 30° W. and S. 30° E.
2644.26	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 8, 17, and 18, hereinbefore described.</p> <p>N. 0° 04' 46" E., bet. secs. 7 and 8.</p> <p>Ascend over broken SW. slope, posting and blazing.</p>
1310.09	<p>The S 1/16 sec. cor. of secs. 7 and 8, established by Haines in 1963, remonumented by Larry E. Monrean, Douglas County Surveyors Office, in 1976, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 23 S., R. 4 W., Point Identifier No. 200520, and is accepted as the cor., monumented with an iron post, 1¼ ins. diam., firmly set, projecting 6 ins. above a collar of stone, 2 ft. base, 6 ins. high, (with "T" shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above the collar of stone), with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T23S R4W S1/16 S7   S8 1976</p> <p>from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears S. 54¾° E., 38.9 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears N. 58½° W., 6.6 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by Monrean</p> <p style="padding-left: 40px;">A sawed fir stump, 23 ins. diam., bears N. 35¾° E., 13.7 ft. dist., with scribe marks S1/16 S8 CS visible on an open blaze.</p> <p>and new bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 9 ins. diam., bears N. <math>39\frac{3}{4}^{\circ}</math> E., 11.7 ft. dist., mkd. S 1/16 S8 BT.</p> <p>A fir, 7 ins. diam., bears N. <math>80\frac{1}{2}^{\circ}</math> W., 8.2 ft. dist., mkd. S 1/16 S7 BT.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>0^{\circ} 08' 43''</math> E., beginning new measurement.</p> <p>Ascend over broken SW. slope.</p>
1314.87	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8, perpetuated by Larry E. Monrean, Douglas County Surveyors Office, in 1979, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 23 S., R. 4 W., Point Identifier No. 200540, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T 23 S R 4 W S 7   S 8</p> <p style="text-align: center;">1/4 1979</p> <p>from which the remains of the original bearing trees</p> <p>A sawed pine stump, 35 ins. diam., bears S. <math>36^{\circ}</math> E., 11.2 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 40 ins. diam., bears S. <math>17\frac{1}{4}^{\circ}</math> W., 27.7 ft. dist., with fragmentary scribe marks visible on the bark. (Record, S. <math>14^{\circ}</math> W.)</p> <p>and the remains of a bearing object by Monrean</p> <p>A sawed fir stump, 32 ins. diam., bears S. <math>86\frac{3}{4}^{\circ}</math> W., 33.7 ft. dist., with boat spike driven into center of the top.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears S. <math>20\frac{3}{4}^{\circ}</math> E., 15.1 ft. dist., mkd. 1/4 S8 BT.</p> <p>A fir, 9 ins. diam., bears S. <math>61\frac{3}{4}^{\circ}</math> W., 12.6 ft. dist., mkd. 1/4 S7 BT.</p> <p>From this corner, a point erroneously perpetuated as the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8 by Haines in 1960, and perpetuated by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965, recorded in the Douglas County Surveyors Record of Government</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>Corners Renewed T. 23 S., R. 4 W., Point Identifier No. 200540, and is not utilized during the course of this survey, bears N. 38° 31' 22" W., 1.09 ft. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass disk, 1 in. diam., affixed to top, mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of a bearing tree mkd. by Tracy</p> <p style="padding-left: 40px;">A roothole bears N. 64½° E., 15.6 ft. dist., with no remains of the fir trunk.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 11' 50" W., beginning new measurement.</p> <p>Ascend over broken NE. slope.</p>								
1311.58	<p>The N 1/16 sec. cor. of secs. 7 and 8, established by Haines in 1960, and is accepted as the cor., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 14 ins. above the ground, from which the remains of a bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A roothole bears S. 58¼° W., 17.9 ft. dist., with fallen cedar trunk, size indeterminate, lying alongside, with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">N 1/16</td> </tr> <tr> <td style="padding: 0 5px;">S 7</td> <td style="text-align: center; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="3" style="padding: 0 10px;">2007</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 47¼° E., 8.6 ft. dist., mkd. N 1/16 S8 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 65¾° W., 8.8 ft. dist., mkd. N 1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 08' 12" W., beginning new measurement.</p> <p>Descend over NE. slope, posting and blazing.</p>	N 1/16		S 7		S 8	2007		
N 1/16									
S 7		S 8							
2007									

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1312.05	<p>The cor. of secs. 5, 6, 7, and 8, perpetuated by O.F. Thiel, Douglas County Surveyors Office, in 1904, from original evidence no longer in existence, further perpetuated by Haines in 1960, and further perpetuated by Victor Cangie, Douglas County Surveyors Office, in 1976, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 200600, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T 23 S R 4 W S 6   S 5 ----- S 7   S 8 1976</p> <p>from which the remains of a bearing tree mkd. by Thiel</p> <p style="padding-left: 40px;">A cedar, 31 ins. diam., bears S. <math>10\frac{3}{4}^{\circ}</math> E., 11.5 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by Cangie</p> <p style="padding-left: 40px;">A cedar, 29 ins. diam., bears N. <math>41^{\circ}</math> E., 16.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears S. <math>86\frac{1}{4}^{\circ}</math> W., 66.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. <math>68\frac{3}{4}^{\circ}</math> W., 10.6 ft. dist., with a healed double blaze.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. <math>89^{\circ} 36' 07''</math> W., bet. secs. 6 and 7.</p> <p>Ascend over steep W. slope, continue posting and blazing.</p>
990	Ridge, bears N. $35^{\circ}$ W. and S. $35^{\circ}$ E., desc. over NW. slope.
1292.20	<p>The E 1/16 sec. cor. of secs. 6 and 7, established by Haines in 1963, and is accepted as the cor., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 13 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. <math>71\frac{1}{4}^{\circ}</math> E., 4.3 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears S. <math>56^{\circ}</math> W., 9.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{r} S \ 6 \\ \hline E \ 1/16 \\ S \ 7 \\ 2007 \end{array}</math> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">An oak, 12 ins. diam., bears N. 17½° E., 28.1 ft. dist., mkd. E 1/16 S6 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 10¾° E., 18.2 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 52' 31" W., beginning new measurement.</p> <p>Descend over NW slope.</p>
1288.97	<p>The ¼ sec. cor. of secs. 6 and 7, perpetuated by O.F. Thiel, County Surveyor, in 1899, perpetuated by Ben B. Irving, County Surveyor, in 1940, from original evidence no longer in existence, perpetuated by James W. Byron, Douglas County Surveyors Office, in 1957, perpetuated by Gary Langlitz, of the Douglas County Surveyors Office, in 1975, perpetuated by Steven J. Flause, Douglas County Surveyors Office, in 1979, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 23 S., R. 4 W., Point Identifier No. 140600, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above a mound of stone, 2 ft. base, 6 ins. to top, (with an iron bar, ¼ in. X 3ins., firmly set, projecting 6 ins. above the mound of stone, set by persons unknown), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>DOUGLAS COUNTY SURVEYOR</p> <p>T 23 S R 4 W</p> <math display="block">\begin{array}{r} S \ 6 \\ \hline 1/4 \\ S \ 7 \\ 1979 \end{array}</math> </div> <p>from which the remains of a bearing tree mkd. by Byron</p> <p style="margin-left: 40px;">A sawed fir stump, 30 ins. diam., bears S. 32¼° E., 30.5 ft. dist., with no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEEET	<p>and the remains of a bearing tree mkd. by Langlitz</p> <p style="padding-left: 40px;">A sawed fir stump, 24 ins. diam., bears N. 35¼° E., 26.1 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Flause</p> <p style="padding-left: 40px;">A sawed fir stump, 19 ins. diam., bears S. 22¼° W., 46.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears N. 19½° W., 42.9 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 47¼° E., 78.6 ft. dist., mkd. 1/4 S7 BT.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground for a reference monument, bears N. 43° 52' 19" E., 7.10 ft. dist., with aluminum cap mkd. RM 1/4 S6 7.10 FT TO COR 2007 and an arrow pointing to the corner.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 7, T. 23 S., R. 4 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the ¼ sec. cor. of secs. 7 and 18.</p> <p>N. 0° 14' 27" E., on the N. and S. centerline of sec. 7.</p> <p>Ascend over SW. slope.</p> <p>1328.16 The center S 1/16 sec. cor. of sec. 7, established by Hoffine, in 1999, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding: 0 5px;">ROCK</td> <td></td> <td style="padding: 0 5px;">TIMBER</td> </tr> <tr> <td style="padding: 0 5px;">T23S R4W</td> <td style="padding: 0 5px;">LONE</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">CS 1/16</td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S7</td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">1999</td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">PLS 2291</td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> </table> </div> <p>from which bearing trees mkd. by Hoffine</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 39° W., 18.2 ft. dist., with a healed blaze.</p>	ROCK		TIMBER	T23S R4W	LONE		CS 1/16			S7			1999			PLS 2291		
ROCK		TIMBER																	
T23S R4W	LONE																		
CS 1/16																			
S7																			
1999																			
PLS 2291																			

**Subdivision of Section 7,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 15 ins. diam., bears N. 59¼° W., 21.0 ft. dist., with a healed blaze.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 0° 15' 03" E., beginning new measurement.</p> <p>Descend over broken NE. slope, posting and blazing.</p>
430	Graveled road, 15 ft. wide, bears N. 85° E. and S. 85° W.
1328.14	<p>The center ¼ sec. cor. of sec. 7, established by Haines in 1963, and is accepted as the cor., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p style="text-align: center;">A fir, 31 ins. diam., bears S. 81¼° E., 73.2 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A sawed fir stump, 12 ins. diam., bears S. 38¾° W., 39.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W</p> <p style="text-align: center;">C 1/4 S 7</p> <p style="text-align: center;">2007</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A fir, 12 ins. diam., bears N. 12¼° E., 10.8 ft. dist., mkd. C 1/4 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 0° 12' 48" E., beginning new measurement.</p> <p>Across a broken W. slope.</p>
2622.96	<p>The ¼ sec. cor. of secs. 6 and 7.</p> <hr style="width: 80%; margin: auto;"/> <p>From the ¼ sec. cor. of secs. 7 and 8.</p>

**Subdivision of Section 7,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>N. 89° 36' 18" W., on the E. and W. centerline of sec. 7.</p> <p>Ascend over NE. slope.</p>
1322.26	<p>The center E 1/16 sec. cor. of sec. 7, established by Haines in 1963, and is accepted as the cor., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above the ground, from which bearing trees mkd. by Haines,</p> <p style="padding-left: 40px;">A sawed cedar stump, 17 ins. diam., bears N. 7¾° E., 39.1 ft. dist., with fragmentary scribe marks visible on an open blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 66 W., 13.0 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       E 1/16        C ——— C        S 7        2007     </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 23¾° E., 17.5 ft. dist., mkd. CE 1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 52' 42" W., beginning new measurement.</p> <p>Descend over broken NW. slope, posting and blazing.</p>
1322.42	<p>The center ¼ sec. cor. of sec. 7.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 49' 02" W., beginning new measurement.</p> <p>Descend over NW. slope, changing to ascend over SE. slope.</p>
2633.31	<p>The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 7 and 8.</p>

Subdivision of Section 7,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	
1306.49	<p>N. 89° 30' 50" W., on the E. and W. centerline of the NE¼ of sec. 7.</p> <p>Ascend over broken NE. slope, changing to descend over NW. slope, posting and blazing.</p> <p>The NE 1/16 sec. cor. of sec. 7, established by Haines in 1963, and is accepted as the cor., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir snag, 32 ins. diam., bears N. 79° E., 37.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed cedar stump, 48 ins. diam., bears N. 4½° W., 23.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 7 2007</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 7½° E., 22.9 ft. dist., mkd. NE 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 78¾° E., 30.9 ft. dist., mkd. NE 1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located 10 ft. E. of a dirt road, 19 ft. wide, bears N. 10° W. and S. 10° E.</p>
1309.73	<hr/> <p>N. 0° 31' 04" W., on the N. and S. centerline of the NE¼ of sec. 7.</p> <p>Descend over broken NW. slope, continue posting and blazing.</p> <p>The E 1/16 sec. cor. of secs. 6 and 7.</p> <p>Discontinue posting and blazing.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 8.</p>

**Subdivision of Section 7,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>N. 89° 59' 40" W., on the E. and W. centerline of the SE¼ of sec. 7.</p> <p>Descend over broken SW. slope, posting and blazing.</p>
390	Graveled road, 15 ft. wide, bears N. 20° W. and S. 20° E.
1320.44	<p>The SE 1/16 sec. cor. of sec. 7, established by Haines in 1963, and is accepted as the corner, determined at record bearing and dist. from the remaining bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A cedar, 36 ins. diam., bears S. 5° W., 77.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Drive magnetic nail (Mag Nail), 2½ ins. x ¼ ins. flush into root of fir tree, 14 ins. diameter.</p> <p>from which a new accessory</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° 02' 29" E., 10.00 ft. dist. with brass cap mkd. RM SE 1/16 S7 10.0 FT TO COR 2007 and an arrow pointing to the corner.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on a vertical rock face at the base of a fir root crown, 19.0 ft. East of a graveled road, 15 ft. wide, bears N. 35° W. and S. 35° E.</p> <hr/> <p>N. 0° 03' 49" E., on the N. and S. centerline of the SE¼ of sec. 7.</p> <p>Ascend over broken W. slope, posting and blazing.</p>
1323.85	<p>The center E 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 7.</p>
2638.51	<p>N. 89° 47' 55" W., on the E. and W. centerline of the SW¼ of sec. 7.</p> <p>The S 1/16 sec. cor. of secs. 7 and 12 on the W. bdy. of the Tp.</p>

## T. 23 S., R. 4 W., Willamette Meridian, Oregon

FEET	GENERAL DESCRIPTION
	<p>The lands included in the foregoing resurvey are located in Douglas County, approximately 10 miles northeast of the town of Yoncalla, Oregon. The terrain is mountainous, elevations range from approximately 720 feet above sea level near the <math>\frac{1}{4}</math> section corner of sections 6 and 7, to about 2280 feet above sea level near the <math>\frac{1}{4}</math> section corner of sections 17 and 20.</p> <p>The area is drained by numerous small and seasonal drainages flowing northwesterly into Adams Creek. The timber consists of fir, cedar, hemlock, alder, maple, oak, chinquapin, pine, ash, yew, and madrone. The undergrowth is mainly scotch broom, salal, Oregon grape, manzanita, arrowwood, poison oak, vine maple, ferns, and young timber.</p> <p>Access is by logging roads branching from Douglas County Road No. 7, "Elk Head Road".</p> <p>No mineral deposits were noted along the lines resurveyed. The lands are used primarily for timber production.</p>