

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

TOWNSHIP 25 SOUTH, RANGE 4 WEST

AND

THE METES-AND-BOUNDS SURVEY OF A PORTION OF THE EAST BOUNDARY

OF PARCEL 2, STATUTORY SPECIAL WARRANTY DEED OR-49268

TOWNSHIPS 25 AND 26 SOUTH, RANGE 4 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 2, 2004,
approved February 6, 2004, which provided for the
surveys included under Group No. 2069,
and Assignment Instructions dated February 13, 2004.

Survey commenced February 19, 2004

Survey completed March 29, 2004

T. 25 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, Township 25 South, Range 4 West, and the metes-and-bounds survey of a portion of the east boundary of Parcel 2, Statutory Special Warranty Deed OR-49268, Townships 25 and 26 South, Range 4 West, of the Willamette Meridian, Oregon.</p> <p>The history of federal surveys pertaining to this survey is as follows:</p> <p>In 1855, Addison Flint, U.S. Deputy Surveyor, surveyed the township lines and subdivisions of T. 26 S., R. 4 W., as shown on the official plat of survey approved December 10, 1855.</p> <p>In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the north and south boundaries and a portion of the subdivisions of T. 25 S., R. 4 W., as shown on the official plat of survey approved February 20, 1856.</p> <p>In 1856, Aaron Bowser, U.S. Deputy Surveyor, surveyed Donation Land Claim 37 in T. 26 S., R. 4 W., as described in the official field notes of survey, Contract No. 28, bearing the date April 4, 1956.</p> <p>In 1871, William H. Byars, U.S. Deputy Surveyor, completed the subdivisions of T. 25 S., R. 4 W., as shown on the official plat of survey approved April 26, 1872.</p> <p>In 1957-58, Irving Zirpel, Jr., Lynn M. Roseberry, and Harold D. Corbin, Cadastral Surveyors, resurveyed a portion of the subdivisions and subdivided certain sections of T. 25 S., R. 4 W., as shown on the official plat of survey accepted October 6, 1959.</p> <p>In 1982, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the subdivisions and subdivided certain sections of T. 25 S., R. 4 W., as shown on the official plat of survey accepted August 3, 1984.</p> <p>In 1983, Lance J. Bishop and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the subdivisions and subdivided certain sections of T. 25 S., R. 4 W., as shown on the official plat of survey accepted February 22, 1985.</p> <p>The history of private surveys pertaining to this survey is as follows:</p> <p>In 1968, William S. Barnes, Oregon Professional Engineer No. 2128, resurveyed a portion of the subdivisions and surveyed a metes-and-bounds survey in section 33 of T. 25 S., R. 4 W., and sections 4, 5, and 8 of T. 26 S., R. 4 W., as shown on map file M33-39, filed at the Douglas County Surveyors Office.</p>
------	---

T. 25 S., R. 4 W., Willamette Meridian, Oregon

FEET

In 1969, William S. Barnes, Oregon Professional Engineer No. 2128, surveyed a metes-and-bounds "survey for deed description" in sections 5 and 8 of T. 26 S., R. 4 W., as shown on map file M39-32, filed at the Douglas County Surveyors Office.

In 1970, William S. Barnes, Oregon Professional Engineer No. 2128, surveyed a metes-and-bounds "survey for deed description" in sections 8 and 17 of T. 26 S., R. 4 W., as shown on map file M39-2, filed at the Douglas County Surveyors Office.

In 1972, William S. Barnes, Oregon Professional Engineer No. 2128, surveyed a metes-and-bounds survey in section 16 of T. 26 S., R. 4 W., as shown on map file M38-65, filed at the Douglas County Surveyors Office.

In 1974, Glen S. Baughman, Oregon Professional Land Surveyor No. 536, resurveyed a portion of the subdivisions and surveyed a metes-and-bounds survey in sections 31, 32, and 33 of T. 25 S., R. 4 W., as shown on map file M49-75, filed at the Douglas County Surveyors Office.

In 1976, William S. Barnes, Oregon Professional Engineer No. 2128, surveyed a metes-and-bounds survey in sections 7, 8, 17, and 18 of T. 26 S., R. 4 W., as shown on map file M56-51, filed at the Douglas County Surveyors Office.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated February 2, 2004, for Group No. 2069, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO), version 1.61. The GPS portion of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS techniques, and carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the

T. 25 S., R. 4 W., Willamette Meridian, Oregon

FEET

least squares adjustment of the survey data fell between 0.7 and 1.2. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. Adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 28, 29, 32, and 33, T. 25 S., R. 4 W., as determined from a tie to Geodetic Control Station EC41298, established by the Bureau of Land Management (BLM) in 2004 (see Control Data Sheet included in these field notes following General Description), is as follows:

Latitude: 43° 21' 34.79" N. Longitude: 123° 11' 11.61" W.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 8, 9, 16, and 17, T. 26 S., R. 4 W., as determined from a tie to Geodetic Control Station EC41298, established by the BLM in 2004 (see Control Data Sheet included in these field notes following General Description), is as follows:

Latitude: 43° 18' 56.91" N. Longitude: 123° 11' 16.93" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Harvey Gordon and Charles T. Gardner, the 1871 survey by William H. Byars, the 1957-58 resurvey by Irving Zirpel Jr., Lynn M. Roseberry, and Harold D. Corbin, and the 1982 resurvey by James E. Jelley and Wayne L. Rogers)

Beginning at the 1/4 sec. cor. of secs. 28 and 33, perpetuated by the Douglas County Surveyors Office in 1966, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 25 S., R. 4 W., Point Identifier No. 340200, monumented with an iron post, 1½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	COUNTY SURVEYORS OFFICE T 25 S S 28 1/4 ————— S 33 R 4 W 1966
	from which the remains of an original bearing tree A decayed fir stump, size indeterminate, bears S. 50° E., 19.1 ft. dist., with axe marks visible. and bearing trees mkd. by the Douglas County Surveyors Office A fir, 22 ins. diam., bears S. 49¾° W., 9.8 ft. dist., with a healed double blaze. A fir, 17 ins. diam., bears N. 69° W., 11.2 ft. dist., with a healed double blaze. and bearing tree mkd. by persons unknown A fir, 40 ins. diam., bears S. 76¼° W., 33.2 ft. dist., mkd. 1/4 in the bark. N. 87° 18' 25" W., bet. secs. 28 and 33. Ascend broken NE. slope.
1372.72	Point for the W 1/16 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 25 S R 4 W S 28 W 1/16 ————— S 33 2004 </div> from which A fir, 13 ins. diam., bears N. 21½° E., 11.1 ft. dist., mkd. W 1/16 S28 BT. A fir, 10 ins. diam., bears S. 68° E., 24.8 ft. dist., mkd. W 1/16 S33 BT. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.


**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 15 ins. above ground, established by an unauthorized BLM administrative survey in 1972, bears N. 14° 03' 14" W., 2.28 ft. dist. This point was not accepted or utilized in the course of this survey. Remove the iron pipe and bury it alongside the stainless steel post.</p> <p>Ascend broken NE. slope, marking and blazing the true line.</p>
1660	Barbed wire fence, bears N. 22° W. and S. 22° E.
1738.86	<p>Point for Angle Point 34, at intersection with the E. bdy. of Statutory Special Warranty Deed OR-49268, Parcel 2.</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W</p> <p> S 28</p> <hr style="width: 10%; margin: 0 auto;"/> <p>AP 34 S33</p> <p>PAR 2</p> <p> 2004</p> </div> <p>Deposit a magnet, in a white plastic case, alongside the aluminum rod.</p> <p>Ascend broken NE. slope, discontinue posting and blazing.</p>
1830	Top of ridge and dirt road, 12 ft. wide, bears N. 60° W. and S. 60° W.; desc. steep S. slope.
2745.44	<p>The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W</p> <p> S 29 S 28</p> <hr style="width: 10%; margin: 0 auto;"/> <p> S 32 S 33</p> <p> 1957</p> </div> <p>from which the remaining bearing tree mkd. by Zirpel, Roseberry, and Corbin</p> <p style="padding-left: 40px;">A cedar, 33 ins. diam., bears S. 57½° E., 108.2 ft. dist., with fragmentary scribe marks visible on a burned partially healed blaze.</p> <p>and bearing trees mkd. by Jelley and Rogers</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 23 ins. diam., bears N. 84° E., 166.3 ft. dist., with fragmentary scribe marks visible on a burned partially healed blaze. (Record, N. 85° E.)</p> <p>A cedar, 19 ins. diam., bears S. 51° W., 234.3 ft. dist., with a healed blaze.</p> <p>An oak, 13 ins. diam., bears N. 86½° W., 352.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>Corner lies 33 ft. N. of down wire fence, bears N. 80° W. and S. 80° E.</p> <p>From this corner, BLM Geodetic Control Station "EC 41298", at latitude 43° 19' 41.328" N. and longitude 123° 11' 32.087" W., determined by the NAVSTAR GPS utilizing static, dual frequency carrier phase receivers (see the Control Data Sheet included in these field notes following the General Description), bears S. 7° 30' 15" W., 11587.44 ft. dist. (mean bearing and sea level dist.), monumented with an aluminum rod, 3/4 in. diam., firmly set, flush with the ground, with aluminum cap mkd. EC41298 GPS 2004.</p> <hr/> <p style="text-align: center;">Metes-and-Bounds Survey of a Portion of the East Boundary of Parcel 2, Statutory Special Warranty Deed OR-49268, Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>This survey identifies a portion of the boundaries of a parcel of land conveyed by Statutory Special Warranty Deed OR-49268 (Book 1287, page 919, and Recorder's No. 94-07149, Records of Douglas County, Oregon), dated March 24, 1994, from 2Linc., to the United States of America. The deed basis of bearing has been rotated to the true meridian.</p> <hr/> <p>From Angle Point 1, Parcel 2, Statutory Special Warranty Deed OR-49268 (hereinafter referred to as Deed OR-49268), on the northerly right-of-way line of North Bank County Road, as determined by Barnes in 1970, monumented with an iron rod, 1 in. diam., firmly set, buried 18 ins. below ground, and is accepted as a point controlling the alignment of the E. bdy. of Parcel 2.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 54 ins. in the ground, buried 18 ins. below ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

F E E T	<div style="text-align: center; margin-bottom: 20px;"> <p>PAR 2 AP 1</p>  <p>S 8 T 26 S R 4 W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner of fences extending N. 58° E., S. 65° E., and N. 72° W., bears N. 50° E., 15.6 ft. dist.</p> <p>From this corner, the cor. of secs. 8, 9, 16, and 17, T. 26 S., R. 4 W., bears S. 87° 43' 45" E., 2824.92 ft. dist., perpetuated by the Douglas County Surveyors Office in 1947 and 1971, from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 4 W., Point Identifier No. 300500, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 26 S</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S 8</td> <td style="text-align: center;">S 9</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">S 17 S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">R 4 W</td> </tr> <tr> <td colspan="2" style="text-align: center;">1971</td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1947</p> <p style="margin-left: 40px;">A root hole, bears S. 70¼° E., 89.7 ft. dist., with fallen oak trunk, 22 ins. diam., lying alongside, scribe marks R4 S visible on a decayed, partially healed blaze.</p> <p>and new reference monuments</p> <p style="margin-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears N. 15° 18' 05" E., 304.40 ft. dist., with aluminum cap mkd. RM T26S R4W S8 304.4 FT TO COR 2004, and an arrow pointing to the cor.</p> <p style="margin-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears N. 46° 18' 45" W., 272.90 ft. dist., with aluminum cap mkd. RM T26S R4W S9 272.9 FT TO COR 2004, and an arrow pointing to the cor.</p> <p>From this corner, BLM Geodetic Control Station "EC 41298", bears N. 13° 59' 21" W., 4635.04 ft. dist. (mean bearing and sea level dist.), hereinbefore described.</p>	T 26 S		S 8	S 9	S 17 S16		R 4 W		1971	
T 26 S											
S 8	S 9										
S 17 S16											
R 4 W											
1971											

**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>N. 60° 35' 24" E., on the E. bdy. of Parcel 2, Deed OR-49268.</p> <p>Begin posting and blazing.</p>
578.80	<p>Point for Angle Point 2, Parcel 2, Deed OR-49268, determined at distance-distance intersection bet. Angle Point 1 and Angle Point 3</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 AP 2 S 8 T 26 S R 4 W 2004</p> </div> <p>Corner lies 2.0 ft. S. of wire fence extending N. 52° E. and S. 65° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
202.79	<p>N. 47° 01' 31" E., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 3, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 1 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 AP 3 S 8 T 26 S R 4 W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of fences extending N. 50° E., S. 30° E., and S. 50° W.</p> <hr style="width: 20%; margin: 10px auto;"/>
531.78	<p>N. 47° 01' 31" E., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 4, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as the corner.</p>

Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> PAR 2 \ \ AP 4 > T26S / / S 8 R4W 2004 </pre> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies 0.8 ft. S. of wire fence extending N. 47° E. and S. 47° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 35° 32' 22" W., beginning new measurement; continue posting and blazing.</p>
60	<p>Dirt road, 10 ft. wide, bears N. 57° E. and S. 73° W.</p>
1438.40	<p>Point for Angle Point 5, Parcel 2, Deed OR-49268, determined at distance-distance intersection bet. Angle Point 4 and Angle Point 6</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 38 ins. in the ground, buried 2 ins. below ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> AP 5 \ \ PAR 2 > T26S / / S 8 R4W 2004 </pre> </div> <p>Deposit a magnet, in a white plastic case, alongside the aluminum rod.</p> <p>Corner of fences extending N. 6° E. and S. 35° E. bears N. 51¼° E., 7.1 ft. dist.</p> <p>Corner lies on E. edge of all-terrain vehicle trail.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 6° 51' 49" E., beginning new measurement; continue posting and blazing.</p>
568.90	<p>Angle Point 6, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p>

**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 T26S AP 6 S 8 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies beneath wire fence extending N. 30° E. and S. 8° W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 33° 46' 33" E., beginning new measurement; continue posting and blazing.</p>
1089.47	<p>Angle Point 7, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 5 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 T26S AP 7 S 8 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies 1.6 ft. S. of wire fence extending N. 44° E. and S. 38° W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 41° 24' 02" E., beginning new measurement; continue posting and blazing.</p>
1261.80	<p>Angle Point 8, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, and is accepted as the corner.</p> <p>On top of the iron rod, drive an aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 T26S AP 8 S 8 R4W 2004</p> </div> <p>Corner lies at intersection of fences extending N. 8° W. and S. 40° W.</p>

**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
325.38	<p>From this point, BLM Geodetic Control Station "EC 41298" bears N. 41° 07' 19" W., 17.99 ft. dist., hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 9° 05' 26" W., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 9, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, and is accepted as the corner.</p> <p>On top of the iron rod, drive an aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>PAR 2 T26S AP 9 S 8 R4W 2004</p> </div> <p>Corner lies at intersection of fences extending N. 46° E. and S. 8° E., and 11.0 ft. S. of all-terrain vehicle trail extending N. 55° E. and S. 47° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 47° 12' 56" E., beginning new measurement; continue posting and blazing.</p>
1152.24	<p>Angle Point 10, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 5 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>PAR 2 T26S AP 10 S 5 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies beneath wire fence extending N. 10° E. and S. 46° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 12° 01' 05" E., beginning new measurement; continue posting and blazing.</p>
544.20	<p>Angle Point 11, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p>

Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>On top of the iron rod, drive an aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 / T26S AP 11 / S 5 R4W 2004</p> </div> <p>Corner lies 0.4 ft. SE. of fences extending N. 45° E. and S. 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 44° 18' 21" E., beginning new measurement; continue posting and blazing.</p>
<p>395.10</p>	<p>Angle Point 12, Parcel 2, Deed OR-49268, established by Barnes in 1968, and is accepted as the corner, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 / T26S AP 12 / S 5 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies beneath wire fence extending N. 45° E. and S. 45° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 39° 18' 56" E., beginning new measurement; continue posting and blazing.</p>
<p>351.95</p>	<p>Angle Point 13, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 / T26S AP 13 / S 4 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p>




Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEET													
	<p>Corner lies at intersection of wire fences extending N. 20° E. and S. 45° W.</p> <hr/> <p>N. 16° 56' 06" E., beginning new measurement; continue posting and blazing.</p> <p>465.60 Angle Point 14, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 12 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>PAR 2</td> <td> </td> <td>T26S</td> </tr> <tr> <td>AP 14</td> <td>/</td> <td>S 4</td> </tr> <tr> <td></td> <td></td> <td>R4W</td> </tr> <tr> <td></td> <td></td> <td>2004</td> </tr> </table> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies 0.5 ft. E. of wire fences extending N. 8° E. and S. 20° W.</p> <hr/> <p>N. 11° 23' 10" E., beginning new measurement; continue posting and blazing.</p>	PAR 2		T26S	AP 14	/	S 4			R4W			2004
PAR 2		T26S											
AP 14	/	S 4											
		R4W											
		2004											
310.15	<p>Angle Point 15, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>PAR 2</td> <td>/</td> <td>T26S</td> </tr> <tr> <td>AP 15</td> <td>/</td> <td>S 4</td> </tr> <tr> <td></td> <td></td> <td>R4W</td> </tr> <tr> <td></td> <td></td> <td>2004</td> </tr> </table> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies 2.7 ft. W. of wire fences extending N. 42° E. and S. 14° W.</p> <hr/> <p>N. 41° 21' 10" E., beginning new measurement; continue posting and blazing.</p>	PAR 2	/	T26S	AP 15	/	S 4			R4W			2004
PAR 2	/	T26S											
AP 15	/	S 4											
		R4W											
		2004											

**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
596.67	<p>Angle Point 16, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 T26S AP 16 S 4 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies 2.7 ft. W. of wire fences extending N. 14° E. and S. 38° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 13° 28' 47" E., beginning new measurement; continue posting and blazing.</p>
873.03	<p>Angle Point 17, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 30 ins. long, 3/4 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>PAR 2 T26S AP 17 S 4 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. and S. 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 33' 18" E., beginning new measurement; continue posting and blazing.</p>
356.96	<p>Angle Point 18, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as the corner.</p> <p>On top of the iron rod, drive an aluminum cap mkd.</p>



Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<div style="text-align: center;">  <p>PAR 2 T26S AP 18 S 4 R4W 2004</p> </div> <p>Corner lies at intersection of fences extending N. 45° E. and South.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 38° 32' 28" E., beginning new measurement; continue posting and blazing.</p> <p>1965.19 Angle Point 19, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  <p>PAR 2 T26S AP 19 S 4 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner of wire fences extending N. 23° W. and S. 33° W. bears S. 63° E., 1.8 ft. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 15° 56' 29" W., beginning new measurement; continue posting and blazing.</p>
638.74	<p>Angle Point 20, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 16 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  <p>PAR 2 T25S AP 20 S 33 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p>

**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET													
750.32	<p>Corner lies at intersection of wire fences extending N. 14° E. and S. 12° E.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 13° 41' 17" E., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 21, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding-right: 5px;">PAR 2</td> <td style="font-size: 2em; vertical-align: middle;">/</td> <td style="padding-left: 5px;">T25S</td> </tr> <tr> <td style="padding-right: 5px;">AP 21</td> <td style="font-size: 2em; vertical-align: middle;">/</td> <td style="padding-left: 5px;">S 33</td> </tr> <tr> <td></td> <td></td> <td style="padding-left: 10px;">R4W</td> </tr> <tr> <td></td> <td></td> <td style="padding-left: 15px;">2004</td> </tr> </table> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 30° E. and S. 26° W.</p> <hr style="width: 20%; margin: 0 auto;"/>	PAR 2	/	T25S	AP 21	/	S 33			R4W			2004
PAR 2	/	T25S											
AP 21	/	S 33											
		R4W											
		2004											
2125.84	<p>N. 21° 13' 51" E., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 22, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding-right: 5px;">PAR 2</td> <td style="font-size: 2em; vertical-align: middle;">/</td> <td style="padding-left: 5px;">T25S</td> </tr> <tr> <td style="padding-right: 5px;">AP 22</td> <td style="font-size: 2em; vertical-align: middle;">/</td> <td style="padding-left: 5px;">S 33</td> </tr> <tr> <td></td> <td></td> <td style="padding-left: 10px;">R4W</td> </tr> <tr> <td></td> <td></td> <td style="padding-left: 15px;">2004</td> </tr> </table> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner of wire fence extending N. 48° E. bears N. 55° E., 6.5 ft. dist.</p> <p>Corner of wire fence extending S. 19° W. bears S. 8° W., 7.5 ft. dist.</p> <hr style="width: 20%; margin: 0 auto;"/>	PAR 2	/	T25S	AP 22	/	S 33			R4W			2004
PAR 2	/	T25S											
AP 22	/	S 33											
		R4W											
		2004											



**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	N. 50° 58' 16" E., beginning new measurement; continue posting and blazing.
850.98	<p>Angle Point 23, Parcel 2, Deed OR-49268, established by Barnes in 1968, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W</p>  <p>AP 23 S 33</p> <p>PAR 2</p> <p>2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner of wire fences extending S. 48° W. and S. 76° W. bears S. 74° E., 1.6 ft. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 44' 22" W., beginning new measurement; continue posting and blazing.</p>
10	Dirt road, 10 ft. wide, bears N. 62° E. and S. 62° W.
885.62	<p>Angle Point 24, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W</p>  <p> S 33</p> <p>AP 24</p> <p>PAR 2</p> <p>2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 78° W. and S. 54° E.</p> <hr style="width: 20%; margin: 10px auto;"/>



**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
210.00	<p>N. 82° 04' 26" W., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 25, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W S 33 AP 25 PAR 2 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 66° W. and S. 78° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 70° 05' 08" W., beginning new measurement; continue posting and blazing.</p>
311.32	<p>Angle Point 26, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W S 33 AP 26 PAR 2 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 43° W. and S. 63° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 44° 24' 32" W., beginning new measurement; continue posting and blazing.</p>



Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEET	
180.43	<p>Angle Point 27, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  <p>AP 27 PAR 2</p> <p>T25S S 33 R4W</p> <p>2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 23° W. and S. 40° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 24° 51' 07" W., beginning new measurement; continue posting and blazing.</p>
115.74	<p>Angle Point 28, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  <p>AP 28 PAR 2</p> <p>T25S S 33 R4W</p> <p>2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 4° E. and S. 23° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 23' 14" W., beginning new measurement; continue posting and blazing.</p>
222.24	<p>Angle Point 29, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p>


Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W</p>  <p>AP 29 S33 PAR 2 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 24° W. and S. 4° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 30° 20' 01" W., beginning new measurement; continue posting and blazing.</p>
<p>161.07</p>	<p>Angle Point 30, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 4 W</p>  <p>AP 30 S33 PAR 2 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner of wire fences extending N. 54° W. and S. 28° E. bears S. 60° W., 1.6 ft. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 56° 46' 24" W., beginning new measurement; continue posting and blazing.</p>
<p>236.85</p>	<p>Angle Point 31, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.</p>

Metes-and-Bounds Survey of the East Boundary of
 Parcel 2, Statutory Special Warranty Deed OR-49268,
 Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<div style="text-align: center;">  <p>T25S AP 31 S33 PAR 2 R4W 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner of wire fences extending N. 20° W. and S. 55° E. bears S. 47° W., 2.7 ft. dist.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 30° 15' 39" W., beginning new measurement; continue posting and blazing.</p>
95	<p>Dirt road, 12 ft. wide, bears N. 16° W. and S. 16° E.</p>
255	<p>Dirt road, 12 ft. wide, bears N. 40° W. and S. 40° E.</p>
314.39	<p>Angle Point 32, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  <p>T 25 S R 4 W AP 32 S33 PAR 2 2004</p> </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies at intersection of wire fences extending N. 54° W. and S. 40° E.</p> <hr style="width: 20%; margin: 10px auto;"/>
290.42	<p>N. 43° 23' 21" W., beginning new measurement; continue posting and blazing.</p> <p>Angle Point 33, Parcel 2, Deed OR-49268, established by Baughman in 1974, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and is accepted as the corner.</p> <p>At the corner point</p> <p>Set a finned aluminum rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.</p>

**Metes-and-Bounds Survey of the East Boundary of
Parcel 2, Statutory Special Warranty Deed OR-49268,
Tps. 25 and 26 S., R. 4 W., Willamette Meridian, Oregon**

FEEET	<div style="text-align: center; margin-bottom: 20px;"> <p>T 25 S R 4 W</p>  </div> <p>Bury the iron rod, 30 ins. long, alongside the aluminum rod.</p> <p>Corner lies on east side of overgrown bulldozer trail beneath wire fence extending N. 26° W. and S. 26° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 43° 23' 21" W., beginning new measurement; continue posting and blazing.</p> <p>213.78 Angle Point 34, Parcel 2, Deed OR-49268, on the line bet. secs. 28 and 33, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in rolling hills approximately 11 miles northeasterly of the community of Roseburg, Oregon.</p> <p>Elevation ranges from approximately 800 feet above sea level near the corner of sections 8, 9, 16, and 17 to approximately 2200 feet above sea level near Angle Point 23, Parcel 2, Deed OR-49268.</p> <p>The area is drained by Cooper Creek to the east and an unnamed creek to the west, which flow southwesterly to the North Fork of the Umpqua River.</p> <p>Timber consists of fir, cedar, oak, and madrone. Undergrowth consists of poison oak and grasses.</p> <p>The soil is generally composed of rocky clay.</p> <p>Access to the survey was made by all-terrain vehicle trails branching from North Bank Road.</p> <p>The mean magnetic declination for the area surveyed is 19° East, as shown on the "OAK CREEK VALLEY, OREG." 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1987.</p>
-------	--