

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE NORTH BOUNDARY AND SUBDIVISIONAL LINES, AND

THE SUBDIVISION OF SECTION 2,

TOWNSHIP 25 SOUTH, RANGE 7 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated May 19, 2004, approved May 20, 2004,
which provided for the surveys included under Group No. 2079,
and Assignment Instructions dated June 7, 2004.

Survey commenced July 12, 2004

Survey completed August 10, 2004

T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the north boundary and subdivisional lines, and the subdivision of section 2, Township 25 South, Range 7 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1857-58, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the north and west boundaries, and a portion of the subdivisional lines.</p> <p>In 1874, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the west boundary and a portion of the subdivisional lines.</p> <p>In 1893-94, Williams R. Whipple, U.S. Deputy Surveyor, surveyed portions of the north boundary, while completing the subdivisional lines of T. 24 S., R. 7 W.</p> <p>In 1896, William P. Heydon, U.S. Deputy Surveyor, surveyed portions of the north, east, and south boundaries and completed the subdivisional lines.</p> <p>In 1958, Irving Zirpel Jr., Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines.</p> <p>In 1967-68, Lynn M. Roseberry, Cadastral Surveyor, dependently resurveyed a portion of the north boundary and subdivisional lines.</p> <p>In 1973, Daniel L. Berry and Charles E. Akin, Jr., Cadastral Surveyors, dependently resurveyed a portion of the south boundary of T. 24 S., R. 7 W.</p> <p>In 1979, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, dependently resurveyed a portion of the south boundary of T. 24 S., R. 7 W.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and Special Instructions dated May 19, 2004, for Group No. 2079, Oregon.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>The directions of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements carried forward by sustained angulation using conventional survey techniques.</p>
------	---

T. 25 S., R. 7 W., Willamette Meridian, Oregon

F E E T	<p>Distances along the lines were derived through the use of electronic measuring equipment.</p> <p>The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.</p> <p>The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at the 95% confidence level is 0.30 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The unadjusted data assured a closure not exceeding 1:4000 in error. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of sections 1 and 2, as determined by ties to stations "DODSON BUTTE CORS ARP" and "CAPE BLANCO CORS ARP" is as follows:</p> <p>Latitude: 43° 25' 29.82" N. Longitude: 123° 29' 08.98" W.</p> <p>Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the North Boundary, T. 37 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the 1893-94 survey by Williams R. Whipple, the 1896 survey by William P. Heydon, the 1967-68 resurvey by Lynn M. Roseberry, the 1973 resurvey by Daniel L. Berry and Charles E. Akin, Jr., and the 1979 resurvey by James E. Jelley and Wayne L. Rogers)</p> <hr/> <p>Beginning at the ¼ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 7 W S 35 1/4 ————— S 2 T 25 S 1967</p>
---------	---

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET													
	<p>from which bearing trees mkd. by Roseberry</p> <p>A fir, 24 ins. diam., bears S. 39¼° E., 51.5 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears N. 29½° W., 34.0 ft. dist., with a healed blaze.</p> <p>N. 89° 23' 59" W., bet. secs. 2 and 35, posting and blazing the true line.</p> <p>Descend broken NW. slope.</p>												
2170	Creek, 2 ft. wide, course N. 15° W.; asc. broken NE. slope.												
2580	Spur, slopes N. 15° E.; desc. broken NW. slope.												
2720.21	<p>The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p>												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td>T 24 S</td> <td>R 7 W</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 25 S</td> </tr> <tr> <td colspan="2" style="text-align: center;">1958</td> </tr> </table>	T 24 S	R 7 W	S 34	S 35	— —		S 3	S 2	T 25 S		1958	
T 24 S	R 7 W												
S 34	S 35												
— —													
S 3	S 2												
T 25 S													
1958													
	<p>from which the remains of bearing trees mkd. by person(s) unknown, reported by Zirpel</p> <p>A cedar, 24 ins. diam., bears S. 75½° E., 43.2 ft. dist., with scribe marks T W visible on open blaze. (Record, S. 71° E)</p> <p>A fir, 39 ins. diam., bears S. 66° E., 49.5 ft. dist., with fragmentary scribe marks visible on a bark blaze.</p> <p>A sawed fir stump, 40 ins. diam., bears S. 33½° W., 45.6 ft. dist., with fragmentary scribe marks visible on a bark blaze. (Record, S. 35° W., 47.2 ft.)</p> <p>and bearing trees mkd. by Zirpel</p> <p>A cedar, 20 ins. diam., bears N. 45½° E., 35.6 ft. dist., with a healed blaze.</p> <p>A fir, 26 ins. diam., bears N. 71½° W., 51.2 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 2003, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 07 W., Point Identifier No. 500700</p>												

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 14 ins. diam., bears S. 71° E., 2.0 ft. dist., with scribe marks S2 BT visible on a partially healed blaze.</p>
	<p>and a new bearing tree</p>
	<p>A hemlock, 11 ins. diam., bears S. 78½° W., 45.6 ft. dist., mkd. T25S R7W S3 BT.</p>
	<hr/>
	<p>S. 89° 35' 27" W., bet. secs. 3 and 34; continue posting and blazing.</p>
	<p>Continue descent over broken NW. slope.</p>
135	<p>Creek, 1 ft. wide, course N. 45° E.; asc. broken E. slope.</p>
710	<p>Graveled road, 15 ft. wide, bears S. 10° W. and N. 10° W.</p>
985	<p>Spur, slopes N. 10° W.; desc. broken NW. slope.</p>
2525	<p>Creek, 1 ft. wide, course N. 25° W.; asc. broken NE. slope.</p>
2624.52	<p>The ¼ sec. cor. of secs. 3 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 24 S S 34 1/4 ——— S 3 T 25 S R 7W 1973</p>
	<p>from which the remaining original bearing tree</p>
	<p>A fir, 46 ins. diam., bears S. 82° E., 25.1 ft. dist., with fragmentary scribe marks visible on a burned partially healed blaze and axe marks W visible on the bark.</p>
	<p>and bearing trees mkd. by Berry and Akin</p>
	<p>A hemlock, 14 ins. diam., bears S. 18½° E., 17.2 ft. dist., with scribe marks S3 B visible on a partially healed blaze.</p>
	<p>A fir, 30 ins. diam., bears N. 56° W., 25.7 ft. dist., with a healed blaze.</p>
	<p>and a bearing tree mkd. by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 2003, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 07 W., Point Identifier No. 440700</p>

**Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon**

FEET							
	<p>A hemlock, 8 ins. diam., bears S. $86\frac{1}{2}^{\circ}$ W., 20.3 ft. dist., with scribe marks 1/4 S BT visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ} 32' 51''$ W., beginning new measurement; continue posting and blazing.</p> <p>Continue ascent over broken NE. slope.</p>						
1800	Spur, slopes N. 15° W.; desc. broken NW. slope.						
1860	Dirt road, 10 ft. wide, bears S. 10° E. and N. 10° W.						
2185	Dirt road, 10 ft. wide, bears N. 25° E. and S. 25° W.						
2405.54	<p>The closing cor. of secs. 33 and 34 only, on the S. bdy. of T. 24 S., R. 7 W., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">CC</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">T 24 S</td><td style="padding: 0 5px;">R 7 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 33</td><td style="padding: 0 5px;">S 34</td></tr> </table> </div> <p style="text-align: center; margin: 10px 0;">S 3 T 25 S R 7 W 1973</p> <p>from which bearing trees mkd. by Berry and Akin</p> <p style="margin-left: 40px;">A fir, 23 ins. diam., bears N. 37° E., 127.0 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. $43\frac{1}{2}^{\circ}$ W., 83.5 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. $35\frac{1}{4}^{\circ}$ E., 44.9 ft. dist., mkd. T24S R7W CC S34 BT.</p> <p style="margin-left: 40px;">A cedar, 6 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ W., 20.3 ft. dist., mkd. T24S R7W CC S33 BT.</p> <p>From this point, the original closing cor. of secs. 33 and 34 bears S. $0^{\circ} 53' 00''$ W. (record, S. $0^{\circ} 12' E.$), 4.95 ft. dist., perpetuated by the Douglas County Surveyor's Office, in 1970, and Bruce Shaner, Registered Engineer No. 4906, in 1972, and filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 7 W., Point Identifier No. 403700, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p>	CC		T 24 S	R 7 W	S 33	S 34
CC							
T 24 S	R 7 W						
S 33	S 34						

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 24 S R 7 W W.M. 1973 <u>S 33 S 34</u> C.C. 1972</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 31 ins. diam., bears N. 61° E., 42.2 ft. dist., with a healed blaze and axe marks visible in the bark.</p> <p style="padding-left: 40px;">A double trunk fir snag, 17 ins. diam., bears N. 20° W., 24.4 ft. dist., with no marks visible.</p> <p>and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A fir snag, 36 ins. diam., bears N. 21° E., 57.8 ft. dist., with scribe marks T24S R7W S34 CS BT visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 32' 57" W., beginning new measurement; continue posting and blazing.</p>
204.78	<p>The cor. of secs. 3 and 4 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, in a loose mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 7 W S 33 <u>S 4 S 3</u> T 25 S 1973</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 39½° E., 14.5 ft. dist., with fragmentary scribe marks visible on an opened blaze. (Record, N. 43° E.)</p> <p>and remains of a bearing tree mkd. by Zirpel</p> <p style="padding-left: 40px;">A decayed cedar stump, 30 ins. diam., bears S. 31° W., 21.5 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by Berry and Akin</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 12½° E., 20.8 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 20 ins. diam., bears S. 81° W., 40.6 ft. dist., with a healed blaze.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/> <p>(Restoring the 1896 survey by William P. Heydon, and the 1958 resurvey by Irving Zirpel Jr.)</p> <hr/> <p>From the ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, in a loose mound of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 7 W 1/4 S 4 S 3 1958</p> </div> <p>from which bearing trees mkd. by Zirpel</p> <p>A cedar, 28 ins. diam., bears N. 29° E., 33.7 ft. dist., with a healed blaze.</p> <p>A fir, 28 ins. diam., bears N. 45° W., 46.9 ft. dist., with scribe marks 1/4 S4 BT visible on a partially healed blaze.</p> <p>N. 1° 02' 57" W., bet. secs. 3 and 4, posting and blazing.</p> <p>Ascend steep S. slope.</p>
1210	Top of ridge, bears N. 85° E. and S. 85° W.; desc. broken W. slope.
1825	Dirt road, 10 ft. wide, bears N. 30° E. and S. 30° W.
2705.71	The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp., described on page 21589.
	<hr/> <p style="text-align: center;">Subdivision of Section 2, T. 25 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 2 and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p>

Subdivision of Section 2,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	T 25 S R 7 W S 2 1/4 ——— S 11 1958
	from which bearing trees mkd. by Zirpel A fir, 23 ins. diam., bears S. 39½° W., 5.6 ft. dist., with a healed blaze. A cedar, 27 ins. diam., bears N. 12° W., 70.3 ft. dist., with a healed blaze. Official record iron post, 1 in. diam., with brass cap, set by the Douglas County Surveyor's Office in 1957, reported by Zirpel, was removed by the Douglas County Surveyor's Office in 1959, as described in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 7 W., Point Identifier No. 540600. N. 0° 51' 50" W., on the N. and S. centerline of sec. 2 Descend broken NW. slope.
100	Graveled road, 15 ft. wide, bears N. 80° E. and S. 80° W.
2714.89	The center ¼ sec. cor. of sec. 2, established by David A. Edwards, Oregon Professional Land Surveyor No. 2339, in 2001, filed in the Douglas County Surveyor's Office, Map File No. M139-10, and Record of Government Corners Renewed, T. 25 S., R. 7 W., Point Identifier No. 540640, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, with alum. cap mkd.
	ROSEBURG RESOURCES T 25 S R 7 W C 1/4 —·— S 2 LS 2339 2001 COMPANY
	from which the bearing trees mkd. by Edwards A fir, 22 ins. diam., bears N. 48¼° E., 19.4 ft. dist., with scribe marks 1/4 S2 BT visible on a partially healed blaze. A fir, 5 ins. diam., bears S. 37¼° E., 25.4 ft. dist., with scribe marks C1/4 S2 BT visible on a partially healed blaze.

Subdivision of Section 2,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET			
	<p>A fir, 9 ins. diam., bears S. $43\frac{3}{4}^{\circ}$ W., 11.6 ft. dist., with scribe marks C1/4 S2 BT visible on a partially healed blaze.</p> <p>A fir, 14 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ W., 6.2 ft. dist., with scribe marks C1/4 S2 BT visible on a partially healed blaze.</p> <hr/> <p>N. $0^{\circ} 52' 43''$ W., beginning new measurement, posting and blazing.</p> <p>Descend broken NE. slope.</p>		
605	Creek, 1 ft. wide, course N. 25° W.; asc. broken W. slope.		
1130	Spur, slopes W.; desc. broken W. slope.		
2775.26	The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., described on page 21585.		
	<hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 7 W</p> <p>1/4</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> </table> <p>1967</p> </div> <p>from which the remains of bearing trees mkd. by Roseberry</p> <p>A cedar, 47 ins. diam., bears N. $73\frac{1}{4}^{\circ}$ E., 97.0 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 42 ins. diam., bears S. $17\frac{1}{4}^{\circ}$ W., 149.2 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p>A fir, 22 ins. diam., bears N. 17° W., 34.5 ft. dist., mkd. 1/4 S2 BT.</p> <p>N. $89^{\circ} 29' 38''$ W., on the E. and W. centerline of sec. 2, posting and blazing.</p> <p>Ascend steep NE. slope.</p>	S 2	S 1
S 2	S 1		
1690	Spur, slopes N. 15° W.; desc. broken W. slope.		
2190	Ravine, drains N. 45° W.; asc. broken NE. slope.		

Subdivision of Section 2,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET	
2670.98	<p>The center $\frac{1}{4}$ sec. cor. of sec. 2.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. $89^{\circ} 30' 43''$ W., beginning new measurement.</p> <p>Descend broken NW. slope.</p>
465	Graveled road, 15 ft. wide, bears N. 30° W. and S. 30° E.
2055	Graveled road, 15 ft. wide, bears N. 60° W. and S. 60° E.
2180	Graveled road, 15 ft. wide, bears N. 65° E. and S. 60° W.
2395	Creek, 1 ft. wide, course N. 25° E.; asc. broken E. slope.
2510	Graveled road, 15 ft. wide, bears N. 20° E. and S. 20° W.
2679.34	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, and in a loose mound of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 7 W</p> <p>1/4</p> <p style="margin: 0 10px;"> </p> <p>S 3 S 2</p> <p>1958</p> </div> <p>from which the remains of bearing trees mkd. by Zirpel</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 39° E., 63.7 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A roothole bears S. $62\frac{1}{2}^{\circ}$ W., 65.0 ft. dist., with fallen hemlock snag, 20 ins. diam., lying alongside, no marks visible. (Record, S. 66° W.)</p> <p>and a bearing tree mkd. by Bruce Shaner, Registered Professional Engineer No. 4906, in 1972, and filed in Douglas County Surveyor's Office, Map File No. M47-40</p> <p style="margin-left: 40px;">A yew, 13 ins. diam., bears S. $66\frac{3}{4}^{\circ}$ W., 48.2 ft. dist., with scribe marks $\frac{1}{4}$ S3 BT visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 0 auto;"/>

T. 25 S., R. 7 W., Willamette Meridian, Oregon

FEET

GENERAL DESCRIPTION

The lands included in the foregoing survey are located in mountainous terrain, approximately 9 miles west-northwesterly from the community of Sutherlin, Oregon.

The elevation ranges from approximately 800 feet above sea level near the corner of sections 2, 3, 34, and 35, on the north boundary of the township, to approximately 1900 feet near the corner of sections 3 and 4 only, on the north boundary of the township.

The area is drained by Lost Creek which flows northwesterly to the Umpqua River.

Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

The soil is generally composed of rocky clay.

Access to the survey was made by graveled roads branching from Tyee Road.

The mean magnetic declination for the area surveyed is 19° East, as shown on the "TYEE MOUNTAIN, OREG." 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1987.