

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY

AND SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 20 AND 30,

**TOWNSHIP 21 SOUTH, RANGE 7 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

***Edith M. Forkner, Cadastral Surveyor***

Under Special Instructions dated July 1, 2005, approved July 1, 2005,

and Supplemental Special Instructions dated December 5, 2005,

approved December 6, 2005,

which provided for the surveys included under Group No. 2114,

and Assignment Instructions dated August 15, 2005, and December 16, 2005

***Survey commenced September 8, 2005***

***Survey completed October 26, 2006***

## T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the corrective dependent resurvey of a portion of the subdivisional lines, dependent resurvey of a portion of the west boundary and subdivisional lines, and the subdivision of sections 20 and 30, Township 21 South, Range 7 West, Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1855, Harvey Gordon and Charles T. Gardiner, U.S. Deputy Surveyors, surveyed the south boundary of the township.</p> <p>In 1883, Laban H. Wheeler, U.S. Deputy Surveyor, surveyed the west boundary of the township and a portion of the subdivisional lines.</p> <p>In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines and retraced a portion of the south boundary of the township.</p> <p>In 1952-54, Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, resurveyed the east boundary of Township 21 South, Range 8 West.</p> <p>In 1964, Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines and remonumented an original corner.</p> <p>In 1967, Donald E. Beck, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and established the E 1/16 section corner of sections 17 and 20. Les Roberts, Registered Land Surveyor No. 1039, recovered and utilized this BLM E 1/16 section corner on a survey filed in the Douglas County Surveyors Office under Map File No. M77-13, in 1979. An investigation by Edith M. Forkner, Cadastral Surveyor, documented in an Investigation Report dated October 12, 2005, found that the 1967 BLM E 1/16 section corner of sections 17 and 20 was erroneously positioned, necessitating this corrective action.</p> <p>In 1986, Wayne L. Rogers and Joel E. Robb, Cadastral Surveyors, resurveyed a portion of the subdivisional lines and subdivided section 28.</p> <p>In 1999-2000, Aaron M. Graham, Cadastral Surveyor, remonumented and rehabilitated certain original corner points without survey.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the <u>Special Instructions dated July 1, 2005</u>, and <u>Supplemental Special Instructions dated December 5, 2005</u>, for Group No. 2114, Oregon.</p>
------	---

## T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by direct solar observations.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (91)) of the quarter corner of sections 19 and 30, as determined by a direct tie from a Global Positioning System (GPS) observation on a temporary monument processed using the National Geodetic Survey's Online Positioning User Service (OPUS), in 2006, is as follows:

Latitude: 43° 43' 17.27" N.      Longitude: 123° 34' 29.43" W.

The geographic position (NAD 1983 (91)) of the quarter corner of sections 18 and 19, as determined by a tie from a GPS observation on a temporary monument processed using the National Geodetic Survey's OPUS, in 2006, is as follows:

Latitude: 43° 44' 06.00" N.      Longitude: 123° 34' 29.77" W.

---

**Corrective Dependent Resurvey  
of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

---

(Correcting the survey by Beck in 1967)

---

Beginning at the cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 21 S	R 7 W
S 17	S 16
S 20	S 21
1964	

Corrective Dependent Resurvey  
of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEEET	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 44 ins. diam., bears N. 61° E., 44.9 ft. dist., with illegible marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 20 ins. diam., bears S. 60° E., 50.6 ft. dist., no marks visible, with a hemlock, 3 ins. diam., growing out of the S. side. (Record, 51.5 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 54 ins. diam., bears S. 22° W., 42.9 ft. dist., with a healed blaze. (Record, 60 ins. diam.)</p> <p style="padding-left: 40px;">A fir, 56 ins. diam., bears N. 47° W., 62.7 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 79 1/4° E., 13.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 47 1/4° E., 28.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 86 1/2° W., 45.9 ft. dist., with axe marks on bark.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 53° W., 19.1 ft. dist., with axe marks on bark.</p> <p>N. 89° 43' 00" W., bet. secs. 17 and 20.</p> <p>Descend over SW. slope through medium timber and moderate undergrowth.</p> <p>1324.13 Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 17  E 1/16 ———  S 20  2005</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 32 ins. diam., bears S. 39 1/4° W., 26.4 ft. dist., mkd. E1/16 S20 BT.</p> <p style="padding-left: 40px;">A cedar, 29 ins. diam., bears N. 19° W., 24.1 ft. dist., mkd. E1/16 S17 BT with Mag Nail at left side center.</p>
-------	---

**Corrective Dependent Resurvey  
of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post. Corner is located southerly of down fir log, 2 1/2 ft. diam., in hole chainsawed out of down log.</p> <p>From this cor., a point established as the E 1/16 sec. cor. of secs. 17 and 20 by Beck, in 1967, and recovered and utilized by Les Roberts, Registered Land Surveyor No. 1039, in 1979, filed in the Douglas County Surveyors Office under Map File No. M77-13, bears N. 89° 18' 36" E., 20.15 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the official record, from which the remains of the bearing trees mkd. by Beck in 1967</p> <p style="padding-left: 40px;">A roothole bears N. 44 1/2° E., 8.6 ft. dist., alongside of which is a down hemlock, 29 ins. diam., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 27 ins. diam., bears S. 56 1/2° E., 19.1 ft. dist., with a healed blaze.</p> <p>This point was erroneously positioned and was not utilized for control in this resurvey. Remark the cap to read AM 20.2 FT TO COR 2005 with an arrow pointing to the corner and destroy the marks on the remaining bearing tree.</p> <p>Descend over SW. slope through medium timber and moderate undergrowth.</p>
2325	<p>Halfway Creek Road, graveled surface, 10 ft. wide, bears N. 75° W. and S. 70° E.</p>
2648.26	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 7 W S 17 1/4 ——— S 20 1967</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole bears South, 4.0 ft. dist., with a down decayed cedar, 45 ins. diam., alongside, no marks visible.</p> <p>and a bearing tree mkd. by Beck in 1967</p> <p style="padding-left: 40px;">A maple, 24 ins. diam., bears S. 35° W., 17.4 ft. dist., no marks visible. (Record, 19.1 ft. dist.)</p> <p>and a new bearing tree</p>

**Corrective Dependent Resurvey  
of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET

A hemlock, 25 ins. diam., bears N. 70 1/2° W.,  
40.0 ft. dist., mkd. 1/4 S17 BT.

Corner is located N., 45 ft. of Halfway Creek, 15 ft. wide,  
course W., and S., 90 ft. of Halfway Creek Road, graveled  
surface, 10 ft. wide, bears N. 65° W. and S. 80° E.

---

**Dependent Resurvey of a Portion of the West Boundary,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

---

(Restoring the survey by Laban H. Wheeler in 1883 and  
the resurvey by Marvin J. Lytle, et al., in 1952-54)

From the cor. of Tps. 21 and 22 S., Rgs. 7 and 8 W., monumented  
with an iron post, 3 ins. diam., firmly set, projecting 6 ins.  
above ground, with brass cap mkd.

T 21 S	
R 8 W	R 7 W
S 36	S 31
S 1	S 6
T 22 S	
1952	

from which the remains of the original bearing trees

A cedar, 56 ins. diam., bears S. 30° E., 18.5 ft. dist.,  
with a healed blaze.

A roothole bears N. 30° W., 36.3 ft. dist., with a down  
cedar, 30 ins. diam., alongside, no marks visible.

and the bearing trees mkd. by Lytle, et al., in 1952-54

A cedar, 27 ins. diam., bears N. 50 1/2° E.,  
28.4 ft. dist., with a healed blaze.

A hemlock, 25 ins. diam., bears S. 34 1/2° W.,  
17.2 ft. dist., with a healed blaze.

A fir, 30 ins. diam., bears N. 42 3/4° W., 58.7 ft. dist.,  
with a healed blaze.

A steel fence post is alongside the cor.

N. 0° 19' 03" E., bet. secs. 31 and 36, marking and blazing the  
true line.

**Dependent Resurvey of a Portion of the West Boundary,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	Across nearly level land through medium timber and light undergrowth.
250	Ravine, drains SE.; asc. over broken SE. slope.
555	Creek, 2 ft. wide, course S. 50° E.; asc. across W. slope.
785	Same creek, course S. 20° W.; asc. over S. slope.
1885	From this point, W., 20 ft. to new dirt road, 15 ft. wide, bears N. 5° W. and S. 30° W.
2600	Little Paradise Creek Road, asphalt surface, 12 ft. wide, bears N. 80° E. and S. 85° W.
2677.78	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S\ 36 \quad   \quad S\ 31 \\ 1952 \end{array}$
	from which the remains of the original bearing trees
	A decayed fir stump, 27 ins. diam., bears N. 80° E., 17.8 ft. dist., no marks visible.
	A roothole bears N. 35° W., 23.8 ft. dist., with a down fir, 35 ins. diam., alongside, no marks visible.
	and the bearing trees mkd. by Graham in 1999-2000
	A fir, 20 ins. diam., bears N. 51 1/4° E., 23.9 ft. dist., with a healed blaze.
	A fir, 17 ins. diam., bears S. 84° W., 27.3 ft. dist., with a healed blaze.
	and the bearing trees mkd. by Gary T. Smither, Registered Land Surveyor No. 2485, in 2005, and filed in the Douglas County Surveyor's Office, under CS File No. 65/54-19
	A fir, 15 ins. diam., bears S. 72° E., 21.9 ft. dist., with scribe marks 21 R7 1/4 S31 BT visible on partially healed blaze.
	A fir, 18 ins. diam., bears S. 19 3/4° W., 27.8 ft. dist., with scribe marks S36 BT and other illegible marks visible on partially healed blaze.
	A steel fence post is alongside the cor.

**Dependent Resurvey of a Portion of the West Boundary,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET													
	N. 2° 12' 29" E., beginning new measurement.												
	Ascend over S. slope through medium timber and light undergrowth.												
1485	Ridge, bears E. and W.; desc. over N. slope.												
1830	Bottom of descent, slopes NW.; asc. over broken SW. slope.												
2140	Spur, slopes NW.; desc. over NE. slope through dense undergrowth.												
2516.01	The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.												
	<table style="margin: auto;"> <tr><td colspan="2">T 21 S</td></tr> <tr><td>R 8 W</td><td>R 7 W</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td colspan="2">1952</td></tr> </table>	T 21 S		R 8 W	R 7 W	S 25	S 30			S 36	S 31	1952	
T 21 S													
R 8 W	R 7 W												
S 25	S 30												
S 36	S 31												
1952													
	from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54												
	A fir, 38 ins. diam., bears N. 74 1/4° E., 53.5 ft. dist., no marks visible.												
	A decayed fir stump, 20 ins. diam., bears S. 65 1/2° W., 29.7 ft. dist., no marks visible. (Record, 30.4 ft. dist.)												
	A fir, 40 ins. diam., bears N. 60 3/4° W., 63.4 ft. dist., with a healed blaze.												
	and new bearing trees												
	A fir, 9 ins. diam., bears S. 64° E., 41.1 ft. dist., mkd. T21S R7W S31 BT.												
	A fir, 6 ins. diam., bears S. 62 3/4° W., 33.5 ft. dist., mkd. T21S R8W S36 BT.												
	N. 0° 43' 00" W., bet. secs. 25 and 30, on the W. bdy. of the Tp.												
	Descend over steep NE. slope through medium timber and dense undergrowth.												
300	Ravine, drains N. 45° W.; asc. across steep W. slope.												

**Dependent Resurvey of a Portion of the West Boundary,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1115	Spur, slopes N. 30° W.; desc. over steep N. slope through light undergrowth.
1247.12	Point for the S 1/16 sec. cor. of secs. 25 and 30. Not monumented.
1915	Paradise Creek, 12 ft. wide, course S. 65° W., in center of bottom land, 150 ft. wide; asc. over S. slope changing to W. slope.
2494.24	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	<div style="text-align: center;"> <math display="block">\begin{array}{c} 1/4 \\ \text{S } 25 \quad   \quad \text{S } 30 \\ \hline 1952 \end{array}</math> </div>
	from which the bearing trees mkd. by Lytle, et al. in 1952-54
	<div style="padding-left: 40px;"> <p>A fir, 30 ins. diam., bears N. 66° E., 7.9 ft. dist., with a healed blaze.</p> </div>
	<div style="padding-left: 40px;"> <p>A fir, 41 ins. diam., bears S. 62 3/4° W., 7.9 ft. dist., with a healed blaze.</p> </div>
	An iron rod with an International Paper Co. sign is alongside the cor.
	Corner is located E., 50 ft., of creek, 2 ft. wide, course S. 10° W.
	<hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/>
	<p style="text-align: center;">(Restoring the survey by William P. Wright in 1884, the resurvey by Floyd A. Brooks and James E. Jelley in 1964, and the resurvey by Donald E. Beck in 1967)</p> <hr/>
	From the cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.
	<div style="text-align: center;"> <math display="block">\begin{array}{c} \text{T } 21 \text{ S } \quad \text{R } 7 \text{ W} \\ \text{S } 29 \quad   \quad \text{S } 28 \\ \hline \text{S } 32 \quad   \quad \text{S } 33 \\ \hline 1964 \end{array}</math> </div>
	from which the bearing trees mkd. by Brooks and Jelley in 1964

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	A fir, 21 ins. diam., bears N. 63° E., 41.8 ft. dist., with a healed blaze. (Record, 45.5 ft. dist.)
	A fir, 21 ins. diam., bears S. 86° E., 53.2 ft. dist., with a healed blaze. (Record, 56.1 ft. dist.)
	A fir, 14 ins. diam., bears S. 2° W., 50.8 ft. dist., with a healed blaze.
	A white fir, 27 ins. diam., bears N. 12° W., 67.3 ft. dist., with a healed blaze. (Record, 66.7 ft. dist.)
	Corner is located N., 45 ft. of a rock gully, 20 ft. wide, 25 ft. deep, drains W., on a SW. cor. older fir reproduction, edge bears N. and E.
	N. 3° 10' 00" E., bet. secs. 28 and 29.
	Ascend over SW. slope through medium timber and moderate undergrowth, along the W. edge of older fir reproduction.
145	Creek, 1 ft. wide, course S. 45° W.; asc. over SW. slope.
340	Drainage, course S. 80° W.; asc. over S. slope.
670	Ascend over gentle SW. slope.
825	Graveled road, 12 ft. wide, bears N. 60° W. and S. 85° E. 15 ft. to its junction with Little Tom Folley Road, graveled surface, 12 ft. wide, bears N. 40° E. and S. 40° E., at the NE. cor. of timber, edge bears N. 60° W. and S.; con. along E. edge of timber through older fir reproduction.
1085	Ridge, bears N. 70° W. and S. 70° E.; con. across nearly level land.
1130	Descend over steep N. slope.
1360	Drainage, course N. 40° W.; con. across W. slope.
1660	Beginning of rock faces, bears W.
1840	End of rock faces; asc. over SW. slope.
2255	SE. cor. of timber, edge bears N. and W.; con. along W. edge of fir reproduction.
2295	Ridge, bears N. 20° W. and S. 20° E.; desc. over NE. slope.
2527.55	The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	$\frac{1}{4}$ S 29   S 28 T 21 S R 7 W 1964
	from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964
	A decayed fir stump, 16 ins. diam., bears S. 26 1/4° E., 8.6 ft. dist., with a healed blaze.
	A fir snag, 13 ins. diam., bears S. 87° W., 12.5 ft. dist., with a healed blaze.
	and new bearing trees
	A fir, 7 ins. diam., bears S. 27 1/4° E., 31.4 ft. dist., mkd. 1/4 S28 BT.
	A fir, 20 ins. diam., bears S. 80 3/4° W., 24.2 ft. dist., mkd. 1/4 S29 BT.
	Corner is located on W. edge fir of reproduction, edge bears N. and S.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 3° 19' 14" E., beginning new measurement.
	Descend over steep N. slope, along top of ascent, through medium timber and moderate undergrowth, along the W. edge fir reproduction.
655	Little Tom Folley Creek, 10 ft. wide, course N. 80° W.; asc. over broken S. slope.
1040	NW. cor. of fir reproduction, edge bears S. and E.; enter timber and con. across W. slope.
1475	Ascend over SW. slope.
1940	Westerly tip of triangle junction of Little Paradise Creek Road, asphalt surface, 15 ft. wide, bears N. 45° W. and S. 70° E., and graveled road, 10 ft. wide, bears S. 45° E., at the SW. cor. fir reproduction, edge bears N. and S. 70° E., on a ridge, bears N. 45° W. and S. 55° E.; desc. over NE. slope, along W. edge of fir reproduction.
2075	Drainage, course N. 80° E.; con. across E. slope.
2529.88	The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEEET	<div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 21 S</td><td>R 7 W</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td colspan="2">1964</td></tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 21 1/2° E., 7.3 ft. dist., with a healed blaze. (Record, N. 16 3/4° E.)</p> <p style="padding-left: 40px;">A fir snag, 11 ins. diam., bears S. 74 1/4° E., 13.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 41° W., 11.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 11 ins. diam., bears N. 62° W., 3.6 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 85 3/4° E., 30.5 ft. dist., mkd. T21S R7W S28 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 86 3/4° W., 28.9 ft. dist., mkd. T21S R7W S20 BT.</p> <p>Corner is located at the NW. and SE. cors. of fir reproduction, edges bear N., S., E., and W., with timber to the NE. and SW.</p> <hr style="width: 50%; margin-left: 0;"/> <p>N. 6° 07' 26" W., bet. secs. 20 and 21.</p> <p>Descend over broken NE. slope through medium timber and moderate undergrowth, along the E. edge of fir reproduction.</p> <p>1276.64 The S 1/16 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto;"> <tr><td>S 1/16</td></tr> <tr><td>S 20   S 21</td></tr> <tr><td>1964</td></tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A metal capped fir stump, 12 ins. diam., bears N. 7 1/2° E., 10.9 ft. dist., with a healed blaze.</p>	T 21 S	R 7 W	S 20	S 21			S 29	S 28	1964		S 1/16	S 20   S 21	1964
T 21 S	R 7 W													
S 20	S 21													
S 29	S 28													
1964														
S 1/16														
S 20   S 21														
1964														

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A metal capped fir stump, 14 ins. diam., bears N. 36 1/2° W., 27.1 ft. dist., with a healed blaze. (Record and slope distance, N. 35° W., 29.4 ft. dist.)</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears S. 40° E., 9.7 ft. dist., mkd. S1/16 S21 BT.</p> <p>A fir, 7 ins. diam., bears N. 70 3/4° W., 8.1 ft. dist., mkd. S1/16 S20 BT.</p> <p>Corner is located on an E. slope on the E. edge of fir reproduction, edge bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 6° 07' 36" W., beginning new measurement.</p> <p>Ascend over SE. slope through medium timber and moderate undergrowth, along the E. edge fir reproduction.</p>
370	Overgrown graveled road, 10 ft. wide, bears N. 45° E. and S. 45° W.
550	Ridge, bears N. 45° E. and S. 45° W.; desc. over NW. slope.
1269.71	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4 S 20   S 21 T 21 S R 7 W 1964</p> </div> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p>A fir, 31 ins. diam., bears S. 25° E., 23.4 ft. dist., with a healed blaze.</p> <p>A shattered fir stump, size indeterminate, bears S. 61° W., 18.2 ft. dist., no marks visible.</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears N. 41 1/4° W., 157.0 ft. dist., mkd. 1/4 S20 BT. Tree is located on W. edge of overgrown graveled road, 20 ft. wide, bears N. 20° W. and S. 20° W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located W., 1/2 ft. of fir, 3 ft. diam., with International Paper Co. property sign, on the E. edge of fir reproduction, edge bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 6° 03' 48" W., beginning new measurement.</p> <p>Descend over NW. slope through medium timber and moderate undergrowth, along E. edge of fir reproduction.</p>
1125	Halfway Creek, 4 ft. wide, course N. 50° W.; con. across nearly level land.
1265	Creek, 2 ft. wide, course S. 50° W.; con. across nearly level land.
1275.40	<p>The N 1/16 sec. cor. of secs. 20 and 21, remonumented by Wilford Haines, Registered Land Surveyor No. 239, in 1973, filed in the Douglas County Surveyors Office, under CS File No. 51/309; monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 7 W N 1/16 S 20 S 21 RS 239</p> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A decayed fir stump, covered with road fill, flush with surface, size indeterminate, bears N. 65 3/4° E., 69.3 ft. dist., no marks visible. (Record, N. 67 1/2° E.)</p> <p style="padding-left: 40px;">A hemlock, 24 ins. diam., bears S. 3° W., 48.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 51 ins. diam., bears S. 86 1/2° E., 101.6 ft. dist., mkd. N1/16 S21 BT.</p> <p>Corner is located in heavy alder blowdown in road clearing, on the NE. cor. of fir reproduction, edge bears S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 5° 56' 46" W., beginning new measurement.</p> <p>Ascend over S. slope through medium timber and moderate undergrowth.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEEET													
120	Halfway Creek Road, graveled surface, 10 ft. wide, bears S. 70° E. and W.												
1261.17	<p>The cor. of secs. 16, 17, 20, and 21.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 21 S</td> <td>R 7 W</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2">T 22 S</td> </tr> <tr> <td colspan="2">1964</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 63 1/2° E., 12.3 ft. dist., with a healed blaze. (Record, N. 38 1/2° E., 13.2 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 73° E., 13.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 16 ins. diam., bears S. 36 3/4° W., 10.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N. 5° W., 26.4 ft. dist., with a healed blaze.</p> <p>No suitable trees to the SW. available.</p> <p>A metal fence post is alongside the cor.</p> <p>Corner is located on the NE. cor. of fir reproduction, edge bears S. and W.</p> <p>N. 2° 28' 37" W., bet. secs. 31 and 32.</p> <p>Ascend over broken W. slope through medium timber and moderate undergrowth.</p>	T 21 S	R 7 W	S 31	S 32	<hr style="width: 50%; margin: 0 auto;"/>		S 6	S 5	T 22 S		1964	
T 21 S	R 7 W												
S 31	S 32												
<hr style="width: 50%; margin: 0 auto;"/>													
S 6	S 5												
T 22 S													
1964													
190	Top of ascent, slopes W.; desc. over NW. slope.												
330	Creek, 1 ft. wide, course S. 55° W.; asc. over SW. slope.												
625	Spur, slopes S. 60° W.; desc. over NW. slope.												
750	Drainage, course SW.; asc. across W. slope.												

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
900	Top of ascent, slopes W.; desc. across W. slope.
1095	Descend over NW. slope.
1210	Creek, 2 ft. wide, course W.; asc. over SW. slope.
1290	Top of ascent, slopes W.; desc. across W. slope.
1500	Creek, 1 ft. wide, course W.; con. across nearly level land.
1720	Little Paradise Creek, 4 ft. wide, course S. 15° W.; asc. over SE. slope.
2260	Creek, 1 ft. wide, course S. 70° E.; con. asc. over SE. slope.
2697.70	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">           1/4            S 31   S 32            T 21 S R 7 W            1964         </p> <p>from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A cedar stump, 27 ins. diam., bears N. 21° E., 21.8 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A roothole bears N. 24 1/4° W., 10.2 ft. dist., with a down cedar, 9 ins. diam., alongside, no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 86 1/2° E., 3.4 ft. dist., mkd. 1/4 S32 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 52 1/4° W., 5.1 ft. dist., mkd. 1/4 S31 BT.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 2° 41' 31" W., beginning new measurement.</p> <p>Ascend over SE. slope through medium timber and moderate undergrowth.</p>
280	Top of ascent, slopes E.; desc. across E. slope.
525	Creek, dry, 1 ft. wide, course S. 50° E.; asc. over SE. slope.
870	Spur, slopes SE.; desc. over NE. slope.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEEET																																													
975	Creek, 1 ft. wide, course S. 55° E.; asc. over SE. slope.																																												
2005	Graveled road, 15 ft. wide, bears N. 65° E. and S. 60° W.																																												
2280	Ridge, bears N. 55° E. and S. 55° W.; desc. over NW. slope.																																												
2300	Little Paradise Creek Road, asphalt surface, 18 ft. wide, bears N. 25° E. and S. 45° W.; desc. across W. slope.																																												
2693.34	<p>Point for the cor. of secs. 29, 30, 31, and 32, determined at record bearing and distance from the witness corner established by the Douglas County Surveyor in 1973, filed in the Douglas County Surveyors Office under C.S. File No. 56/25; monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, bears East, 36.00 ft. dist., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td colspan="4">W.C. 36 W. TO</td></tr> <tr><td>T 21 S</td><td></td><td>R 7 W</td><td></td></tr> <tr><td>S 30</td><td> </td><td>S 29</td><td></td></tr> <tr><td colspan="4" style="border-top: 1px solid black;"></td></tr> <tr><td>S 31</td><td> </td><td>S 32</td><td></td></tr> <tr><td colspan="4">1973</td></tr> </table> </div> <p>from which the bearing trees mkd. by the Douglas County Surveyor in 1973</p> <p style="margin-left: 40px;">A chinquapin, 16 ins. diam., bears N. 8 3/4° E., 14.1 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears N. 56 1/2° E., 21.9 ft. dist., with a healed blaze.</p> <p>The 1964 iron post set by Brooks and Jelley was found lying loose on the surface of the ground.</p> <p>At the Corner Point</p> <p>Reset 1964 iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T 21 S</td><td></td><td>R 7 W</td><td></td></tr> <tr><td>S 30</td><td> </td><td>S 29</td><td></td></tr> <tr><td colspan="4" style="border-top: 1px solid black;"></td></tr> <tr><td>S 31</td><td> </td><td>S 32</td><td></td></tr> <tr><td colspan="4">1964</td></tr> </table> </div> <p>from which an original bearing tree</p> <p style="margin-left: 40px;">A fir, 41 ins. diam., bears N. 27° E., 38.3 ft. dist., with a healed blaze at breast height.</p> <p>and the remains of the bearing trees mkd. by Brooks and Jelley in 1964, which are on an unstable slump on top of a cut bank</p>	W.C. 36 W. TO				T 21 S		R 7 W		S 30		S 29						S 31		S 32		1973				T 21 S		R 7 W		S 30		S 29						S 31		S 32		1964			
W.C. 36 W. TO																																													
T 21 S		R 7 W																																											
S 30		S 29																																											
S 31		S 32																																											
1973																																													
T 21 S		R 7 W																																											
S 30		S 29																																											
S 31		S 32																																											
1964																																													

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 22 ins. diam., bears N. 25 3/4° E., 8.1 ft. dist., with a healed blaze. (Record, N. 35° E., 6.6 ft. dist.)</p> <p>A decayed fir stump, size indeterminate, bears S. 50 3/4° E., 17.8 ft. dist., no marks visible. (Record, S. 53° E., 21.8 ft. dist.)</p> <p>and new bearing trees</p> <p>A fir, 14 ins. diam., bears S. 7 1/4° E., 54.8 ft. dist., mkd. T21S R7W S32 BT.</p> <p>A fir, 29 ins. diam., bears S. 12 1/4° W., 60.5 ft. dist., mkd. T21S R7W S31 BT.</p> <p>A fir, 13 ins. diam., bears N. 50 1/2° W., 68.6 ft. dist., mkd. T21S R7W S30 BT. Tree is located on the W. edge of overgrown graveled road, 20 ft. wide, bears N. 10° E. and S. 10° W.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Corner is located just below the top of a steep road cutbank, bears W., and partly under the roots of the NE. bearing tree mkd. by Brooks and Jelley in 1964.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 85° 21' 27" W., bet. secs. 29 and 32.</p> <p>Descend over W. slope through medium timber and moderate undergrowth.</p>
65	Creek, 1 ft. wide, course S. 55° W.; desc. across broken S. slope.
485	Drainage, course S. 30° W.; asc. across rocky S. slope.
675	Seep down rock face, 1/2 ft. wide, drains S.; asc. across rocky S. slope.
820	Top of ascent, slopes S.; desc. over SW. slope.
2010	Abandoned graveled road, 20 ft. wide, bears N. and S.
2165	Top of rock face, 50 ft. high; desc. over SW. slope
2540	Little Tom Folley Creek, 10 ft. wide, course S. 5° E.; asc. over steep E. slope.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEEET 2668.25	<p>The 1/4 sec. cor. of secs. 29 and 32, determined at record bearing and distance from the remains of the original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, 52 ins. diam., bears N. 35° W., 15.8 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A multi-top hemlock, 15 ins. diam., bears S. 28° W., 28.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A half decayed live hemlock, 11 ins. diam., bears N. 32 3/4° W., 25.9 ft. dist., no marks visible. (Record, N. 41 1/2° W., 23.1 ft. dist.)</p> <p>At the Corner Point</p> <p>Set an iron rod, 18 ins. long, 5/8 ins. diam., 6 ins. in solid sandstone, in a mound of dirt, 2 ft. base, 8 ins. high, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 21 S R 7 W</p> <p style="padding-left: 40px;">S 29</p> <p style="padding-left: 40px;">1/4 ———</p> <p style="padding-left: 40px;">S 32</p> <p style="padding-left: 40px;">2005</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 57° E., 29.5 ft. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 11 1/2° W., 8.9 ft. dist., mkd. 1/4 S32 BT.</p> <p>The 1964 iron post set by Brooks and Jelley was found lying loose. Dispose of the 1964 iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 45' 38" W., beginning new measurement.</p> <p>Ascend over steep NE. slope through medium timber and moderate undergrowth.</p>
700	Ascend over steep SE. slope.
985	Spur, slopes N. 70° E.; con. across nearly level land along top of spur.
1085	Leave spur; asc. across steep N. slope.
1250	Ascend over steep NE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1585	Ridge, bears N. 50° W. and S. 50° E., at the NE. cor. of fir reproduction, edge bears S. 50° E. and W.; desc. over SW. slope, along N. edge of fir reproduction.
1795	Across shallow S. slope.
2040	Ascend over SE. slope.
2175	Top of knob; desc. over W. slope.
2445	NW. cor. of fir reproduction, edge bears S. 10° E. and E.; leave fir reproduction.
2510	Little Paradise Creek Road, asphalt surface, 15 ft. wide, bears N. 15° E. and S. 15° W.
2654.07	The cor. of secs. 29, 30, 31, and 32. <hr/>
	S. 87° 40' 32" W., bet. secs. 30 and 31.
	Descend over steep cutbank, slopes W., through medium timber and moderate undergrowth.
45	Abandoned graveled road, 15 ft. wide, bears N. 20° E. and S. 15° W.; desc. over steep W. slope.
205	Descend over shallow W. slope.
365	Headwaters of creek, dry, 20 ft. uphill of spring, 1/2 ft. wide, course S. 75° W.; desc. over SW. slope.
610	Descend over very steep W. slope.
650	Creek, 2 ft. wide, course N. 25° W.; asc. across steep N. slope.
795	Creek, slid out to bedrock in winter of 2005-06, 1/2 ft. wide, course N. 35° E.; asc. over steep E. slope.
1010	Across steep N. slope.
1237.37	The E 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.  <div style="text-align: center;">           S 30            E 1/16 ———            S 31            1964         </div> from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 34 ins. diam., bears S. 11 1/2° W., 29.7 ft. dist., with a healed blaze. (Record, S. 13 1/2° W., 31.7 ft. dist.)</p> <p>A fir stump, 26 ins. diam., bears N. 15 1/2° W., 12.3 ft. dist., with a healed blaze. (Record, N. 20° W., 14.2 ft. dist.)</p> <p>and a new bearing tree</p> <p>A fir, 7 ins. diam., bears N. 19° E., 24.0 ft. dist., mkd. E1/16 S30 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 52' 19" W., beginning new measurement.</p> <p>Descend across steep N. slope through medium timber and moderate undergrowth.</p>
70	Bottom of descent, slopes N.; asc. over steep NE. slope.
320	Across nearly level land along top of spur.
680	Overgrown graveled road, 15 ft. wide, bears S. 75° E. and W.; con. along S. edge of road across S. slope.
1050	Leave road edge, road bears N. 75° W. and E.
1237.94	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> <p>T 21 S R 7 W</p> <p>1964</p> </div> <p>from which a bearing tree mkd. by Brooks and Jelley in 1964</p> <p>A cedar, 77 ins. diam., bears S. 63° E., 43.6 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 16 ins. diam., bears N. 8 1/2° E., 59.6 ft. dist., mkd. 1/4 S30 BT. Tree is located on top of the N. cutbank of overgrown graveled road, 15 ft. wide, bears N. 80° W. and S. 80° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 49' 30" W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	Descend across shallow S. slope through medium timber and light undergrowth.
285	Overgrown graveled road, 15 ft. wide, bears N. 55° E. and S. 55° W., on spur, slopes S. 55° W.; desc. over NW. slope.
365	Different overgrown graveled road, 15 ft. wide, bears N. 50° E. and S. 45° W.
595	Bottom of descent, slopes N.; asc. across steep N. slope.
750	Top of ascent, slopes N.; desc. across steep N. slope.
1195	Bottom of descent, slopes N.; asc. across steep N. slope.
1242.57	The W 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.
	S 30 W 1/16 ——— S 31 1964
	from which the bearing trees mkd. by Brooks and Jelley in 1964
	A hemlock, 14 ins. diam., bears S. 13 1/2° E., 13.1 ft. dist., with a healed blaze. (Record, S. 10 1/2° E., 14.5 ft. dist.)
	A hemlock, 22 ins. diam., bears N. 43° W., 29.0 ft. dist., with a healed blaze.
	—————
	S. 87° 51' 57" W., beginning new measurement.
	Ascend across steep N. slope through medium timber and moderate undergrowth.
50	Ascend over steep NE. slope.
250	Spur, slopes N.; desc. over steep W. slope.
350	Overgrown graveled road, 10 ft. wide, bears N. 10° W. and S. 10° E.
635	Drainage, course N. 20° E.; asc. over steep NE. slope.
1079.71	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp.
	—————
	From the cor. of secs. 29, 30, 31, and 32.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	N. 1° 20' 37" W., bet. secs. 29 and 30.
	Descend across steep cutbank, slopes W., through medium timber and moderate undergrowth.
170	Abandoned graveled road, 15 ft. wide, bears N. and S. 20° W.; con. along road on W. slope.
385	Leave road, bears N. 25° W. and S.; asc. across W. slope.
705	Spur, slopes N. 85° W.; desc. over NW. slope.
1120	Headwaters of creek, dry, drains N. 25° W.; asc. across W. slope.
1240.27	The S 1/16 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set in solid rock, projecting 8 ins. above surface of rock, bent over to the W., tied in center of drill hole, with brass cap mkd.
	S 1/16 S 30   S 29 1964
	from which a bearing tree mkd. by Brooks and Jelley in 1964
	A fir, 18 ins. diam., bears S. 80 1/4° E., 36.3 ft. dist., with a healed blaze.
	and a new bearing tree
	A fir, 12 ins. diam., bears S. 24° W., 39.4 ft. dist., mkd. S1/16 S30 BT.
	Corner is located on small rock face below roots of fir, 3 ft. diam., bears NE., 10 ft. dist.
	_____
	N. 0° 57' 24" W., beginning new measurement.
	Descend across W. slope through medium timber and light undergrowth.
1165	Descend over NW. slope.
1220	Creek, 1 ft. wide, course S. 70° W.; asc. over S. slope.
1243.87	The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;"> <math>\frac{1}{4}</math>            S 30   S 29            T 21 S R 7 W            1964         </p> <p>from which the bearing trees mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 68 1/4° E., 21.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. 9 1/2° W., 72.6 ft. dist., with a healed blaze.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 87° 46' 24" W., bet. secs. 20 and 29.</p> <p>Ascend over NE. slope through medium timber and moderate undergrowth, along S. edge of fir reproduction.</p> <p>70 Spur, slopes N. 45° E.; asc. across N. slope.</p> <p>610 Spur, slopes N.; desc. over NW. slope.</p> <p>1030 Overgrown graveled road, 10 ft. wide, bears N. 70° E. and S. 45° W.</p> <p>1170 Bottom of descent, slopes N.; asc. over NE. slope.</p> <p>1268.92 The E 1/16 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">           S 20            E 1/16 ———            S 29            1964         </p> <p>from which a bearing tree mkd. by Brooks and Jelley in 1964</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 8° E., 23.8 ft. dist., with a healed blaze. (Record, S. 7 1/4° E.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A pistol butt fir, 18 ins. diam., bears N. 70° W., 18.2 ft. dist., mkd. E1/16 S20 BT.</p> <p>Corner is located on S. edge of fir reproduction, edge bears E. and W.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>N. 87° 49' 10" W., beginning new measurement.</p>
	<p>Ascend over NE. slope through medium timber and moderate undergrowth, along the S. edge of fir reproduction.</p>
430	<p>Top of knob; desc. over steep W. slope.</p>
580	<p>Graveled road, 20 ft. wide, bears N. 15° E. and S. 60° W., at the bottom of rock face, 50 ft. high; desc. over NW. slope.</p>
1260.90	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">           S 20            1/4 ———            S 29            T 21 S R 7 W            1964         </p>
	<p>from which the remains of the original bearing trees</p>
	<p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 30° E., 7.3 ft. dist., no marks visible.</p>
	<p style="padding-left: 40px;">A roothole bears S. 5° E., 21.1 ft. dist., with a down fir, size indeterminate, alongside, no marks visible.</p>
	<p>and the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p>
	<p style="padding-left: 40px;">A fir stump, 18 ins. diam., bears N. 44 1/4° E., 48.7 ft. dist., with a healed blaze. (Record, 49.5 ft. dist.)</p>
	<p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 72 3/4° E., 43.9 ft. dist., with a healed blaze.</p>
	<p>A rebar with International Paper Co. property sign is alongside the cor. A BLM location tag is on a fir, 3 ft. diam., E., 25 ft. dist.</p>
	<p>Corner is located on S. edge of fir reproduction, edge bears E. and W.</p>
	<p style="text-align: center;">—————</p>
	<p>N. 89° 14' 25" W., beginning new measurement.</p>
	<p>Descend over NW. slope through medium timber and moderate undergrowth, along S. edge fir reproduction.</p>
670	<p>Drainage, course N. 10° W.; asc. over NE. slope.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEEET									
1295	Spur, slopes N.; desc. over NW. slope.								
1587.07	<p>The W 1/16 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S 20</td> </tr> <tr> <td style="text-align: center;">W 1/16</td> <td style="text-align: center;">-----</td> </tr> <tr> <td></td> <td style="text-align: center;">S 29</td> </tr> <tr> <td></td> <td style="text-align: center;">1967</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Beck in 1967</p> <p style="padding-left: 40px;">A decayed fir stump, 14 ins. diam., bears N. 31° E., 35.7ft. dist., with a healed blaze. (Record, 36.3 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. 33° W., 37.3 ft. dist., with a healed blaze. (Record, 38.3 ft. dist.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 14 1/2° E., 39.7 ft. dist., mkd. W1/16 S20 BT.</p> <p>A rebar with International Paper Co. property sign is alongside the cor.</p> <p>Corner is located on S. edge fir reproduction, edge bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 13' 56" W., beginning new measurement.</p> <p>Descend over NW. slope through medium timber and moderate undergrowth on S. edge of fir reproduction.</p>		S 20	W 1/16	-----		S 29		1967
	S 20								
W 1/16	-----								
	S 29								
	1967								
100	Drainage, course N. 20° W.; asc. over NE. slope.								
1135	Overgrown dirt road, 8 ft. wide, bears N. 10° E. and S. 5° E. on spur, slopes N. 10° E.; desc. over steep W. slope.								
1578.60	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T 21 S</td> <td style="text-align: center;">R 7 W</td> </tr> <tr> <td style="text-align: center;">S 19</td> <td style="text-align: center;">S 20</td> </tr> <tr> <td style="text-align: center;">S 30</td> <td style="text-align: center;">S 29</td> </tr> <tr> <td></td> <td style="text-align: center;">1964</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p>	T 21 S	R 7 W	S 19	S 20	S 30	S 29		1964
T 21 S	R 7 W								
S 19	S 20								
S 30	S 29								
	1964								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A burned decayed fir snag, 46 ins. diam., bears S. 3° E., 21.4 ft. dist., no marks visible. (Record, 19.8 ft. dist.)</p> <p>A roothole with bark and decayed fir remains bears S. 40° W., 37.0 ft. dist., no marks visible.</p> <p>A roothole with bark and decayed fir remains bears N. 13° W., 85.8 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Brooks and Jelley in 1964</p> <p>A fir stump, 40 ins. diam., bears N. 5° E., 40.6 ft. dist., with a healed blaze.</p> <p>A fir, 44 ins. diam., bears S. 56 1/2° W., 70.6 ft. dist., with a healed blaze. (Record, S. 53° W.)</p> <p>A fir, 10 ins. diam., bears N. 15° W., 71.3 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 83° E., 61.4 ft. dist., mkd. T21S R7W S20 BT.</p> <p>A fir, 24 ins. diam., bears S. 65 3/4° E., 68.1 ft. dist., mkd. T21S R7W S29 BT.</p> <p>A rebar with International Paper Co. property sign is alongside the cor.</p> <p>Corner is located on SW. cor. of fir reproduction, edge bears N. and E., and NE., 25 ft. of drainage, course N. 50° W.</p> <hr/> <p>N. 0° 03' 32" W., bet. secs. 19 and 20.</p> <p>Descend across steep W. slope through medium timber and moderate undergrowth, along the W. edge of fir reproduction.</p>
300	Spur, slopes W.; desc. over NW. slope.
725	Creek, 2 ft. wide, course S. 80° W.; asc. over SW. slope.
1224.72	<p>The S 1/16 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 19   S 20 1967</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>from which the remains of the bearing trees mkd. by Beck in 1967</p> <p style="padding-left: 40px;">A decayed fir stump, 11 ins. diam., bears S. 62 1/2° E., 14.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 30° W., 4.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 78 1/2° E., 20.7 ft. dist., mkd. S1/16 S20 BT.</p> <p>A rebar with International Paper Co. property sign is alongside the cor.</p> <p>Corner is located on W. edge of fir reproduction, edge bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' 04" W., beginning new measurement.</p> <p>Ascend over SW. slope through medium timber and moderate undergrowth, along the W. edge fir reproduction.</p>
575	Spur, slopes S. 60° W.; desc. over NW. slope.
1000	Creek, 1 ft. wide, course S. 45° W.; asc. over S. slope.
1219.19	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4</p> <p>S 19   S 20</p> <p>1967</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears N. 35° E., 37.0 ft. dist.</p> <p style="padding-left: 40px;">A fir snag, 44 ins. diam., bears N. 78° W., 13.2 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Beck in 1967</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 36° E., 2.6 ft. dist., with a healed blaze and snow blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 17° W., 20.8 ft. dist., with a healed blaze. (Record, N. 19 1/2° W.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET

A rebar with International Paper Co. property sign is alongside the cor.

Corner is located on NW. cor. of fir reproduction, edge bears S. and E.

From the cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.

T 21 S	R 7 W
S 18	S 17
S 19	S 20
1967	

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears S. 42° E., 20.5 ft. dist., no marks visible.

A decayed fir stump, burned to ground, size indeterminate, bears S. 31 1/2° W., 31.7 ft. dist., no marks visible. (Record, S. 28° W.)

A burned decayed fir stump, size indeterminate, bears N. 13° W., 42.2 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Beck in 1967

A decayed hemlock stump, size indeterminate, bears N. 32° E., 23.8 ft. dist., no marks visible. (Record, N. 26° E., 25.7 ft. dist.)

A fir stump, 37 ins. diam., bears S. 74 1/2° E., 72.5 ft. dist., with scribe marks and reverse scribe marks 0 BT visible on partially opened blaze. (Record, S. 73° E., 74.6 ft. dist.)

A decayed hemlock stump, size indeterminate, bears S. 35 1/2° W., 13.9 ft. dist., no marks visible, with a down hemlock log, tin-capped, 14 ins. diam., alongside, with illegible scribe marks visible on partially healed blaze. (Record, S. 34° W.)

A hemlock stump, 17 ins. diam., bears N. 27° W., 37.0 ft. dist., no marks visible. (Record, N. 29° W., 38.3 ft. dist.)

and the remains of a bearing tree mkd. by the Douglas County Surveyor in 1977, filed in the Douglas County Surveyors Office under C.S. File No. 59/38

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A roothole bears N. 87° W., 5.4 ft. dist., with a down decayed hemlock log, tin-capped, 8 ins. diam., alongside, with scribe marks T21S R7W S18 CS BT visible on open blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor in 1980, filed in the Douglas County Surveyors Office under C.S. File No. 61/6</p> <p>A cedar stump, 24 ins. diam., bears N. 58 1/4° E., 25.8 ft. dist., no marks visible.</p> <p>A decayed fir stump, 41 ins. diam., bears N. 69° W., 28.4 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 5 ins. diam., bears N. 42° E., 23.8 ft. dist., mkd. X BT.</p> <p>A hemlock, 6 ins. diam., bears S. 78 1/2° E., 17.2 ft. dist., mkd. T21S R7W S20 BT.</p> <p>A fir, 10 ins. diam., bears S. 51° W., 23.1 ft. dist., mkd. T21S R7W S19 BT.</p> <p>A hemlock, 10 ins. diam., bears N. 59 1/2° W., 20.7 ft. dist., mkd. T21S R7W S18 BT.</p> <p>S. 89° 07' 15" W., bet. secs. 18 and 19.</p> <p>Ascend over NE. slope through medium timber and moderate undergrowth.</p>
100	Spur, slopes N.; desc. over steep NW. slope.
335	Creek, 1 ft. wide, course N.; asc. over steep E. slope.
570	Ascend across steep N. slope.
645	Top of ascent, slopes N.; desc. across steep N. slope.
860	Creek, dry, 2 ft. wide, course N. 40° E.; asc. over very steep E. slope.
1220	Abandoned graveled road, 10 ft. wide, bears N. 15° W. and S. 10° W.
1280	Spur, slopes N. 15° E.; desc. across steep N. slope.
1420	Bottom of descent, slopes N.; asc. across steep N. slope.
1555	Spur, slopes N.; desc. over very steep W. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1890	Creek, 2 ft. wide, course N.; asc. over steep NE. slope.
2140	Spur, slopes N. 15° E.; desc. over steep NW. slope.
2325	Bottom of descent, slopes N.; asc. over steep NE. slope.
2416	Spur, slopes N.; desc. over NW. slope.
2521.00	The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	T 21 S R 7 W S 18 1/4 ——— S 19 1967
	from which the remains of the bearing trees mkd. by Beck in 1967
	A cedar, 21 ins. diam., bears S. 27° W., 23.3 ft. dist., with a healed blaze. (Record, 22.4 ft. dist.)
	A decayed cedar stump, 14 ins. diam., bears N. 61 3/4° W., 27.6 ft. dist., with illegible marks visible on partially healed blaze. (Record, N. 60° W., 26.4 ft. dist.)
	and a new bearing tree
	A hemlock, 8 ins. diam., bears N. 4° W., 32.9 ft. dist., mkd. 1/4 S18 BT.
	—————
	S. 88° 41' 59" W., beginning new measurement.
	Descend over NW. slope through medium timber and moderate undergrowth.
65	Creek, dry, 1 ft. wide, course N. 15° E., in small slide; asc. over steep E. slope.
405	Abandoned graveled road, 15 ft. wide, bears N. 20° W. and S. 20° E.
440	Ridge, bears N. 20° W. and S. 20° E.; desc. over steep W. slope.
685	Abandoned graveled road, 15 ft. wide, bears N. and S.
750	Overgrown graveled road, 10 ft. wide, bears N. 15° W. and S. 10° E.; desc. over broken SW. slope.
1305	Creek, 2 ft. wide, course N. 55° W.; asc. across steep N. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET													
1435	Top of ascent, slopes N.; desc. across steep N. slope.												
1540	Descend over steep NW. slope.												
1695	Creek, dry, 1 ft. wide, in center of bottom, 40 ft. wide, course N. 10° E.; asc. over steep E. slope.												
2150	Across steep N. slope.												
2263.12	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 21 S</td></tr> <tr><td>R 8 W</td><td>R 7 W</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2">1954</td></tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Lytle, et al. in 1952-54</p> <p style="padding-left: 40px;">A fir stump, 21 ins. diam., bears N. 47° E., 23.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 34 1/2° E., 13.9 ft. dist., with a healed blaze. Tree has a significant northerly curve.</p> <p style="padding-left: 40px;">A hemlock, 19 ins. diam., bears S. 69 3/4° W., 27.0 ft. dist., with a healed blaze. (Record, S. 71° W., 29.7 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 101/2° W., 28.4 ft. dist., with a healed blaze. (Record, 38 ins. diam.)</p> <p>and a bearing tree mkd. by Graham in 1999-2000</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears N. 87 1/2° E., 15.4 ft. dist., with a healed blaze.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 20, T. 21 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 7° 33' 17" W., on the N. and S. center line of sec. 20.</p>	T 21 S		R 8 W	R 7 W	S 13	S 18	<hr/>		S 24	S 19	1954	
T 21 S													
R 8 W	R 7 W												
S 13	S 18												
<hr/>													
S 24	S 19												
1954													

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
1240.66	<p>The center S 1/16 sec. cor. of sec. 20, established by Les Roberts, Registered Land Surveyor No. 1039, in 1979, filed in the Douglas County Surveyors Office, under Map File No. M77-13, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">PLS 1039 S 1/16 C S 20   C 1979</p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., with a cedar, 2 ft. diam., growing against it to the southwest, bears N. 4° E., 15.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 36 ins. diam., bears S. 9° W., 26.8 ft. dist., no marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 73 3/4° E., 10.5 ft. dist., mkd. CS1/16 S20 BT.</p> <p>A rebar with International Paper Co. property sign is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 7° 32' 10" W., beginning new measurement.</p>
1240.02	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 7 W C 1/4 S 20 2005</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 41 1/2° E., 4.3 ft. dist., mkd. C1/4 S20 BT.</p> <p style="padding-left: 40px;">A chinquapin, 22 ins. diam., bears N. 51 1/2° W., 36.0 ft. dist., mkd. C1/4 S20 BT.</p>

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located in older fir reproduction, W., 25 ft. of top of spur ridge, slopes S. 15° W., and E., 90 ft. of graveled road, 12 ft. wide, bears N. 20° W. and S. 10° E.</p>
2506.50	Point for the center N 1/16 sec. cor. of sec. 20. No permanent monument established.
3772.98	The 1/4 sec. cor. of secs. 17 and 20.
	<hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>N. 89° 26' 45" W., on the E. and W. center line of sec. 20.</p>
1290.34	<p>The center E 1/16 sec. cor. of sec. 20, established by Les Roberts, Registered Land Surveyor No. 1039, in 1979, filed in the Douglas County Surveyors Office, under Map File No. M77-13, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">PLS 1039 E 1/16 C———C S 20 1979</p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir stump, 25 ins. diam., bears S. 82 1/2° E., 15.1 ft. dist., with illegible scribe marks visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 70° W., 6.8 ft. dist., with a healed double blaze. Tree leans southeasterly.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 20° W., 27.8 ft. dist., mkd. CE1/16 S20 BT.</p> <p>A rebar established by person(s) unknown is alongside the cor.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89° 27' 34" W., beginning new measurement.</p>
1291.47	The center 1/4 sec. cor. of sec. 20.
2712.47	The center W 1/16 sec. cor. of sec. 20, established by Les Roberts, Registered Land Surveyor No. 1039, in 1979, filed in the Douglas County Surveyors Office, under Map File

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>No. M77-13, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">PLS 1039 W 1/16 C ——— C S 20 1979</p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A decayed hemlock stump, 11 ins. diam., bears S. 31 1/2° W., 8.1 ft. dist., with scribe marks CW1/16 S20 BT visible on open double blaze.</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 1 1/4° W., 6.7 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 1 1/2° W., 20.5 ft. dist., mkd. CW 1/16 S20 BT.</p> <p>A rebar with International Paper Co. property sign is alongside the cor.</p> <p>Corner is located on N. edge fir reproduction, edge bears E. and W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 27' 18" W., beginning new measurement.</p> <p>Descend over SW. slope through medium timber and moderate undergrowth, along N. edge of fir reproduction.</p>
700	Descend over steep W. slope.
1170	Paradise Creek, 3 ft. wide, course S. 55° W.; asc. over SE. slope.
1421.14	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center E 1/16 sec. cor. of sec. 20.</p> <p>N. 6° 46' 59" W., on the calculated N. and S. center line of the NE 1/4 of sec. 20.</p> <p>Ascend over SE. slope through fir reproduction.</p>
110	SE. cor. timber, edge bears N. and W.; con. along E. edge timber.

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
180	Top of ascent, slopes E.; desc. over NE. slope.
370	Drainage, course S. 80° E.; asc. over steep S. slope.
670	Spur, slopes E.; desc. over NE. slope.
945	Drainage, course E.; asc. over SE. slope.
1235	Spur, slopes E.; desc. over N. slope.
1270.61	<p>Point for the NE 1/16 sec. cor. of sec. 20, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 20 2005</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears N. 61° E., 7.8 ft. dist., mkd. NE1/16 S20 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 19° W., 13.3 ft. dist., mkd. NE1/16 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on NW. cor. of fir reproduction, edge bears S. and E.</p> <p>From this cor., a point established as the NE 1/16 sec. cor. of sec. 20 by Les Roberts, Registered Land Surveyor No. 1039, in 1979, filed in the Douglas County Surveyors Office, under Map File No. M77-13, bears N. 87° 26' 19" E., 9.77 ft. dist.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. LS1039 NE1/16 S20 1979, and was not used for control during this survey due to improper procedures, from which the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 69° E., 5.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 11 1/2° E., 15.7 ft. dist., with a healed double blaze.</p> <p>A rebar with International Paper Co. property sign is alongside the iron post.</p> <hr style="width: 60%; margin-left: 0;"/>

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	S. 89° 44' 22" E., on the calculated E. and W. center line of the NE 1/4 of sec. 20.
	Across N. slope through medium timber and moderate undergrowth, along N. edge fir reproduction.
170	Descend over E. slope along top of spur.
635	Across nearly level land.
850	Halfway Creek, 10 ft. wide, course N. 10° E.; con. across nearly level land.
885	Ascend over SW. slope
940	Across S. slope.
1305.58	The N 1/16 sec. cor. of secs. 20 and 21.
	<hr/>
	From the center E 1/16 sec. cor. of sec. 20.
	S. 6° 42' 34" E., on the calculated N. and S. center line of the SE 1/4 of sec. 20.
	Descend over SE. slope through fir reproduction.
295	Creek, 2 ft. wide, course N. 40° E.; con. across bottom land.
415	Ascend across W. slope.
525	Top of ascent, slopes W.; desc. across W. slope.
610	Creek, 2 ft. wide, course N. 25° W.; con. across E. slope.
865	Ascend over NE. slope.
1254.50	The SE 1/16 sec. cor. of sec. 20, established by Les Roberts, Registered Land Surveyor No. 1039, in 1979, filed in the Douglas County Surveyors Office, under Map File No. M77-13, and is accepted as the corner, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.
	PLS 1039 SE 1/16 S 20 1979
	from which the remains of the bearing trees mkd. by Roberts

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A decayed hemlock snag, 23 ins. diam., bears N. 33° E., 6.8 ft. dist., with scribe marks SE1/16 and other illegible scribe marks visible on partially healed blaze.</p> <p>A decayed hemlock stump, 19 ins. diam., bears S. 74° E., 16.9 ft. dist., with scribe marks SE1/16 S20 BT visible on unhealed blaze.</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears S. 60 1/2° E., 22.5 ft. dist., mkd. SE 1/16 S20 BT.</p> <p>A cedar, 30 ins. diam., bears N. 15 1/2° W., 42.3 ft. dist., mkd. SE 1/16 S20 BT.</p> <p>A rebar with International Paper Co. property sign is lying alongside the cor.</p> <p>Corner is located on the SE. cor. of a small stand of timber, edge bears N. and W., in the middle of fir reproduction.</p> <hr/> <p>N. 88° 42' 26" W., on the calculated E. and W. center line of the SE 1/4 of sec. 20.</p> <p>Ascend over NE. slope through fir reproduction.</p>
50	Ascend over steep E. slope.
315	Top of rock face, 45 ft. high; asc. across N. slope.
655	Graveled spur road, 10 ft. wide, bears N. 35° W. and S. 35° E. 50 ft. to junction with main road, on spur, slopes S. 35° E.; desc. over SW. slope.
715	Graveled road, 10 ft. wide, bears N. 45° W. and S. 55° E.
935	Across nearly level land.
1275.75	The center S 1/16 sec. cor. of sec. 20.
	<hr/> <p>N. 89° 17' 29" W., on the calculated E. and W. center line of the SW 1/4 of sec. 20.</p> <p>Across nearly level land through older fir reproduction.</p>
150	Graveled road, 10 ft. wide, bears N. 25° E. and S. 25° W.
280	Descend over SW. slope.

Subdivision of Section 20,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
405	Abandoned dirt road, 10 ft. wide, bears N. 35° W. and S. 25° E.
1503.64	<p>The SW 1/16 sec. cor. of sec. 20, established by Les Roberts, Registered Land Surveyor No. 1039, in 1981, filed in the Douglas County Surveyors Office, under Map File No. M87-59, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 7 W SW 1/16 - S 20 1981 PLS 1039</p> <p>from which the remains of the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A battered fir stump, 20 ins. diam., bears N. 55° W., 47.4 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 32 ins. diam., bears N. 6° W., 35.4 ft. dist., with scribe marks SW1/16 S20 BT visible on partially healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N 20 1/2° E., 24.7 ft. dist., mkd. SW1/16 S20 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 74° W., 10.0 ft. dist., mkd. SW1/16 S20 BT.</p> <p>A rebar with International Paper Co. property sign is alongside and a BLM location tag on a fir stump, 1 ft. diam., bears N., 15 ft. from the cor.</p> <hr/> <p>N. 3° 44' 41" W., on the calculated N. and S. center line of the SW 1/4 of sec. 20.</p> <p>Ascend over SW. slope through fir reproduction.</p>
190	Top of ascent, slopes S. 60° W.; desc. over NW. slope.
240	Drainage, course S. 60° W.; asc. over SW. slope.
740	Abandoned dirt road, 6 ft. wide, bears E. and W.
1226.73	<p>The center W 1/16 sec. cor. of sec. 20.</p> <hr/>

Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEEET	<p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 1° 07' 15" W., on the N. and S. center line of sec. 30.</p>												
1245.40	<p>The center S 1/16 sec. cor. of sec. 30, established by Les Roberts, Registered Land Surveyor No. 1039, in 1982, filed in the Douglas County Surveyors Office, under Map File No. M90-21, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding: 0 5px;">T21S</td> <td style="padding: 0 5px;">PLS 1039</td> <td style="padding: 0 5px;">R</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">CS 1/16</td> <td style="padding: 0 5px;">7</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">W</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">1982</td> <td style="padding: 0 5px;"></td> </tr> </table> </div> <p>from which the bearing trees mkd. by Roberts</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears S. 33 1/2° E., 18.6 ft. dist., with a healed blaze. Tree is located on top of W. cutbank of overgrown graveled road, 15 ft. wide, bears N. 15° E. and S. 15° W.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears S. 44° W., 11.9 ft. dist., with a healed blaze.</p> <p>A steel fence post with a 1972 BLM location tag is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 08' 14" W., beginning new measurement.</p> <p>Descend across steep E. slope through medium timber and moderate undergrowth.</p>	T21S	PLS 1039	R		CS 1/16	7		S 30	W		1982	
T21S	PLS 1039	R											
	CS 1/16	7											
	S 30	W											
	1982												
25	Spur, slopes N. 10° E.; desc. across steep W. slope.												
100	W. edge of landing at N. end of overgrown graveled road, 15 ft. wide, bears S. 5° E.												
1080	Spur, slopes N. 5° W.; desc. across steep E. slope.												
1245.62	<p>The center 1/4 sec. cor. of sec. 30, established by Les Roberts, Registered Land Surveyor No. 1039, in 1982, filed in the Douglas County Surveyors Office; under Map File No. M90-21, and is accepted as the corner; monumented with a brass tablet, 2 1/2 ins. diam., firmly set in sandstone, in a ledge big enough for the cap, 2 ins. below the surface of the ground, with brass cap mkd.</p>												



Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	N. 1° 08' 35" W., beginning new measurement.
1242.93	The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.
	T 21 S R 7 W S 19 1/4 ——— S 30 1967
	from which the remains of the bearing trees mkd. by Beck in 1967
	A fir stump, 52 ins. diam., bears S. 19° E., 23.1 ft. dist., with scribe marks and reverse scribe mark T visible on partially opened blaze.
	A fir, 50 ins. diam., bears N. 41° W., 29.7 ft. dist., with a healed blaze.
	and a new bearing tree
	A fir, 19 ins. diam., bears S. 48 1/2° E., 25.6 ft. dist., mkd. 1/4 S30 BT.
	A rebar with International Paper Co. property sign is alongside the cor.
	Corner is located on N. edge of older fir reproduction., edge bears E. and W., and W., 40 ft., of graveled road, 10 ft. wide, bears N. and S.
	_____
	From the 1/4 sec. cor. of secs. 29 and 30.
	S. 87° 55' 23" W., on the E. and W. center line of sec. 30.
	Descend across S. slope through medium timber and light undergrowth.
120	Creek, 3 ft. wide, course N. 35° W.; asc. over NE. slope.
460	Spur, slopes N. 20° E.; desc. over NW. slope.
575	Creek, 1 ft. wide, course N. 40° E.; asc. over N. slope.
915	Top of ascent, slopes N. 20° E.; desc. across NE. slope.
1020	Bottom of descent; asc. over NE. slope.

**Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1236.83	<p>The center E 1/16 sec. cor. of sec. 30, established by Les Roberts, Registered Land Surveyor No. 1039, in 1982, filed in the Douglas County Surveyors Office, under Map File No. M90-21, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">PLS 1039 S CE 1/16 R T 21 S S 30 7 1982 W</p> <p>from which the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 87° E., 26.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 9 3/4° E., 14.2 ft. dist., with a healed blaze.</p> <p>A steel fence post with a 1972 BLM location tag is alongside the cor.</p> <p>Corner is located on spur ridge, slopes N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 56' 34" W., beginning new measurement.</p> <p>Descend over steep W. slope through medium timber and light undergrowth.</p>
245	Bottom of rock face, 75 ft. high; con. across nearly level land.
375	W. edge bench; desc. over W. slope.
1000	Creek, 3 ft. wide, course N. 30° W.; asc. over steep E. slope.
1237.16	<p>The center 1/4 sec. cor. of sec. 30.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 54' 37" W., beginning new measurement.</p> <p>Ascend over steep E. slope through medium timber and light undergrowth.</p>
75	Spur, slopes N.; desc. over steep NW. slope.
355	Creek, 2 ft. wide, course N.; asc. over steep NE. slope.
605	Spur, slopes N. 20° E.; desc. over NW. slope.
1215	Creek, dry, 1 ft. wide, course N. 25° W.; con. across N. slope.

Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
1241.06	<p>The center W 1/16 sec. cor. of sec. 30, established by Les Roberts, Registered Land Surveyor No. 1039, in 1982, filed in the Douglas County Surveyors Office, under Map file No. M90-21, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">             PLS 1039              T21S CW 1/16 R              S 30 7              1982 W           </p> <p>from which the bearing trees mkd. by Roberts</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears N. 68° E., 11.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 58 ins. diam., bears S. 28 1/2° W., 10.2 ft. dist., with a healed blaze.</p> <p>A rebar with International Paper Co. property sign is alongside and a steel fence post with a 1972 BLM location tag bears E., 6 ft., of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 55' 05" W., beginning new measurement.</p> <p>Descend across N. slope through medium timber and light undergrowth.</p>
335	Paradise Creek, 10 ft. wide, course S. 75° W.; asc. across S. slope.
665	Across bench on S. slope.
1015	Descend over W. slope.
1062.96	<p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>S. 87° 53' 27" W., on the calculated E. and W. center line of the SE 1/4 of sec. 30.</p> <p>Descend over steep W. slope through medium timber and moderate undergrowth.</p>
80	Drainage, course N. 30° E.; asc. across steep N. slope.
340	Drainage, course N. 55° E.; asc. over steep E. slope.

Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
520	Abandoned graveled road, 15 ft. wide, bears N. 20° E. and S. 15° W.
570	Ridge, bears N. and S.; desc. over steep W. slope through boulders.
670	Bottom of rock face, 15 ft. high.
1232.87	Point for the SE 1/16 sec. cor. of sec. 30, at its calculated position.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in rocky ground, with brass cap mkd.  SE 1/16 S 30 2006  from which  A fir, 14 ins. diam., bears N. 19 3/4° E., 19.9 ft. dist., mkd. X BT.  A fir, 14 ins. diam., bears S. 28° W., 21.3 ft. dist., mkd. SE1/16 S30 BT.  Deposit a magnet in a white plastic case at the base of the stainless steel post.  A steel fence post with a 1972 BLM location tag is alongside the cor.  <hr/> N. 1° 08' 35" W., on the calculated N. and S. center line of the SE 1/4 of sec. 30.  Ascend slightly across steep W. slope through medium timber and moderate undergrowth.
285	Top of ascent, slopes W.; desc. across steep W. slope.
410	Bottom of descent, slopes NW.; asc. gradually across steep W. slope.
580	Top of ascent, slopes W.; desc. across steep W. slope.
685	Bottom of descent, slopes SW.; asc. gradually across steep W. slope.
1220	Spur, slopes N. 35° W.; desc. over N. slope.
1244.50	The center E 1/16 sec. cor. of sec. 30.  <hr/>

Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	From the W 1/16 sec. cor. of secs. 30 and 31.
	N. 1° 05' 54" W., on the calculated N. and S. center line of the SW 1/4 of sec. 30.
	Descend over steep NE. slope through medium timber and light undergrowth.
190	Bottom of descent, slopes NE.; con. desc. across steep E. slope.
485	Descend over steep NE. slope over intermittent rock faces.
860	Creek, 5 ft. wide, course N. 20° W.; asc. across W. slope.
1010	Creek, dry, 1 ft. wide, course S. 75° W.; asc. across steep W. slope.
1246.64	Point for the SW 1/16 sec. cor. of sec. 30, at its calculated position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	SW 1/16 S 30 2006
	from which
	A fir, 13 ins. diam., bears S. 39 1/2° W., 19.4 ft. dist., mkd. SW1/16 S30 BT.
	A cedar, 17 ins. diam., bears N. 73° W., 27.2 ft. dist., mkd. SW1/16 S30 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	A steel fence post with a 1972 BLM location tag bears N., 4 ft. dist. from the cor.
	Corner is located on S. side of fir, 1 1/2 ft. diam.
	<hr/>
	N. 87° 52' 54" E., on the calculated E. and W. center line of the SW 1/4 of sec. 30.
	Ascend over steep SW. slope through medium timber and moderate undergrowth.
500	Ascend over steep W. slope.
680	Spur, slopes N. 40° W.; con. across the top of steep N. slope.

Subdivision of Section 30,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

FEET	
785	Descend over steep NE. slope.
980	Bottom of descent, slopes N.; asc. over steep NW. slope.
1225	Spur, slopes N. 10° E.; desc. over steep E. slope.
1241.99	The center S 1/16 sec. cor. of sec. 30.
	<hr/>