

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,

AND SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 11, 18, AND 19,

TOWNSHIP 32 SOUTH, RANGE 5 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Arthur R. Rambo, Cadastral Surveyor

Francis J. Simon, Cadastral Surveyor

Under Special Instructions dated May 4, 2006, approved May 12, 2006,

which provided for the surveys included under Group No. 2143,

and Assignment Instructions dated May 16, 2006, August 28, 2006,

and December 6, 2006.

Survey commenced May 18, 2006

Survey completed February 5, 2007

T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines, and the subdivision of sections 11, 18, and 19, Township 32 South, Range 5 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1854, Butler Ives and George W. Hyde, U.S. Deputy Surveyors, surveyed the south and east boundaries of the township (Offset Meridian).

In 1855, Wells Lake and George W. Hyde, U.S. Deputy Surveyors, surveyed the north and west boundaries of the township, and a portion of the subdivisional lines, as shown on the plat of survey approved March 31, 1856.

In 1856, James A. Burnett, U.S. Deputy Surveyor, surveyed Donation Land Claim Nos. 37, 38, 39, and 40, as shown on the official plat of survey approved June 1, 1860

In 1871, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved April 26, 1872.

In 1901-1904, Oscar F. Thiel, U.S. Deputy Surveyor, retraced a portion of the north and south boundaries and subdivisional lines, and surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved July 17, 1902, subsequently amended and approved December 16, 1904.

In 1955, Hans W. Thielsen, Cadastral Engineer, resurveyed a portion of the north boundary and subdivisional lines, and subdivided section 2, as shown on the official plat of survey accepted July 9, 1956.

In 1962, Joseph S. Gawron and Norman J. McDonald, Cadastral Surveyors, resurveyed a portion of the north boundary and subdivisional lines, and subdivided sections 5 and 29, as shown on the official plat of survey accepted September 4, 1964.

In 1980, Rollin D. Aanrud, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, in T. 32 S., R. 6 W., as shown on the official plat of survey accepted August 17, 1983.

In 1992, Francis J. Simon, Cadastral Surveyor, resurveyed portions of the east boundary and subdivisional lines, and subdivided section 24, in T. 32 S., R. 6 W., as shown on the official plat of survey accepted February 28, 1996.

In 1994, Francis J. Simon, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey accepted January 31, 1997.

T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 4, 2006, for Group No. 2143, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic positions (NAD 1983 (CORS 96)) as determined by a direct conventional tie to a temporary point, established utilizing NAVSTAR Global Positioning System static data, with NSRS CORS stations, "DODSON BUTTE", "CAPE BLANCO", and "ROSEBURG COOP" are as follows:

The corner of sections 13, 18, 19, and 24, on the west boundary of the township.

Latitude: 42° 47' 51.77" N. Longitude: 123° 20' 52.22" W.

The closing corner of sections 31 and 32, on the south boundary of the township.

Latitude: 42° 44' 22.14" N. Longitude: 123° 19' 39.23" W.

The N 1/16 section corner of sections 10 and 11.

Latitude: 42° 48' 29.30" N. Longitude: 123° 16' 05.67" W.

Only those lines which represent Bureau of Land Management (BLM) property lines were blazed, painted, and tagged with BLM boundary signs.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Dependent Resurvey of a Portion of the West Boundary,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>(Restoring the 1855 survey by Wells Lake and George W. Hyde)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Beginning at the cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 32 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">R</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 10px;">S 13</td> <td style="padding: 0 10px;">S 18</td> <td style="padding: 0 10px;">R</td> </tr> <tr> <td style="padding: 0 10px;">6</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-bottom: 1px solid black; padding: 0 10px;">S 24</td> <td style="border-bottom: 1px solid black; padding: 0 10px;">S 19</td> <td style="padding: 0 10px;">5</td> </tr> <tr> <td style="padding: 0 10px;">W</td> <td style="padding: 0 10px;">1967</td> <td style="padding: 0 10px;">W</td> <td></td> </tr> </table> <p>from which the remains of a bearing tree mkd. by Wenderoth, reported by Simon in 1992</p> <p style="padding-left: 40px;">A stump hole bears S. 8 3/4° W., 44.9 ft. dist. with a sawed cedar stump, 37 ins. diam., alongside, with no visible marks.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office, reported by Simon in 1992</p> <p style="padding-left: 40px;">A fir snag, 11 ins. diam., bears S. 11° E., 24.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 24 1/2° W., 7.5 ft. dist., with a healed blaze. (Record, N. 27° W., 6.6 ft.)</p> <p>and a bearing tree mkd. by Simon in 1992</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 44 1/4° E., 45.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 88 1/2° E., 23.1 ft. dist., mkd. T32S R5W S19 BT.</p> <p style="padding-left: 40px;">A maple, 20 ins. diam., bears S. 40 3/4° W., 50.1 ft. dist., mkd. T32S R6W S24 BT.</p> <p>N. 0° 06' 10" E., bet. secs. 13 and 18, on the W. bdy. of the Tp.</p> <p>2645.02 The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., reestablished by proportionate measurement, by Lloyd D. Smith, Registered Land Surveyor No. 1101, in 1997, filed in Survey No. M124-46, in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron post,</p>	R	S 13	S 18	R	6	S 24	S 19	5	W	1967	W	
R	S 13	S 18	R										
6	S 24	S 19	5										
W	1967	W											

Dependent Resurvey of a Portion of the West Boundary,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>1 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with an aluminum cap, mkd.</p> <p style="text-align: center;">T 32 S R6W R5W S13 1/4 S18 1997 LS1101</p> <p>from which bearing trees mkd. by Smith</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 84 1/4° W., 91.6 ft. dist., with no marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 14 3/4° W., 79.1 ft. dist., with no marks visible on partially healed blaze.</p> <p>Cor. falls in the NW. side of power and gas line right of way, course N. 40° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 44" E., beginning new measurement.</p>
2645.07	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">R S12 S7 R 6 + 5 W S13 S18 W 1959</p> <p>from which remains of original bearing trees</p> <p style="padding-left: 40px;">A madrone, 19 ins. diam., bears N. 34° E., 29.9 ft. dist., with open rotten face. (Record, 31.0 ft.)</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears S. 24° E., 22.4 ft. dist., with a healed blaze.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office, reported by Aanrud</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 32° E., 38.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 59 3/4° E., 51.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir stob 8 ft. tall, 50 ins. diam., bears South, 9.9 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

F E E T

A madrone, 10 ins. diam., main stem sawed off at 4 ft. above the ground, with live limbs still intact, bears N. 52° W., 24.4 ft. dist., with a healed double blaze.

and a new bearing tree

A fir, 12 ins. diam., bears S. 79° W., 20.1 ft. dist., mkd. T32S R6W S13 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Wells Lake and George W. Hyde, the 1871 survey by William H. Byars, the 1901-1904 survey by Oscar F. Thiel, and the 1994 resurvey by Francis J. Simon)

From the cor. of secs. 10, 11, 14, and 15, reestablished by proportionate measurement by Gregory D. Lang, Registered Land Surveyor No. 2295, in 1995, filed in Survey No. M125-7 in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a yellow plastic cap mkd. LANG SURVEYING, from which bearing trees mkd. by Lang:

A fir, 11 ins. diam., bears N. 32° E., 42.5 ft. dist., with a healed double blaze.

A fir, 19 ins. diam., bears S. 56° E., 17.8 ft. dist., with a healed double blaze.

A fir, 12 ins. diam., bears S. 9° W., 35.8 ft. dist., with a healed double blaze.

A madrone, 16 ins. diam., bears N. 72 3/4° W., 31.3 ft. dist., with scribe marks S10 visible on partially healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 32 S	R 5 W
S 10	S 11
S 15	S 14
2007	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>N. 0° 06' 41" W., bet. secs. 10 and 11.</p>
2628.73	<p>The 1/4 sec. cor. of secs. 10 and 11, reestablished by proportionate measurement by Gregory D. Lang, Registered Land Surveyor No. 2295, in 1995, filed in Survey No. M125-7 in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, flush with the ground, with a yellow plastic cap mkd. LANG SURVEYING, from which bearing trees mkd. by Lang:</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 77° E., 29.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 4 1/2° E., 33.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 17 1/2° W., 42.4 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 15 1/2° W., 29.6 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W 1/4 S 10 S 11 2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 0° 05' 51" W., beginning new measurement.</p>
140	<p>Creek, 2 ft. wide, course S. 60° E.; ascend SE. slope along E. edge of recently cut timber and W. edge of medium timber.</p>
1315.07	<p>Point for the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 10 S 11 2007</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>from which</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 32° E., 41.9 ft. dist., mkd. N1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 79° E., 43.5 ft. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
2630.14	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 32 S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 5 W</td> </tr> <tr> <td style="padding: 0 10px;">S 3</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 2</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 10</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 10px;">S 11</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1955</td> </tr> </table> </div> <p>from which bearing trees mkd. by the Douglas County Surveyor's Office, reported by Simon in 1994</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 69 1/4° E., 62.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears S. 86 1/4° E., 33.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 31 1/2° W., 35.6 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Thielsen, reported by Simon in 1994</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 56° E., 79.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 82 3/4° E., 63.4 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Thielsen</p> <p style="padding-left: 40px;">A fir, 56 ins. diam., bears N. 54 1/2° W., 80.2 ft. dist., with a healed blaze. (Record, 87.1 ft.)</p> <p>and a bearing tree mkd. by Simon in 1994</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S. 5° W., 9.2 ft. dist., with a healed blaze.</p>	T 32 S	R 5 W	S 3	S 2	S 10	S 11	1955	
T 32 S	R 5 W								
S 3	S 2								
S 10	S 11								
1955									

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

<p>FEEET</p>	<p>The iron pipe set by the Douglas County Surveyor's Office, 1 in. diam., firmly set, projecting 17 ins. above the ground, is alongside the iron post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21, restored by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey Nos. M7-53 and M8-25, both in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron T post, 5 ft. long, projecting 4 ft. above the ground, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A madrone, 27 ins. diam., bears N. 17 3/4° E., 87.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 17 ins. diam., bears S. 26 3/4° E., 99.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 16 ins. diam., bears S. 77° W., 85.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears N. 51 1/2° W., 21.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T 32 S R 5 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td colspan="2">2006</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post, and set T post alongside.</p> <p>From this cor., the 1/4 sec. cor. of secs. 20 and 21, perpetuated from original evidence no longer in existence by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey Nos. M7-53 and M8-25, both in the Douglas County Surveyor's Office, and utilized by various professional land surveyors, bears S. 0° 00' 34" E., 2666.40 ft. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 5 ins. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>	T 32 S R 5 W		S 17	S 16	S 20	S 21	2006	
T 32 S R 5 W									
S 17	S 16								
S 20	S 21								
2006									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">T 32 S R 5 W 1/4 S 20 S 21 2006</p> <p>from which new reference objects</p> <p style="padding-left: 40px;">A sawed madrone stump, 18 ins. tall, 8 ins. diam., bears N. 35° E., 26.1 ft. dist.</p> <p style="padding-left: 40px;">An oak stump broken flush with the ground, 10 ins. diam., bears S. 16° W., 26.2 ft. dist. (Mag Nail top center of stump.)</p> <p style="padding-left: 40px;">An oak snag, 20 ins. diam., bears N. 48 3/4° W., 53.4 ft. dist.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A search for intervening cors. was not made along this tie line.</p> <p>From this same cor., the 1/4 sec. cor. of secs. 16 and 21, perpetuated by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey Nos. M7-53 and M8-25, both in the Douglas County Surveyor's Office, and utilized by Arthur R. Rambo, Registered Land Surveyor No. 1086, in 1992, recorded in Survey No. M114-78 in the Douglas County Surveyor's Office, bears N. 89° 54' 45" E., 2643.96 ft. dist.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, from which remains of an original bearing tree:</p> <p style="padding-left: 40px;">An oak stump hole, bears S. 65° E., 403.4 ft. dist., with a 24 ins. diam., sawed oak stump lying alongside, no marks visible. (Record, 406.6 ft.)</p> <p>and bearing trees mkd. by Wenderoth</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears N. 45° E., 14.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears S. 10 3/4° E., 26.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>
------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 32 S R 5 W S 16 1/4 ——— S 21 2006</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>A search for intervening cors. was not made along this tie line.</p> <p>N. 0° 02' 56" E., bet. secs. 16 and 17</p>
2631.28	<p>The 1/4 sec. cor. of secs. 16 and 17, reestablished by proportionate measurement by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey No. M7-53 in the Douglas County Surveyor's Office, and utilized by Arthur R. Rambo, Registered Land Surveyor No. 1086, in 1992, recorded in Survey No. M114-78 in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A madrone, 23 ins. diam., bears S. 50 1/4° E., 17.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A madrone, 19 ins. diam., bears N. 40° W., 11.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>
1308.82	<p style="text-align: center;">T 32 S R 5 W 1/4 S 17 S 16 2006</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner falls on W. edge of N. and S. dirt road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' 04" W., beginning new measurement</p> <p>The N 1/16 sec. cor. of secs. 16 and 17, established by Arthur R. Rambo, Registered Land Surveyor No. 1086, in 1992, filed in Survey No. M114-78 in the Douglas County Surveyor's Office, and is accepted as the cor.; monumented with an iron</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEEET	<p>rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">T32S R5W N 1/16 S17 . S16 LS 1086</p> <p>from which bearing trees mkd. by Rambo</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 68 1/2° E., 21.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 38° W., 7.7 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 35" W., beginning new measurement</p>
1245	<p>Creek, 4 ft. wide, course W.</p>
1309.12	<p>The cor. of secs. 8, 9, 16, and 17, restored by person(s) unknown, perpetuated by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey Nos. M7-53 and M8-25, both in the Douglas County Surveyor's Office, and perpetuated by the Douglas County Surveyor's Office, in 1967, filed in C.S. file No. 53/52, and utilized by Arthur R. Rambo, Registered Land Surveyor No. 1086, in 1992, filed in Survey No. M114-78 in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an axle, 1 in. diam., firmly set, projecting 10 ins. above the ground, from which a bearing tree mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 16 1/2° W., 33.7 ft. dist., with a healed blaze.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 7 3/4° E., 36.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A maple, 30 ins. diam., bears S. 1/2° E., 40.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock snag, 25 ins. diam., bears S. 84 1/2° W., 30.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over axle, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

F E E T	<div style="text-align: center; margin-bottom: 10px;"> <p>T 32 S R 5 W S 8 S 9 <hr style="width: 100%; border: 0.5px solid black;"/>S 17 S 16 2006</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 55 1/2° W., 44.0 ft. dist., mkd. T32S R5W S17 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 31 and 32, reestablished by proportionate measurement by Donald A. Bentz, Registered Land Surveyor No. 839, in 1987, filed in Survey No. M101-16, in the Douglas County Surveyor's Office, and utilized by various professional land surveyors. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with plastic cap mkd. BENTZ SUR INC., from which bearing trees mkd. by Bentz:</p> <p style="margin-left: 40px;">A fir, 31 ins. diam., bears N. 51 1/2° E., 24.8 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A madrone, 11 ins. diam., bears N. 55 3/4° W., 10.9 ft. dist., with scribe marks 1/4 S31 BT visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <p>T 32 S R 5 W 1/4 S 31 S 32 2006</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, the closing cor. of secs. 31 and 32, on the S. bdy. of the Tp., bears S. 0° 09' 38" E., 2655.18 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p>
---------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T32S R5W S31 S32 S5 T33S R5W 1958</p> <p>from which the remains of original bearing trees</p> <p>A sawed decayed fir stump, 36 ins. diam., bears N. 43° E., 37.6 ft. dist., no marks visible.</p> <p>A root hole with madrone alongside, 14 ins. diam., bears N. 38° W., 21.1 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by George J. Wenderoth, Registered Land Surveyor No. 5, in 1953, filed in C.S. file 49/112 in the Douglas County Surveyor's Office, reported by Nickerson in 1989-92 as being marked by the Douglas County Surveyor's Office</p> <p>A fir, 17 ins. diam., bears N. 39 1/2° E., 29.7 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by George J. Wenderoth, Registered Land Surveyor No. 5, in 1953, filed in C.S. file 49/112 in the Douglas County Surveyor's Office</p> <p>A fir, 14 ins. diam., bears N. 39 1/2° W., 15.0 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1958, filed in Survey No. M12-51, reported by Nickerson in 1989-92</p> <p>A fir snag, 8 ins. diam., bears S. 65° W., 11.6 ft. dist., with a healed blaze.</p> <p>A quartz stone 6 x 8 ins. projecting 4 ins. above the ground, and an iron pipe, 1 1/2 ins. diam., projecting 11 ins. above the ground, are both found alongside the iron post.</p> <p>N. 0° 06' 39" W., bet. secs. 31 and 32.</p>
115	Top of spur bears E.
2510	Dirt road, bears S. 22° E. and N. 22° W.
2652.88	The cor. of secs. 29, 30, 31, and 32, monumented with an iron post 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET											
	<table style="margin: auto;"> <tr><td>T 32 S</td><td>R 5 W</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2" style="text-align: center;">1962</td></tr> </table>	T 32 S	R 5 W	S 30	S 29			S 31	S 32	1962	
T 32 S	R 5 W										
S 30	S 29										
S 31	S 32										
1962											
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed decayed fir stump, 29 ins. diam., bears N. 46° E., 16.5 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by George C. Baker, Registered Land Surveyor No. 77, in 1947, filed in C.S. file 40/3, in the Douglas County Surveyor's Office, reported by Gawron and McDonald</p> <p style="padding-left: 40px;">A cedar, 26 ins. diam., bears N. 20 1/2° E., 72.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 46 1/4° E., 41.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An ash, 21 ins. diam., bears S. 24° W., 99.7 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. 88° W., 11.9 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Gawron and McDonald</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 29° E., 21.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 15° E., 31.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 12° W., 25.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 33° W., 52.8 ft. dist., with a healed blaze.</p> <p>and a bearing tree not of record</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 89° W., 31.3 ft. dist., with a healed blaze.</p> <hr style="width: 60%; margin-left: 0;"/> <p style="padding-left: 40px;">N. 89° 44' 00" W., bet. secs. 30 and 31.</p>										
1311.64	<p>The E 1/16 sec. cor. of secs. 30 and 31, established by George C. Baker, Registered Land Surveyor No. 77, in 1947, filed in C.S. file 40/3, in the Douglas County Surveyor's</p>										

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>Office, and is accepted as the cor.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 7 ins. above the ground, witnessed by a steel fence post alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T32S R5W S 30 E 1/16 ——— S 31 2006</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 47 3/4° W., 45.8 ft. dist., mkd. E1/16 S31 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 14° W., 32.4 ft. dist., mkd. E1/16 S30 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="text-align: center;">—————</p> <p>N. 89° 43' 42" W., beginning new measurement.</p>
430	Center of graveled road, 14 ft. wide, bears S. 15° E., and N. 10° W.
815	Center of graveled road, 15 ft. wide, bears N. 20° E. and S. 20° W.
1185	Center of graveled, road 12 ft. wide, bears N. 75° E. and S. 75° W.
1309.05	<p>The 1/4 sec. cor. of secs. 30 and 31, perpetuated by George C. Baker, Registered Land Surveyor No. 77, in 1947, filed in C.S. file 40/3, in the Douglas County Surveyor's Office, and further perpetuated by the Douglas County Surveyor's Office, in 1967, filed in C.S. file 53/52; monumented with a steel axle, 1 in. diam., firmly set, projecting 8 ins. above the ground, from which an original bearing tree:</p> <p style="padding-left: 40px;">A cedar, 37 ins. diam., bears S. 62 1/2° W., 82.5 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 24 ins. diam., bears S. 39 1/2° W., 9.2 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over axle, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 5 W</p> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> <p>2006</p> </div> <p>from which a new bearing tree</p> <p>A fir, 12 ins. diam., bears N. 78° W., 22.1 ft. dist., mkd. 1/4 S30 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 10' 55" W., beginning new measurement.</p>																
825	Center of gravel road, 12 ft. wide bears S. 10° E. and N. 10° W.																
2741.01	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., perpetuated from original evidence no longer in existence by the Douglas County Surveyor's Office, in 1958, filed in C.S. file 49/91, in 1967, recorded in C.S. file 53/52, and in 1999, filed in C.S. file 66/12-16, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">R</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="padding: 0 10px;">S 30</td> <td style="padding: 0 10px;">R</td> </tr> <tr> <td style="padding: 0 10px;">6</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 10px;">S 31</td> <td style="padding: 0 10px;">5</td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 0 10px;">T 32 S</td> </tr> <tr> <td style="padding: 0 10px;">W</td> <td colspan="2" style="padding: 0 10px;">1958</td> <td style="padding: 0 10px;">W</td> </tr> </table> </div> <p>from which remains of bearing trees mkd. by the Douglas County Surveyor's Office, in 1958</p> <p>A fir, 28 ins. diam., bears N. 68 1/2° E., 80.3 ft. dist., with a healed blaze.</p> <p>A sawed cedar stump, 23 ins. diam., bears S. 31 1/4° W., 72.0 ft. dist., with a healed blaze.</p>	R	S 25	S 30	R	6	S 36	S 31	5	T 32 S				W	1958		W
R	S 25	S 30	R														
6	S 36	S 31	5														
T 32 S																	
W	1958		W														

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>A root hole, bears N. 14° W., 69.5 ft. dist., alongside of which is an uprooted sawed cedar stump, 32 ins. diam., with a healed blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1967</p> <p>A fir, 29 ins. diam., bears S. 87 3/4° E., 73.0 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyor's Office, in 1999</p> <p>A pine, 13 ins. diam., bears S. 6 3/4° E., 29.9 ft. dist., with a healed double blaze.</p> <p>A pine, 14 ins. diam., bears N. 41° W., 42.5 ft. dist., with a healed double blaze.</p> <p>Corner is located along westerly edge of a natural gas pipeline right of way, bears N. and S.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W 1/4 S 19 S 20 1962</p> <p>from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1904, filed in Volume 2, page 135, reported by Gawron and McDonald as being mkd. by the Douglas County Surveyor's Office in 1900</p> <p>A root hole, bears S. 29° W., 31.7 ft. dist.</p> <p>and bearing trees mkd. by Gawron and McDonald</p> <p>A fir, 23 ins. diam., bears S. 84 1/2° E., 119.5 ft. dist., with a healed blaze.</p> <p>A pine, 23 ins. diam., bears S. 79 1/2° W., 58.7 ft. dist., with a healed blaze.</p> <p>N. 0° 27' 09" W., bet. secs. 19 and 20.</p>
1331.50	<p>The N 1/16 sec. cor. of secs. 19 and 20, established by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey No. M8-25, in the Douglas County Surveyor's Office, and is accepted as the cor.; monumented with an iron</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEEET	<p>pipe, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 55° E., 8.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears S. 9 1/2° E., 30.3 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 19 S 20 2006</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 27° W., 11.9 ft. dist., mkd. N1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 21' 49" W., beginning new measurement.</p>
1304.25	<p>The cor. of secs. 17, 18, 19, and 20, perpetuated by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey No. M8-25, in the Douglas County Surveyor's Office, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A black oak, 22 ins. diam., bears S. 59° W., 37.6 ft. dist., no marks visible on open and rotted face.</p> <p>and a bearing tree mkd. by Wenderoth</p> <p style="padding-left: 40px;">A black oak, 32 ins. diam., bears S. 43° E., 33.8 ft. dist., with illegible scribe marks visible on open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T 32 S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 5 W</td> </tr> <tr> <td style="padding: 0 5px;">S 18</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 17</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 19</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 5px;">S 20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">2006</td> </tr> </table>	T 32 S	R 5 W	S 18	S 17	S 19	S 20	2006	
T 32 S	R 5 W								
S 18	S 17								
S 19	S 20								
2006									
	<p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 25° E., 13.6 ft. dist., mkd. T32S R5W S17 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 64° E., 34.3 ft. dist., mkd. T32S R5W S20 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 22 1/4° W., 9.4 ft. dist., mkd. T32S R5W S19 BT.</p> <p style="padding-left: 40px;">A black oak, 12 ins. diam., bears N. 25° W., 24.5 ft. dist., mkd. T32S R5W S18 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89° 54' 28" W., bet. secs. 17 and 20.</p>								
1125	Center of gravel road 12 ft. wide bears N. and S.								
1325.16	<p>The E 1/16 sec. cor. of secs. 17 and 20, established by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1969, filed in Survey No. M38-61, in the Douglas County Surveyor's Office, and is accepted as the cor., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, from which new accessories:</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 82 1/4° E., 86.2 ft. dist., mkd. E 1/16 S17 BT.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 64° 47' 31" E., 52.5 ft. dist., with brass cap mkd. RM E 1/16 52.5 ft. TO COR. S20 2008 and an arrow pointing to the cor.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner falls on the east bank of Fortune Branch Creek, 8 ft. wide, course S.</p> <hr style="width: 20%; margin-left: 0;"/>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>S. 89° 57' 01" W., beginning new measurement.</p> <p>1323.18 The 1/4 sec. cor. of secs. 17 and 20, reestablished by proportionate measurement by George J. Wenderoth, Registered Land Surveyor No. 5, in 1952, filed in Survey No. M8-25, in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 8 ins. above the ground, from which the remains of bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 66 3/4° E., 36.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A rotted, sawed cedar stump, size indeterminate, bears S. 48 3/4° E., 33.4 ft. dist., with a partially healed blaze, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>T 32 S R 5 W</p> <p style="margin-left: 40px;">S 17</p> <p style="margin-left: 40px;">1/4 ———</p> <p style="margin-left: 40px;">S 20</p> <p style="margin-left: 40px;">2006</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. 11° W., 20.5 ft. dist., mkd. 1/4 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 55' 09" W., beginning new measurement.</p>
2642.91	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr style="width: 60%; margin: 10px auto;"/>
2632.69	<p>N. 89° 41' 54" W., bet. secs. 18 and 19.</p> <p>The 1/4 sec. cor. of secs. 18 and 19, reestablished by proportionate measurement, by H. W. Lawrence, Registered Engineer No. 1543, in 1955, filed in C.S. file 42/78, in the Douglas County Surveyor's Office. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, from which a bearing tree mkd. by Lawrence:</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>A madrone, 23 ins. diam., bears S. 23° E., 5.3 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W S 18 1/4 ——— S 19 2006</p> <p>from which new bearing trees</p> <p>A fir, 12 ins. diam., bears N. 44° E., 24.0 ft. dist., mkd. 1/4 S18 BT.</p> <p>A fir, 11 ins. diam., bears S. 76 1/2° E., 25.2 ft. dist., mkd. 1/4 S19 BT</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="text-align: center;">—————</p> <p>N. 89° 49' 01" W., beginning new measurement.</p>
50	Spring branch 2 ft. wide, course S. 28° E.
1295.37	Point for the W 1/16 sec. cor. of sec. 18 only. No permanent monument set.
1324.59	Point for the W 1/16 sec. cor. of sec. 19 only.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">————— W 1/16 S 19 2006</p> <p>from which</p> <p>A fir, 19 ins. diam., bears S. 37 1/4° E., 39.2 ft. dist., mkd. W1/16 S19 BT.</p> <p>A fir, 9 ins. diam., bears S. 80° W., 55.0 ft. dist., mkd. W1/16 S19 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
2847.87	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of Tp. <hr/>
	From the cor. of secs. 17, 18, 19, and 20. N. 2° 47' 21" E., bet. secs. 17 and 18. Ascend over east slope.
2608.83	The 1/4 sec. cor. of secs. 17 and 18, perpetuated by the Douglas County Surveyor's Office, in 1967, filed in C.S. file 53/52, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. T 32 S R 5 W 1/4 S 18 S 17 1967 from which the remains of the original bearing trees A sawed cedar stump, 74 ins. diam., bears East, 11.2 ft. dist., with scribe marks 1/4 S17 CS BT visible on partially opened blaze (the visible marks were added by the Douglas County Surveyor's Office). A sawed fir stump, 36 ins. diam., bears N. 35° W., 5.9 ft. dist., no marks visible. and a bearing tree mkd. by the Douglas County Surveyor's Office A sawed cedar stump, 18 ins. diam., bears S. 71 1/4° W., 38.2 ft. dist., with a healed blaze. and new bearing trees A fir, 10 ins. diam., bears N. 66 1/4° E., 9.4 ft. dist., mkd. 1/4 S17 BT. A fir, 7 ins. diam., bears S. 22 3/4° W., 28.8 ft. dist., mkd. 1/4 S18 BT. <hr/>
	N. 0° 15' 52" E., beginning new measurement.
2627.42	The cor. of secs. 7, 8, 17, and 18, perpetuated by the Douglas County Surveyor's Office, in 1967, recorded in C.S. file 53/52, and in 1982, filed in C.S. file 62/1, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">COUNTY SURVEYOR'S OFFICE T 32 S R 5 W S 7 S 8 ----- S 18 S 17 RESET 1982 1967</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 37 ins. diam., bears S. 41 1/2° W., 25.7 ft. dist., with a healed blaze. (Record, S. 45° W.)</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyor's Office, in 1967</p> <p style="padding-left: 40px;">A sawed fir stump, 33 ins. diam., bears S. 13° E., 45.2 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office, in 1982</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 11 3/4° W., 83.7 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 13 ins. diam., bears N. 78 3/4° E., 67.9 ft. dist., with scribe marks 32 visible on partially healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A madrone, 5 ins. diam., bears N. 83 3/4° E., 12.5 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 25° E., 15.4 ft. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 79 1/4° W., 11.0 ft. dist., mkd. X at breast height and BT at the base.</p> <hr/> <p>From the sec. cor. of secs. 8, 9, 16, and 17.</p> <p>S. 89° 52' 24" W., bet. secs. 8 and 17.</p> <p>2575.53 Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
-------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	T 32 S R 5 W S 8 1/4 ——— S 17 2006
	from which
	<p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 7° W., 25.3 ft. dist., mkd. 1/4 S17 BT.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 78 1/2° W., 34.6 ft. dist., mkd. 1/4 S8 BT.</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
5151.06	The sec. cor. of secs. 7, 8, 17, and 18.

	N. 89° 11' 02" W., bet. secs. 7 and 18.
1328.52	Point for the E 1/16 sec. cor. of secs. 7 and 18. No permanent monument set.
2657.04	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 32 S R 5 W S 7 1/4 ——— S 18 2006
	from which
	<p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 2 1/2° E., 30.6 ft. dist., mkd. 1/4 S7 BT.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 27 1/4° W., 41.3 ft. dist., mkd. 1/4 S18 BT.</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
5609.70	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of Tp.

Subdivision of Section 11,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>From the 1/4 sec. cor. of secs. 11 and 14, perpetuated from original evidence no longer in existence by the Douglas County Surveyor's Office in 1900, filed in Volume 2, page 99, in 1909, filed in Field Book 10, page 55, in 1946, filed in C.S. No. 43/26, in 1952, filed in C.S. No. 45/98, in 1956 and 1971, both filed in C.S. No. 47/75, and in 1982, filed in C.S. No. 61/36, all on file in the Douglas County Surveyor's Office; monumented with an iron post, 1 1/2 ins. diam., loose and bent to the SW., projecting 8 ins. above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE SEC. 11 1/4 COR. SEC. 14 L.S. 5 and a +, from which the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1956:</p> <p style="padding-left: 40px;">A root hole, bears S. 83° E., 108.7 ft. dist., alongside of which is a on down pine, size indeterminate, no marks visible.</p> <p>and bearing trees mkd., and an object called for, by the Douglas County Surveyor's Office, in 1982</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears S. 78 1/2° E., 48.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A white oak, 21 ins. diam., bears S. 14° W., 163.2 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A wooden power pole, bears N. 45 1/2° W., 41.9 ft. dist., P.P.&L. No. 3859.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, directly over inverted iron post, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 32 S R 5 W</p> <p style="margin-left: 40px;">S 11</p> <p style="margin-left: 40px;">1/4 ———</p> <p style="margin-left: 40px;">S 14</p> <p style="margin-left: 40px;">2006</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, the cor. of secs. 10, 11, 14, and 15, hereinbefore described, bears N. 89° 23' 09" W., 2670.38 ft. dist.</p> <p>N. 0° 13' 28" E., on the N. and S. centerline of sec. 11.</p>
65.59	<p>From this point, a point established by George J. Wenderoth, Registered Land Surveyor No. 5, in 1946, filed in C.S. No. 43/26, in the Douglas County Surveyor's Office, bears East, 1.11 ft. dist., monumented with an iron pipe, 3/4 in. diam.,</p>

Subdivision of Section 11,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	firmly set, projecting 8 ins. above the ground, and is not utilized in this survey.
346.04	From this point, a point recovered by Louis W. Amort, Registered Professional Engineer No. 2311, in 1964, filed in Survey No. M29-7, in the Douglas County Surveyor's Office, bears West, 1.69 ft. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 1 in. above the ground, and is not utilized in this survey.
695.75	From this point, a point established by Louis W. Amort, Registered Professional Engineer No. 2311, in 1964, filed in Survey No. M29-7, in the Douglas County Surveyor's Office, bears West, 1.67 ft. dist., monumented with an iron bolt, 5/8 in. diam., firmly set, flush with the ground, and is not utilized in this survey.
1326.84	From this point, a point established by Donald R. Martin, Registered Professional Engineer No. 3900, in 1971, filed in Survey No. M42-37, in the Douglas County Surveyor's Office, bears West, 5.13 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, and is not utilized in this survey.
2599.35	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. centerline. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 32 S R 5 W C 1/4 S 11 2007</div> from which <div style="margin-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 27 1/2° W., 28.4 ft. dist., mkd. X at breast height and BT at the base.</div> <div style="margin-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 80° W., 24.3 ft. dist., mkd. C1/4 S11 BT.</div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
3111.87	From this point, a point established by F. Neil Hibbs, Registered Land Surveyor No. 52989, in 2006, recorded in Survey No. M146-35, in the Douglas County Surveyor's Office, bears East, 2.21 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a yellow plastic cap mkd. HIBBS LS 52989, and is not utilized in this survey.

Subdivision of Section 11,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
3935.90	Point for the center N 1/16 sec. cor. of sec. 11. No permanent monument set.
4894.49	A point established by F. Neil Hibbs, Registered Land Surveyor No. 52989, in 2006, recorded in Survey No. M146-35, in the Douglas County Surveyor's Office, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a yellow plastic cap mkd. HIBBS LS 52989.
5272.45	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, determined at record bearing and distance from the 1994 witness points. Point falls in the southbound lane of Interstate Highway No. 5. No permanent monument set.</p> <p>From this point, the witness point in the easterly direction, bears S. 89° 34' 00" E., 415.80 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. WP S2 S11 1994 and a horizontal line, from which bearing trees mkd. by Simon in 1994:</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears N. 46 1/2° E., 21.5 ft. dist., with illegible scribe marks visible on a partially healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 16 1/4° E., 8.6 ft. dist., with illegible scribe marks visible on a partially healed double blaze.</p> <p>Also from this same point, the witness point in the westerly direction, bears N. 89° 39' 00" W., 300.30 ft. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. WP S2 S11 1994 and a horizontal line, from which bearing trees mkd. by Simon in 1994:</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 59° E., 33.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 36° W., 25.7 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin-left: 0;"/> <p>From the 1/4 sec. cor. of secs. 11 and 12, perpetuated by the Douglas County Surveyor's Office in 1900, filed in Volume 2, page 99, in 1920, filed in Field Book 107, page 38, and further perpetuated by Douglas County Surveyor's Office in 1952, filed in C.S. No. 45/98, monumented with an axle, 1 in. diam., firmly set, flush with the ground, from which an original bearing tree:</p> <p style="padding-left: 40px;">A hollow white oak, 41 ins. diam., bears S. 85° W., 19.1 ft. dist., with a partially healed blaze.</p>

**Subdivision of Section 11,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1952</p> <p style="padding-left: 40px;">A broken off black oak snag, 18 ins. diam., bears N. 84° E., 68.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 33 1/2° W., 60.8 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, directly over axle, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W 1/4 S 11 S 12 2006</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A white oak, 18 ins. diam., bears N. 75 1/2° E., 60.0 ft. dist., mkd. 1/4 S12 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>S. 89° 42' 48" W., on the E. and W. centerline of section 11.</p>
1409.50	<p>From this point, a point recovered and reported by Donald R. Martin, Registered Professional Engineer No. 3900, in 1956, filed in C.S. No 42/267, in the Douglas County Surveyor's Office, bears North, 3.14 ft. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 12 ins. above the ground, and is not utilized in this survey.</p>
2680.86	<p>The center 1/4 sec. cor. of section 11.</p>
3949.32	<p>The center W 1/16 sec. cor., established by the Douglas County Surveyor's Office in 1900, filed in Volume 2, page 99, and perpetuated by the Douglas County Surveyor's Office in 1909 and 1952, both filed in 1952 in C.S. No 45/98, utilized by F. Neil Hibbs, Registered Land Surveyor No. 52989, in 2006, filed in Survey No. M146-35, and is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, from which the remains of bearing trees reported by the Douglas County Surveyor's Office in 1952:</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 9 3/4° E., 10.4 ft. dist., with a healed blaze.</p>

Subdivision of Section 11,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>A root hole, bears N. 54 1/2° W., 14.8 ft. dist., with down decayed fir alongside, size indeterminate, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C————C S 11 2007</p> <p>from which a new bearing tree</p> <p style="text-align: center;">A madrone, 10 ins. diam., bears N. 88 1/2° W., 28.2 ft. dist., mkd. CW1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87° 23' 55" W., beginning new measurement.</p>
1418.23	<p>The 1/4 sec. cor. of secs. 10 and 11.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>S. 89° 13' 20" E., on the calculated E. and W. centerline of the NW¼ of sec. 11.</p>
1382.88	<p>Point for the NW 1/16 sec. cor. of sec. 11, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 11 2007</p> <p>from which</p> <p style="text-align: center;">A fir, 10 ins. diam., bears N. 88° W., 50.2 ft. dist., mkd. NW1/16 S11 BT.</p> <p style="text-align: center;">A cedar, 19 ins. diam., bears N. 31 1/4° W., 31.5 ft. dist., mkd. NW1/16 S11 BT. (Mag Nail left side center.)</p>

**Subdivision of Section 11,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
1327.09	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 1° 31' 22" W., on the calculated N. and S. centerline of the NW¼ of sec. 11.</p> <p>The W 1/16 sec. cor. of secs. 2 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 W 1/16 ——— S 11 1994</p> <p>from which bearing trees mkd. by Simon in 1994</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 72 1/4° W., 28.4 ft. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 33 1/4° W., 24.1 ft. dist., with a healed blaze.</p> <hr/> <p style="text-align: center;">Subdivision of Section 18, T. 32 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 1° 14' 45" E., on the N. and S. centerline of sec. 18.</p> <p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W C 1/4 S 18 2006</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 58 1/2° E., 34.6 ft. dist., mkd. C1/4 S18 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 21 1/4° W., 6.1 ft. dist., mkd. C1/4 S18 BT.</p>
2622.51	

**Subdivision of Section 18,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
3940.43	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the center N 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \quad \quad S\ 18 \\ C \\ 2006 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 58 1/2° E., 12.9 ft. dist., mkd. CN1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 31° W., 14.4 ft. dist., mkd. CN1/16 S18 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
5258.35	<p>The 1/4 sec. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N. 89° 21' 49" W., on the E. and W. centerline of sec. 18.</p>
2702.44	<p>The center 1/4 sec. cor. of sec. 18.</p>
5602.42	<p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 19, T. 32 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30, perpetuated by the Douglas County Surveyors Office, in 2002, filed in C.S. No. 57/41, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>DOUGLAS CO. S 19 1/4 ——— S 30 2002 SURVEYOR</p> </div> <p>from which the remains of a bearing tree mkd. by Gawron</p>

**Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon**

FEET

A decayed fir stump, size indeterminate, bears N. 27 1/2° E., 75.2 ft. dist., with scribe marks 1/4 S19 BT visible on partially opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
S 19
1/4 ———
S 30
2006

from which new bearing trees

An oak, 31 ins. diam., bears S. 80° W., 156.0 ft. dist., mkd. 1/4 S30 BT.

A maple, 10 ins. diam., bears N. 16° W., 21.7 ft. dist., mkd. 1/4 S19 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron rod alongside.

Corner is located E., 1.3 ft. dist., from a fence line, bears N. and S.

From this cor., the witness point bet. secs. 19 and 30, perpetuated by the Douglas County Surveyor's Office, in 2002, recorded in C.S. file 57/41, bears N. 89° 46' 59" E., 49.50 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS
T32S
WP R
S 19 5
1/4 ——— W
S 30
COR WEST
49.5 FT.
2002
OFFICE

from which an original bearing tree

An ash, 29 ins. diam., bears N. 27° E., 21.8 ft. dist., with a healed blaze. (Record, N. 25° E.)

and bearing trees mkd. by Gawron and McDonald

Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>An oak, 35 ins. diam., bears S. 69° E., 79.9 ft. dist., with a healed blaze.</p> <p>A pine, 29 ins. diam., bears N. 33° W., 61.4 ft. dist., with a healed blaze.</p> <p>From this same cor., the monument set for the 1/4 sec. cor. of secs. 19 and 30, by Gawron and McDonald, in 1962, found to be disturbed and out of position and rotated 90° to the right, bears N. 1° 28' 37" W., 16.05 ft., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground. Removed the marks S30 1962 and added the marks R.M., 16.05 FT., TO COR., 2006, with an arrow pointing to the cor. This point now functions as a reference monument.</p> <p>N. 0° 21' 51" E., on the N. and S. centerline of sec. 19</p>
2668.13	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W C 1/4 S 19 2006</p> <p>from which</p> <p>A fir, 13 ins. diam., bears S. 77° E., 22.1 ft. dist., mkd. C1/4 S19 BT.</p> <p>A fir, 11 ins. diam., bears N. 15 1/2° W., 20.2 ft. dist., mkd. C1/4 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
3989.10	<p>Point for the center N 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32S R5W C N 1/16 S 19 C 2006</p> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 31 3/4° E., 25.7 ft. dist., mkd. CN1/16 S19 BT.</p>

Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">A fir, 7 ins. diam., bears S. 88° E., 28.6 ft. dist., mkd. CN1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
5310.07	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>N. 89° 50' 09" W., on the E. and W. centerline of sec. 19.</p>
251.37	<p>From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 6.04 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, flush with the ground, with no cap or marks, and is not utilized in this survey.</p>
420.88	<p>From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 8.41 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with no cap or marks, and is not utilized in this survey.</p>
607.40	<p>From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 10.66 ft. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with no cap or marks, and is not utilized in this survey.</p> <p>From this same point, an iron rod, 5/8 in. diam., of unknown origin, bears North, 11.16 ft. dist., with no cap or marks.</p>
754.24	<p>From this point, a point established as being on the E. and W. centerline by William J. Ruppert, Registered Land Surveyor No. 866, in 1979, filed in Survey No. M77-72, in the Douglas County Surveyor's Office, bears North, 13.49 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, buried 2 ins. below the surface of the ground, with no cap or marks, and is not utilized in this survey.</p>
780.71	<p>From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 13.64 ft. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 10 ins. above the ground, with no cap or marks, and is not utilized in this survey.</p>

Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
949.08	From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 16.42 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with no cap or marks, and is not utilized in this survey.
1170.92	From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 19.55 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with no cap or marks, and is not utilized in this survey.
1638.67	From this point, a point established as being on the E. and W. centerline by George J. Wenderoth, Registered Land Surveyor No. 5, in 1955, filed in Survey No. M7-15, in the Douglas County Surveyor's Office, bears North, 26.31 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, flush with the ground, with no cap or marks, and is not utilized in this survey.
1828.70	From this point, the NE cor. of Donation Land Claim No. 39, perpetuated from original evidence no longer in existence, by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950, filed in Survey No. M27-12, in the Douglas County Surveyor's Office, bears North, 28.77 ft. dist., monumented with an iron pipe, 1 in. diam., bent SW., firmly set, projecting 7 ins. above the ground, with no cap or marks, from which the remains of bearing trees mkd. by Wenderoth: <p style="margin-left: 40px;">A decayed oak stump, size indeterminate, bears S. 79 1/4° E., 14.6 ft. dist., with axe marks visible.</p> <p style="margin-left: 40px;">A decayed fir stump, 28 ins. diam., bears N. 41 1/2° W., 9.5 ft. dist., with axe marks visible.</p>
2461.52	From this point, a point established as being on the N. bdy. of Donation Land Claim No. 39 by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950, filed in Survey No. M27-12, in the Douglas County Surveyor's Office, bears North, 23.52 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, flush with the ground, with no cap or marks.
2668.55	The center 1/4 sec. cor. of sec. 19.
2862.18	From this point, a point established as being on the N. bdy. of Donation Land Claim No. 39 by William J. Ruppert, Registered Land Surveyor No. 866, in 1986, filed in C.S. file 63/13-6, in the Douglas County Surveyor's Office, bears North, 19.32 ft. dist., monumented with an iron rod, 5/8 in. diam.,

Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET							
	firmly set, projecting 1 in. above the ground, with a plastic cap mkd. LS 866.						
3271.78	From this point, a point established as being on the N. bdy. of Donation Land Claim No. 39 by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950, filed in Survey No. M27-12, in the Douglas County Surveyor's Office, bears North, 14.86 ft. dist., monumented with an iron pipe, 1 1/4 ins. diam., firmly set, buried 2 ins. below the ground, with no cap or marks.						
3712.05	From this point, a point established as being on the N. bdy. of Donation Land Claim No. 39 by William J. Ruppert, Registered Land Surveyor No. 866, in 1986, filed in C.S. file 63/13-6, in the Douglas County Surveyor's Office, bears North, 11.56 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with a plastic cap mkd. LS 866.						
3993.03	Point for the center W 1/16 sec. cor. of sec. 19. No permanent monument set.						
4464.60	<p>From this point, a point reestablished as the NW. cor. of Donation Land Claim No. 39, by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950, filed in Survey No. M27-12, in the Douglas County Surveyor's Office, bears North, 6.04 ft. dist., monumented with an iron pipe, 1 1/4 ins. diam., firmly set, flush with the ground, with no cap or marks, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A black oak, 16 ins. diam., bears N. 68 1/2° E., 51.0 ft. dist., with decayed blaze.</p> <p style="padding-left: 40px;">A white oak, 33 ins. diam., bears S. 63 1/2° E., 80.2 ft. dist., with healed blaze.</p>						
4777.47	From this point, a point established by Romanso E. Ware, Registered Land Surveyor No. 1005, in 1979, filed in Survey No. M79-3, in the Douglas County Surveyor's Office, bears North, 3.26 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with no cap or marks, and is not utilized in this survey.						
5496.31	<p>The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 20px 0;"> <p>T 32 S</p> <p>1/4</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">R 6 W</td> <td style="border-left: 1px solid black; padding: 0 10px;"> </td> <td style="padding: 0 10px;">R 5 W</td> </tr> <tr> <td style="padding: 0 10px;">S 24</td> <td style="border-left: 1px solid black; padding: 0 10px;"> </td> <td style="padding: 0 10px;">S 19</td> </tr> </table> <p>1992</p> </div>	R 6 W		R 5 W	S 24		S 19
R 6 W		R 5 W					
S 24		S 19					

Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>from which bearing trees mkd. by Wenderoth in 1950, reported by Simon in 1992</p> <p style="padding-left: 40px;">An oak, 24 ins. diam., bears N. 12 1/2° E., 193.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 78 1/4° W., 59.4 ft. dist., with a healed blaze.</p> <p>The corner is located 2 ft. N. of the corner of a barbed wire fence, 4 strands, extends E. and S.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>S. 89° 56' 17" W., on the E. and W. centerline of the NE 1/4 of sec. 19.</p>
2649.48	<p>The center N 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S 24 S 19 1992</p> </div> <p>from which bearing trees mkd. by Simon in 1992</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 9 3/4° E., 46.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 84 3/4° W., 4.3 ft. dist., with a healed blaze.</p> <p>S. 89° 49' 33" E., on the calculated E. and W. centerline of the NW 1/4 of Sec. 19.</p>
1513.63	<p>Point for the NW 1/16 sec. cor. of sec. 19, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>NW 1/16 S 19 2006</p> </div> <p>from which</p>

Subdivision of Section 19,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 15 ins. diam., bears S. $43\ 1/4^\circ$ E., 38.9 ft. dist., mkd. NW1/16 S19 BT. (Mag Nail left side center.)</p> <p>A fir, 19 ins. diam., bears N. $88\ 1/4^\circ$ W., 45.9 ft. dist., mkd. NW1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. $0^\circ\ 21'\ 30''$ E., on the calculated N. and S. centerline of the NW 1/4 of sec. 19.</p>
1321.17	<p>The W 1/16 sec. cor. of sec. 19 only.</p> <hr/>