

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF SECTION 7
TOWNSHIP 22 SOUTH, RANGE 5 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 10, 2006,
approved February 13, 2006, which provided for the surveys included
under Group No. 2133, and Assignment Instructions dated April 19, 2006.

Survey commenced April 24, 2006

Survey completed May 15, 2006

T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of section 7, Township 22 South, Range 5 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the township exteriors and a portion of the subdivisional lines.</p> <p>In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and Special Instructions dated February 10, 2006, for Group No. 2133, Oregon.</p> <p>The directions of lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements carried forward by sustained angulation using conventional survey techniques. Distances along lines were derived through the use of electronic measuring equipment.</p> <p>The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. GPS measurements were made using dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.</p> <p>GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. Based on local accuracy standards, the GPS error ellipses do not exceed 0.30 feet at the 95% confidence level. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The unadjusted data assured a closure not exceeding 1:4000 in error. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the corner of sections 5, 6, 7 and 8, as determined by direct occupation with dual frequency carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP", is as follows:</p> <p>Latitude: 43° 40' 42.779" N. Longitude: 123° 19' 39.442" W.</p>
------	--

T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEEET

New bearing trees have a 2 1/2 x 1/4 inch magnetic nail (MagNail) driven at the base on the right side center.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon**

(Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner, and the 1884 survey by William P. Wright)

Beginning at the 1/4 sec. cor. of secs. 7 and 18, perpetuated by the Douglas County Surveyor's Office, in 1995, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 5 W., Point Identifier No. 140500, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

	COUNTY		
	T22S		
	S 7	R	
DOUGLAS	1/4	—	5
	S18	W	SURVEYORS
	1995		
	OFFICE		

from which the remains of an original bearing tree

A sawed fir stump, 32 ins. diam., bears S. 7 1/2° E., 66.7 ft. dist., with fragmentary scribe marks visible on an open blaze.

and bearing trees mkd. by the County Surveyor's Office in 1995

A maple, 9 ins. diam., bears N. 73 1/4° E., 10.7 ft. dist., with a healed blaze.

A fir, 18 ins. diam., bears S. 53 3/4° E., 71.0 ft. dist., with a healed blaze.

A fir, 10 ins. diam., bears S. 13 1/2° W., 59.5 ft. dist., with a healed blaze.

A fir, 20 ins. diam., bears N. 6 3/4° W., 56.0 ft. dist., with a healed double blaze.

N. 89° 52' 55" W., bet. secs. 7 and 18.

185

Dirt road, 10 ft. wide, bears N. 30° E. and S. 30° W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEEET 1326.70	<p>Point for the W 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">W 1/16</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S 7</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S18</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">2006</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears N. 5 1/4° E., 25.9 ft. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A maple, 9 ins. diam., bears S. 73°W., 39.2 ft. dist., mkd. W 1/16 S18 BT.</p> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Begin posting and blazing the true line.</p>	W 1/16	S 7		S18		2006						
W 1/16	S 7												
	S18												
	2006												
1500	Spur, slopes S.												
1860	Spur, slopes S. 22° W.												
2830.51	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., perpetuated by James W. Byron, Douglas County Surveyor's Office, in 1959, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 5 W., Point Identifier No. 100500, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">COUNTY</td> <td style="padding: 0 5px;">R S12</td> <td style="border-right: 1px solid black; padding: 0 5px;">S7 R</td> <td style="padding: 0 5px;">OFFICE</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">6</td> <td style="padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px;">5</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">W S13</td> <td style="padding: 0 5px;">S18</td> <td style="border-right: 1px solid black; padding: 0 5px;">W</td> <td style="padding: 0 5px;"></td> </tr> </table> <p style="margin: 10px 0 0 0;">T22S 1959</p> </div> <p>from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A decayed fir stump, 33 ins. diam., bears N. 69 1/2° E., 72.6 ft. dist., with scribe marks T22S visible on an opened blaze.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 34 1/2 E., 15.8 ft. dist., with a healed double blaze.</p>	COUNTY	R S12	S7 R	OFFICE	6		5		W S13	S18	W	
COUNTY	R S12	S7 R	OFFICE										
6		5											
W S13	S18	W											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 25 ins. diam., bears S. 18° E., 21.8 ft. dist., with a healed double blaze.</p> <p>A sawed fir stump, 16 ins. diam., bears S. 78 1/2° W., 15.9 ft. dist., with a healed double blaze.</p> <p>A sawed fir stump, 23 ins. diam., bears N. 41 3/4° W., 20.4 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears S. 57 1/4° W., 5.6 ft. dist., mkd. T22S R6W S13 BT.</p> <p>A fir, 13 ins. diam., bears N. 19° W., 14.0 ft. dist., mkd. T22S R6W S12 BT.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8, perpetuated by Oscar F. Thiel, Douglas County Surveyor, in 1899; subsequently perpetuated by William C. Thomson, Professional Land Surveyor No. 174, in 1955; and further perpetuated by Vernon "Ray" Tracy, et al, Douglas County Surveyor's Office, in 1965; filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 5 W., Point Identifier No. 200540, monumented with a reinforcing bar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of an original bearing tree</p> <p>A sawed, decayed fir stump, 77 ins. diam., bears S. 85° E., 17.1 ft. dist., no marks visible. (Record, 13.9 ft.)</p> <p>and a bearing tree mkd. by Thomson</p> <p>A fir, 35 ins. diam., bears N. 30 1/2° W., 27.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Tracy</p> <p>A fir, 19 ins. diam., bears N. 24 1/2° E., 31.8 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over the existing reinforcing bar, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T22S R5W 1/4 S 7 S 8 2006</p> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>N. 0° 06' 02" W., bet. secs. 7 and 8, posting and blazing.</p>
395	<p>Spur, slopes S. 80° E.</p>
1326.60	<p>The N 1/16 sec cor. of secs. 7 and 8, established by Harvey M. Christensen, Oregon Professional Land Surveyor No. 2603, in 1995, filed in the Douglas County Surveyor's Office, Map File No. M123-34, and is accepted as the corner, monumented with a reinforcing bar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with yellow plastic cap mkd. LS 2603, from which bearing trees mkd. by Christensen</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 26 1/4° E., 59.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 35° W., 26.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over the existing reinforcing bar, with brass cap mkd.</p>
	<p style="text-align: center;">N 1/16 S 7 S 8 2006</p> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 06' 48" W., beginning new measurement.</p>
20	<p>Gravel road, 10 ft. wide, bears S. 50° E. and N. 60° W.</p>
1327.41	<p>The cor. of secs. 5, 6, 7, and 8, perpetuated by James W. Byron, Douglas County Deputy Surveyor, in 1958, from original evidence no longer in existence, filed in the Douglas County Surveyor's Office, C.S. File 49/158, and M15-18, and is accepted as the</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon**

FEET	
	<p>corner, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS</p> <p style="text-align: center;"> T22S</p> <p style="text-align: center;"> S 6 S 5</p> <p style="text-align: center;"> S 7 S 8</p> <p style="text-align: center;"> R5W</p> <p style="text-align: center;">OFFICE 1958</p> <p>from which the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A sawed fir stump, 18 ins. diam., bears N. 2 1/4° E., 139.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 27 ins. diam., bears S. 76 1/2° W., 133.7 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 19 ins. diam., bears N. 59 1/2° W., 119.5 ft. dist., with a healed blaze.</p> <p>and new accessories</p> <p style="padding-left: 40px;">A reinforcing bar, 30 ins. long, 5/8 in. diam., driven 29 ins. in the ground for a reference monument, bears S. 65°24' E., 7.9 ft. dist., with aluminum cap mkd. RM T22S R5W S8 7.9 FT TO COR 2006 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A reinforcing bar, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears S. 9°28' W., 8.0 ft. dist., with aluminum cap mkd. RM T22S R5W S7 8.0 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>From the corner, a point erroneously positioned as the original cor. of secs. 5, 6, 7, and 8, by Oscar F. Thiel, County Surveyor, in 1899, filed in the Douglas County Surveyor's Office, Volume 2, page 81, and Field Book 113, pages 36 and 37 (and Field Book 116, page 51) perpetuated by person(s) unknown with a reinforcing bar, 3/4 in. diam., firmly set, projecting 2 ins. above ground, bears S. 20° 14' 15" E., 17.62 ft. dist. This point is not properly positioned and is not utilized in this survey.</p> <hr/> <p>S. 89° 29' 17" W., bet. secs. 6 and 7.</p>
1312.54	<p>The E 1/16 sec. cor. of secs. 6 and 7, established by Harvey M. Christensen, Oregon Professional Land Surveyor No. 2603, in 1995, filed in the Douglas County Surveyor's Office, Map File No. M123-34, and is accepted as the corner, monumented with a reinforcing bar, 5/8 in. diam., firmly set,</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>projecting 3 ins. above ground, with yellow plastic cap mkd. LS 2603, from which the remains of bearing trees mkd. by Christensen</p> <p>A sawed fir stump, 21 ins. diam., bears S. 54° E., 10.4 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears N. 54 1/4° W., 13.0 ft. dist., with scribe marks 1/16 S6 BT visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over the existing reinforcing bar, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>S 6</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 7</p> <p>2006</p> </div> <p>from which a new bearing tree</p> <p>A cedar, 25 ins. diam., bears S. 66 1/4° W., 33.4 ft. dist., mkd. E 1/16 S7 BT.</p> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From the corner, a point established by person(s) unknown, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 2 ins. above ground, bears N. 87° 32' 25" W., 5.78 ft. dist. This point is not properly positioned and is not utilized in this survey.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89° 29' 10" W., beginning new measurement, posting and blazing.</p>
795	Ravine, drains S. 35° W.
1100	Spur, slopes N.
1312.43	<p>The 1/4 sec. cor. of secs. 6 and 7, reestablished by person(s) unknown, there is no remaining evidence of the original corner, therefore this position is accepted as the corner, perpetuated by Harvey M. Christensen, Oregon Professional Land Surveyor No. 2603, in 1995, filed in the Douglas County Surveyor's Office, Map File No. M123-34, and the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 5 W., Point Identifier No. 140600, monumented with an iron pipe, 1 in.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>diam., firmly set, projecting 1 in. above ground, from which a reference by person(s) unknown</p> <p>A fir, 37 ins. diam., bears S. 49° E., 34.4 ft. dist., no scribe marks visible, with two Bureau of Land Management metal bearing tree signs attached, mkd. KC JB 1979.</p> <p>and bearing trees mkd. by Christensen</p> <p>A fir, 36 ins. diam., bears N. 82 3/4° E., 44.1 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 67° E., 20.5 ft. dist., with a healed blaze.</p> <p>A fir, 33 ins. diam., bears S. 40 1/2° W., 18.9 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears N. 79 3/4° W., 33.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over the existing iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S R5W</p> <p> S 6</p> <p>1/4 ———</p> <p> S 7</p> <p> 2006</p> </div> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>S. 89° 28' 24" W., beginning new measurement, posting and blazing.</p>
385	Spur, slopes S. 68° W.
900	Spur, slopes N. 70° W.
2430	Spur, slopes N. 45° W.
2750.98	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., perpetuated by Oscar F. Thiel, Douglas County Surveyor, in 1906 and 1931, from original evidence no longer in existence, remonumented by Milo E. Godfrey, Douglas County Surveyor's Office, in 1961, filed in the Douglas County Record of Government Corners Renewed, T. 22 S., R. 5 W., Point Identifier No. 100600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

F E E T	<p style="text-align: center;">SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td rowspan="3" style="text-align: center; vertical-align: middle;">C O U N T Y</td> <td colspan="2" style="text-align: center;">T22S</td> <td rowspan="3" style="text-align: center; vertical-align: middle;">O F F I C E</td> </tr> <tr> <td style="text-align: center;">R6W</td> <td style="text-align: center;">R5W</td> </tr> <tr> <td style="text-align: center;">S 1</td> <td style="text-align: center;">S 6</td> </tr> <tr> <td></td> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> <td></td> </tr> </table> <p style="text-align: center;">1961</p> <p>from which the remains of bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 37° E., 20.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 71 1/4° E., 16.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 63° W., 8.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 26 ins. diam., bears N. 16° W., 46.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 29 1/4° W., 12.0 ft. dist., mkd. T22S R6W S1 BT.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 22 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18, hereinbefore described.</p> <p>N. 0° 55' 05" W., on the N. and S. centerline of sec. 7.</p> <p>2653.41 Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W centerline.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center;">T22S</td> <td style="text-align: center;">R5W</td> </tr> <tr> <td colspan="2" style="text-align: center;">C 1/4</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">2006</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 76 1/2° W., 42.8 ft. dist., mkd. C 1/4 S7 BT.</p>	C O U N T Y	T22S		O F F I C E	R6W	R5W	S 1	S 6		S12	S 7		T22S	R5W	C 1/4		S 7		2006	
C O U N T Y	T22S		O F F I C E																		
	R6W			R5W																	
	S 1	S 6																			
	S12	S 7																			
T22S	R5W																				
C 1/4																					
S 7																					
2006																					

Subdivision of Section 7,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 36 ins. diam., bears N. 17° W., 45.5 ft. dist., mkd. C 1/4 S7 BT.</p> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p>
3979.03	Point for the center N 1/16 sec. cor. of sec. 7, no permanent monument set.
5304.65	The 1/4 sec. cor. of secs. 6 and 7, hereinbefore described.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8, hereinbefore described.</p> <p>S. 89° 32' 54" W., on the E. and W. centerline of sec. 7, posting and blazing.</p>
240	Spur, slopes S. 15° E.
990	Ravine, drains S. 10° W.
1293.88	Point for the center E 1/16 sec. cor. of sec. 7, no permanent monument set.
1435	Spur, slopes S. 15° W.
2265	Post Creek, 2 ft. wide, course S. 60° W.
2587.76	The center 1/4 sec. cor. of sec. 7.
3535	Spur, slopes S. 10° W.; also dirt road, 10 ft. wide, bears N. 10° E. and S. 10° W.
3880	Ravine, drains S. 5° W.
3907.91	<p>Point for the center W 1/16 sec. cor. of sec. 7</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 C ——— C S 7 2006</p> </div> <p>from which</p> <p>A fir, 7 ins. diam., bears N. 10 3/4° E., 3.6 ft. dist., mkd. X BT.</p> <p>A fir, 8 ins. diam., bears S. 74 1/2° W., 11.2 ft. dist., mkd. CW 1/16 S7 BT.</p>

Subdivision of Section 7,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEEET	<p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p>						
4245	<p>Spur, slopes S. 60° W.</p>						
5378.89	<p>The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., perpetuated by James W. Byron, Douglas County Surveyor's Office, in 1959; subsequently perpetuated by Milo E. Godfrey, Douglas County Surveyor's Office, in 1961, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22. S., R. 5 W., Point Identifier No. 100540, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears S. 83° W., 14.5 ft. dist., with corresponding fallen fir trunk, 31 ins. diam., lying 50 ft. downhill, no marks visible.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A maple, 14 ins. diam., bears S. 84 1/2° E., 45.2 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Godfrey</p> <p style="padding-left: 40px;">A shattered fir snag, 38 ins. diam., bears North, 53.1 ft. dist., with fragmentary scribe marks visible on an open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over the existing iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">R6W</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">R5W</td> </tr> <tr> <td style="padding: 0 10px;">S12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S 7</td> </tr> </table> <p style="margin: 5px 0 0 0;">1/4</p> <p style="margin: 0 0 0 0;">2006</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 12 1/2° W., 7.2 ft. dist., mkd. 1/4 S12 BT.</p> <p>Bury a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 60%; margin-left: 0;"/>	R6W		R5W	S12		S 7
R6W		R5W					
S12		S 7					

Subdivision of Section 7,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET	
	<p>From the E 1/16 sec. cor. of secs. 6 and 7, hereinbefore described.</p> <p>S. 0° 31' 02" E., on the N. and S. centerline of the NE 1/4 of sec. 7, posting and blazing.</p>
1326.35	<p>The NE 1/16 sec. cor. of sec. 7, established by Harvey M. Christensen, Oregon Professional Land Surveyor No. 2603, in 1995, filed in the Douglas County Surveyor's Office, Map File No. M123-34, and is accepted as the corner, occupied by a fir, 22 ins. diam., with healed blaze on N. face, from which bearing trees and a reference monument by Christensen</p> <p style="padding-left: 40px;">A reinforcing bar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, for a reference monument, bears N. 45°00' E., 3.0 ft. dist. Drive aluminum cap mkd. RM NE 1/16 S7 3.0 FT TO COR 2006 with an arrow pointing to the corner on top of iron rod.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 66° E., 60.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 68° W., 10.0 ft. dist., with a healed blaze.</p> <hr/> <p>N. 89° 32' 01" E., on the E. and W. centerline of the NE 1/4 of sec. 7, posting and blazing.</p>
45	Ravine, drains S. 32° W.
350	Spur, slopes N. 60° W.
1303.27	<p>The N 1/16 sec. cor. of secs. 7 and 8.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 7 and 18, hereinbefore described.</p> <p>N. 0° 46' 59" W., on the N. and S. centerline of the SW 1/4 of sec. 7, posting and blazing.</p>
2640.17	<p>The center W 1/16 sec. cor. of sec. 7.</p> <hr/>

T. 22 S., R. 5 W., Willamette Meridian, Oregon

FEET

GENERAL DESCRIPTION

The lands included in the foregoing survey are located in mountainous terrain, approximately 1.5 miles northwesterly from the community of Drain, Oregon.

Elevation ranges from approximately 400 feet above sea level near the corner of sections 7, 12, 13, and 18, on the west boundary of the township, to approximately 1000 feet near the NE 1/16 section corner of section 7.

The northerly portion of the area surveyed is drained by minor unnamed tributaries of Hardscrable Creek which flows southerly to Elk Creek. The central portion of the survey is drained by Post Creek which flows southerly to Elk Creek. Elk Creek then flows westerly to the Umpqua River.

Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

Access is by way of graveled roads branching from State Highway No. 38 and Hardscrable Creek Road.

The mean magnetic declination for the area surveyed is 19° East, as shown on the "DRAIN, OREG." 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1987.