

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

REHABILITATION OF CERTAIN CORNER POINTS

TOWNSHIP 20 SOUTH, RANGE 8 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Aaron M. Graham, Cadastral Surveyor

Under Special Instructions dated February 22, 2002,

approved February 22, 2002,

which provided for the surveys included under Group No. 2000,

and Assignment Instructions dated November 29, 2004.

Survey commenced January 10, 2005

Survey completed March 31, 2005

T. 20 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the rehabilitation of certain corner points, Township 20 South, Range 8 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this rehabilitation is as follows.

In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed the south, east, west, and north boundaries and subdivisional lines.

In 1891, Charles M. Collier, U.S. Deputy Surveyor, resurveyed the south boundary of T. 19 S., R. 8 W.

In 1891, Thomas E. Todd, U.S. Deputy Surveyor, resurveyed the west boundary of T. 20 S., R. 7 W.

In 1945, Norman D. Price, Cadastral Engineer, and Geo. F. Rigby, Associate Cadastral Engineer, resurveyed a portion of the south, west, and north boundaries and a portion of the subdivisional lines.

In 1950, Thomas A. Tillman, Cadastral Engineer, resurveyed a portion of the south, east, and west boundaries and a portion of the subdivisional lines.

In 1952, Marvin J. Lytle and Palmer Norseth, Cadastral Engineers, resurveyed a portion of the south boundary of township 19 south, range 8 west.

In 1953-54, Thomas A. Tillman, Raymond M. Bicknell, Hans W. Thielsen, and Joseph S. Gawron, Cadastral Engineers, resurveyed a portion of the east, west, and north boundaries and a portion of the subdivisional lines.

In 1966-67, Lynn M. Roseberry and William W. Glenn, Cadastral Surveyors, resurveyed a portion of the east boundary.

In 1967, William W. Glenn, C. Albert White and James E. Jelley, Cadastral Surveyors, rehabilitated and remonumented certain corner points.

The rehabilitation was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated February 22, 2002, for Group No. 2000, Oregon.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

**Rehabilitation of Certain Corner Points on the South Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

(Rehabilitating the corners established by Wright in 1884
and remonumented by Tillman in 1950)

The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 20 S	R 8 W
S 35	S 36
S 2	S 1
T 21 S	
1950	

from which the remains of the original bearing trees

A burned decayed fir stump, 17 ins. diam., bears S. 45° W., 38.3 ft. dist., with a healed blaze. (Record, S. 41° W.)

A burned decayed fir stump, 33 ins. diam., bears N. 87° W., 44.9 ft. dist., no marks visible.

and the remains of bearing trees mkd. by Tillman in 1950

A decayed fir snag, 26 ins. diam., bears N. 60° E., 31.0 ft. dist., with scribe marks 20S 8W 6 B and other illegible scribe marks visible on partially healed blaze.

A decayed fir snag, 20 ins. diam., bears S. 46¾° E., 14.5 ft. dist., with illegible scribe marks visible on partially healed blaze. (Record, S. 44¼° E.)

A decayed fir snag, 19 ins. diam., bears S. 34¾° W., 11.9 ft. dist., with a healed blaze. (Record, S. 39° W.)

A decayed fir snag, 14 ins. diam., bears N. 36¼° W., 12.5 ft. dist., with a healed blaze. (Record, N. 34¼° W.)

and new bearing trees

A fir, 8 ins. diam., bears N. 15° E., 15.8 ft. dist., mkd. T20S R8W S36 BT.

A fir, 8 ins. diam., bears S. 42½° E., 13.1 ft. dist., mkd. T21S R8W S1 BT.

A fir, 11 ins. diam., bears S. 63½° W., 23.0 ft. dist., mkd. T21S R8W S2 BT.

Rehabilitation of Certain Corner Points on the South Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>A fir, 8 ins. diam., bears N. 53° W., 17.0 ft. dist., mkd. T20S R8W S35 BT.</p> <p>There is a steel fence post alongside the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>The ¼ sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 34 1/4 _____ S 3 1950</p> </div> <p>from which the remains of an original bearing tree</p> <p>A fir stump, 25 ins. diam., bears S. 5° W., 12.5 ft. dist. to a rebar, ½ in. diam., driven in the center of the stump, no marks visible. (Record, 13.2 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Tillman in 1950</p> <p>A fir stump, 25 ins. diam., bears N. 15° E., 10.6 ft. dist., to a rebar, ½ in. diam., driven in the center of the stump, with scribe marks S34 visible on open blaze.</p> <p>and new bearing trees</p> <p>A fir, 14 ins. diam., bears S. 21° W., 9.6 ft. dist., mkd. 1/4 S3 BT.</p> <p>A fir, 11 ins. diam., bears N. 30½° W., 14.9 ft. dist., mkd. 1/4 S34 BT.</p> <p>There is a tag nearby that reads "This is the second corner Bill Glenn was at starting his survey career 1950 1986."</p> <hr style="width: 60%; margin: 10px auto;"/> <p style="text-align: center;">(Rehabilitating the corner established by Wright in 1884, remonumented by Price and Rigby in 1945, and rehabilitated by Glenn, et al., in 1967)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>The ¼ sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 33 1/4 _____ S 4 1945</p> </div>
------	---

**Rehabilitation of Certain Corner Points on the South Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

from which the remains of a bearing tree mkd. by Price and Rigby in 1945

A fir snag, 70 ins. diam., bears N. $18\frac{3}{4}^{\circ}$ E., 36.3 ft. dist., with scribe marks 1/4 S33 BT visible on open burned blaze.

and new bearing trees

A fir, 12 ins. diam., bears S. 67° E., 15.8 ft. dist., mkd. 1/4 S4 BT.

A fir, 11 ins. diam., bears N. $1\frac{1}{2}^{\circ}$ W., 20.0 ft. dist., mkd. 1/4 S33 BT.

(Rehabilitating the corner established by Wright in 1884, remonumented by Price and Rigby in 1945, and remonumented by Glenn, et al., in 1967)

The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground with brass cap mkd.

T 20 S	R 8 W
S 32	S 33
S 5	S 4
T 21 S	R 8 W
1967	

from which the remaining original bearing tree

A root hole bears S. 62° W., 4.0 ft. dist.

and the remains of a bearing tree mkd. by Price and Rigby in 1945

A burned fir snag, 54 ins. diam., bears S. 61° E., 43.6 ft. dist., with scribe marks T21S R8W S visible on open decayed blaze.

and the remains of bearing trees mkd. by Glenn, et al., in 1967

A cedar stump, 42 ins. diam., bears N. $\frac{1}{4}^{\circ}$ E., 73.3 ft. dist., with scribe marks T20S R8W S33 BT visible on open decayed blaze.

A cedar stump, 47 ins. diam., bears N. 56° W., 114.8 ft. dist., with scribe marks T20S R8W S32 BT visible on open decayed blaze.

**Rehabilitation of Certain Corner Points on the South Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

and new bearing trees

A fir, 8 ins. diam., bears S. 82° E., 30.1 ft. dist., mkd. T21S R8W S4 BT.

A fir, 14 ins. diam., bears S. ½° W., 14.6 ft. dist., mkd. T21S R8W S5 BT.

A fir, 15 ins. diam., bears N. 56½° W., 25.2 ft. dist., mkd. T20S R8W S32 BT.

No suitable trees to the NE. available.

**Rehabilitation of Certain Corner Points, on the East Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman in 1950)

The ¼ sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground with brass cap mkd.

¼ S 36 |
1950

from with the remains of the original bearing trees

A fir snag, 55 ins. diam., bears S. 60° E., 25.1 ft. dist., to face, no marks visible.

A fir stump, 65 ins. diam., bears West, 17.2 ft. dist., no marks visible.

and new bearing trees

A fir, 14 ins. diam., bears S. 61¾° W., 12.9 ft. dist., mkd. 1/4 S36 BT.

A fir, 15 ins. diam., bears N. 48° W., 25.4 ft. dist., mkd. X BT.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman in 1950, and
rehabilitated by Roseberry and Glenn in 1966-67))

The cor. of secs. 25 and 36 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.

**Rehabilitation of Certain Corner Points, on the East Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

T 20 S	T 20 S
S 25	R 7 W
S 36	S 31
R 8 W	
	1950

from which the remains of an original bearing tree

A root hole with maple remains bears N. 77° W.,
7.9 ft. dist.

and the remains of a bearing tree mkd. by Roseberry and Glenn in
1966-67

A fir snag, 29 ins. diam., bears S. 26½° W.,
85.8 ft. dist., with a healed blaze.

and new bearing trees

A fir, 16 ins. diam., bears S. 44¼° W., 38.7 ft. dist.,
mkd. T20S R8W S36 BT.

A fir, 14 ins. diam., bears N. 9¼° W., 19.2 ft. dist.,
mkd. T20S R8W S25 BT.

There is a steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman in 1950)

The cor. of secs. 24 and 25 only, monumented with an iron post,
2 ins. diam., firmly set, projecting 10 ins. above the ground,
with brass cap mkd.

T 20 S	T 20 S
S 24	R 7 W
S 25	S 30
R 8 W	
	1950

from with the remains of the original bearing trees

A decayed fir stump, 41 ins. diam., bears S. 71° W.,
55.4 ft. dist., with no marks visible on partially
healed blaze. (Record, 53.5 ft. dist.)

A decayed fir stump, 27 ins. diam., bears N. 47° W.,
46.9 ft. dist., no marks visible.

**Rehabilitation of Certain Corner Points, on the East Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	and the remains of a bearing tree mkd. by Tillman in 1950
	A decayed fir stump, 65 ins. diam., bears N. 55° W., 81.5 ft. dist., no marks visible. (Record, 83.2 ft. dist.)
	and new bearing trees
	A fir, 12 ins. diam., bears S. 71¾° W., 39.7 ft. dist., mkd. T20S R8W S25 BT.
	A fir, 13 ins. diam., bears N. 13¾° W., 11.1 ft. dist., mkd. T20S R8W S24 BT.
	<hr/> (Rehabilitating the corners established by Wright in 1884 and remonumented by Tillman, et al., in 1953-54) <hr/>
	The ¼ sec. cor. of sec. 24 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.
	$\frac{1}{4}$ S 24 1954
	from which the remains of the original bearing trees
	A decayed cedar stump, 39 ins. diam., bears N. 62° E., 15.8 ft. dist., with no marks visible on partially healed blaze.
	A root hole with uprooted burned cedar log, 20 ins. diam., bears S. 53° W., 7.9 ft. dist., no marks visible.
	and a bearing tree mkd. by Tillman, et al., in 1953-54
	A fir snag, 56 ins. diam., bears N. 7° W., 48.8 ft. dist., with scribe marks 1/4 visible on open blaze.
	and new bearing trees
	A fir, 8 ins. diam., bears N. 78° W., 7.7 ft. dist., mkd. X BT.
	A fir, 16 ins. diam., bears N. 9½° W., 33.6 ft. dist., mkd. 1/4 S24 BT.
	<hr/> The ¼ sec. cor. of sec. 13 only, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. <hr/>

Rehabilitation of Certain Corner Points, on the East Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;"> $\frac{1}{4}$ S 13 1954 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A burned decayed fir stump, 48 ins. diam., bears N. 12° E., 16.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A burned decayed fir stump, 70 ins. diam., bears N. 73° W., 23.9 ft. dist., no marks visible. (Record, 18.5 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54</p> <p style="padding-left: 40px;">A burned decayed fir stump, 53 ins. diam., bears S. 89° W., 24.4 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 23½° W., 13.8 ft. dist., mkd. 1/4 S13 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 86° W., 11.4 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>The cor. of secs. 12 and 13 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 20 S</td> <td style="padding: 0 5px;">T 20 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">R 7 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 8 W</td> <td></td> </tr> </table> 1954 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A burned decayed fir stump, 58 ins. diam., bears S. 80° E., 16.5 ft. dist., with no scribe marks visible on decayed blaze.</p> <p style="padding-left: 40px;">A burned decayed cedar stump, 58 ins. diam., bears N. 35° W., 10.6 ft. dist., with scribe mark B visible on open blaze. (Record, 7.9 ft. dist.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 20½° W., 33.7 ft. dist., mkd. T20S R8W S13 BT.</p>	T 20 S	T 20 S	S 12	R 7 W	S 13	S 18	R 8 W	
T 20 S	T 20 S								
S 12	R 7 W								
S 13	S 18								
R 8 W									

**Rehabilitation of Certain Corner Points, on the East Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A fir, 22 ins. diam., bears N. $58\frac{1}{2}^{\circ}$ W., 34.8 ft. dist.,
mkd. T20S R8W S12 BT.

**Rehabilitation of Certain Corner Points, on the West Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman in 1950)

The cor. of secs. 19 and 30 only, monumented with an iron post,
2 ins. diam., firmly set, projecting 7 ins. above the ground,
with brass cap mkd.

T 20 S	T 20 S
R 9 W	S 19
S 25	S 30
	R 8 W
	1950

from which an original bearing tree

A fir, 33 ins. diam., bears S. 21° W., 46.9 ft. dist., no
marks visible.

and the remains of bearing trees mkd. by Tillman in 1950

A fir, 38 ins. diam., bears N. $47\frac{1}{2}^{\circ}$ E., 21.0 ft. dist.,
with a healed blaze. (Record, 19.8 ft. dist.)

A fir stump, 22 ins. diam., bears S. 58° E.,
16.5 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 7 ins. diam., bears S. $14\frac{1}{2}^{\circ}$ E., 10.2 ft. dist.,
mkd. T20S R8W S30 BT.

There is a steel fence post and an aluminum fence post with a
monument sign on it alongside the corner.

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman, et al., in 1953-54)

The $\frac{1}{4}$ sec. cor. of sec. 19 only, monumented with an iron post,
1 in. diam., firmly set, projecting 3 ins. above the ground,
with brass cap mkd.

Rehabilitation of Certain Corner Points, on the West Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;"> 1/4 S 19 1954</p> <p>from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54</p> <p style="padding-left: 40px;">A decayed fir stump, 40 ins. diam., bears N. 88½° E., 70.6 ft. dist., with no marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock stump, 33 ins. diam., bears S. 56° E., 16.5 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 19¼° E., 54.2 ft. dist., mkd. 1/4 S19 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 74¼° E., 83.7 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>The ¼ sec. cor. of sec. 18 only, determined at record bearing and distance from the remains of a bearing tree mkd. by Tillman, et al., in 1953-54.</p> <p style="padding-left: 40px;">A fir stump, 26 ins. diam., bears N. 41¼° E., 20.5 ft. dist., with no marks visible on partially healed blaze.</p> <p>Corner is located on edge of a graveled road, where it is impractical to establish a permanent monument.</p> <p>From this point, a witness corner established by the Douglas County Surveyor's Office in 1965, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 20 S., R. 8 W., Point Identifier No. 100440, and reported by Glenn et. al., in 1967, bears East, 43.89 ft. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">WC 40' WEST S 18 1/4 T 20 S R 8 W 1965</p> <p>from which the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1965 and reported by Glenn, et. al., in 1967</p>
------	---

**Rehabilitation of Certain Corner Points, on the West Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A decayed hemlock stump, size indeterminate, bears N. 46° E., 4.6 ft. dist., no marks visible.

and new bearing trees

A fir, 7 ins. diam., bears N. 68¼° E., 13.0 ft. dist., mkd. X BT.

A fir, 9 ins. diam., bears N. 37½° W., 3.8 ft. dist., mkd. WC S18 BT.

There is a steel fence post alongside the corner.

The cor. of secs. 6 and 7 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 20 S	T 20 S
R 9 W	S 6
S 12	S 7
	R 8 W
1953	

from which the remains of the original bearing trees

A decayed fir stump, 66 ins. diam., bears N. 45° E., 44.8 ft. dist., with a healed blaze. (Record, 46.9 ft. dist.)

A decayed fir stump, 72 ins. diam., bears S. 62° E., 24.0 ft. dist., no marks visible. (Record, 19.8 ft. dist.)

A fir stump, 50 ins. diam., bears S. 57° W., 21.1 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A hemlock stump, size indeterminate, bears N. 23½° E., 31.0 ft. dist., no marks visible.

and new bearing trees

A fir, 9 ins. diam., bears N. 18½° E., 16.2 ft. dist., mkd. T20S R8W S6 BT.

A fir, 7 ins. diam., bears S. 29° E., 9.8 ft. dist., mkd. T20S R8W S7 BT.

**Rehabilitation of Certain Corner Points on the North Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

(Rehabilitating the corner established by Wright in 1884,
reestablished by Collier in 1891, and
remonumented by Lytle and Norseth in 1952)

The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 19 S	R 8 W
S 33	S 34
S 4	S 3
T 20 S	
1952	

from which the remains of the original bearing trees

A metal capped fir stump, 46 ins. diam., bears N. 26½° E., 48.2 ft. dist., no marks visible.

A fir, 62 ins. diam., bears S. 49° E., 45.5 ft. dist., with a healed blaze.

A fir snag, 42 ins. diam., bears N. 54° W., 52.8 ft. dist., with a healed blaze. (Record, 54.8 ft. dist.)

and the remains of the bearing tree mkd. by Lytle and Norseth in 1952

A decayed hemlock stump, 27 ins. diam., bears S. 55¾° W., 59.4 ft. dist., no marks visible.

and new bearing trees

An alder, 5 ins. diam., bears N. 36° E., 18.7 ft. dist., mkd. T19S R8W S34 BT on bark.

A fir, 9 ins. diam., bears S. 45° W., 4.8 ft. dist., mkd. T20S R8W S4 BT.

A fir, 12 ins. diam., bears N. 8¼° W., 6.7 ft. dist., mkd. T19S R8W S33 BT.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman in 1950)

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam. firmly set, 42 ins. below the ground with brass cap mkd.

T 20 S	R 8 W
S 26	S 25
S 35	S 36
1950	

from which the remains of a bearing tree mkd. by Tillman in 1950

A fir stump, 49 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ W.,
62.0 ft. dist., no marks visible.

and new bearing trees

A fir, 9 ins. diam., bears N. $47\frac{1}{4}^{\circ}$ E., 30.7 ft. dist.,
mkd. T20S R8W S25 BT.

A fir, 9 ins. diam., bears S. 66° E., 21.9 ft. dist., mkd.
T20S R8W S36 BT.

A fir, 8 ins. diam., bears S. 69° W., 14.1 ft. dist., mkd.
T20S R8W S35 BT.

A fir, 9 ins. diam., bears N. $74\frac{1}{4}^{\circ}$ W., 13.5 ft. dist.,
mkd. T20S R8W S26 BT.

The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.

S 24
1/4 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/>
S 25
1950

from which the remains of bearing trees mkd. by Tillman in 1950

A hemlock snag, 22 ins. diam., bears S. 9° W.,
17.2 ft. dist., no marks visible.

A decayed hemlock stump, 40 ins. diam., bears N. 36° W.,
39.6 ft. dist., no marks visible.

and new bearing trees

A fir, 13 ins. diam., bears S. $44\frac{3}{4}^{\circ}$ E., 16.1 ft. dist.,
mkd. 1/4 S25 BT.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A fir, 9 ins. diam., bears N. $71\frac{3}{4}^{\circ}$ W., 8.6 ft. dist., mkd. 1/4 S24 BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, remonumented by Wilford N. Haines, Registered Land Surveyor No. 239, in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 20 S., R. 8 W., Point Identifier No. 600340, 55/98; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 8 W 23 $\frac{1}{4}$ S 24 RS 239</p> <p>from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54</p> <p style="text-align: center;">A burned fir stump, 66 ins. diam., bears N. $27\frac{1}{2}^{\circ}$ E., 54.8 ft. dist., with scribe marks 1/4 S2 visible on loose piece of open decayed blaze. (Record, N. $23\frac{3}{4}^{\circ}$ E.)</p> <p style="text-align: center;">A fir stump, 34 ins. diam., bears N. $21\frac{1}{4}^{\circ}$ W., 70.0 ft. dist., with no marks visible on open blaze.</p> <p>and new bearing trees</p> <p style="text-align: center;">A fir, 14 ins. diam., bears S. 8° E., 22.7 ft. dist., mkd. 1/4 S24 BT.</p> <p style="text-align: center;">A fir, 16 ins. diam., bears N. $1\frac{1}{4}^{\circ}$ W., 4.0 ft. dist., mkd. 1/4 S23 BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p style="text-align: center;">(Rehabilitating the corners established by Wright in 1884 and remonumented by Tillman, et al., in 1953-54)</p> <hr style="width: 30%; margin: 10px auto;"/> <p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 22 ins. above the ground, in a mound of stone, 4 ft. base, 15 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 8 W S 14 S 13 ----- S 23 S 24 1954</p> <p>from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54</p>
------	--

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A burned fir stump, 27 ins. diam., bears N. $52\frac{1}{2}^{\circ}$ E., 53.5 ft. dist., with a healed blaze. (Record, N. 51° E.)

A maple clump growing around a root hole, bears N. 27° W., 22.4 ft. dist., no marks visible.

and new bearing trees

A fir, 17 ins. diam., bears N. $13\frac{1}{2}^{\circ}$ E., 33.7 ft. dist., mkd. T20S R8W S13 BT.

A fir, 11 ins. diam., bears S. 32° E., 38.8 ft. dist., mkd. T20S R8W S24 BT.

A fir, 14 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ W., 56.4 ft. dist., mkd. T20S R8W S23 BT.

A fir, 10 ins. diam., bears N. $86\frac{1}{2}^{\circ}$ W., 46.5 ft. dist., mkd. T20S R8W S14 BT.

Corner falls on a steep rocky slope with thin soil cover.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

1/4
S 14 | S 13
1954

from which new bearing trees

A fir, 9 ins. diam., bears N. 40° E., 5.5 ft. dist., mkd. 1/4 S13 BT.

A fir, 12 ins. diam., bears S. $34\frac{1}{2}^{\circ}$ W., 13.2 ft. dist., mkd. 1/4 S14 BT.

(Rehabilitating the corners established by Wright in 1884,
reestablished by Tillman in 1950,
and rehabilitated by Glenn, et al., in 1967)

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

T 20 S	R 8 W
S 22	S 23
1950	

from which the remains of bearing trees mkd. by Tillman in 1950

A roothole bears N. $85\frac{1}{2}^{\circ}$ E., 14.5 ft. dist., with a down decayed fir lying alongside, size indeterminate, no marks visible.

A decayed fir snag, 16 ins. diam., bears S. $69\frac{1}{2}^{\circ}$ E., 11.2 ft. dist., with scribe marks 20 8W 26 and other illegible marks visible on partially healed blaze. (Record, S. $66\frac{1}{2}^{\circ}$ E.)

A burned fir stump, 39 ins. diam., bears S. 7° W., 28.4 ft. dist., with scribe mark B visible on partially healed blaze.

A fir snag, 48 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 26.4 ft. dist., with scribe marks 2 R S B and other illegible marks visible on partially healed blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A fir snag, 39 ins. diam., bears S. 31° W., 14.5 ft. dist., with scribe marks T20S R8W S27 BT visible on open blaze. (Record, 16.2 ft. dist.)

and new bearing trees

A fir, 10 ins. diam., bears N. $29\frac{1}{2}^{\circ}$ E., 19.9 ft. dist., mkd. T20S R8W S23 BT.

A fir, 10 ins. diam., bears S. $80\frac{1}{4}^{\circ}$ E., 23.7 ft. dist., mkd. T20S R8W S26 BT.

A fir, 10 ins. diam., bears S. 6° W., 13.4 ft. dist., mkd. T20S R8W S27 BT.

A fir, 8 ins. diam., bears N. 45° W., 23.0 ft. dist., mkd. T20S R8W S22 BT.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

1/4	
S 22	S 23
1950	

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

from which the remains of a bearing tree mkd. by Tillman in 1950

A decayed fir stump, 50 ins. diam., bears S. 66° W.,
37.6 ft. dist., with scribe marks 1/4 S22 BT visible on
open blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A root hole with cedar log alongside, 8 ins. diam., bears
S. 86° E., 17.8 ft. dist., no marks visible.

and new bearing trees

A fir, 13 ins. diam., bears S. 48° E., 7.7 ft. dist., mkd.
1/4 S23 BT.

A fir, 9 ins. diam., bears S. 20° W., 19.0 ft. dist., mkd.
1/4 S22 BT.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman in 1950, and
rehabilitated by Glenn, et al., in 1967)

The cor. of secs. 14, 15, 22, and 23, monumented with an iron
post, 2 ins. diam., firmly set, projecting 3 ins. above the
ground, with brass cap mkd.

T 20 S	R 8 W
S 15	S 14
S 22	S 23
1950	

from which the remains of a bearing tree mkd. by Tillman in 1950

A burned decayed fir stump, 50 ins. diam., bears
S. 13¾° W., 106.3 ft. dist., no marks visible.

and the remains of bearing trees mkd. by Glenn, et al., in 1967

A burned fir stump, 50 ins. diam., bears N. 25½° E.,
68.3 ft. dist., no marks visible.

A burned fir stump, 53 ins. diam., bears S. 68½° E.,
108.2 ft. dist., with a healed blaze.

A burned fir stump, 50 ins. diam., bears N. 78½° W.,
107.6 ft. dist., with a healed blaze.

and new bearing trees

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A fir, 17 ins. diam., bears N. $34\frac{3}{4}^{\circ}$ E., 20.5 ft. dist.,
mkd. T20S R8W S14 BT.

A fir, 17 ins. diam., bears S. $84\frac{1}{4}^{\circ}$ E., 113.3 ft. dist.,
mkd. T20S R8W S23 BT.

A fir, 14 ins. diam., bears S. 13° W., 74.5 ft. dist.,
mkd. T20S R8W S22 BT.

An alder, 8 ins. diam., bears N. 84° W., 31.8 ft. dist.,
mkd. T20S R8W S15 BT on bark.

(Rehabilitating the corner established by Wright in 1884
and reestablished by Tillman in 1950)

The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with an iron
post, 1 in. diam., firmly set, projecting 9 ins. above the
ground, with brass cap mkd.

1/4
S 33 | S 34
1950

from which the remains of bearing trees mkd. by Tillman in 1950

A decayed fir snag, 18 ins. diam., bears S. 85° E.
12.5 ft. dist., with a healed blaze.

A decayed burned fir snag, 18 ins. diam., bears N. 81° W.,
13.9 ft. dist., with a healed blaze.

and new bearing trees

A fir, 9 ins. diam., bears N. $71\frac{1}{2}^{\circ}$ E., 12.2 ft. dist.,
mkd. 1/4 S34 BT.

A fir, 12 ins. diam., bears S. 34° W., 12.2 ft. dist.,
mkd. 1/4 S33 BT.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman in 1950, and
rehabilitated by Glenn, et al., in 1967)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron
post, 2 ins. diam., firmly set, projecting 13 ins. above the
ground, with brass cap mkd.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

T 20 S	R 8 W
S 28	S 27
S 33	S 34
1950	

from which the remains of bearing trees mkd. by Tillman in 1950

A fir stump, 40 ins. diam., bears S. 61° E., 15.2 ft. dist., no marks visible.

A burned fir stump, 24 ins. diam., bears N. 21° W., 44.2 ft. dist., with scribe marks T20S and other illegible marks visible on open blaze.

and new bearing trees

A fir, 22 ins. diam., bears N. ½° E., 22.1 ft. dist., mkd. T20S R8W S27 BT.

A fir, 11 ins. diam., bears S. 89¾° E., 41.6 ft. dist., mkd. T20S R8W S34 BT.

A fir, 10 ins. diam., bears S. 38° W., 8.6 ft. dist., mkd. T20S R8W S33 BT.

A fir, 15 ins. diam., bears N. 59¾° W., 15.5 ft. dist., mkd. T20S R8W S28 BT.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman in 1950, and
rehabilitated by Glenn, et al., in 1967)

The cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.

S 27
1/4 ———
S 34
1950

from which the remains of a bearing tree mkd. by Tillman in 1950

A root hole bears S. 30¾° E., 52.8 ft. dist., alongside of which is a down decayed fir, size indeterminate, no marks visible.

and the remains of bearing trees mkd. by Glenn, et al., in 1967

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A cedar snag, 20 ins. diam., bears N. 25° E., 47.5 ft. dist., no marks visible.

A burned decayed fir snag, 22 ins. diam., bears S. 10° E., 92.4 ft. dist., with scribe marks S 4 B visible on open blaze.

and new bearing trees

A fir, 9 ins. diam., bears S. 66½° E., 13.7 ft. dist., mkd. 1/4 S34 BT.

A fir, 12 ins. diam., bears N. 7¾° W., 15 ft. dist., mkd. 1/4 S27 BT.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman in 1950, and
rehabilitated by Glenn et al., in 1967)

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T 20 S	R 8 W
S 21	S 22
S 28	S 27
1950	

from which the remains of bearing trees mkd by Tillman in 1950

A decayed hemlock snag, 14 ins. diam., bears S. 31° W., 53.5 ft. dist., no marks visible.

A cedar stump, 70 ins. diam., bears N. 83½° W., 46.2 ft. dist., with no marks visible on open blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A burned cedar snag, 44 ins. diam., bears N. 13° E., 115.5 ft. dist., no marks visible.

and new bearing trees

A fir, 20 ins. diam., bears N. 80½° E., 22.8 ft. dist., mkd. T20S R8W S22 BT.

A fir, 21 ins. diam., bears S. 4½° E., 53.0 ft. dist., mkd. T20S R8W S27 BT.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A fir, 23 ins. diam., bears S. 41° W., 56.2 ft. dist.,
mkd. T20S R8W S28 BT.

A fir, 21 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 109.9 ft. dist.,
mkd. T20S R8W S21 BT.

The cor. of secs. 15, 16, 21, and 22, monumented with an iron
post, 2 ins. diam., firmly set, projecting 10 ins. above the
ground, with brass cap mkd.

T 20 S	R 8 W
S 16	S 15
S 21	S 22
1950	

from which the remains of the original bearing trees

A burned cedar stump, 46 ins. diam., bears S. $33\frac{3}{4}^{\circ}$ E.,
17.2 ft. dist., no marks visible.

A fir snag, 73 ins. diam., bears S. 54° W.,
12.5 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Tillman in 1950

A cedar stump, 51 ins. diam., bears N. 30° W.,
40.3 ft. dist., with no scribe marks visible on open
blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A decayed cedar stump, size indeterminate, bears
N. 76° E., 8.3 ft. dist., no marks visible.

and new bearing trees

A fir, 11 ins. diam., bears N. 48° E., 24.9 ft. dist.,
mkd. T20S R8W S15 BT.

A fir, 21 ins. diam., bears S. $51\frac{1}{4}^{\circ}$ E., 30.0 ft. dist.,
mkd. T20S R8W S22 BT.

A fir, 22 ins. diam., bears S. 31° W., 54.7 ft. dist.,
mkd. T20S R8W S21 BT.

A fir, 8 ins. diam., bears N. $7\frac{3}{4}^{\circ}$ W., 16.4 ft. dist., mkd.
T20S R8W S16 BT.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman, et al., in 1953-54, and
rehabilitated by Glenn, et al., in 1967)

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

1/4
S 16 | S 15
1954

from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54

A root hole bears S. 8° E., 3.0 ft. dist., with a down decayed fir lying alongside, size indeterminate, no marks visible.

A hemlock stump, 54 ins. diam., bears N. 44° W., 5.9 ft. dist., no marks visible.

and new bearing trees

A fir, 14 ins. diam., bears N. $55\frac{1}{4}^{\circ}$ E., 13.4 ft. dist., mkd. 1/4 S15 BT.

A fir, 14 ins. diam., bears S. 61° W., 20.4 ft. dist., mkd. 1/4 S16 BT.

There is a steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman, et al., in 1953-54)

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

T 20 S R 8 W
S 9 | S 10

S 16 | S 15
1954

From which the remains of the original bearing trees

A burned fir stump, 50 ins. diam., bears S. 80° W., 32.3 ft. dist., with scribe marks T20S R8W S16 BT visible on open blaze.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A burned fir stump, 50 ins. diam., bears N. 36° W., 23.1 ft. dist., with no marks visible on decayed blaze.</p> <p>and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54</p> <p>A burned fir stump, 43 ins. diam., bears S. 30° E., 31.0 ft. dist., with scribe marks 20S R8W S15 BT visible on open blaze.</p> <p>and new bearing trees</p> <p>A fir, 12 ins. diam., bears N. 21¼° E., 6.6 ft. dist., mkd. T20S R8W S10 BT.</p> <p>A fir, 13 ins. diam., bears S. 40¼° E., 13.7 ft. dist., mkd. T20S R8W S15 BT.</p> <p>A fir, 15 ins. diam., bears S. 30½° W., 11.9 ft. dist., mkd. T20S R8W S16 BT.</p> <p>A fir, 12 ins. diam., bears N. 80° W., 5.9 ft. dist., mkd. T20S R8W S9 BT.</p> <hr/> <p style="text-align: center;">(Rehabilitating the corner established by Wright in 1884, reestablished by Tillman, et al., in 1953-54, and rehabilitated by Glenn, et al., in 1967)</p> <hr/> <p>The ¼ sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 9 S 10 1954</p> </div> <p>from which the remains of bearing trees mkd. by Glenn, et al., in 1967</p> <p>A decayed fir stump, 53 ins. diam., bears S. 36° E., 46.9 ft. dist., with scribe marks 1/4 S1 visible on open blaze.</p> <p>A decayed fir snag, 35 ins. diam., bears N. 11° W., 33.0 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 28¾° E., 15.9 ft. dist., mkd. 1/4 S10 BT.</p>

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A fir, 16 ins. diam., bears S. $48\frac{1}{2}^{\circ}$ W., 8.5 ft. dist.,
mkd. 1/4 S9 BT.

There is a steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884,
reestablished by Tillman, et al., in 1953-54, and
rehabilitated by Glenn, et al., in 1967)

The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with an iron post,
1 in. diam., firmly set, projecting 5 ins. above the ground,
with brass cap mkd.

1/4
S 4 | S 3
1954

from which the remains of a bearing tree mkd. by Tillman, et
al., in 1954

A fir stump, 38 ins. diam., bears S. $66\frac{1}{4}^{\circ}$ E.,
14.5 ft. dist., with illegible scribe marks visible on
open blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A fir stump, 60 ins. diam., bears N. 56° W.,
10.6 ft. dist., with scribe marks S 1/4 BT visible on
open blaze.

and new bearing trees

A fir, 13 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ E., 6.6 ft. dist.,
mkd. 1/4 S3 BT.

A fir, 12 ins. diam., bears S. $87\frac{1}{2}^{\circ}$ W., 9.8 ft. dist.,
mkd. 1/4 S4 Bt.

(Rehabilitating the corners established by Wright in 1884,
remonumented by Tillman in 1950, and
rehabilitated by Glenn, et al., in 1967)

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with an iron
post, 1 in. diam., firmly set, 4 ins. below the ground, with
brass cap mkd.

1/4
S 29 | S 28
1950

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

from which the remains of a bearing tree and a reference monument mkd. by Glenn, et al., in 1967

A burned fir stump, 34 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 99.7 ft. dist., with a healed blaze.

An iron post, $2\frac{1}{2}$ ins. diam., firmly set, flush with the ground, bears N. 41° W., 38.3 ft. dist., with brass cap mkd. 1/4 S29 RM 1967 and an arrow pointing to the corner.

and a new bearing tree

A fir, 10 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., 56.4 ft. dist., mkd. 1/4 S28 BT.

The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd.

S 21
1/4 ———
S 28
T 20 S R 8 W
1967

from which the remains of the bearing trees mkd. by Tillman in 1950

A fir stump, 58 ins. diam., bears N. 30° E., 40.3 ft. dist., no marks visible.

A fir stump, 44 ins. diam., bears S. 26° W., 44.9 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A cedar stump, 33 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ W., 99.7 ft. dist., with a healed blaze.

and new bearing trees

A fir, 18 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ E., 37.2 ft. dist., mkd. 1/4 S21 BT.

A fir, 17 ins. diam., bears S. 10° W., 56.1 ft. dist., mkd. 1/4 S28 BT.

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman, et al., in 1953-54)

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.

S 16
1/4 ———
S 21
1954

from which the remains of an original bearing tree

A fir snag, 34 ins. diam., bears S. 70° E., 4.0 ft. dist., with no marks visible on open blaze.

and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 35 ins. diam., bears N. 35° E., 25.6 ft. dist., with no marks visible on partially healed blaze. (Record, 23.8 ft. dist.)

and new bearing trees

A fir, 8 ins. diam., bears S. 48° W., 31.5 ft. dist., mkd. 1/4 S21 BT.

A fir, 10 ins. diam., bears N. 9½° W., 31.0 ft. dist., mkd. 1/4 S16 BT.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman, et al., in 1953-54,
and rehabilitated by Glenn, et al., in 1967)

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

T 20 S R 9 W
S 8 | S 9
———
S 17 | S 16
1954

from which the remains of the original bearing trees

A fir stump, 86 ins. diam., bears S. 47° E., 42.2 ft. dist., with no marks visible on open blaze. (Record, 44.9 ft. dist.)

A fir stump, 40 ins. diam., bears N. 23° W., 29.1 ft. dist., with a healed blaze. (Record, 27.1 ft. dist.)

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

and the remains of bearing trees mkd. by Tillman, et al., in 1953-54

A cedar stump, 38 ins. diam., bears S. $56\frac{1}{4}^{\circ}$ E., 47.9 ft. dist., with no marks visible on decayed blaze. (Record, 50.2 ft. dist.)

A fir stump, 75 ins. diam., bears S. $85\frac{1}{2}^{\circ}$ W., 31.7 ft. dist., no marks visible.

A cedar stump, 27 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ W., 19.1 ft. dist., with scribe marks T20S R8W S8 BT visible on partially healed blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A cedar stump, 36 ins. diam., bears N. 31° E., 49.2 ft. dist., with scribe marks T20S R8W visible on open decayed blaze.

and new bearing trees

An alder, 9 ins. diam., bears N. 63° E., 28.5 ft. dist., mkd. T20S R8W S9 BT in the bark.

A fir, 16 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ E., 35.6 ft. dist., mkd. T20S R8W S16 BT.

A fir, 10 ins. diam., bears S. $71\frac{1}{2}^{\circ}$ W., 35.5 ft. dist., mkd. T20S R8W S17 BT.

A hemlock, 17 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., 32.6 ft. dist., mkd. T20S R8W S8 BT.

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman, et al., in 1953-54)

The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, in a collar of stone, projecting 6 ins. above the ground, with brass cap mkd.

S 9
1/4 ———
S 16
1954

from which the remains of an original bearing tree

A root hole bears S. 10° W., 19.8 ft. dist.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A root hole bears N. $67\frac{1}{2}^{\circ}$ W., 23.8 ft. dist.

and new bearing trees

A fir, 10 ins. diam., bears S. $30\frac{3}{4}^{\circ}$ E., 44.3 ft. dist., mkd. 1/4 S16 BT.

An alder, 11 ins. diam., bears N. $70\frac{3}{4}^{\circ}$ W., 21.5 ft. dist., mkd. 1/4 S9 BT on bark.

There is a steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884,
remonumented by Tillman, et al., in 1953-54,
and rehabilitated by Glenn, et al., in 1967)

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

$$\begin{array}{c} 1/4 \\ S \ 8 \ | \ S \ 9 \\ 1954 \end{array}$$

from which the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 49 ins. diam., bears N. 11° W., 50.2 ft. dist., with a burned healed blaze.

and the remains of a bearing tree mkd. by Glenn, et al., in 1967

A cedar stump, 17 ins. diam., bears N. $8\frac{3}{4}^{\circ}$ E., 46.2 ft. dist., with no marks visible on open burned blaze.

and new bearing trees

A fir, 11 ins. diam., bears N. $9\frac{1}{4}^{\circ}$ E., 22.4 ft. dist., mkd. 1/4 S9 BT.

A fir, 15 ins. diam., bears S. $54\frac{1}{2}^{\circ}$ W., 15.0 ft. dist., mkd. 1/4 S8 BT.

(Rehabilitating the corners established by Wright in 1884
and remonumented by Tillman, et al., in 1953-54)

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground with brass cap mkd.

T 20 S	5	R 8 W
S 8	5	S 4
	8	S 9
1954		

from which the remains of an original bearing tree

A decayed fir stump, 18 ins. diam., bears S. 65° E., 21.8 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by Tillman, et al., in 1953-54

A fir stump, 35 ins. diam., bears S. 12° W., 24.4 ft. dist., with scribe marks T20S R8W S8 BT visible on open blaze. (Record, S. 13¼° W.)

A fir stump, 27 ins. diam., bears N. 31½° W., 40.2 ft. dist., with illegible scribe marks visible on open blaze. (Record, 37.6 ft. dist.)

and new bearing trees

A fir, 23 ins. diam., bears N. 63° E., 16.9 ft. dist., mkd. T20S R8W S4 BT.

A fir, 19 ins. diam., bears S. 4° E., 31.8 ft. dist., mkd. T20S R8W S9 BT.

A fir, 7 ins. diam., bears S. 42° W., 30.5 ft. dist., mkd. T20S R8W S8 BT.

A fir, 13 ins. diam., bears N. 57° W., 20.5 ft. dist., mkd. T20S R8W S5 BT.

An iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, established by person(s) unknown for unknown purpose is alongside the corner and was not utilized for control in this rehabilitation.

The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, in a boulder 4 x 3 x 2 ft. above ground, with a brass cap mkd.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

S 4
1/4 ———
S 9
1954

from which an original bearing tree

A fir, 46 ins. diam., bears S. 75° E., 8.6 ft. dist., with no marks visible on open blaze.

and the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 61 ins. diam., bears N. 62½° E., 37.6 ft. dist., with no marks visible on burned partially healed blaze.

and a new bearing tree

A fir, 12 ins. diam., bears N. 15½° W., 5.6 ft. dist., mkd. 1/4 S4 BT.

There is a bent-over steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884
and reestablished by Tillman, et al., in 1953-54)

The ¼ sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

1/4
S 5 | S 4
1954

from which the remains of a bearing tree mkd. by Tillman, et al., in 1953-54

A fir stump, 30 ins. diam., bears N. 13° E., 25.3 ft. dist., with a healed blaze. (Record, 22.4 ft. dist.)

and new bearing trees

A fir, 7 ins. diam., bears N. 56½° E., 25.6 ft. dist., mkd. 1/4 S4 BT.

A fir, 7 ins. diam., bears S. 27° W., 5.4 ft. dist., mkd. 1/4 S5 BT.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman in 1950)

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T 20 S	R 8 W
S 19	S 20
S 30	S 29
1950	

from which the remains of bearing trees mkd. by Tillman in 1950

A fir snag, 13 ins. diam., bears N. 10° E., 15.8 ft. dist., with scribe marks R8W S20 BT visible on burned partially healed blaze.

A fir stump, 26 ins. diam., bears S. 71½° W., 32.3 ft. dist., no marks visible.

A decayed fir stump, 10 ins. diam., bears N. 36½° W., 23.1 ft. dist., with scribe mark T visible on open blaze.

and new bearing trees

A fir, 17 ins. diam., bears N. 56° E., 20.4 ft. dist., mkd. T20S R8W S20 BT.

A fir, 8 ins. diam., bears S. 67½° E., 26.6 ft. dist., mkd. T20S R8W S29 BT.

A fir, 11 ins. diam., bears S. 74° W., 23.0 ft. dist., mkd. T20S R8W S30 BT.

A fir, 11 ins. diam., bears N. 27½° W., 36.9 ft. dist., mkd. T20S R8W S19 BT.

There is a steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884
and reestablished by Tillman, et al., in 1953-54)

The ¼ sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in., diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	S 17 1/4 ——— S 20 1954
	from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54
	A fir stump, 43 ins. diam., bears S. 28° W., 17.8 ft. dist., with no marks visible on partially healed blaze.
	A fir, 52 ins. diam., bears N. 30° W., 29.7 ft. dist., with a healed blaze.
	and a new bearing tree
	A fir, 7 ins. diam., bears S. 52½° E., 9.3 ft. dist., mkd. 1/4 S20 BT.
	<hr/> (Rehabilitating the corner established by Wright in 1884, remonumented by Tillman, et al., in 1953-54, and rehabilitated by Glenn, et al., in 1967) <hr/>
	The ¼ sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, 4 ins. below the ground, with brass cap mkd.
	S 18 1/4 ——— S 19 1954
	from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54
	A cedar stump, 46 ins. diam., bears S. 73° E., 25.1 ft. dist., with no marks visible on burned partially healed blaze.
	A cedar stump, 33 ins. diam., bears N. 38½° W., 68.6 ft. dist., no marks visible.
	and new bearing trees
	A fir, 9 ins. diam., bears S. 2° W., 14.2 ft. dist., mkd. 1/4 S19 BT.
	A fir, 15 ins. diam., bears N. 48° W., 19.7 ft. dist., mkd. 1/4 S18 BT.

**Rehabilitation of Certain Corner Points
on the Subdivisional Lines,
T. 20 S., R. 8 W., Willamette Meridian, Oregon**

FEET

There is a steel fence post alongside the corner.

(Rehabilitating the corner established by Wright in 1884
and remonumented by Tillman, et al., in 1953-54)

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap. mkd.

S 5
1/4 ———
S 8
1954

from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54

A fir snag, 23 ins. diam., bears S. $54\frac{1}{4}^{\circ}$ W., 47.5 ft. dist., with scribe marks 1/4 S8 BT visible on partially healed blaze.

A burned cedar stump, 31 ins. diam., bears N. 59° W., 46.2 ft. dist., no marks visible.

and new bearing trees

A fir, 16 ins. diam., bears S. 17° E., 12.2 ft. dist., mkd. 1/4 S8 BT.

A fir, 9 ins. diam., bears N. $7\frac{1}{2}^{\circ}$ W., 23.0 ft. dist., mkd. 1/4 S5 BT.

T. 20 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this rehabilitation are nestled in the Coast Range of Oregon approximately 12 miles north of the town of Elkton. Access to the areas are via the Smith River access road and various BLM and privately maintained logging roads.</p> <p>The area is drained by Smith River and North and South Sister Creeks, all of which are fed by numerous unnamed tributaries. The primary use of this land is for timber production and recreation.</p> <p>The vegetation in the area is consistent with Western Oregon Rainforest with timber of fir, hemlock, cedar, maple, myrtle, and alder. Undergrowth consists of ferns, vine maple, Oregon grape, and poison oak. This area is prime habitat for large, forest-dwelling mammals such as elk, deer, bear, and cougar.</p>
------	---