

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND A PORTION OF THE SUBDIVISION OF SECTION LINES IN SECTION 20,  
AND THE SUBDIVISION OF SECTIONS 21 AND 23,  
**TOWNSHIP 22 SOUTH, RANGE 4 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

***Robert H. Browning, Surveying Technician***

Under Special Instructions dated May 21, 2007, approved May 24, 2007,  
which provided for the surveys included under Group No. 2170,  
and Assignment Instructions dated July 25, 2007.

***Survey commenced August 1, 2007***

***Survey completed February 19, 2008***

## T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and a portion of the subdivision of section lines in section 20, and the subdivision of sections 21 and 23, Township 22 South, Range 4 West, of the Willamette Meridian, Oregon.</p> <p>The history of surveys that pertain to this survey is as follows:</p> <p>In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines.</p> <p>In 1879, William Thiel, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.</p> <p>In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.</p> <p>In 1901, Oscar F. Thiel, U.S. Deputy Surveyor, surveyed the remainder of the subdivisional lines.</p> <p>In 1963, Donald R. Beck, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 20.</p> <p>In 1965, James E. Jelley, Cadastral Surveyor, remonumented certain original corner points.</p> <p>In 1980-81, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the subdivisional lines.</p> <p>In 1988, Wayne L. Rogers, Cadastral Surveyor, and Garry L. Moore, Surveying Technician, resurveyed a portion of the subdivisional lines.</p> <p>In 1993-94, Dale T. Bedell, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.</p> <p>In 2000, A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the subdivisional lines and subdivided section 9.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and Special Instructions dated May 21, 2007, for Group No. 2170, Oregon.</p> <p>The survey was performed using a combination of Global Positioning System (GPS) satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.</p>
-------	---

## T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment.

Static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS measurement error ellipse at the 95% confidence level is 0.30 feet based on local accuracy standards. Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The unadjusted data assured a closure not exceeding 1:4000 in error. The adjusted bearings and distances are reported to the nearest second of arc and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the true line field notes are given herein.

New bearing trees have a 2 1/2 x 1/4 inch magnetic nail (Mag Nail) driven at the base on the center of the right side.

New stainless steel corner post monuments have a magnet in a white plastic case deposited at the base of the post.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined in a least squares adjusted network of conventional survey control and GPS occupied points, utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Stations (CORS) "DCSO CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows.

For the corner of sections 23, 24, 25, and 26:

Latitude: 43° 38' 07.32" N.      Longitude: 123° 07' 39.09" W.

For the 1/4 section corner of sections 21 and 28:

Latitude: 43° 38' 05.23" N.      Longitude: 123° 10' 36.76" W.

For the corner of sections 20, 21, 28, and 29:

Latitude: 43° 38' 05.35" N.      Longitude: 123° 11' 13.12" W.

For the corner of sections 9, 10, 15, and 16:

Latitude: 43° 39' 49.01" N.      Longitude: 123° 10' 00.60" W.

For the 1/4 section corner of sections 9 and 16:

T. 22 S., R. 4 W., Willamette Meridian, Oregon

F E E T

Latitude: 43° 39' 49.39" N.      Longitude: 123° 10' 37.53" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Harvey Gordon and Charles Gardner,  
the 1879 survey by William Thiel,  
the 1884 survey by William P. Wright,  
the 1901 survey by Oscar F. Thiel,  
the 1963 resurvey by Donald R. Beck,  
the 1965 remonumentation by James E. Jelley,  
the 1980-81 resurvey by James E. Jelley and Wayne L. Rogers,  
the 1988 resurvey by Wayne L. Rogers and Garry L. Moore,  
the 1993-94 resurvey By Dale T. Bedell, and  
the 2000 resurvey by A. Bert Skeesick and Robert H. Browning)

Beginning at the cor. of secs. 23, 24, 25, and 26, monumented  
with an iron post, 2 1/2 ins. diam., firmly set, projecting  
5 ins. above ground, with brass cap mkd.

T22S	R4W
S23	S24
S26	S25
1965	

from which the remains of an original bearing tree

A root hole, bears N. 23° W., 29.7 ft. dist., with fallen  
cedar snag, 16 ins. diam., lying alongside, no marks  
visible.

and the remains of bearing trees mkd. by William L. Wilt,  
Weyerhaeuser Co. Land Agent, in 1963, filed in the Lane County  
Surveyor's Office, Reestablishment Record No. 8911, reported by  
Jelley

A sawed cedar stump, 36 ins. diam., bears N. 7° E.,  
35.6 ft. dist., no marks visible.

A sawed decayed cedar stump, 42 ins. diam., bears  
S. 81° W., 42.9 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by Jelley

A sawed hemlock stump, 28 ins. diam., bears N. 3° E.,  
21.1 ft. dist., with a healed blaze. (Record, cedar)

A cedar, 38 ins. diam., bears S. 60 1/2° E.,  
15.2 ft. dist., with fragmentary scribe marks visible on  
a partially healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 0 3/4° E., 61.6 ft. dist., mkd. T22S R4W S24 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 68 1/2° W., 28.5 ft. dist., mkd. T22S R4W S23 BT.</p> <p>No suitable trees available in sec. 26.</p> <p>Corner is located on a shallow NE. slope.</p> <p>From the cor. S., 45 ft. dist., a graveled road, 10 ft. wide, bears S. 70° E. and N. 70° W.</p> <p>N. 0° 22' 31" E., bet. secs. 23 and 24, posting and blazing the true line.</p>
2663.82	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, and in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>1/4</p> <p> </p> <p>S23   S24</p> <p>T22S R4W</p> <p>1965</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 48 ins. diam., bears S. 27° E., 33.0 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 52 ins. diam., bears N. 52° W., 5.3 ft. dist., with axe marks visible.</p> <p>and the remains of bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A sawed fir stump, 28 ins. diam., bears N. 81 3/4° E., 90.5 ft. dist., no marks visible. (Record, N. 83 1/2° E., 88.4 ft.)</p> <p style="padding-left: 40px;">A root hole, bears N. 47° W., 77.9 ft. dist., with fallen, decayed hemlock snag, 8 ins. diam., lying alongside, no marks visible.</p> <p>and bearing trees mkd. by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 2003, not filed in the county</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 17 1/2° E., 10.9 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 8 ins. diam., bears S. 52 3/4° W., 23.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>A fir, 38 ins. diam., bears N. 14 1/4° W., 16.1 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 06' 50" E., beginning new measurement, posting and blazing.</p>						
2296.10	<p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T22S</td> <td style="padding: 2px 5px;">R4W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S14</td> <td style="padding: 2px 5px;">S13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S23</td> <td style="padding: 2px 5px;">S24</td> </tr> </table> <p>1965</p> </div> <p>from which the remains of the original bearing trees</p> <p>A sawed, decayed cedar stump, size indeterminate, bears S. 8° E., 43.6 ft. dist., no marks visible.</p> <p>A burnt, decayed cedar stump, size indeterminate, bears N. 55° W., 23.8 ft. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by Glen McChesney, Weyerhaeuser Co. Land Agent, in 1962, filed in the Lane County Surveyor's Office, Reestablishment Record No. 3062, reported by Jelley</p> <p>A sawed decayed fir stump, 65 ins. diam., bears S. 56 1/2° E., 37.0 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Jelley</p> <p>A hemlock snag, 10 ins. diam., bears S. 63 1/2° E., 62.0 ft. dist., with a healed blaze.</p> <p>A yew, 16 ins. diam., bears S. 55 1/2° W., 54.8 ft. dist., with scribe marks T22S R4W visible on a partially healed blaze.</p> <p>A hemlock, 17 ins. diam., bears N. 69° W., 144.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, not filed in the county</p>	T22S	R4W	S14	S13	S23	S24
T22S	R4W						
S14	S13						
S23	S24						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET					
	<p>A fir, 16 ins. diam., bears N. 40° E., 21.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 17 ins. diam., bears S. 13° E., 14.1 ft. dist., mkd. T22S R4W S24 BT.</p>				
	<hr/> <p>From the cor. of secs. 26, 27, 34, and 35, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, filed in the Douglas County Surveyor's Office, File No. M4-51, monumented with an iron T-post, 1 in. sq., firmly set, projecting 11 ins. above ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remaining orig. bearing trees</p> <p>A fir, 50 ins. diam., bears N. 14° E., 9.9 ft. dist., with a healed blaze.</p> <p>A fir, 35 ins. diam., bears N. 20° W., 17.8 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Glen McChesney, Weyerhaeuser Co. Land Agent, in 1958, filed in the Douglas County Surveyor's Office, C.S. File No. 53/105</p> <p>A fir, 39 ins. diam., bears S. 75 1/4° E., 27.3 ft. dist., with a healed blaze.</p> <p>A fir, 38 ins. diam., bears S. 39 3/4° W., 37.3 ft. dist., with a healed blaze.</p>				
	<p>At the cor. point</p>				
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the T-post, with brass cap mkd.</p>				
	<div style="text-align: center;"> <p>T22S R4W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S34</td> <td style="padding: 0 5px;">S35</td> </tr> </table> <p>2007</p> </div>	S27	S26	S34	S35
S27	S26				
S34	S35				
	<p>N. 0° 27' 14" W., bet. secs. 26 and 27, posting and blazing.</p>				
85	<p>Ravine, drains S. 67° W.</p>				
265	<p>Spur, slopes N. 60° W.</p>				

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

<p>FEEET 2636.73</p>	<p>The 1/4 sec. cor. of secs. 26 and 27, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, filed in the Douglas County Surveyor's Office, File No. M4-51; subsequently perpetuated by Larry E. Monrean, Deputy County Surveyor, in 1987, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 500240, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground (alongside of which is an iron T-post, 1 in. sq., with brass washer on top), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS</p> <table style="margin: auto; border: none;"> <tr> <td style="text-align: center; vertical-align: middle;">DOUGLAS</td> <td style="text-align: center; vertical-align: middle;">T22S 1/4   S27   S26</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center; vertical-align: middle;">R4W 1987</td> <td></td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed decayed fir stump, 35 ins. diam., bears N. 21° E., 24.4 ft. dist., no scribe marks visible on opened decayed blaze.</p> <p style="margin-left: 40px;">A sawed decayed fir stump, 33 ins. diam., bears N. 9° W., 37.0 ft. dist., no scribe marks visible on opened decayed blaze.</p> <p>and references by Monrean</p> <p style="margin-left: 40px;">A cedar stump, 30 ins. diam., bears N. 45 3/4° E., 47.8 ft. dist. to a boat spike in top center, no marks visible.</p> <p style="margin-left: 40px;">A fir stump, 43 ins. diam., bears S. 37° W., 61.4 ft. dist. to a boat spike in top center, no marks visible.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 64 3/4° E., 9.4 ft. dist., mkd. 1/4 S26 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 31 1/4° W., 22.2 ft. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. of secs. 23, 24, 25, and 26, hereinbefore described.</p> <p>S. 87° 47' 08" W., bet. secs. 23 and 26, posting and blazing.</p>	DOUGLAS	T22S 1/4   S27   S26	OFFICE		R4W 1987	
DOUGLAS	T22S 1/4   S27   S26	OFFICE					
	R4W 1987						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

<p>F E E T</p> <p>1318.99</p>	<p>The E 1/16 sec. cor. of secs. 23 and 26, established by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1998, filed in the Lane County Surveyor's Office, Reestablishment Record No. 13529, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap incorrectly mkd.</p> <p style="text-align: center;">T22S R6W S23 E 1/16 ————— S26 PLS 1978 1998</p> <p>from which bearing trees mkd. by Baker</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 83 3/4° E., 8.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 4° W., 11.8 ft. dist., with a healed blaze.</p> <p style="text-align: center;">—————</p> <p>S. 87° 43' 09" W., beginning new measurement, posting and blazing.</p>															
<p>1319.29</p>	<p>The 1/4 sec. cor. of secs. 23 and 26, reestablished by Herbert R. Jones, Oregon Registered Professional Engineer No. 2461, in 1958, filed in the Douglas County Surveyor's Office, File No. M12-042, subsequently perpetuated by the Douglas County Surveyor's Office in 1991, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 540300. There is no remaining evidence of the original corner, therefore this position is accepted as the best available evidence of the original cor., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; vertical-align: middle;">DOUGLAS</td> <td style="text-align: center; vertical-align: middle;">T22S R4W</td> <td style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">S23</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1/4 —————</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S26</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1991</td> <td></td> </tr> </table> <p>from which the remains of bearing trees mkd. by Jones</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 83° E., 25.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears S. 87 1/4° W., 16.1 ft. dist., no marks visible.</p>	DOUGLAS	T22S R4W	OFFICE		S23			1/4 —————			S26			1991	
DOUGLAS	T22S R4W	OFFICE														
	S23															
	1/4 —————															
	S26															
	1991															

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

<p>FEEET</p>	<p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A sawed fir stump, 15 ins. diam., bears S. 0 3/4° W., 51.6 ft. dist., with a healed blaze.</p> <p>A fir, 19 ins. diam., bears N. 19 1/2° E., 20.6 ft. dist., with a healed blaze.</p> <p>and new bearing tree</p> <p>A fir, 12 ins. diam., bears S. 71 1/4° W., 71.7 ft. dist., mkd. 1/4 S26 BT.</p> <hr/> <p>S. 87° 36' 02" W., beginning new measurement, posting and blazing.</p>
<p>60</p>	<p>Graveled road, 9 ft. wide, bears S. 2° E. and N. 7° W.</p>
<p>1319.04</p>	<p>The W 1/16 sec. cor. of secs. 23 and 26, established by Herbert R. Jones, Oregon Registered Professional Engineer No. 2461, in 1958, filed in the Douglas County Surveyor's Office, File No. M12-42, and is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above ground, from which the bearing trees mkd. by Jones</p> <p>A fir, 30 ins. diam., bears N. 15 1/2° E., 22.9 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 36 3/4° W., 36.8 ft. dist., with a healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>S23</p> <hr style="width: 100px; margin: 0 auto;"/> <p>W 1/16</p> <hr style="width: 100px; margin: 0 auto;"/> <p>S26</p> <p>2007</p> </div> <p>Discontinue posting and blazing.</p> <hr/> <p>S. 87° 57' 50" W., beginning new measurement.</p>
<p>1317.87</p>	<p>The cor. of secs. 22, 23, 26 and 27, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, subsequently perpetuated by Gregory Quibell, Deputy County Surveyor, in 1982, filed in the Douglas County Surveyor's Record</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 500300, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td></td> <td style="text-align: center;">CO</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">T22S</td> <td></td> </tr> <tr> <td style="text-align: center;">DOUGLAS</td> <td style="text-align: center;">S22   S23</td> <td style="text-align: center;">SURVEYOR</td> </tr> <tr> <td></td> <td style="text-align: center;">S27   S26</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R4W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1982</td> <td></td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed fir stump, 59 ins. diam., bears S. 55 1/4° E., 16.2 ft. dist., with axe marks visible. (Record, S. 70 1/2° E., 13.9 ft.)</p> <p style="margin-left: 40px;">A sawed fir stump, 42 ins. diam., bears N. 22 3/4° W., 27.1 ft. dist., with no marks visible on opened blaze. (Record, N. 19 1/2° W.)</p> <p>and the remains of bearing trees mkd. by Haines</p> <p style="margin-left: 40px;">A fir, 34 ins. diam., bears S. 4° E., 15.2 ft. dist., with fragmentary scribe marks visible on the bark.</p> <p style="margin-left: 40px;">A sawed cedar stump, 50 ins. diam., bears N. 63 1/2° W., 44.2 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Quibell</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 68 3/4° E., 27.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 51 1/4° W., 4.3 ft. dist., mkd. T22S R4W S27 BT.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 13 3/4° W., 20.2 ft. dist., mkd. T22S R4W S22 BT.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 0° 22' 37" W., bet. secs. 22 and 23.</p> <p>1165 Creek, 1 ft. wide, course N. 46° W.</p> <p>1278.83 The S 1/16 sec. cor. of secs. 22 and 23, established by Bruce A. Shaner, Oregon Professional Land Surveyor No. 430, in 2001, filed in the Douglas County Surveyor's Office, File No. M137-19, and is accepted as the cor., monumented with an</p>		CO			T22S		DOUGLAS	S22   S23	SURVEYOR		S27   S26			R4W			1982	
	CO																		
	T22S																		
DOUGLAS	S22   S23	SURVEYOR																	
	S27   S26																		
	R4W																		
	1982																		

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">SHANER ENGINEERING</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">S 1/16</td> <td></td> <td></td> </tr> <tr> <td style="padding: 0 10px;">S22</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S23</td> </tr> <tr> <td style="padding: 0 10px;">2001</td> <td></td> <td style="padding: 0 10px;">INC</td> </tr> </table> <p style="text-align: center;">RLS 430</p>	S 1/16			S22		S23	2001		INC
S 1/16										
S22		S23								
2001		INC								
90	<p>from which the bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 67° E., 29.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 89 1/2° W., 26.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 23' 40" W., beginning new measurement, posting and blazing.</p>									
1278.93	<p>Creek, 2 ft. wide, course S. 85° W.</p> <p>The 1/4 sec. cor. of secs. 22 and 23, reestablished by Nick Juliano, Oregon Registered Professional Engineer No. 3449, in 1958, filed in the Douglas County Surveyor's Office, File No. M13-55, subsequently perpetuated by Bruce A. Shaner, Oregon Professional Land Surveyor No. 430, in 2001, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 500340, and is accepted as the cor., monumented with an aluminum cap, 3 ins. diam., firmly set in concrete, with top mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T22S</td> <td style="padding: 0 10px;">R4W</td> <td style="padding: 0 10px;">WM</td> </tr> <tr> <td style="padding: 0 10px;">S22</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 10px;">S23</td> </tr> <tr> <td style="padding: 0 10px;">RLS430</td> <td></td> <td style="padding: 0 10px;">2001</td> </tr> </table> <p>from which the remains of bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A decayed madrone stump, size indeterminate, bears S. 49 1/4° E., 67.1 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A root hole bears N. 85 1/2° W., 28.8 ft. dist., with fallen, decayed madrone stump, size indeterminate, lying alongside, no marks visible.</p> <p>and bearing trees mkd. by Shaner</p>	T22S	R4W	WM	S22		S23	RLS430		2001
T22S	R4W	WM								
S22		S23								
RLS430		2001								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 14 ins. diam., bears S. 65° W., 39.9 ft. dist., with a healed blaze.</p> <p>A fir, 15 ins. diam., bears N. 48° W., 77.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 7 ins. diam., bears N. 60 3/4° E., 123.6 ft. dist., mkd. 1/4 S23 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 17' 04" W., beginning new measurement, posting and blazing.</p>									
2560.15	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T22S</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">R4W</td> </tr> <tr> <td style="padding: 0 5px;">S15</td> <td style="border-left: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S14</td> </tr> <tr> <td style="padding: 0 5px;">S22</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S23</td> </tr> </table> <p>1988</p> </div> <p>from which the remains of the original bearing trees</p> <p>A root hole bears S. 52° E., 33.0 ft. dist., with pushed over fir stump, 30 ins. diam., lying alongside, no marks visible.</p> <p>A root hole bears S. 77° W., 14.5 ft. dist., with pushed over fir stump, size indeterminate, lying alongside, no marks visible.</p> <p>A fir snag, 35 ins. diam., bears N. 47° W., 11.9 ft. dist., with axe marks visible.</p> <p>and the remains of a bearing tree mkd. by Nick Juliano, Oregon Registered Professional Engineer No. 3449, in 1958, filed in the Douglas County Surveyor's Office, C.S. File No. 53/105. (Record, incorrectly attributed to Leo J. Martin by Rogers and Moore.)</p> <p>A decayed fir snag, size indeterminate, bears N. 75° E., 21.1 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 500400, reported by Rogers and Moore</p>	T22S		R4W	S15		S14	S22		S23
T22S		R4W								
S15		S14								
S22		S23								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 24 ins. diam., bears S. 68° W., 50.2 ft. dist., no marks visible.</p> <p>A fir, 43 ins. diam., bears N. 42° W., 87.8 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Rogers and Moore</p> <p>A fir, 16 ins. diam., bears N. 54 1/2° E., 5.3 ft. dist., with a healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 23° E., 13.9 ft. dist., with a healed blaze.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24, hereinbefore described.</p> <p>S. 88° 55' 45" W., bet. secs. 14 and 23, posting and blazing.</p>																								
2649.76	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td colspan="3">SURVEYORS</td> </tr> <tr> <td style="padding: 0 10px;">DOUG</td> <td style="padding: 0 10px;">CO</td> <td style="padding: 0 10px;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;">T22S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1/4    S14</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">          S23</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R4W</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">BLM 1965</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1962</td> <td></td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A decayed fir snag, size indeterminate, bears S. 60° W., 25.7 ft. dist., no marks visible.</p> <p>A cedar, 43 ins. diam., bears N. 8° W., 23.8 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962, filed in the Douglas County Surveyor's Office, C.S. File No. 49/42, reported by Jelly</p> <p>A root hole bears S. 66° W., 50.8 ft. dist., with fallen, decayed fir snag, size indeterminate, lying alongside, no marks visible.</p> <p>A fir, 30 ins. diam., bears N. 64 1/2° W., 11.2 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by person(s) unknown</p>	SURVEYORS			DOUG	CO	OFFICE		T22S			1/4    S14			S23			R4W			BLM 1965			1962	
SURVEYORS																									
DOUG	CO	OFFICE																							
	T22S																								
	1/4    S14																								
	S23																								
	R4W																								
	BLM 1965																								
	1962																								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 23 ins. diam., bears S. 43 1/2° E., 27.3 ft. dist., with a healed blaze.</p> <p>A fir, 14 ins. diam., bears S. 37° W., 25.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p>
	<p>N. 89° 55' 37" W., beginning new measurement, continue posting and blazing.</p>
2752.74	<p>The cor. of secs. 14, 15, 22, and 23, hereinbefore described.</p>
	<p>N. 1° 23' 48" W., bet. secs. 14 and 15, posting and blazing.</p>
2662.72	<p>The 1/4 sec. cor. of secs. 14 and 15, perpetuated by John Woodward and Chester Gilham, in 1940, from original evidence no longer in existence, Woodward affidavit filed in the Douglas County Surveyor's Office, C.S. File No. 53/105, subsequently perpetuated by William L. Wilt, Weyerhaeuser Co. Land Agent, in 1963, filed in the Douglas County Surveyor's Office, C.S. File No. 53/105, monumented with an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above ground, from which the remains of the references by Wilt</p> <p>A sawed, decayed fir stump, 48 ins. diam., bears N. 32 1/2° E., 49.3 ft. dist., no marks visible on an opened blaze.</p> <p>A sawed, decayed cedar stump, 42 ins. diam., bears N. 21 1/2° W., 6.9 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Bruce Rogers, Deputy County Surveyor, in 1965, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T 22 S., R. 4 W., Point Identifier No. 500440</p> <p>A cedar, 30 ins. diam., bears West, 10.7 ft. dist., with axe marks visible on open blaze.</p> <p>and bearing trees mkd. by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 2006, not yet filed in the Douglas County Surveyor's Office</p> <p>A fir, 15 ins. diam., bears N. 87° E., 16.6 ft. dist., with a healed blaze.</p> <p>An alder, 12 ins. diam., bears S. 6 1/2° E., 15.0 ft. dist., with scribe marks W1/4 S14 BT visible on bark.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	<p>A fir, 7 ins. diam., bears N. 23° W., 28.5 ft. dist., with a healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T22S</td><td>R4W</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>2007</td><td></td></tr> </table> <hr style="width: 20%; margin: 5px auto;"/> </div> <p>N. 0° 09' 08" E., beginning new measurement, continue posting and blazing.</p>	T22S	R4W	1/4		S15	S14	2007												
T22S	R4W																			
1/4																				
S15	S14																			
2007																				
2460	<p>Spur, slopes W.</p>																			
2668.45	<p>The cor. of secs. 10, 11, 14, and 15, perpetuated by the Weyerhaeuser Company, in 1957, subsequently perpetuated by William L. Wilt, Weyerhaeuser Co. Land Agent, in 1963, filed in the Douglas County Surveyor's Office, C.S. File No. 53/105; further perpetuated by Bruce Rogers, Deputy County Surveyor, in 1965, filed in the Douglas County Surveyor's Office, C.S. File No. 53/101, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="4">SURVEYORS</td></tr> <tr><td></td><td>T22S</td><td></td><td>OFFICE</td></tr> <tr><td rowspan="2" style="writing-mode: vertical-rl; transform: rotate(180deg);">COUNTY</td><td>S10</td><td>S11</td><td>R</td></tr> <tr><td>S15</td><td>S14</td><td>W</td></tr> <tr><td></td><td colspan="2">1965</td><td></td></tr> </table> </div> <p>from which the remains of original bearing trees</p> <p>A burnt decayed fir stump, size indeterminate, bears N. 15° E., 23.1 ft. dist., no marks visible.</p> <p>A root hole bears S. 10° E., 24.4 ft. dist., with a fallen decayed fir snag, 30 ins. diam., lying alongside, no marks visible.</p> <p>A decayed fir stump, size indeterminate, bears N. 28° W., 43.6 ft. dist., with fragmentary scribe marks visible on remaining center stock.</p> <p>and the remains of a bearing tree mkd. by Wilt</p>	SURVEYORS					T22S		OFFICE	COUNTY	S10	S11	R	S15	S14	W		1965		
SURVEYORS																				
	T22S		OFFICE																	
COUNTY	S10	S11	R																	
	S15	S14	W																	
	1965																			

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEEET	<p style="text-align: center;">A fir, 25 ins. diam., bears N. 24 1/4° E., 24.3 ft. dist., no marks visible on open blaze.</p> <p>and the remains of bearing trees mkd. by Bruce Rogers</p> <p style="text-align: center;">A fir, 25 ins. diam., bears N. 87° E., 16.6 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A sawed decayed fir stump, 47 ins. diam., bears S. 47° E., 44.6 ft. dist., no marks visible.</p> <p style="text-align: center;">A root hole bears S. 39 3/4° W., 38.5 ft. dist., with a fallen decayed fir snag, 14 ins. diam., lying alongside, no marks visible.</p> <p style="text-align: center;">A decayed cedar snag, size indeterminate, bears N. 71° W., 70.0 ft. dist., with marks T22S R4W S10 CS B visible on remaining center stock.</p> <p>and bearing trees mkd. by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1995, filed in the Douglas County Surveyor's Office, C.S. File No. 65/1-2</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 2 3/4° E., 13.7 ft. dist., with a healed double blaze.</p> <p style="text-align: center;">A fir, 16 ins. diam., bears S. 80° E., 6.7 ft. dist., with a healed blaze.</p> <p style="text-align: center;">An alder, 12 ins. diam., bears S. 43 1/4° W., 9.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="text-align: center;">A fir, 10 ins. diam., bears N. 13 3/4° W., 17.4 ft. dist., mkd. T22S R4W S10 BT.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35, hereinbefore described.</p> <p>N. 89° 49' 12" W., bet. secs. 27 and 34, posting and blazing.</p>
155	Ravine, drains S. 70° W.
2623.03	<p>The 1/4 sec. cor. of secs. 27 and 34, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, and by Glen McChesney, Weyerhaeuser Co. Land Agent, in 1958, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 440200, monumented with an iron T-post, 1 in. sq., firmly set, buried 3 ins. below ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir snag, size indeterminate, bears N. 37° W., 27.1 ft. dist., with scribe marks 1/4 S visible.</p> <p>and the remains of a bearing tree mkd. by McChesney</p> <p>A sawed fir stump, 56 ins. diam., bears N. 67 1/2° E., 22.3 ft. dist., with axe marks visible.</p> <p>and bearing tree mkd. by person(s) unknown</p> <p>A fir, 19 ins. diam., bears S. 29 1/2° W., 4.3 ft. dist., with a healed double blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, directly over the T-post, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S R4W S27 1/4 ————— S34 2007</p> </div> <p>from which new bearing tree</p> <p>A fir, 12 ins. diam., bears N. 35 3/4° E., 29.3 ft. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 54' 06" W., beginning new measurement, continue posting and blazing.</p>
1305.67	<p>The W 1/16 sec. cor. of secs. 27 and 34, established by Herbert R. Jones, Oregon Registered Engineer No. 2461, in 1963, filed in the Douglas County Surveyor's Office, C.S. File No. 51/87-8, and is accepted as the cor., monumented with an aluminum pipe, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, from which witness trees by Jones</p> <p>A fir, 28 ins. diam., bears S. 25 3/4° W., 13.2 ft. dist., with aluminum sign attached. I mark this tree W1/16 S34 BT.</p> <p>A fir, 30 ins. diam., bears N. 65 1/4° W., 19.6 ft. dist., with aluminum sign attached. I mark this tree W 1/16 S27 BT.</p> <p>At the cor. point</p> <p>Cement a brass tablet, 3 ins. diam., with 3 1/2 in. stem, in the existing aluminum pipe, cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET																			
	<div style="text-align: center;"> <p>S27</p> <p>W 1/16 <hr style="display: inline-block; width: 100px; border: 0.5px solid black; vertical-align: middle; margin: 0 10px;"/></p> <p>S34</p> <p>2008</p> <hr style="width: 30%; margin: 10px auto;"/> </div>																		
	<p>N. 89° 54' 24" W., beginning new measurement, continue posting and blazing.</p>																		
1055	<p>Ravine, drains S. 20° W.</p>																		
1304.81	<p>The cor. of secs. 27, 28, 33, and 34, perpetuated by Oscar F. Thiel in 1950, filed in the Douglas County Surveyor's Office, Thiel Field Book No. 20, page 1, subsequently perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, from original evidence no longer in existence, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 400200, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>																		
	<div style="text-align: center;"> <p>SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">T22S</td> <td></td> </tr> <tr> <td style="text-align: center;">COUNTY</td> <td style="text-align: center;">S28   S27</td> <td style="text-align: center;">OFFICE</td> </tr> <tr> <td></td> <td style="text-align: center;"> </td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S33   S34</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">R4W    W.L.W.</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1963   8-22-63</td> <td></td> </tr> </table> </div>		T22S		COUNTY	S28   S27	OFFICE					S33   S34			R4W    W.L.W.			1963   8-22-63	
	T22S																		
COUNTY	S28   S27	OFFICE																	
	S33   S34																		
	R4W    W.L.W.																		
	1963   8-22-63																		
	<p>from which the remains of the bearing trees mkd. by Thiel</p> <p style="margin-left: 40px;">A fir, 65 ins. diam., bears N. 10 3/4° E., 175.4 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">An oak, 19 ins. diam., bears S. 47 1/2° E., 119.2 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">An oak, 34 ins. diam., bears S. 17 1/4° W., 39.8 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">An oak, 47 ins. diam., bears N. 20 1/4° W., 180.2 ft. dist., with a healed blaze.</p> <hr style="width: 60%; margin: 10px auto;"/>																		
	<p>N. 0° 57' 39" E., bet. secs. 27 and 28, posting and blazing.</p>																		
235	<p>Ridge, bears S. 80° E. and N. 65° W.</p>																		
2614.16	<p>The 1/4 sec. cor. of secs. 27 and 28, perpetuated by C.C. Boyer in 1915; subsequently perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 400240, monumented with an iron T-post, 1 in. sq., firmly set, projecting 8 ins. above</p>																		

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole bears S. 33 3/4° W., 26.3 ft. dist., with a fallen decayed fir, size indeterminate, lying alongside, no marks visible. (Record, S. 18° W., 20.5 ft.)</p> <p>and the remains of a bearing tree mkd. by Boyer</p> <p style="padding-left: 40px;">A sawed fir stump, 53 ins. diam., bears N. 14 1/2° W., 14.8 ft. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, directly over the T-post, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T22S R4W</p> <p>1/4</p> <p>S28   S27</p> <p>2007</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 2 1/4° E., 15.2 ft. dist., mkd. 1/4 S27 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 60° W., 34.2 ft. dist., mkd. 1/4 S28 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 17' 47" E., beginning new measurement, continue posting and blazing.</p>
5	Creek, 1 ft. wide, course N. 50° E.
170	Spur, slopes N. 40° E.
1100	Cox Creek, 10 ft. wide, course N. 10° W.
1318.66	<p>The N 1/16 sec. cor. of secs. 27 and 28, established by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, filed in the Douglas County Surveyor's Office, File No. M4-51, and is accepted as the cor., monumented with an iron T-post, 1 in. sq., firmly set, projecting 5 ins. above ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed fir stump, 43 ins. diam., bears S. 34 1/4° E., 83.4 ft. dist., no marks visible.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 58 ins. diam., bears S. 43 1/2° W., 16.8 ft. dist., with a healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the T-post, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> </table> <p>2007</p> </div> <p>from which new bearing trees</p> <p>A fir, 17 ins. diam., bears S. 42 1/4° E., 52.6 ft. dist., mkd. N1/16 S27 BT.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 15' 13" E., beginning new measurement.</p>	S28	S27													
S28	S27															
1225	<p>Graveled road, 10 ft. wide, bears N. 20° E. and S. 20° W.</p>															
1318.08	<p>The cor. of secs. 21, 22, 27, and 28, perpetuated by person(s) unknown, subsequently perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, filed in the Douglas County Surveyor's Office, File No. M4-51, further perpetuated by Bruce A. Shaner, Oregon Professional Land Surveyor No. 430, in 1997, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 400300. This position is harmoniously related with identified existing original cors. in the area, has long been recognized by owners of the adjacent lands as the cor., and is accepted as the best available evidence of the original cor. position, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>SHANER ENGR</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">T22S</td> <td style="padding: 0 5px;">R4W</td> <td style="padding: 0 5px;">WM</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td colspan="2" style="padding: 0 5px;">S22</td> </tr> <tr> <td style="border-top: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S28</td> <td colspan="2" style="border-top: 1px solid black; padding: 0 5px;">S27</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1997</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">RLS 430</td> </tr> </table> </div> <p>from which bearing trees mkd. by Haines</p> <p>A fir, 38 ins. diam., bears N. 88 1/2° E., 97.5 ft. dist., with fragmentary scribe marks visible on the bark.</p>	T22S	R4W	WM	S21	S22		S28	S27		1997			RLS 430		
T22S	R4W	WM														
S21	S22															
S28	S27															
1997																
RLS 430																

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 72 ins. diam., bears N. 30° W., 54.7 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Shaner</p> <p>A fir, 17 ins. diam., bears S. 16° E., 15.6 ft. dist., with a healed blaze.</p> <p>A fir, 9 ins. diam., bears S. 85° W., 26.2 ft. dist., with a healed blaze.</p> <p>and a reference monument</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground, for a reference monument, bears S. 70°10' E., 12.3 ft. dist., with aluminum cap mkd. RM T22S R4W S27 12.3 FT TO COR 2007 and an arrow pointing toward the cor.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27, hereinbefore described.</p> <p>S. 89° 49' 11" W., bet. secs. 22 and 27, posting and blazing.</p>									
2563.74	<p>The 1/4 sec. cor. of secs. 22 and 27, reestablished by proportionate measurement by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1957, filed in the Douglas County Surveyor's Office, File No. M4-51, perpetuated by Gregory Quibell, Deputy County Surveyor, in 1982, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 440300; there is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">CO</td> <td></td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">DOUGLAS</td> <td style="text-align: center;">T22S S22</td> <td style="text-align: center; vertical-align: middle;">SURVEYOR</td> </tr> <tr> <td></td> <td style="text-align: center; border-top: 1px solid black;">S27 R4W 1982</td> <td></td> </tr> </table> <p>from which the remains of bearing trees mkd. by Haines</p> <p>A sawed fir stump, 29 ins. diam., bears N. 46 1/2° E., 34.7 ft. dist., with a healed blaze.</p> <p>A sawed cedar stump, 19 ins. diam., bears S. 46 1/2° E., 81.7 ft. dist., no marks visible.</p>		CO		DOUGLAS	T22S S22	SURVEYOR		S27 R4W 1982	
	CO									
DOUGLAS	T22S S22	SURVEYOR								
	S27 R4W 1982									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>and remains of bearing trees mkd. by Quibell</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 31 3/4° W., 40.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 83 1/2° W., 22.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir snag, 24 ins. diam., bears N. 45 3/4° W., 20.4 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 56 1/2° W., 99.0 ft. dist., mkd. 1/4 S22 BT.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 46' 59" W., beginning new measurement.</p>		
2558.64	<p>The cor. of secs. 21, 22, 27, and 28, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/>		
1300.16	<p>N. 0° 48' 31" E., bet. secs. 21 and 22, posting and blazing.</p> <p>The S 1/16 sec. cor. of secs. 21 and 22, established by Bruce A. Shaner, Oregon Professional Land Surveyor No. 430, in 2001, filed in the Douglas County Surveyor's Office, File No. M137-19, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>SHANER ENGINEERING</p> <p>S 1/16</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> </table> <p>RLS 430 2001</p> </div> <p>from which bearing trees mkd. by Shaner</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 30 1/2° E., 17.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 76° W., 14.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 28 1/2° W., 9.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/>	S21	S22
S21	S22		

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>N. 0° 51' 45" E., beginning new measurement, continue posting and blazing.</p>
1300.69	<p>The 1/4 sec. cor. of secs. 21 and 22, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, date unknown, subsequently perpetuated by Lester E. Calder, Oregon Registered Engineer No. 2149, in 1962, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 400340, monumented with an iron T-post, 1 in. sq., firmly set, projecting 5 ins. above ground (alongside of which is an iron pipe, 17 ins. long, 1 in. diam., firmly set, projecting 1 in. above ground), with brass disk mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE, from which the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, 53 ins. diam., bears N. 34° E., 45.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 73° W., 33.7 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 62° E., 6.2 ft. dist., with scribe marks 4 S22 BT visible on the bark.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 86° W., 6.2 ft. dist., with a healed blaze.</p> <p>and a reference by Calder</p> <p style="padding-left: 40px;">A fir snag, 26 ins. diam., bears S. 35° W., 34.8 ft. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the T-post, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S    R4W</p> <p>      1/4</p> <p>       </p> <p>      S21   S22</p> <p>      2007</p> </div> <p>Place the iron pipe inside the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 19' 25" W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET			
1318.07	<p>The N 1/16 sec. cor. of secs. 21 and 22, established by Steven P. Ness, Oregon Professional Land Surveyor No. 811, in 1993, filed in the Douglas County Surveyor's Office, File No. M116-66, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S    R4W N 1/16</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> </table> <p>1993    RPLS 811</p> </div> <p>from which the remains of bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A sawed decayed fir stump, 17 ins. diam., bears N. 30° E., 16.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 28 ins. diam., bears S. 9 3/4° W., 9.7 ft. dist., with a healed blaze.</p> <p>and references by Ness</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears S. 9 3/4° E., 21.2 ft. dist. to a "W" nail in top center.</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears N. 53 1/2° W., 13.3 ft. dist. to a "W" nail in top center.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 62 1/4° E., 7.2 ft. dist., mkd. N1/16 S22 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 38 1/2° W., 6.9 ft. dist., mkd. N1/16 S21 BT.</p> <p>From the cor., a point established as the N 1/16 sec. cor. of secs. 21 and 22, reported by Ness as being set by the Weyerhaeuser Company, date unknown, bears S. 73 36' 00" E., 4.69 ft. dist., monumented with an aluminum pipe, 3/4 in. diam., firmly set, projecting 8 ins. above ground. This point is not utilized in this survey.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 18' 14" W., beginning new measurement, posting and blazing.</p>	S21	S22
S21	S22		
15	Spur, slopes N. 60° W.		
225	Ravine, drains N. 80° W.		

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEEET									
380	Spur, slopes N. 85° W.								
905	Ravine, drains N. 75° W.								
1317.64	<p>The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T22S</td> <td style="padding: 2px;">R4W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S16</td> <td style="padding: 2px;">S15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S21</td> <td style="padding: 2px;">S22</td> </tr> <tr> <td colspan="2" style="padding: 2px;">1988</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A hollowed, decayed, burnt fir stump, size indeterminate, bears S. 28° E., 77.9 ft. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by William S. Stoffel, Douglas County Surveyor's Office, in 1964, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 400400, reported by Rogers and Moore</p> <p style="padding-left: 40px;">A root hole, bears N. 84° E., 64.0 ft. dist., with decayed fir stump, size indeterminate, lying alongside, no marks visible.</p> <p>and bearing trees mkd. by Rogers and Moore</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 69 1/2° E., 12.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 25 1/2° E., 20.5 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 59 1/2° W., 35.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 81 1/2° W., 29.0 ft. dist., with a healed double blaze.</p> <p>Corner is located on a shallow NW. slope.</p> <p>From the cor. N., 45 ft. dist., a graveled road, 14 ft. wide, bears N. 78° E. and S. 78° W.</p> <hr style="width: 50%; margin-left: 0;"/> <p>From the cor. of secs. 10, 11, 14, and 15, hereinbefore described.</p>	T22S	R4W	S16	S15	S21	S22	1988	
T22S	R4W								
S16	S15								
S21	S22								
1988									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>N. 87° 55' 44" W., bet. secs. 10 and 15, posting and blazing.</p>																					
2392.59	<p>The 1/4 sec. cor. of secs. 10 and 15, perpetuated by Clyde Randall, in 1955, subsequently perpetuated by William L. Wilt, Land Agent, Weyerhaeuser Company, in 1963, further perpetuated by Bruce Rogers, Deputy County Surveyor, in 1965, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 440500, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="3">SURVEYORS</td> </tr> <tr> <td></td> <td>T22S</td> <td>OFFICE</td> </tr> <tr> <td></td> <td>S10</td> <td></td> </tr> <tr> <td style="text-align: center;">COUNTY</td> <td style="text-align: center;">1/4</td> <td style="text-align: center;">OFFICE</td> </tr> <tr> <td></td> <td>S15</td> <td></td> </tr> <tr> <td></td> <td>R4W</td> <td></td> </tr> <tr> <td></td> <td>1965</td> <td></td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed maple root crown, size indeterminate, bears S. 2° E., 40.3 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A root hole bears N. 39° W., 23.1 ft. dist., with an uprooted, sawed, decayed fir stump, 43 ins. diam., lying alongside, no marks visible.</p> <p>and the remains of bearing trees mkd. by Bruce Rogers</p> <p style="padding-left: 40px;">A sawed, decayed cedar stump, 26 ins. diam., bears N. 24 1/4° E., 55.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 41 ins. diam., bears N. 51° W., 88.7 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 75 3/4° E., 13.9 ft. dist., mkd. 1/4 S10 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 10 1/4° W., 19.6 ft. dist., mkd. 1/4 S15 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 18' 29" W., beginning new measurement, posting and blazing.</p>	SURVEYORS				T22S	OFFICE		S10		COUNTY	1/4	OFFICE		S15			R4W			1965	
SURVEYORS																						
	T22S	OFFICE																				
	S10																					
COUNTY	1/4	OFFICE																				
	S15																					
	R4W																					
	1965																					
20	Creek, 1 ft. wide, course N. 30° W.																					
2350	Graveled road, 14 ft. wide, bears N. 10° E. and S. 10° W.																					

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

<p>F E E T</p> <p>2655.55</p>	<p>The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground (alongside of which is an iron T-post, 1 in. sq., firmly set, projecting 14 ins. above ground with brass disk mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">COUNTY</td> <td colspan="2">SURVEYORS</td> </tr> <tr> <td colspan="4">T22S</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">S9</td> <td style="border-bottom: 1px solid black; padding: 2px 5px;">S10</td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S16</td> <td style="padding: 2px 5px;">S15</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">R4W</td> </tr> <tr> <td colspan="2">OFFICE</td> <td colspan="2">1958</td> </tr> </table> </div> <p>from which an original bearing tree</p> <p style="margin-left: 40px;">A fir, 38 ins. diam., bears N. 78° W., 14.5 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1958, reported by Skeesick and Browning</p> <p style="margin-left: 40px;">A decayed cedar snag, size indeterminate, bears N. 14 1/4° E., 67.5 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears S. 38° W., 60.7 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Rogers and Moore, reported by Skeesick and Browning</p> <p style="margin-left: 40px;">A root hole bears N. 72° E., 21.5 ft. dist., with fallen fir snag, 19 ins. diam., lying alongside, no marks visible.</p> <p style="margin-left: 40px;">A fir, 27 ins. diam., bears S. 60 3/4° E., 31.5 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 21 1/2° E., 59.0 ft. dist., mkd. T22S R4W S10 BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 21 3/4° W., 49.8 ft. dist., mkd. X BT.</p> <p>From the cor. N., 20 ft. dist., a creek, 2 ft. wide, course N. 75° W.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 21, 22, 27, and 28, hereinbefore described.</p>	COUNTY		SURVEYORS		T22S				S9	S10			S16	S15			R4W				OFFICE		1958	
COUNTY		SURVEYORS																							
T22S																									
S9	S10																								
S16	S15																								
R4W																									
OFFICE		1958																							

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	N. 89° 44' 40" W., bet. secs. 21 and 28, posting and blazing.
5	Creek, 2 ft. wide, course S. 20° W.
445	Spur, slopes South.
1620	Paved road, 20 ft. wide, bears S. 64° E. and N. 64° W.
2490	Cox Creek, 4 ft. wide, course N. 35° W.
2674.23	<p>The 1/4 sec. cor. of secs. 21 and 28, reestablished by Donald L. Peel, Oregon Professional Land Surveyor No. 752, in 1991, filed in the Douglas County Surveyor's Office, File No. M111-66. There is no remaining evidence of the original cor., therefore this position is accepted as the best available evidence of the original cor.; monumented with an iron pipe, 41 ins. long, 2 ins. diam., firmly set, projecting 2 ins. above ground, from which a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A cedar snag, 27 ins. diam., bears N. 18 3/4° E., 127.3 ft. dist., with fragmentary scribe marks visible on an open blaze.</p> <p>and the remains of bearing trees and an accessory by Peel</p> <p style="padding-left: 40px;">A sawed fir stump, 25 ins. diam., bears N. 58° E., 170.0 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 32 ins. diam., bears S. 89 1/2° E., 246.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A power pole, 8 ins. diam., bears S. 20 1/2° E., 40.3 ft. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>T22S R4W</p> <p>S21</p> <p>1/4 ———</p> <p>S28</p> <p>2007</p> </div> <p>Bury the iron pipe alongside the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/>
18	<p>N. 89° 45' 05" W., beginning new measurement.</p> <p>Cox Creek, 4 ft. wide, course S. 40° W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET							
2673.96	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T22S</td> <td>R4W</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> </table> <p>1963</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears N. 86° E., 173.6 ft. dist., with fallen fir snag, size indeterminate, lying alongside, no marks visible.</p> <p>and the remains of bearing trees mkd. by Beck</p> <p style="padding-left: 40px;">A sawed fir stump, 24 ins. diam., bears N. 26° E., 87.8 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 17 ins. diam., bears S. 82° E., 7.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears S. 27° W., 20.4 ft. dist., no marks visible. (Record, 19.1 ft.)</p> <p style="padding-left: 40px;">A sawed fir stump, 30 ins. diam., bears N. 54 1/2° W., 31.0 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears N. 55 1/2° E., 69.1 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears S. 37° E., 17.5 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears S. 26 3/4° W., 35.0 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 48 1/4° W., 4.4 ft. dist., mkd. T22S R4W S20 BT.</p> <hr/> <p>N. 0° 38' 59" W., bet. secs. 20 and 21.</p>	T22S	R4W	S20	S21	S29	S28
T22S	R4W						
S20	S21						
S29	S28						
1323.35	<p>The S 1/16 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">S 1/16</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S20</td> <td style="padding: 0 5px;">S21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T22S</td> <td style="padding: 0 5px;">R4W</td> </tr> </table> <p style="text-align: center;">1963</p> <p>from which the bearing trees mkd. by Beck</p> <p style="margin-left: 40px;">A fir, 34 ins. diam., bears N. 46° E., 3.3 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 33 ins. diam., bears N. 72° W., 20.8 ft. dist., with a healed blaze.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 0° 33' 24" W., beginning new measurement, posting and blazing.</p> <p>1320.81 The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="4" style="text-align: center;">SURVEYORS</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T22S</td> <td style="padding: 0 5px;">R4W</td> <td rowspan="2" style="border-left: 1px solid black; padding: 0 5px;">OFFICE</td> <td rowspan="2" style="padding: 0 5px;">COUNTY</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1/4 S20</td> <td style="padding: 0 5px;">S21</td> </tr> <tr> <td colspan="4" style="text-align: center;">1961</td> </tr> </table> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A root hole with maple shoots, bears N. 62° E., 22.4 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A decayed fir snag, size indeterminate, bears S. 50° W., 15.2 ft. dist., no marks visible.</p> <p>and the remains of a bearing tree mkd. by O.F. Thiel, in 1947, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 300340 (Record, incorrectly attributed to Godfrey by Beck)</p> <p style="margin-left: 40px;">A decayed cedar stump, size indeterminate, bears N. 22° E., 10.6 ft. dist., with a hollow blaze, no marks visible.</p> <p>and a bearing tree mkd by Milo E. Godfrey, Deputy County Surveyor, in 1961, filed in the Douglas County Surveyor's Office, C.S. File No. 49/42, reported by Beck</p> <p style="margin-left: 40px;">A cedar, 22 ins. diam., bears N. 56 1/4° W., 21.4 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Beck</p>	S20	S21	T22S	R4W	SURVEYORS				T22S	R4W	OFFICE	COUNTY	1/4 S20	S21	1961			
S20	S21																		
T22S	R4W																		
SURVEYORS																			
T22S	R4W	OFFICE	COUNTY																
1/4 S20	S21																		
1961																			

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A cedar, 31 ins. diam., bears S. 88° E., 35.0 ft. dist., with a healed blaze.</p> <p>A cedar, 25 ins. diam., bears S. 27° W., 29.0 ft. dist., with a healed blaze.</p> <hr/>
	<p>N. 0° 03' 13" W., beginning new measurement, posting and blazing.</p>
120	<p>Creek, 3 ft. wide, course S. 15° W.</p>
1317.30	<p>The N 1/16 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground (alongside of which is an aluminum pipe, 1 ins. diam., firmly set, projecting 4 ins. above ground), with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S20   S21 T22S   R4W 1963</p> <p>from which the remains of bearing trees mkd. by Beck</p> <p>A fir, 48 ins. diam., bears N. 34 3/4° E., 37.0 ft. dist., with a healed blaze.</p> <p>A sawed fir stump, 21 ins. diam., bears N. 32 1/2° W., 56.8 ft. dist., no marks visible on a partially opened blaze.</p> <p>and a new bearing tree</p> <p>A fir, 14 ins. diam., bears S. 84° W., 76.1 ft. dist., mkd. N1/16 S20 BT.</p> <hr/>
	<p>N. 0° 21' 55" W., beginning new measurement, posting and blazing.</p>
195	<p>Ridge, bears S. 60° E. and N. 70° W.</p>
1320.15	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground (alongside of which is an iron T-post, 1 in. sq., firmly set, projecting 5 ins. above ground with brass disk mkd. WILFORD N HAINES 239 DRAIN ORE), with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

F E E T	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T22S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R4W</td> </tr> <tr> <td style="padding: 0 5px;">S17</td> <td style="border-left: 1px solid black; padding: 0 5px;">S16</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S20</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 5px;">S21</td> </tr> </table> <p>1963</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 60° W., 55.4 ft. dist. to face, no marks visible.</p> <p>and the remains of bearing trees mkd. by Ben B. Irving, Deputy County Surveyor, in 1928, filed in the Douglas County Surveyor's Office, C.S. File No. 22/32, reported by Beck</p> <p style="padding-left: 40px;">A decayed fir stump, 39 ins. diam., bears S. 85° E., 8.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 30 3/4° W., 194.3 ft. dist., no marks visible. (Record, N. 29° W., 198.0 ft.)</p> <p>and the remains of a bearing tree mkd. by Lester B. Calder, Oregon Registered Engineer No. 2149, in 1962, filed in the Douglas County Surveyor's Office, C.S. File Nos. 51/87 and 53/105, reported by Beck</p> <p style="padding-left: 40px;">A sawed fir stump, 28 ins. diam., bears S. 22 1/2° W., 29.4 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by David H. Wellman, Oregon Professional Land Surveyor No. 2163, in 1997, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R.4 W., Point Identifier No. 300400</p> <p style="padding-left: 40px;">A sawed fir stump, 30 ins. diam., bears N. 88° W., 34.1 ft. dist., with scribe marks T22S R4W S20 visible on an open blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 11 ins. diam., bears N. 72 3/4° W., 17.5 ft. dist., with scribe marks T22S R S17 BT visible on an open blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 75 1/4° E., 19.6 ft. dist., mkd. T22S R4W S16 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 1 1/4° E., 21.9 ft. dist., mkd. T22S R4W S21 BT.</p>	T22S	R4W	S17	S16	S20	S21
T22S	R4W						
S17	S16						
S20	S21						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A maple, 4 ins. diam., bears N. 18° W., 26.0 ft. dist., mkd. X BT.</p> <hr/>
	<p>From the cor. of secs. 15, 16, 21, and 22, hereinbefore described.</p>
	<p>N. 89° 17' 28" W., bet. secs. 16 and 21, posting and blazing.</p>
120	<p>Graveled road, 14 ft. wide, bears N. 65° E. and S. 85° W.</p>
2708.58	<p>The 1/4 sec. cor. of secs. 16 and 21, perpetuated by Wilford N. Haines, Oregon Professional Land Surveyor No. 239, in 1975, filed in the Douglas County Surveyor's Office, Haines' Envelope No. 7, subsequently perpetuated by Donald L. Peel, Oregon Professional Land Surveyor No. 752, in 1990, filed in the Douglas County Surveyor's Office, File No. M109-58, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, (alongside of which is the disturbed Haines' T-post, 1 in. sq., firmly set, projecting 21 ins. above ground) with brass cap mkd.</p> <p style="text-align: center;">T22S R4W S16 1/4 ——— S21 PLS 752 1990</p>
	<p>from which the remains of the original bearing trees</p> <p>A decayed fir stump, size indeterminate, bears N. 15° E., 11.9 ft. dist., no marks visible.</p> <p>A sawed, decayed fir stump, 60 ins. diam., bears S. 10° W., 38.9 ft. dist., no marks visible.</p>
	<p>and new bearing trees</p> <p>A fir, 9 ins. diam., bears N. 56 1/2° E., 19.0 ft. dist., mkd. 1/4 S16 BT.</p> <p>A fir, 10 ins. diam., bears S. 10° E., 13.0 ft. dist., mkd. 1/4 S21 BT.</p> <hr/>
	<p>N. 89° 15' 13" W., beginning new measurement, posting and blazing.</p>
2699.68	<p>The cor. of secs. 16, 17, 20, and 21, hereinbefore described.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET																													
	<p>From the 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground (alongside of which is an iron pipe, 1/2 in. diam., firmly set, projecting 18 ins. above ground), with brass cap mkd.</p>																												
	<table style="border: none;"> <tr> <td></td> <td colspan="2">SURVEYORS</td> <td></td> </tr> <tr> <td></td> <td></td> <td>T22S</td> <td></td> </tr> <tr> <td></td> <td></td> <td>S9</td> <td>OFFICE</td> </tr> <tr> <td></td> <td>COUNTY</td> <td>1/4</td> <td></td> </tr> <tr> <td></td> <td></td> <td>S16</td> <td></td> </tr> <tr> <td></td> <td></td> <td>R4W</td> <td></td> </tr> <tr> <td></td> <td></td> <td>1966</td> <td></td> </tr> </table>		SURVEYORS					T22S				S9	OFFICE		COUNTY	1/4				S16				R4W				1966	
	SURVEYORS																												
		T22S																											
		S9	OFFICE																										
	COUNTY	1/4																											
		S16																											
		R4W																											
		1966																											
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 48 ins. diam., bears N. 32° W., 19.1 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Vernon Ray Tracy, Deputy County Surveyor, in 1966, reported by Skeesick and Browning</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 1° E., 120.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A root hole bears S. 12 3/4° E., 54.1 ft. dist., with sawed, burnt cedar stump, size indeterminate, lying alongside, no marks visible.</p> <p>and a bearing tree mkd. by Skeesick and Browning</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 0 3/4° W., 51.9 ft. dist., with a healed blaze.</p> <p>N. 89° 52' 08" W., bet. secs. 9 and 16, posting and blazing.</p>																												
2320	Lees Creek, 5 ft. wide, course S. 60° W.																												
2435	Dirt road, 9 ft. wide, bears N. 40° E. and S. 40° W.																												
2656.44	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>																												
	<table style="border: none;"> <tr> <td>T22S</td> <td>R4W</td> </tr> <tr> <td>S8</td> <td>S9</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> </table> <p>1963</p>	T22S	R4W	S8	S9			S17	S16																				
T22S	R4W																												
S8	S9																												
S17	S16																												
	<p>from which the remains of an original bearing tree</p>																												

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET

A cedar snag, 35 ins. diam., bears S. 20° W., 6.6 ft. dist., no marks visible on an opened, decayed blaze.

and the remains of bearing trees mkd. by Kenneth P. McReynolds, Oregon Professional Land Surveyor No. 277, in 1955 (record, incorrectly attributed to the Douglas County Surveyor by Beck), filed in the Douglas County Surveyor's Office, C.S. File No. 41/340

A maple, 34 ins. diam., bears N. 57 1/2° E., 72.6 ft. dist., with a healed blaze.

A maple, 44 ins. diam., bears S. 70° E., 71.3 ft. dist., with a healed blaze.

A cedar snag, 14 ins. diam., bears N. 58 1/4° W., 34.2 ft. dist., no marks visible on a partially healed blaze. (Record, N. 60° W., 31.0 ft.)

and the remains of a bearing tree mkd. by Beck

A decayed cedar stump, 35 ins. diam., bears S. 4° W., 102.3 ft. dist., no marks visible on an opened, decayed blaze.

and new bearing trees

A cedar, 5 ins. diam., bears S. 59 1/4° W., 28.4 ft. dist., mkd. X BT.

A cedar, 18 ins. diam., bears N. 47 3/4° W., 34.9 ft. dist., mkd. T22S R4W S8 BT.

---

From the N 1/16 sec. cor. of secs. 8 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

N 1/16  

S8	S9
T22S	R4W
1963	

from which the remains of bearing trees mkd. by Beck

A fir, 26 ins. diam., bears S. 58° E., 16.3 ft. dist., with a healed blaze.

A sawed fir stump, 21 ins. diam., bears N. 28 1/2° W., 16.9 ft. dist., with a healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>and a bearing tree mkd. by Skeesick and Browning</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 41 3/4° E., 18.5 ft. dist., with a healed blaze.</p> <p>No suitable tree available in sec. 8.</p> <p>N. 0° 20' 26" E., bet. secs. 8 and 9, posting and blazing.</p>						
1307.09	<p>The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 1/2 ins diam., loosely set and leaning, projecting 18 ins. above ground (alongside of which is an iron pipe, 25 ins. long, 3/4 in. diam.), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T22S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R4W</td> </tr> <tr> <td style="padding: 0 10px;">S5</td> <td style="border-left: 1px solid black; padding: 0 10px;">S4</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S8</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 10px;">S9</td> </tr> </table> <p>1963</p> </div> <p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 62 ins. diam., bears N. 38° E., 47.5 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed fir root crown bears S. 80° W., 33.0 ft. dist., with fallen fir trunk, 72 ins. diam., lying alongside, no marks visible.</p> <p style="padding-left: 40px;">A fir, 47 ins. diam., bears N. 46 1/2° W., 42.2 ft. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1958, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 300600, reported by Beck</p> <p style="padding-left: 40px;">A root hole, bears N. 34 3/4° E., 60.1 ft. dist., with fallen fir trunk, 32 ins. diam., lying alongside, no marks visible.</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 51 3/4° E., 21.4 ft. dist., with a healed blaze.</p> <p>At the cor. point</p> <p>Reset the iron post, 28 ins. long, 2 1/2 ins diam., 24 ins. in the ground, from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 10 3/4° E., 66.0 ft. dist., mkd. T22S R4W S4 BT.</p>	T22S	R4W	S5	S4	S8	S9
T22S	R4W						
S5	S4						
S8	S9						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p style="text-align: center;">A fir, 13 ins. diam., bears S. 36 3/4° W., 35.6 ft. dist., mkd. T22S R4W S8 BT.</p> <p>Deposit the iron pipe inside the iron post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 1/2 ins diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">SURVEYORS</td> <td></td> </tr> <tr> <td rowspan="4" style="text-align: center; vertical-align: middle;">COUNTY</td> <td style="text-align: center;">T22S</td> <td rowspan="4" style="text-align: center; vertical-align: middle;">OFFICE</td> </tr> <tr> <td style="text-align: center;">S4   S3</td> </tr> <tr> <td style="text-align: center;">S9   S10</td> </tr> <tr> <td style="text-align: center;">R4W 1962</td> </tr> </table> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears N. 47° E., 21.1 ft. dist., with fallen fir trunk, size indeterminate, lying alongside, no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 45 ins. diam., bears N. 6° W., 62.0 ft. dist., with a healed blaze.</p> <p>and remains of a bearing tree mkd. by Oscar F. Thiel, U.S. Deputy Surveyor, in 1901, reported by Jelley and Rogers</p> <p style="padding-left: 40px;">A cedar, 31 ins. diam., bears S. 72 1/2° E., 25.7 ft. dist., with a healed blaze.</p> <p>and remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962, filed in the Douglas County Surveyor's Office, C.S. File No. 49/42, reported by Jelley and Rogers</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 10° E., 40.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 61 1/4° E., 8.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 40° W., 6.3 ft. dist., with a healed blaze.</p> <p>and remains of a bearing tree mkd. by Glen McChesney, Weyerhaeuser Co. Land Agent, in 1962, filed in the Douglas County Surveyor's Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 400600, not reported by Jelley and Rogers</p>	SURVEYORS			COUNTY	T22S	OFFICE	S4   S3	S9   S10	R4W 1962
SURVEYORS										
COUNTY	T22S	OFFICE								
	S4   S3									
	S9   S10									
	R4W 1962									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	<p>A chinquapin snag, 13 ins. diam., bears N. 74 1/2° E., 29.2 ft. dist., with a healed blaze.</p>
	<p>and a bearing tree mkd. by Jelley and Rogers</p>
	<p>A fir, 18 ins. diam., bears S. 18 1/2° W., 69.3 ft. dist., with a healed blaze.</p>
	<p>N. 89° 38' 15" W., bet. secs. 4 and 9, posting and blazing.</p>
25	<p>Graveled road, 15 ft. wide, bears S. 25° E. and N. 25° W.</p>
1155	<p>Graveled road, 12 ft. wide, bears S. 45° E. and N. 45° W.</p>
1565	<p>Graveled road, 12 ft. wide, bears N. 65° E. and S. 65° W.</p>
1770	<p>Graveled road, 12 ft. wide, bears S. 65° E. and N. 65° W.</p>
2713.78	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">COUNTY SURVEYORS T22S S4 1/4 ——— S9 R4W OFFICE 1958</p>
	<p>from which the remains of an original bearing tree</p>
	<p>A root hole bears N. 14° E., 9.9 ft. dist., with fallen cedar trunk, size indeterminate, lying alongside, no marks visible on decayed face.</p>
	<p>and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1958, reported by Skeesick and Browning</p>
	<p>A fir, 24 ins. diam., bears S. 28 1/2° W., 24.9 ft. dist., with a healed double blaze.</p>
	<p>and bearing trees mkd. by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1994, reported by Skeesick and Browning</p>
	<p>A fir, 13 ins. diam., bears N. 12 1/4° E., 21.3 ft. dist., with a healed double blaze.</p>
	<p>A fir, 28 ins. diam., bears S. 87 3/4° E., 20.6 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 21 ins. diam., bears N. 62 1/2° W., 11.0 ft. dist., with a healed double blaze.</p> <hr/> <p>S. 89° 22' 27" W., beginning new measurement, posting and blazing.</p>
2540	Creek, 1 ft. wide, course N. 15° E.
2649.84	The cor. of secs. 4, 5, 8, and 9, hereinbefore described.
<hr/> <p><b>Dependent Resurvey of a Portion of the Subdivision of Section Lines of Section 20, T. 22 S., R. 4 W., Willamette Meridian, Oregon</b></p> <hr/> <p>(Restoring the 1963 survey by Donald R. Beck)</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 20 and 21, hereinbefore described.</p> <p>S. 89° 53' 07" W., on the E. and W. centerline of sec. 20, posting and blazing.</p>
280	Graveled road, 13 ft. wide, bears N. 18° E. and S. 18° W.
1318.05	The center E 1/16 sec. cor. of sec. 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.
	<p>E 1/16 C ————— C S20 1963</p>
	<p>from which bearing trees mkd. by Beck</p> <p>A fir, 28 ins. diam., bears N. 50 3/4° E., 60.7 ft. dist., with a healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 0 1/4° W., 24.4 ft. dist., with a healed blaze.</p> <p>Corner is located on top of a spur, slopes S. 40° W.</p> <hr/>
830	<p>N. 0° 10' 52" W., on the N. and S. centerline of the NE 1/4 of sec. 20, posting and blazing.</p> <p>Ridge, bears S. 10° E. and N. 5° W.</p>

**Dependent Resurvey of a Portion of the  
Subdivision of Section Lines of Section 20,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1316.80	<p>The NE 1/16 sec. cor. of sec. 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16</p> <p style="text-align: center;">S20 1963</p> <p>from which the remains of bearing trees mkd. by Beck</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 22 ins. diam., bears N. 47° E., 93.7 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 31 ins. diam., bears N. 82 1/2° W., 46.9 ft. dist., no marks visible.</p> <p>and bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 25 1/2° E., 30.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 88 1/4° W., 7.6 ft. dist., mkd. NE 1/16 S20 BT.</p> <hr/> <p>N. 89° 51' 47" E., on the E. and W. centerline of the NE 1/4 of sec. 20, posting and blazing.</p>
60	Spur, slopes N. 65° E.
1320.91	<p>The N 1/16 sec. cor. of secs. 20 and 21, hereinbefore described.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 21, T. 22 S., R. 4 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28, hereinbefore described.</p> <p>N. 0° 06' 42" W., on the N. and S. centerline of sec. 21, posting and blazing.</p>
30	Cox Creek, 4 ft. wide, course S. 75° W.
55	Cox Creek Road, paved surface, 20 ft. wide, bears S. 75° E. and N. 65° W.
1186	Creek, 3 ft. wide, course S. 60° W.

Subdivision of Section 21,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEEET 1311.63	<p>The center S 1/16 sec. cor. of sec. 21, established by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1998, filed in the Douglas County Surveyor's Office, File No. M137-51, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins above ground, with brass cap incorrectly mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S    R1W</p> <p>          C</p> <p>          1  </p> <p>          S      S21</p> <p>          1  </p> <p>          C</p> <p>          PLS 1978</p> <p>          1998</p> </div> <p>from which bearing trees mkd. by Baker</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears S. 1 1/4° W., 40.5 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A cedar, 43 ins. diam., bears N. 44 1/2° W., 14.1 ft. dist., with a fragmentary scribe marks visible on a partially healed blaze.</p> <p>Discontinue posting and blazing</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 10' 53" W., beginning new measurement.</p>
1310.65	<p>The center 1/4 sec. cor. of sec 21, established by Steven P. Ness, Oregon Professional Land Surveyor No. 811, in 1993, filed in the Douglas County Surveyor's Office, File No. M116-66, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T22S    R1W</p> <p>          C 1/4    S21</p> <p>          1993 RPLS811</p> </div> <p>from which bearing trees mkd. by Ness</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 0 1/4° E., 25.1 ft. dist., with a healed double blaze.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 45 1/4° E., 32.8 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 56" W., beginning new measurement.</p>

Subdivision of Section 21,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
1317.67	<p>The center N 1/16 sec. cor. of sec. 21, established by Steven P. Ness, Oregon Professional Land Surveyor No. 811, in 1993, filed in the Douglas County Surveyor's Office, File No. M116-66, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22S    R1W</p> <p>          C</p> <p>      1/16         S21</p> <p>          C</p> <p>1993 RPLS811</p> </div> <p>from which the remains of bearing trees mkd. by Ness</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 84° E., 28.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 12 ins. diam., bears S. 1 3/4° E., 15.8 ft. dist., with scribe marks CN1/16 S21 visible on upper and BT visible on lower open blazes.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 26 3/4° E., 9.1 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 08' 06" W., beginning new measurement.</p>
1317.93	<p>The 1/4 sec. cor. of secs. 16 and 21, hereinbefore described</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 21 and 22, hereinbefore described.</p> <p>N. 89° 17' 30" W., on the E. and W. centerline of sec. 21, posting and blazing.</p>
2718.74	<p>The center 1/4 sec. cor. of sec. 21, hereinbefore described.</p> <hr style="width: 40%; margin: 10px auto;"/> <p>N. 89° 17' 29" W., beginning new measurement, posting and blazing.</p>
2694.97	<p>The 1/4 sec. cor. of secs. 20 and 21, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 21 and 22, hereinbefore described.</p>

**Subdivision of Section 21,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	N. 89° 17' 54" W., on the E. and W. centerline of the NE 1/4 of sec. 21, posting and blazing.
2712.62	The center N 1/16 sec. cor. of sec. 21, hereinbefore described. <hr/>
	From the center S 1/16 sec. cor. of sec. 21, hereinbefore described.
	N. 89° 30' 16" W., on the E. and W. centerline of the SW 1/4 of sec. 21, posting and blazing.
2686.34	The S 1/16 sec. cor. of secs. 20 and 21, hereinbefore described. <hr/>
	From the center N 1/16 sec. cor. of sec. 21, hereinbefore described.
	N. 89° 17' 55" W., on the E. and W. centerline of the NW 1/4 of sec. 21, posting and blazing.
2694.51	The N 1/16 sec. cor. of secs. 20 and 21, hereinbefore described. <hr/>
	<b>Subdivision of Section 23, T. 22 S., R. 4 W., Willamette Meridian, Oregon</b>
	From the 1/4 sec. cor. of secs. 23 and 26, hereinbefore described.
	N. 1° 00' 42" E., on the N. and S. centerline of sec. 23.
1307.27	Point for the center S 1/16 sec. cor. of sec. 23, no permanent monument established.
2614.54	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. centerline.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.  T22S R4W C 1/4  S23  2007  from which  A fir, 14 ins. diam., bears N. 65° E., 12.7 ft. dist., mkd. C1/4 S23 BT.

Subdivision of Section 23,  
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	A fir, 15 ins. diam., bears S. 43 1/2° E., 21.4 ft. dist., mkd. C1/4 S23 BT.
5013.07	The 1/4 sec. cor. of secs. 14 and 23, hereinbefore described. <hr/>
	From the 1/4 sec. cor. of secs. 23 and 24, hereinbefore described.
	S. 86° 38' 19" W., on the E. and W. centerline of sec. 23.
2611.72	The center 1/4 sec. cor. of sec. 23, described on page 21820.
3963.04	Point for the center W 1/16 sec. cor. of sec. 23, no permanent monument established.
5314.36	The 1/4 sec. cor. of secs. 22 and 23, hereinbefore described. <hr/>
	From the W 1/16 sec. cor. of secs. 23 and 26, hereinbefore described.
	N. 0° 19' 46" E., on the calculated N. and S. centerline of the SW 1/4 of sec. 23, posting and blazing.
1297.14	Point for the SW 1/16 sec. cor. of sec. 23 at its calculated position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	SW 1/16    S23  2007
	from which
	A fir, 5 ins. diam., bears N. 79° E., 4.5 ft. dist., mkd. SW 1/16 S23 BT.
	A fir, 7 ins. diam., bears S. 15° E., 27.8 ft. dist., mkd. SW 1/16 S23 BT.
	<hr/>
	S. 87° 12' 08" W., on the calculated E. and W. centerline of the SW 1/4 of sec. 23, posting and blazing.
1334.42	The S 1/16 sec. cor. of secs. 22 and 23, hereinbefore described. <hr/>

## T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET

**GENERAL DESCRIPTION**

The lands included in the foregoing survey are located in mountainous terrain of Douglas County, approximately 8 miles easterly of the community of Drain, Oregon.

Elevation ranges from approximately 1900 feet above sea level near the corner of sections 14, 15, 22, and 23, to approximately 600 feet near the 1/4 section corner of sections 21 and 28.

The area is drained by Cox Creek, Curtis Creek, and Lees Creek, which flow westerly to Thief Creek.

Timber consists of fir, cedar, maple, and madrone. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

The soil is generally composed of rocky clay.

Access to the survey was made by graveled roads branching from Cox Creek Road and Lees Creek Road.

The mean magnetic declination for the area surveyed is 19° East, as shown on the "CURTIN, OREG." 7 1/2 minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1987.