

Dependent Resurvey of North Boundary of T. 31 S., R. 2 E.

Chains

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap mkd.

1/4 S 3

1937

from which

A white fir, 12 ins. diam., bears N.39°E., 29 lks. dist., mkd. $\frac{1}{4}$ S B.T. I obliterate the marks on this tree. (Old B.T.)

A white fir, 40 ins. diam., bears S.11°W., 15 lks. dist., mkd. $\frac{1}{4}$ S B.T. (Old B.T.)

A cedar, 22 ins. diam., bears S.28°E., 52 lks. dist., mkd. $\frac{1}{4}$ S 3 B.T. (New B.T.)

A white fir, 32 ins. diam., bears S.62°W., 96 lks. dist., mkd. $\frac{1}{4}$ S 3 B.T. (New B.T.)

Thence

N.88° 49' W., continuing measurements.

Asc. 160 ft. over E. slope, changing to NE. slope.

55.50 Spur, slopes SE.; asc. 5 ft. over rolling S. slope.

71.15 Draw, drains SE.; asc. 85 ft. over E. slope.

79.44 A point 40.00 chs. in departure from the $\frac{1}{4}$ sec. cor. of sec. 34 only, previously described.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 33 and 34 only, with brass cap mkd.

T30S R2E

S33|S34

T31S R2E

S 3

1937

from which

A white fir, 55 ins. diam., bears N.25°E., 52 lks. dist., mkd. T 30 S R 2 E S 34 B.T.

A white fir, 55 ins. diam., bears N.45°W., 30 lks. dist., mkd. T 30 S R 2 E S 33 B.T.

Asc. 25 ft. over E. slope.

80.68 The original cor. of secs. 3, 4, 33, and 34, which is a basalt stone, 14x10x8 ins., firmly set, with no legible marks.

I now change this cor. to refer to secs. 3 and 4 only.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone deposited at the base, for cor. of secs. 3 and 4 only, with brass cap mkd.