

Dependent Resurvey of North Boundary of T. 31 S., R. 2 E.

Chains

from which

A white fir snag, 30 ins. diam., bears S.50°E., 17 lks. dist., mkd. $\frac{1}{4}$ S. (Old B.T.)

A white fir, 27 ins. diam., bears S.30°E., 85 lks. dist., mkd. $\frac{1}{4}$ S 4 B T. (New B.T.)

A white fir, 28 ins. diam., bears S.1°W., 77 lks. dist., mkd. $\frac{1}{4}$ S 4 B T. (New B.T.)

Abbott Butte Lookout, bears N.43° 03' E.

Ridge, bears NW. and SE.

Thence

N.88° 58' W., continuing measurements.

Desc. 235 ft. over gradual SW. slope.

45.55 Road, bears N. and S.; telephone line parallels the road.

78.77. A point 40.00 chs. in departure from the $\frac{1}{4}$ sec. cor. of sec. 33 only, previously described.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 32 and 33 only, with brass cap mkd.

T30S R2E

S32|S33

T31S R2E

S 4

1937

from which

A white fir, 22 ins. diam., bears N.52°E., 57 lks. dist., mkd. T 30 S R 2 E S 33 B T.

A white fir, 40 ins. diam., bears N.33°W., 67 lks. dist., mkd. T 30 S R 2 E S 32 B T.

Desc. 20 ft. over SW. slope.

80.42 The original cor. of secs. 4, 5, 32, and 33, which is a sandstone, 16x12x10 ins., firmly set, mkd. with four notches on E. and two notches on W. edge.

I now change this cor. to refer to secs. 4 and 5 only.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone deposited at the base, for cor. of secs. 4 and 5 only, with brass cap mkd.

T30S R2E

S32

E 5|S 4

T31S R2E

1937

from which

A white fir, 50 ins. diam., bears N.30°E., 44 lks. dist., mkd. T 30 S R 2 E S 33 B T. I obliterate the marks on this tree. (Old B.T.)

A white fir, 35 ins. diam., bears S.23°E., 12 lks. dist., blaze healed. I do not open. (Old B.T.)