

21856 256

Dependent Resurvey of Part of the South Boundary of  
T. 29 S., R. 2 E.

"Reestablishment of the Surveys executed by Fred Mensch,  
Cadastral Engineer, in 1923."

Chains	Retracements
	From the cor. of secs. 3, 4, 33, and 34. West, bet. secs. 4 and 33.
40.00	Fall 2 lks. S. of $\frac{1}{4}$ sec. cor.
79.92	Fall 6 lks. S. of cor. of secs. 4, 5, 32, and 33.
	From the cor. of secs. 4, 5, 32, and 33. West, bet. secs. 5 and 32.
39.97	Intersect $\frac{1}{4}$ sec. cor.
79.86	Fall 2 lks. N. of cor. of secs. 5, 6, 31, and 32.
	From the cor. of secs. 5, 6, 31, and 32. West, bet. secs. 6 and 31.
39.92	Fall 3 lks. S. of $\frac{1}{4}$ sec. cor.
76.93	Fall 7 lks. S. of cor. of Tps. 29 and 30 S., Rs. 1 and 2 E.
	From the cor. of secs. 3, 4, 33, and 34, previously described.
	N.89° 58' W., on true line, along S. bdy. of sec. 33.
	Asc. 200 ft. over SE. slope, through heavy timber and dense undergrowth.
11.00	Spur, slopes S.15°E.; desc. 66 ft. over SW. slope.
15.30	Creek, 3 lks. wide, course S.15°E.; asc. 220 ft. over SE. slope.
30.00	Spur, slopes S.15°W.; desc. 133 ft. over SW. slope.
40.00	The original $\frac{1}{4}$ sec. cor. of secs. 4 and 33, which is an iron post, 1 in. diam., 10 ins. above ground, firmly set, with marks conforming to the record.
	I now change this cor. to refer to sec. 33 only and re- mark the brass cap as follows:
	<u><math>\frac{1}{4}</math> S 33</u>
	1923
	from which
	A fir, 13 ins. diam., bears N.7°E., 47 lks. dist., mkd. $\frac{1}{4}$ S 33 B T. (Old B.T.)
	A fir, 6 ins. diam., bears S.47°W., 63 lks. dist., mkd. $\frac{1}{4}$ S 4 B T. I obliterate the marks on this tree. (Old B.T.)
	A fir, 27 ins. diam., bears N.40°W., 79 lks. dist., mkd. $\frac{1}{4}$ S 33 B T. (New B.T.)
	Thence
	N.89° 57' W., continuing measurements.
	Desc. 180 ft. over SW. slope.
61.30	Draw, drains SW.; asc. 10 ft. over SE. slope.
64.00	Spur, slopes S.60°W.; desc. 90 ft. over SW. slope.
79.92	The original cor. of secs. 4, 5, 32, and 33, which is an iron post, 2 ins. diam., 9 ins. above ground, firmly set, with marks conforming to the record.
	I now change this cor. to refer to secs. 32 and 33 only and re-mark the brass cap as follows: