


21880

Subdivisions of T. 30 S., R. 2 E.

Chains	
	A fir, 12 ins. diam., bears S.32°E., 12 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.
	Along S. slope.
40.05	Draw, drains S.; asc. 161 ft. over SE. slope.
45.45	Spur, slopes S.20°W.; desc. 145 ft. over SW. slope.
54.00	Draw, drains S.; asc. 15 ft. over SE. slope.
55.65	Spur, slopes S.20°W.; desc. 39 ft. over SW. slope.
57.52	Creek, 3 lks. wide, course S.; asc. 268 ft. over SE. slope.
68.52	Spur, slope S.; desc. 31 ft. over SW. slope.
70.30	Spring branch, 1 lk. wide, course S.; asc. 20 ft. over SE. slope.
72.60	Spur, slopes S.10°E.; desc. 80 ft. over SW. slope.
74.60	Draw, drains SE.; asc. 60 ft. over SE. slope.
76.97	Spring branch, 1 lk. wide, course S.30°E.; asc. 159 ft. over NE. slope.
80.00	The cor. of secs. 26, 27, 34, and 35. Land, mountainous. Soil, clay loam and rocky; 3rd and 4th rate. Timber, fir, hemlock, pine, and cedar. Undergrowth, yinemaple, 2nd growth, manzanita, spirea, alder, and mountain ash.
	N.0° 11' E., bet. secs. 26 and 27. Desc. 80 ft. over NE. slope, through heavy timber and dense undergrowth.
3.30	Spring branch, 1 lk. wide, course S.70°E.; asc. 810 ft. over SE. slope.
33.85	Divide between South Umpqua River and Rogue River, bears N.20°E. and S.20°W.; telephone line, bears N.20°E. and S.20°W.; asc. 100 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;">  </div> from which A fir, 12 ins. diam., bears S.85°E., 67 lks. dist., mkd. $\frac{1}{4}$ S 26 B T. A fir, 16 ins. diam., bears N.65°W., 51 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.
	Top of ascent on W. slope; desc. 73 ft. over NW. slope.
41.40	Road, bears N.30°E. and S.30°W.
50.10	Spring branch, 1 lk. wide, course W.; asc. 74 ft. over rolling SW. slope.