

Subdivisions of T. 30 S., R. 2 E.

Chains	
67.40	Spur, slopes W.; desc. 95 ft. over NW. slope.
71.70	Spring branch, 1 lk. wide, course W.; enter scattering timber and light undergrowth, bears E. and W.; asc. 83 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.
	T30S R2E S22 S23 S27 S26
	1937
	from which
	A cedar, 10 ins. diam., bears N.10°E., 36 lks. dist., mkd. T 30 S R 2 E S 23 B T.
	A cedar, 20 ins. diam., bears S.39°E., 90 lks. dist., mkd. T 30 S R 2 E S 26 B T.
	A cedar, 17 ins. diam., bears S.18°W., 62 lks. dist., mkd. T 30 S R 2 E S 27 B T.
	A cedar, 12 ins. diam., bears N.66°W., 88 lks. dist., mkd. T 30 S R 2 E S 22 B T.
	Land, mountainous. Soil, clay loam and rocky; 3rd and 4th rate. Timber, fir, cedar, hemlock, pine, and maple. Undergrowth, vinemaple, 2nd growth, slickleaf, manzanita, spirea, and salal.
	East, on a random line bet. secs. 23 and 26.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect N. and S. line at the cor. of secs. 23, 24, 25, and 26.
	Thence
	West, on true line bet. secs. 23 and 26.
	Asc. 205 ft. over E. slope, through scattering timber and light undergrowth.
2.60	Top of bluff, 60 ft. high, bears N. and S.
5.50	Spur, slopes SE.; asc. 300 ft. over SE. slope.
5.78	Road, bears N.20°E. and S.20°W.
34.60	Spur, slopes S.; desc. 30 ft. over SW. slope.
39.80	Dry wash, 2 lks. wide, course S.; along S. slope.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 23}{S 26}$
	1937
	from which
	A cedar, 12 ins. diam., bears N.83°E., 122 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.