

Subdivisions of T. 30 S., R. 2 E.

- Chains
 3.00 Spur, slopes NE.; desc. 30 ft. over NE. slope.
 7.61 Creek, 1 lk. wide, course E.; asc. 70 ft. over SE. slope.
 21.00 Spring branch, 1 lk. wide, course S.60°E.; asc. 115 ft. over SE. slope.
 29.13 Head of draw, drains S.30°E.; asc. 125 ft. over SE. slope.
 36.52 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

↑
 S33 | S34
 1937

from which

A white pine, 23 ins. diam., bears N.37°E., 87 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

A white pine, 28 ins. diam., bears N.52°W., 45 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.

Asc. 205 ft. over SE. slope.

- 47.50 Divide bet. South Umpqua River and Rogue River, bears NE. and SW.; desc. 290 ft. over NW. slope.
 70.35 Road, bears N.30°E. and SW.; telephone line parallels the road.
 74.00 Creek, 1 lk. wide, course N.30°E.; desc. 5 ft. along E. slope.
 76.52 Intersect sectional correction line, 10 lks. E. of temp. cor. of secs. 27, 28, 33, and 34.
 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 27, 28, 33, and 34, with brass cap mkd.

T30S R2E
 S28 | S27
 S33 | S34

1937

from which

A white fir, 25 ins. diam., bears N.52°E., 16 lks. dist., mkd. T 30 S R 2 E S 27 B T.

A white fir, 50 ins. diam., bears S.65°E., 157 lks. dist., mkd. T 30 S R 2 E S 34 B T.

A fir, 13 ins. diam., bears S.23°W., 31 lks. dist., mkd. T 30 S R 2 E S 33 B T.

A fir, 38 ins. diam., bears N.23°W., 89 lks. dist., mkd. T 30 S R 2 E S 28 B T.

Land, mountainous.

Soil, sandy clay and rocky; 3rd and 4th rate.

Timber, fir, pine, hemlock, alder, and yew.

Undergrowth, vinemaple, serviceberry, 2nd growth, and salal.