

Subdivisions of T. 30 S., R. 2 E.

Chains	
	From the cor. of secs. 26, 27, 34, and 35.
	West, on sectional correction line, bet. secs. 27 and 34.
	Asc. 5 ft. over NE. slope, through heavy timber and dense undergrowth.
0.50	Spur, slopes SE.; asc. 217 ft. over SE. slope.
9.75	Spur, slopes S.20°E.; desc. 12 ft. over SW. slope.
11.74	Draw, drains SE.; asc. 715 ft. over SE. slope.
26.40	Top of bluff, 75 ft. high, bears N.20°E. and S.20°W.
28.40	Top of bluff, 60 ft. high, bears NE. and SW.
29.35	Divide bet. South Umpqua River and Rogue River, bears NE. and SW.; desc. 78 ft. over NW. slope.
33.70	Draw, drains N.; asc. 90 ft. over NE. slope.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 27 \\ S 34 \end{array}$
	1937
	from which
	A cedar, 13 ins. diam., bears N.26 $\frac{1}{2}$ °W., 26 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.
	A fir, 35 ins. diam., bears S.76 $\frac{1}{2}$ °W., 26 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.
	Asc. 175 ft. over NE. slope.
42.50	Top of bluff, 60 ft. high, bears NW. and SE.
44.15	Spur, slopes N.; desc. 435 ft. over NW. slope.
77.70	Road, bears N.30°E. and S.30°W.; telephone line parallels the road.
78.20	Creek, 1 lk. wide, course N.; asc. 7 ft. over NE. slope.
79.96	The cor. of secs. 27, 28, 33, and 34.
	Land, mountainous.
	Soil, sandy clay and rocky; 3rd and 4th rate.
	Timber, fir, hemlock, pine, cedar, and yew.
	Undergrowth, vinemaple, slickleaf, 2nd growth, and salal.
	N.0° 11' E., bet. secs. 27 and 28.
	Desc. 30 ft. over NE. slope, through heavy timber and light undergrowth.
4.20	Creek, 1 lk. wide, course NW.; along W. slope.
10.00	Spur, slopes N.60°W.; desc. 415 ft. over NE. slope.
33.25	Spring branch, 1 lk. wide, course N.35°E.; desc. 40 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.