

Subdivisions of T. 30 S., R. 2 E.

Chains

- 68.73 Spring branch, 1 lk. wide, course N.20°W.; desc. 105 ft. over N. slope.
- 73.67 Intersect sectional correction line, 10 lks. E. of temp. cor. of secs. 29, 30, 31, and 32.
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 29, 30, 31, and 32, with brass cap mkd.
- T30S R2E
S30|S29
S31|S32
- 1937
- from which
- A fir, 37 ins. diam., bears N.35°E., 57 lks. dist., mkd. T 30 S R 2 E S 29 B T.
- A fir, 45 ins. diam., bears S.35°E., 70 lks. dist., mkd. T 30 S R 2 E S 32 B T.
- A fir, 50 ins. diam., bears S.40°W., 56 lks. dist., mkd. T 30 S R 2 E S 31 B T.
- A fir, 25 ins. diam., bears N.37½°W., 47 lks. dist., mkd. T 30 S R 2 E S 30 B T.

Land, mountainous.

Soil, sandy loam and rocky; 2nd and 4th rate.

Timber, fir, hemlock, cedar, and pine.

Undergrowth, vine maple, 2nd growth, rhododendron, and salal.

From the cor. of secs. 28, 29, 32, and 33.

West, on sectional correction line bet. secs. 29 and 32.

Asc. 4 ft. over NE. slope, through heavy timber and light undergrowth.

- 2.00 Spur, slopes N, 10°W.; desc. 295 ft. over NW. slope.
- 14.00 Enter opening, bears N. and S.
- 18.00 Leave opening; enter heavy timber and dense undergrowth, bears N. and S.
- 21.00 Creek, 4 lks. wide, course N.20°W.; asc. 170 ft. over NE. slope.
- 34.15 Spur, slopes N.; desc. 67 ft. over NW. slope.
- 39.98 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.
- S 29
¼ S 32
- 1937
- from which
- A white fir, 10 ins. diam., bears N.4°W., 62 lks. dist., mkd. ¼ S 29 B T.
- A white fir, 15 ins. diam., bears S.70°E., 21 lks. dist., mkd. ¼ S 32 B T.
- Desc. 165 ft. over W. slope.