

21912 312

Subdivisions of T. 30 S., R. 2 E.

Chains	
	East, on a random line bet. secs. 20 and 29.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.84	Intersect N. and S. line, 5 lks. S. of cor. of secs. 20, 21, 28, and 29.
	Thence
	S.89° 58' W., on true line bet. secs. 20 and 29.
	Desc. 15 ft. over NW. slope, through heavy timber and dense undergrowth.
0.75	Creek, 3 lks. wide, course N.20°W.; asc. 65 ft. over NE. slope.
5.75	Spur, slopes N.; desc. 60 ft. over NW. slope.
9.03	Spring branch, 1 lk. wide, course NE.; asc. 160 ft. over NE. slope.
18.10	Top of ascent on N. slope; desc. 12 ft. along N. slope.
23.85	Spur, slopes NW.; desc. 330 ft. over NW. slope.
32.50	Draw, drains N.70°W.; desc. 33 ft. over NW. slope.
35.65	Spur, slopes NW.; desc. 95 ft. over NW. slope.
39.92	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S. 20}{S. 29}$
	1937
	from which
	A yew, 10 ins. diam., bears N.57°W., 47 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.
	A fir, 35 ins. diam., bears S.8°W., 14 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.
	Draw, drains NW.; asc. 33 ft. over NE. slope.
44.20	Spur, slopes N.20°W.; desc. 350 ft. over NW. slope.
58.25	Creek, 5 lks. wide, course N.10°W.; asc. 160 ft. over NE. slope.
59.45	Top of bluff, 50 ft. high, bears N. and S.
61.75	Spur, slopes N.; desc. 335 ft. over NW. slope.
67.65	Squaw Creek, 15 lks. wide, course S.75°W.; asc. 160 ft. over SE. slope.
69.00	Enter scattering timber and light undergrowth, bears NE. and SW.
79.84	The cor. of secs. 19, 20, 29, and 30.
	Land, mountainous. Soil, sandy loam and rocky; 3rd and 4th rate. Timber, fir, hemlock, cedar, yew, and pine. Undergrowth, rhododendron, manzanita, vinemaple, salal, 2nd growth, and chinquapin.