

TOWNSHIP 29 SOUTH, RANGE 9 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

RETRACEMENT AND REHABILITATION

OFFICIALLY FILED: 1/12/2010

THERE ARE NO LINE NOTES TO GO WITH THIS RETRACEMENT - ALL OF THE AVAILABLE INFORMATION IS ON THIS PLAT

FILED
DATE: 3/17/07
BY: [Signature]
This survey complies with the requirements of the Oregon Surveying Act, ORS 315.001 to 315.010.
Map: JAMES IN BOOK A COPY IN: [Blank]
Reference: VOL. 58, PAGE 2395
COUNTY: CLATSOP
SURVEYOR: [Signature]

This plat represents the entire survey record of the retracement of a portion of the subdivisional lines, and the rehabilitation of the 1/4 section corner of sections 34 and 35, T. 29 S., R. 9 W., Willamette Meridian, Oregon.

The history of the surveys pertaining to this retracement is as follows:

In 1855, Dennis Helhorn, U.S. Deputy Surveyor, surveyed the east and south boundaries, portions of the north boundary and subdivisional lines.

In 1855-56, Jason A. Burnett, U.S. Deputy Surveyor, surveyed the Donation Land Claims.

In 1966, John M. Kelley, Cadastral Surveyor, deviously surveyed a portion of the retraced boundaries and subdivisional lines, and re-monumented certain original corner points.

In 1989-90, Wayne L. Rogers, Cadastral Surveyor, and Garry L. Moore, Surveying Technician, deviously resurveyed a portion of the subdivisional lines and subdivided section 35.

The direction of the lines were determined by direct solar observations, carried forward by sustained angulation, and refers to the true meridian.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis. Conventionally measured distances and directions have been adjusted by computer adjusting techniques. The adjusted bearings, distances are reported to the nearest second and 0.01 foot.

The retracement and rehabilitation was executed by A. Bert Skeesick, Cadastral Surveyor, beginning October 9, 2007, and completed October 11, 2007, pursuant to Special Instructions dated March 16, 2007, approved March 21, 2007, and Assignment Instructions dated September 11, 2007 under Group Number 2300, Oregon.

The geodetic position shown hereon was determined by NAVSTAR GPS, utilizing dual frequency, carrier phase GPS receivers, relative to the National Spatial Reference System.

LEGEND
◊ Original corner previously re-monumented
◆ Original corner re-monumented this survey

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT


Portland, Oregon

The retracement and rehabilitation represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

May J. M. Hurd
Chief Cadastral Surveyor of Oregon

October 23, 2009
Date



(B) The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as reported in 1966, from which the remaining original bearing trees

A cedar, 24 ins. diam., bears S. 50° E., 22.8 ft. dist., with a heeled blaze.

A fir, 33 ins. diam., bears S. 51° W., 4.6 ft. dist., with no marks visible on an opened blaze.

and the bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959, recorded in the Douglas County Surveyors' Record of Government Corners Renewed, T. 29 S., R. 9 W., Point Identifier No. 500100

A fir, 26 ins. diam., bears N. 9° E., 25.1 ft. dist., with heeled double blaze

A cedar, 22 ins. diam., bears N. 40° W., 29.0 ft. dist., with heeled double blaze.

Sec. 34 Sec. 35 7.29 S.
Sec. 3 Sec. 2 7.30 S.



(A) The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as reported in 1989-90, from which the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957, recorded in the Douglas County Surveyors' Record of Government Corners Renewed, T. 29 S., R. 9 W., Point Identifier No. 500100, reported by Rogers and Moore

A fir, 28 ins. diam., bears N. 54 1/2° E., 274.6 ft. dist., with a heeled double blaze.

A sawed and burnt cedar stump, 24 ins. diam., bears N. 68° W., 59.4 ft. dist., with scribe marks 1/4 S34 CS BT visible on an open blaze.

and the remains of bearing trees mkd. by Rogers, and Moore

A fir, 11 ins. diam., bears N. 30 1/4° E., 9.2 ft. dist., with a heeled blaze.

A sawed fir stump, 14 ins. diam., bears N. 57 1/4° W., 3.2 ft. dist., with a heeled blaze.

and a new bearing tree
A fir, 6 ins. diam., bears S. 61 1/2° W., 103.9 ft. dist., mkd. 1/4 S34 BT.

I, A. Bert Skeesick, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 16th of March, 2007, I have retraced a portion of the subdivisional lines, and rehabilitated the 1/4 section corner of sections 34 and 35, Township 29 South, Range 9 West, Willamette Meridian, Oregon, which is represented upon this plat as having been acquired by me and under my direction. Said retracement and rehabilitation were made in accordance with the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described on this plat.

October 6, 2009
Date

Cadastral Surveyor