

FILED
DATE: 2/1/2010 BY: JC
THIS SURVEY CONSISTS OF:
MAP, MAP IN BOOK A COPY IN:
COMMISSIONER'S OFFICE
COMMERCIAL VOL. 56 PAGES 2192-7
DOUGLAS COUNTY
SURVEYOR

TOWNSHIP 31 SOUTH, RANGE 4 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

RETRACEMENT AND REMONUMENTATION

ORIGINAL

SHEET 2 OF 2

(A) The 1/4 sec. cor. of secs. 23 and 24, perpetuated by John H. Markham, Jr., Oregon Professional Logging Engineer No. 2880, in 1958, filed in the Douglas County Surveyors Office, C.S. File No. 42/391, further perpetuated by the Douglas County Surveyors Office in 1965 and 1998, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 31 S., R. 4 W., Point Identifier No. 600400, monumented with an iron post, 1 1/2 ins. diam., firmly set, with brass cap mkd. from which the remains of bearing trees mkd. by Markham

A sowed fir stump, 49 ins. diam., bears N. 55° E., 22.4 ft. dist., with scribe mark S visible on opened blaze.

At the corner point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

A root hole bears S. 69° E., 36.3 ft. dist., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

A root hole bears S. 29° W., 6.6 ft. dist., with a fallen fir trunk, 28 ins. diam., lying alongside, with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1965

A fir, 12 ins. diam., bears N. 9° E., 7.7 ft. dist., mkd. 1/4 S24 BT.

A fir, 18 ins. diam., bears S. 50 3/4° W., 19.0 ft. dist., with a healed double blaze.

Deposit a magnet in a white plastic case of the base of the stainless steel post, and bury the iron pipe alongside the stainless steel post.

Corner is located in large rock side area, on a steep SW slope.

(B) The 1/4 sec. cor. of secs. 13, 14, 23 and 24, perpetuated by John H. Markham, Jr., Oregon Professional Logging Engineer No. 2880, in 1958, filed in the Douglas County Surveyors Office, C.S. File No. 42/391, further perpetuated by the Douglas County Surveyors Office in 1965 and 1998, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 31 S., R. 4 W., Point Identifier No. 600400, monumented with an iron post, 1 1/2 ins. diam., firmly set, with brass cap mkd. from which the remains of original bearing trees

A root hole bears S. 69° E., 36.3 ft. dist., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

A root hole bears S. 29° W., 6.6 ft. dist., with a fallen fir trunk, 28 ins. diam., lying alongside, with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1965

A fir, 18 ins. diam., bears N. 33 1/2° E., 20.3 ft. dist., with a healed double blaze.

A sowed fir stump, 35 ins. diam., bears N. 89 3/4° E., 92.3 ft. dist., with a healed double blaze.

A fir, 15 ins. diam., bears S. 7° W., 39.6 ft. dist., with a healed double blaze.

A root hole bears N. 2 1/2° W., 105.1 ft. dist., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

(C) The 1/4 sec. cor. of secs. 13 and 24, perpetuated by John H. Markham, Jr., Oregon Professional Logging Engineer No. 2880, in 1958, filed in the Douglas County Surveyors Office, C.S. File No. 42/391, determined at record bearing and distance from the remains of an original bearing tree

A sowed fir stump, 24 ins. diam., bears N. 17 1/4° E., 10.6 ft. dist., with fragmentary scribe marks visible on the bark.

At the corner point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

from which the remains of original bearing trees

A root hole bears S. 69° E., 36.3 ft. dist., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

A root hole bears S. 29° W., 6.6 ft. dist., with a fallen fir trunk, 28 ins. diam., lying alongside, with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1965

A fir, 18 ins. diam., bears N. 33 1/2° E., 20.3 ft. dist., with a healed double blaze.

A sowed fir stump, 35 ins. diam., bears N. 89 3/4° E., 92.3 ft. dist., with a healed double blaze.

A fir, 15 ins. diam., bears S. 7° W., 39.6 ft. dist., with a healed double blaze.

A root hole bears N. 2 1/2° W., 105.1 ft. dist., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

and bearing trees mkd. by the Douglas County Surveyors Office in 1998

A fir, 8 ins. diam., bears S. 46 1/4° E., 7.8 ft. dist., with a healed double blaze.

A fir, 6 ins. diam., bears N. 65° W., 1.4 ft. dist., with a healed double blaze.

(D) The 1/4 sec. cor. of secs. 16 and 21, perpetuated by John H. Markham, Jr., Oregon Professional Logging Engineer No. 2880, in 1958, filed in the Douglas County Surveyors Office, C.S. File No. 42/391, further perpetuated by the Douglas County Surveyors Office in 1966, and further perpetuated by Mark F. Smalley, Oregon Professional Land Surveyor No. 54633, in 2008, filed in the Douglas County Surveyors Office, Map File No. M96-22, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

A sowed fir stump, 23 ins. diam., bears S. 29 1/4° W., 29.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

and the remains of a bearing tree mkd. by Markham

A fir snag, 26 ins. diam., bears N. 69° W., 64.5 ft. dist., with a healed blaze.

and bearing trees mkd. by Smalley

A fir, 12 ins. diam., bears N. 70° E., 21.6 ft. dist., with a healed blaze.

A fir, 13 ins. diam., bears S. 29 1/4° E., 13.0 ft. dist., with a healed blaze.

A fir, 17 ins. diam., bears S. 70 1/4° W., 20.6 ft. dist., with a healed blaze.

A fir, 19 ins. diam., bears N. 28° W., 17.1 ft. dist., with a healed blaze.

A fir, 40 ins. diam., bears S. 4 3/4° E., 30.0 ft. dist., with scribe marks 1/4 S23 X B' visible on the bark.

A fir snag, 32 ins. diam., bears S. 3/4° E., 61.1 ft. dist., with a healed blaze.

At the corner point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Deposit a magnet in a white plastic case of the base of the stainless steel post, and bury the iron pipe, 40 ins. long, 3/4 in. diam., alongside the stainless steel post.

(E) The 1/4 sec. cor. of secs. 16 and 21, perpetuated by John H. Markham, Jr., Oregon Professional Logging Engineer No. 2880, in 1958, filed in the Douglas County Surveyors Office, C.S. File No. 42/391, further perpetuated by the Douglas County Surveyors Office in 1966, and further perpetuated by Mark F. Smalley, Oregon Professional Land Surveyor No. 54633, in 2008, filed in the Douglas County Surveyors Office, Map File No. M96-22, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

from which the remains of an original bearing tree

A sowed fir stump, 23 ins. diam., bears S. 29 1/4° W., 29.0 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

and the remains of a bearing tree mkd. by Markham

A fir snag, 26 ins. diam., bears N. 69° W., 64.5 ft. dist., with a healed blaze.

and bearing trees mkd. by Smalley

A fir, 12 ins. diam., bears N. 70° E., 21.6 ft. dist., with a healed blaze.

A fir, 13 ins. diam., bears S. 29 1/4° E., 13.0 ft. dist., with a healed blaze.

A fir, 17 ins. diam., bears S. 70 1/4° W., 20.6 ft. dist., with a healed blaze.

A fir, 19 ins. diam., bears N. 28° W., 17.1 ft. dist., with a healed blaze.

A fir, 40 ins. diam., bears S. 4 3/4° E., 30.0 ft. dist., with scribe marks 1/4 S23 X B' visible on the bark.

A fir snag, 32 ins. diam., bears S. 3/4° E., 61.1 ft. dist., with a healed blaze.

At the corner point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Deposit a magnet in a white plastic case of the base of the stainless steel post, and bury the iron pipe, 40 ins. long, 3/4 in. diam., alongside the stainless steel post.

(F) The cor. of secs. 16, 17, 20 and 21, perpetuated by the Douglas County Surveyors Office in 1966, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 31 S., R. 4 W., Point Identifier No. 300400, further perpetuated by Ronald L. Rice, Oregon Professional Land Surveyor No. 54633, in 2008, filed in the Douglas County Surveyors Office, Map File No. M96-22, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

from which the remaining original bearing tree

A fir, 37 ins. diam., bears S. 71 1/2° E., 15.5 ft. dist., with a healed blaze.

and bearing trees mkd. by the Douglas County Surveyors Office

A hemlock, 23 ins. diam., bears a healed blaze.

A fir, 20 ins. diam., bears N. 68° W., 20.5 ft. dist., with a healed blaze.

and a bearing tree mkd. by Rice

A hemlock, 8 ins. diam., bears N. 57° E., 32.1 ft. dist., with scribe marks T31S R4W S16 BT visible on an open blaze.

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Portland, Oregon

This plat is strictly conformable to the approved field notes, and the survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director
Mary J. M. Hartzel
Chief Cadastral Surveyor of Oregon

October 29, 2009
Date

THERE ARE NO LINE NOTES TO GO WITH THIS RETRACEMENT - ALL OF THE AVAILABLE INFORMATION IS ON THIS PLAT