

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

TOWNSHIP 21 SOUTH, RANGE 8 WEST,

THE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,

SUBDIVISIONAL LINES,

CERTAIN LINES OF DONATION LAND CLAIM NOS. 48 AND 49,

A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 5,

AND THE SUBDIVISION OF SECTION 11,

TOWNSHIP 22 SOUTH, RANGE 8 WEST,

AND THE DEPENDENT RESURVEY OF CERTAIN LINES OF DONATION LAND CLAIM NO. 45,

TOWNSHIP 22 SOUTH, RANGE 9 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Aaron M. Graham, Cadastral Surveyor

Michael O. Jones, Surveying Technician

Under Special Instructions dated April 2, 2007, approved April 4, 2008,

which provided for the surveys included under Group No. 2199,

and Assignment Instructions dated April 4, 2008.

Survey commenced April 4, 2008

Survey completed April 15, 2009

T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary, Township 21 South, Range 8 West, the dependent resurvey of a portion of the west boundary, subdivisional lines, certain lines of Donation Land Claim Nos. 48 and 49, a portion of the subdivision-of-section lines of section 5, and the subdivision of section 11, Township 22 South, Range 8 West, and the dependent resurvey of certain lines of Donation Land Claim No. 45, Township 22 South, Range 9 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

T. 22 S., R. 8 W.

In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the north and west boundaries and subdivisional lines and the meander lines of the Umpqua River.

In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the boundaries of Donation Land Claim Nos. 48, and 49. In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed the north boundary and a portion of the east boundary and subdivisional lines.

In 1881, William H. Byars, U.S. Deputy Surveyor, completed the surveys of the township exteriors and subdivisional lines.

In 1931, George F. Rigby, U.S. Cadastral Engineer, dependently resurveyed a portion of the west boundary and subdivisional lines, subdivided section 18, and surveyed the patented portion of Lot 7 in section 18.

In 1945, Norman D. Price, U.S. Cadastral Engineer, and George F. Rigby, Associate Cadastral Engineer, dependently resurveyed a portion of the south boundary, of Township 21 South, Range 8 West.

In 1952-54, Marvin J. Lytle, et al., Cadastral Engineer, dependently resurveyed a portion of the south boundary, of Township 21 South, Range 8 West.

In 1963-65, Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, resurveyed a portion of the north, east, and south boundaries, a portion of the subdivisional lines, and a portion of certain claim lines, subdivided section 5, and remonumented certain original corners.

In 1965-67, Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, resurveyed a portion of the subdivisional lines.

T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET

In 1993, John A. Farmer, Cadastral Surveyor, correctively resurveyed a portion of the subdivisional lines.

In 1999, Aaron M. Graham, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines and subdivided section 3.

In 2007, Edith M. Forkner, Cadastral Surveyor, dependently resurveyed a portion of the south boundary of Township 21 South, Range 8 West.

T. 22 S., R. 9 W.

In 1855-56, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the east boundary and subdivisional lines, and the meanders of the right bank of the Umpqua River.

In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the boundaries of Donation Land Claim No. 45.

In 1874, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1894-95, Alonzo Gesner and Elmer O. Worrick, U.S. Deputy Surveyors, surveyed a portion of the east boundary and subdivisional lines.

In 1993-95, Boyd W. Peterson, Cadastral Surveyor and Richard L. Sanford, Surveying Technician, resurveyed a portion of the east boundary and subdivisional lines, adjusted the record meanders of the left bank of the Umpqua River, and subdivided section 13.

The following plats and field notes filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name and year. This is not a complete list; some information is listed in the corner descriptions.

Date	Name and Registration Number	File Number
1914	F.J. Cole	Old Vol. 2 Pg.192
1958	James Byron D.C.S.	C.S. 49/77
1962-63	Milo E. Godfrey C.S.	C.S. File 52/14
1950	Wilford N. Haines PLS 239	Field Book H-103
1976	Larry E. Monrean C.S.	C.S. File 59/26
1989	Larry E. Monrean C.S.	C.S. File 64/1
1991	Harvey Wilcox PLS 2244	M113-60
1994	John Minor PLS 2052	M118-72
1996	Victor McLind PLS 934	M126-23
1997	L.D. Roberts PLS 1039	M124-44
1999	Randall W. Smith C.S.	C.S. File 66/12-41

T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET			
	Date	Name and Registration Number	File Number
	2000	David Edwards PLS 2339	M134-20
	2006	Mark Heimburger PLS 2287	M151-77
	<p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated April 2, 2007, for Group No. 2199, Oregon.</p>		
	<p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein.</p>		
	<p>The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) measurements and by direct solar observations and were carried forward by means of sustained angulation. All measurements on the lines were derived through the use of electronic measuring equipment.</p>		
	<p>The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.</p>		
	<p>Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p>		
	<p>Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.</p>		
	<p>The geographic position (NAD 1983 (2007)) of the corner of sections 1, 2, 11, and 12, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:</p>		
	<p>Latitude: 43° 40' 44.56" N. Longitude: 123° 36' 18.64" W.</p>		
	<p>The geographic position (NAD 1983 (2007)) of the corner of sections 7, 12, 13, and 18 on the West boundary of the Township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS</p>		

T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET

receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43° 39' 53.95" N. Longitude: 123° 42' 19.43" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

(Restoring the survey by William H. Byars, in 1881, the resurvey by Norman D. Price and George F. Rigby, in 1945 and by Floyd A. Brooks and James E. Jelley in 1963-65)

Beginning at the closing cor. of secs. 4 and 5 only, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.

```

T 21 S R 8 W
  S 32
-----
  S 5 | S 4
T 22 S R 8 W
  CC
  1963

```

from which the bearing trees mkd. by Brooks and Jelley in 1963-65

A fir, 37 ins. diam., bears S. 23 1/2° E., 109.2 ft. dist., with a healed blaze. (Record, S. 21 3/4° E., 114.2 ft. dist.)

A fir, 16 ins. diam., bears S. 49° W., 55.6 ft. dist., with a healed blaze. (Record, S. 47 1/2° W., 58.7 ft. dist.)

From this corner, the original closing corner of secs. 4 and 5, bears N. 0° 28' E., 9.2 ft. dist., monumented with the remains of the original cor. tree, a decayed fir stump, size indeterminate, from which the remains of an original bearing tree

A decayed stump, size indeterminate, bears S. 18 1/2° E., 52.1 ft. dist., no marks visible.

and a bearing tree mkd. by Price and Rigby in 1945

A fir, 42 ins. diam., bears S. 50° W., 35.0 ft. dist., no marks visible.

S. 89° 18' 50" W., bet. secs. 5 and 32.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
1685.61	<p>The 1/4 sec. cor. of sec. 32 only, perpetuated by Price and Rigby in 1945; monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">1/4 S 32 ————— 1945</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 50 ins. diam., bears S. 73° E., 33.0 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Price and Rigby in 1945</p> <p style="padding-left: 40px;">A fir stump, 40 ins. diam., bears N. 56 1/4° E., 122.8 ft. dist., with illegible scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A roothole, bears N. 87 1/2° E., 146.5 ft. dist., alongside of which is a down fir, 35 ins. diam., no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 38° E., 3.2 ft. dist., mkd. 1/4 S32 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 45° E., 19.9 ft. dist., mkd. X BT.</p> <p>A steel fence post is alongside the cor.</p> <p style="text-align: center;">—————</p> <p>S. 89° 22' 20" W., beginning new measurement.</p>
1051.04	<p>The 1/4 sec. cor. of sec. 5 only, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">————— 1/4 S 5 T 22 S R 8 W 1963</p> <p>from which the remains of bearing trees mkd. by Brooks and Jelley in 1963-65</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears S. 31 3/4° E., 367.0 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 50 ins. diam., bears S. 45° W., 224.4 ft. dist., no marks visible.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

F E E T

and new bearing trees


A fir, 18 ins. diam., bears S. 52° E., 10.4 ft. dist.,
mkd. X BT.

A fir, 19 ins. diam., bears S. 20° W., 7.0 ft. dist., mkd.
1/4 S5 BT.

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

(Restoring the survey by Harvey Gordon and Charles T. Gardner,
in 1855 and the resurvey by George F. Rigby, in 1931)

From the cor. of secs. 7, 12, 13, and 18, remonumented by Rigby
in 1931; monumented with an iron post, 2 ins. diam., firmly set,
projecting 10 ins. above ground, with a brass cap mkd.



from which the remains of the bearing trees mkd. by Rigby in
1931

A maple, 27 ins. diam., bears N. 12° E., 38.9 ft. dist.,
no marks visible.

A fir, 43 ins. diam., bears S. 85° W., 35.0 ft. dist.,
with a healed blaze.

A decayed maple stump, size indeterminate, bears
N. 40° W., 48.2 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Godfrey in 1962-63
and reported by Peterson in 1993-95

A fir, 48 ins. diam., bears S. 44° E., 103.0 ft. dist.,
with a healed blaze.

A fir, 38 ins. diam., bears S. 64 1/2° W., 54.8 ft. dist.,
with a healed blaze.

N. 0° 40' 26" E., bet. secs. 7 and 12.

618.20

The closing cor. of secs. 7 and 12, at the intersection with the
NE. bdy. of DLC No. 48 in T. 22 N., R. 8 W., identical with the
NE. bdy. of DLC No. 45 in T. 22 S., R. 9 W., established by

Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 8 W., Willamette Meridian, Oregon


F E E T

Wilcox in 1991, and is accepted as the corner; monumented with a steel reinforcing bar, 5/8 ins. diam., firmly set, projecting 3 ins. above ground, with a yellow plastic cap mkd. STUNTZNER ENGR. LS 2244, from which a bearing object mkd. by Wilcox

A rock face, bears N. 3° W., 26.9 ft. dist., with the mark X visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



from which new bearing trees

A fir, 7 ins. diam., bears N. 43 1/2° E., 15.6 ft. dist., mkd. S7 CC BT.

A fir, 10 ins. diam., bears S. 83° W., 19.8 ft. dist., mkd. X BT.


Deposit the steel reinforcing bar inside and a magnet in a white plastic case at the base of the stainless steel post.

N. 0° 44' 00" E., beginning new measurement.

632.35

The S 1/16 sec. cor. of secs. 7 and 12, established by Wilcox in 1991, and is accepted as the corner; monumented with a steel reinforcing bar, 3/4 ins. diam., firmly set, projecting 5 ins. above ground, with an aluminum cap mkd.

STUNTZNER ENGINEERING



from which bearing trees mkd. by Wilcox in 1991

A fir, 15 ins. diam., bears S. 87° E., 7.5 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
1250.26	<p>A fir, 16 ins. diam., bears S. 21° W., 10.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 39' 44" E., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 7 and 12, monumented with the remains of the original corner tree, a decayed fir stump, size indeterminate, no marks visible, perpetuated by Godfrey in 1962-63, subsequently perpetuated by Wilcox in 1991, and further perpetuated by McLind in 1996, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 50° W., 13.2 ft. dist., no marks visible.</p> <p>No other suitable bearing objects available due to recent logging actives.</p> <p>At the corner point</p> <p>Drive a steel reinforcing bar, 36 ins. long, 5/8 ins. diam., 36 ins. in the stump, with alum. cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 22 S R 9 W R 8 W 1/4 S 12 S 7 2008 </div> <p>From this cor., a point established by Godfrey in 1962-63, as a witness corner for the 1/4 sec. cor. of secs. 7 and 12, bears North, 6.0 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with a brass cap mkd. COUNTY SURVEYORS OFFICE T22S R9W R8W WC 1/4 S12 S7 COR IS 6' SOUTH 1963.</p> <p>from which the remains of a bearing tree mkd. by Godfrey in 1962-63</p> <p style="padding-left: 40px;">A fir stump, size indeterminate, bears N. 40° W., 19.0 ft. dist., with scribe marks WC 1/4 S12 CS BT visible.</p> <p>and the bearing trees mkd by Wilcox in 1991</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 11° W., 9.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 87° W., 6.9 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by McLind in 1996</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 10 ins. diam., bears N. 83° E., 28.5 ft. dist., with a healed blaze.</p> <p>A fir, 13 ins. diam., bears S. 27° E., 14.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 30' 10" W., beginning new measurement.</p>												
2588.78	<p>The cor. of secs. 1, 6, 7, and 12, perpetuated by persons unknown, (tags found by Godfrey, dated 4/27/54), subsequently perpetuated by Godfrey in 1963,; monumented with an iron pipe 44 ins. long, 1 1/2 ins. diam., firmly set, projecting 24 ins. above ground, from which the remains of the original bearing trees</p> <p>A decayed fir stump, size indeterminate, bears N. 40° E., 18.0 ft. dist., no marks visible. (Record, N. 32° E, 15.8 ft. dist.)</p> <p>A decayed fir stump, size indeterminate, bears N. 45° W., 6.6 ft. dist., with illegible scribe marks visible (not original scribe marks). (Record, 4.0 ft. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <table style="margin: 10px auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T 22 S</td> </tr> <tr> <td style="text-align: center;">R 9 W</td> <td style="text-align: center;">R 8 W</td> </tr> <tr> <td style="text-align: center;">S 1</td> <td style="text-align: center;">S 6</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">2008</td> </tr> </table> <p>from which new bearing trees</p> <p>A fir, 16 ins. diam., bears S. 72° E., 6.8 ft. dist., mkd. T22S R8W S7 BT.</p> <p>A fir, 11 ins. diam., bears S. 28° E., 29.9 ft. dist., mkd. X BT.</p> <p>No other suitable bearing objects available due to recent logging activity.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>from this cor., a point established alongside the cor. by Godfrey, in 1963, but utilized as the cor. by McLind in 1996 bears, N. 45° 00' 00" E., 0.25 ft. dist., monumented with an iron post, 30 ins. long, 1 1/2 ins. diam., firmly set,</p>	T 22 S		R 9 W	R 8 W	S 1	S 6	-----		S 12	S 7	2008	
T 22 S													
R 9 W	R 8 W												
S 1	S 6												

S 12	S 7												
2008													

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET

projecting 16 ins. above ground, with a brass cap mkd. COUNTY SURVEYORS OFFICE T22S R9W R8W S1 S6 S12 S7 1963, and was not utilized for control in this survey due to improper survey procedures, from which bearing trees mkd. by McLind in 1996

A fir, 12 ins. diam., bears S. 34° E., 15.1 ft. dist., with a healed blaze.

A fir stump, 9 ins. diam., bears S. 32° W., 13.1 ft. dist., with a healed blaze.

Reset this post at same position, 4 ins. below the surface of the ground.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

(Restoring the survey by Harvey Gordon and Charles T. Gardner, in 1855, and William H Byars, in 1881, and the resurvey by Floyd A. Brooks and James E. Jelley, in 1963-65, and Floyd A. Brooks and Peter A. Peterson, in 1965-67 and the corrective resurvey by John A. Farmer, in 1993)

From the cor. of secs. 11, 12, 13, and 14, perpetuated by Godfrey, in 1962-63; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S	
S 11	S 12
S 14	S 13
R 8 W	
1962	

from which the remains of an original bearing tree

A fir snag, 55 ins. diam., bears N. 70° W., 15.8 ft. dist., with illegible scribe marks visible on partially healed blaze.

and bearing trees mkd. by Godfrey in 1962-63 and reported by Brooks and Jelley in 1963-65

A fir, 28 ins. diam., bears N. 52° E., 15.2 ft. dist., no marks visible.

A maple, 14 ins. diam., bears S. 85° W., 45.7 ft. dist., with a healed blaze. (Record S. 87° W., 46.2 ft. dist.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET																
	<p>A maple, 10 ins. diam., bears N. 79 1/2° W., 31.7 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A maple, 16 ins. diam., bears S. 23° E., 32.8 ft. dist., mkd. S14 BT.</p> <p>N. 0° 09' 37" W., bet. secs. 11 and 12.</p>															
2646.57	<p>The 1/4 sec. cor. of secs. 11 and 12, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>1/4</p> <table style="margin: auto;"> <tr> <td>S 11</td> <td> </td> <td>S 12</td> </tr> <tr> <td colspan="3">T 22 S R 8 W</td> </tr> <tr> <td colspan="3">1967</td> </tr> </table> </div> <p>from which bearing trees mkd. by Brooks and Peterson in 1965-67</p> <p>A fir, 17 ins. diam., bears S. 49° E., 47.5 ft. dist., no marks visible, with BT tag.</p> <p>A fir, 15 ins. diam., bears N. 25° W., 22.4 ft. dist., no marks visible, with BT tag.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 09' 18" W., beginning new measurement.</p>	S 11		S 12	T 22 S R 8 W			1967								
S 11		S 12														
T 22 S R 8 W																
1967																
2651.71	<p>The cor. of secs. 1, 2, 11, and 12, perpetuated by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="3">T 22 S R 8 W</td> </tr> <tr> <td>S 2</td> <td> </td> <td>S 1</td> </tr> <tr> <td colspan="3"><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td>S 11</td> <td> </td> <td>S 12</td> </tr> <tr> <td colspan="3">1967</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A decayed fir stump, 42 ins. diam., bears S. 26° E., 58.7 ft. dist., no marks visible.</p> <p>and the bearing trees mkd. by Brooks and Peterson in 1965-67</p> <p>A fir, 21 ins. diam., bears N. 19° E., 40.9 ft. dist., with a healed blaze.</p> <p>A fir, 17 ins. diam., bears S. 16° E., 90.8 ft. dist., with a healed blaze. (Record, 91.7 ft. dist.)</p>	T 22 S R 8 W			S 2		S 1	<hr style="width: 50%; margin: 0 auto;"/>			S 11		S 12	1967		
T 22 S R 8 W																
S 2		S 1														
<hr style="width: 50%; margin: 0 auto;"/>																
S 11		S 12														
1967																

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A roothole, bears S. 21° W., 10.6 ft. dist., alongside of which is a down hemlock, 16 ins. diam., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Farmer in 1993</p> <p>A roothole, bears N. 21 3/4° W., 6.6 ft. dist., onside of which is a down fir, 11 ins. diam., with a healed blaze.</p> <p>and new bearing trees</p> <p>A hemlock, 14 ins. diam., bears S. 43 3/4° W., 14.2 ft. dist., mkd. T22S R8W S11 BT.</p> <p>A fir, 19 ins. diam., bears N. 25 3/4° W., 23.5 ft. dist., mkd. T22S R8W S2 BT.</p> <hr/> <p>N. 0° 04' 16" W., bet. secs. 1 and 2.</p>
2460.32	<p>The 1/4 sec. cor. of secs. 1 and 2, perpetuated by Godfrey in 1962-63; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 22 S 1/4 S 2 S 1 R 8 W 1962</p> <p>from which the remains of the original bearing trees</p> <p>A roothole, bears S. 55° E., 18.5 ft. dist., onside of which is a down fir, 37 ins. diam., no marks visible.</p> <p>A decayed fir stump, 13 ins. diam., bears S. 55° W., 19.8 ft. dist., with ax mark visible and part of a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 16 ins. diam., bears N. 32° E., 18.8 ft. dist., mkd. 1/4 S1 BT.</p> <p>A fir, 19 ins. diam., bears N. 82° W., 5.5 ft. dist., mkd. 1/4 S2 BT.</p> <hr/> <p>N. 0° 55' 39" W., beginning new measurement.</p>
2809.52	<p>The original closing cor. of secs. 1 and 2, determined at record bearing and distance from the remains of an original bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEEET	<p style="text-align: center;">A decayed fir stump, 42 ins. diam., bears S. 20° W., 28.4 ft. dist., no marks visible on open blaze and axe marks in a diamond on the east side.</p> <p>At the corner point</p> <p>Set a steel reinforcing rod, 36 ins. long, 5/8 in. diam., 36 ins. in the ground.</p> <p>No further monumentation deemed necessary.</p>														
2815.46	<p>The closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., established by Lytle et.al., in 1952-54; monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 21 S R 8 W</td> </tr> <tr> <td colspan="2">S 35</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 22 S</td> <td style="padding: 0 5px;">R 8 W</td> </tr> <tr> <td colspan="2" style="text-align: center;">C C</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p style="margin-left: 40px;">A roothole, bears S. 77 1/4° E., 28.4 ft. dist., onside of which is a down decayed fir, 5 ins. diam., with scribe marks CC T22S R8 visible on open blaze and reverse scribes on loose piece.</p> <p style="margin-left: 40px;">A roothole, bears S. 74° W., 46.9 ft. dist., onside of which is a down fir stump, 30 ins. diam., no marks visible.</p> <p>and the bearing trees mkd. by Godfrey in 1962-63</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 84° W., 63.4 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A madrone, decayed in center but still alive, 20 ins. diam., bears N. 34 1/4° W., 92.3 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Forkner in 2007</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears S. 85 1/4° E., 29.0 ft. dist., with scribe marks T22S R8W S1 CC BT visible on partially healed blaze.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the 1/4 sec. cor. of secs. 2 and 11, perpetuated by Haines in 1950, erroneously reestablished by Brooks and Peterson in</p>	T 21 S R 8 W		S 35				S 2	S 1	T 22 S	R 8 W	C C		1952	
T 21 S R 8 W															
S 35															
S 2	S 1														
T 22 S	R 8 W														
C C															
1952															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>1965-67 and correctively resurveyed by Farmer in 1993; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.</p> <p style="text-align: center;">S 2 1/4 ——— S 11 T 22 S R 8 W 1993</p> <p>from which the remains of bearing trees mkd. by Haines in 1950 and reported by Farmer in 1993</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 76° W., 33.7 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 32 ins. diam., bears N. 61 1/2° W., 91.5 ft. dist., with a healed blaze. (Record, 88.8 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Brooks and Peterson in 1965-67 and correctively resurveyed by Farmer in 1993</p> <p style="padding-left: 40px;">A decayed fir stump, 34 ins. diam., bears N. 30 1/4° W., 67.0 ft. dist., no marks visible.</p> <p>and a bearing tree of unknown origin reported by Farmer in 1993</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears S. 11° E., 44.2 ft. dist., no marks visible.</p> <p>N. 88° 26' 09" W., bet. secs. 2 and 11.</p>
1365.10	<p>The W 1/16 sec. cor. of secs. 2 and 11, erroneously established by Brooks and Peterson in 1965-67 and correctively resurveyed by Farmer in 1993; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">S 2 W 1/16 ——— S 11 1993</p> <p>from which the bearing trees mkd. by Farmer in 1993</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 12° W., 7.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 20 1/2° W., 7.9 ft. dist., with a healed blaze.</p> <hr style="width: 60%; margin-left: 0;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>From the witness cor. to the meander cor. of secs. 4 and 5 for the right bank of the Umpqua River, established by Brooks and Jelley in 1963-65, and perpetuated by Monrean in 1976; monumented with an iron post, 1 1/2 ins. diam., firmly set, with top 12 ins. below the surface of the ground, with a brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T 22 S R 8 W WC S 5 S 4 MC 1976</p> <p>from which a bearing tree mkd by Brooks and Jelley in 1963-65</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 19° E., 142.6 ft. dist., with a healed blaze. (Record, N. 20 1/4° E.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A maple, 21 ins. diam., bears N. 82° E., 84.0 ft. dist., mkd. WC MC S4 BT on bark.</p> <p>Set a carsonite survey monument post alongside the cor.</p> <p>From this cor., the right bank of Umpqua River bears S. 5° 42' 51" W., 8.6 ft. dist., bank bears N. 70° E. and S. 73° W.</p> <p>From this same cor., the witness meander cor. of the NE. bdy. of DLC No. 49 bears S. 65° 17' 03" W. 288.76 ft. dist., hereinafter described.</p> <p>N. 5° 42' 51" E., bet. secs. 4 and 5.</p>
85.47	<p>True point for the meander corner of secs. 4 and 5, established by Byars in 1881, at proportionate dist., there is no remaining evidence of the original cor., not monumented.</p>
997.19	<p>The 1/4 sec. cor. of secs. 4 and 5, perpetuated from original evidence no longer in existence by Byron in 1958; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 24 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 22 S S S 1/4 5 4 R 8 W 1958</p> <p>from which the remains of the bearing trees mkd. by Byron in 1958 and reported by Brooks and Jelley in 1963-65</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEEET	<p>A fir stump, size indeterminate, bears S. 5° E., 68.0 ft. dist., no marks visible.</p> <p>A fir, 41 ins. diam., bears S. 83° W., 9.9 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd by Godfrey in 1962-63 and reported by Brooks and Jelley in 1963-65</p> <p>A fir, 39 ins. diam., bears N. 25° E., 31.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 28' 46" E., beginning new measurement.</p>								
2668.09	<p>The closing corner of secs. 4 and 5 on the N. bdy. of the Tp.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 7, and 8, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 22 S</td> <td style="padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1963</td> </tr> </table> </div> <p>from which the bearing trees and a bearing object mkd. by Brooks and Jelley in 1963-65</p> <p>A maple, 15 ins. diam., bears N. 18 1/2° E., 53.5 ft. dist., with a healed blaze.</p> <p>A maple, 24 ins. diam., bears S. 5° E., 27.3 ft. dist., no marks visible. (Record, 29.0 ft. dist.)</p> <p>A maple, 33 ins. diam., bears S. 72° W., 66.0 ft. dist., with a healed blaze.</p> <p>A rock outcrop, 6 ft. high, bears N. 32° W., 21.1 ft. dist., mkd. X BO on the lower portion.</p> <p>An iron pipe, 1 in. diam., projecting 18 ins., established by person(s) unknown for unknown purpose is alongside the cor.</p> <p>S. 87° 50' 39" W., bet. secs. 6 and 7.</p>	T 22 S	R 8 W	S 6	S 5	S 7	S 8	1963	
T 22 S	R 8 W								
S 6	S 5								
S 7	S 8								
1963									
545.95	<p>The closing corner of secs. 6 and 7, at the intersection with the NW. bdy. of DLC No. 49, established by Minor in 1994, and is accepted as the corner; monumented with a steel reinforcing bar, 5/8 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with a yellow plastic</p>								

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>cap mkd. LS 2052, from which the bearing trees and bearing object mkd. by Minor</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. $43\ 1/4^\circ$ E., 16.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">An oak, 19 ins. diam., bears S. $9\ 1/2^\circ$ W., 31.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A rock face, bears N. $81\ 1/4^\circ$ W., 27.0 ft. dist., with the marks X BO visible.</p> <p>At the corner point</p> <p>Replace the yellow plastic cap with an alum. cap, 2 ins. diam., mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;"> $\begin{array}{c} \text{S } 6 \\ \text{S } 7 \text{ --- } / \text{ CC} \\ \text{C } 49 \\ 2008 \end{array}$ </p> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>S. $87^\circ 56' 11''$ W., beginning new measurement.</p>
2016.61	<p>The 1/4 sec. cor. of secs. 6 and 7, perpetuated by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;"> $\begin{array}{c} \text{S } 6 \\ 1/4 \text{ ---} \\ \text{S } 7 \\ \text{T } 22 \text{ S } \text{ R } 8 \text{ W} \\ 1963 \end{array}$ </p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir stump, size indeterminate, bears N. 7° E., 13.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir stump, size indeterminate, bears S. 20° E., 25.1 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Brooks and Jelley in 1963-65</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. $19\ 1/2^\circ$ W., 56.1 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Minor in 1994</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 49° W., 14.0 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/>



**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	S. 89° 55' 54" W., beginning new measurement.
2600.92	The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp. <hr/>
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0° 15' 10" E., bet. secs. 5 and 6.
647.31	The closing cor. of secs. 5 and 6, at the intersection with the NW. bdy. of DLC No. 49, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd. <div style="text-align: center;"> <p>T 22 S R 8 W</p> <p> C C</p> <p>S 6 S 5</p> <p> / </p> <p> C 49</p> <p> 1963</p> </div>
	from which the remains of a bearing tree mkd. by Brooks and Jelley in 1963-65
	A dead hollow fir snag, 12 ins. diam., bears N. 8 1/2° W., 66.7 ft. dist., no marks visible.
	and new bearing trees
	A fir, 18 ins. diam., bears N. 45° E., 18.0 ft. dist., mkd. CC S5 BT.
	A fir, 18 ins. diam., bears N. 43° W., 10.7 ft. dist., mkd. X BT.
	A steel fence post is alongside the cor. <hr/>
	N 0° 14' 27" E., beginning new measurement.
1956.35	The 1/4 sec. cor. of secs. 5 and 6, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd. <div style="text-align: center;"> <p> 1/4</p> <p>S 6 S 5</p> <p>T 22 S R 8 W</p> <p> 1963</p> </div>
	from which a bearing tree mkd. by Brooks and Jelley in 1963-65
	A fir snag, 42 ins. diam., bears S. 20° E., 22.4 ft. dist., with illegible scribe marks visible.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>and bearing trees mkd. by Minor in 1994</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 73° E., 8.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 55° W., 20.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 62° W., 16.1 ft. dist., with a healed blaze.</p> <p>A steel fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N 0° 13' 24" E., beginning new measurement.</p>
1296.87	<p>The N 1/16 sec. cor. of secs. 5 and 6, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;"> N 1/16 S 6 S 5 T 22 S R 8 W 1963 </p> <p>from which the remains of a bearing tree mkd. by Brooks and Jelley in 1963-65</p> <p style="padding-left: 40px;">A fir stump, 53 ins. diam., bears N. 72° W., 31.0 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 88° E., 15.0 ft. dist., mkd. N 1/16 S5 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 17° W., 17.4 ft. dist., mkd. N 1/16 S6 BT.</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey of Certain Lines of Donation Land Claim No. 49, T. 22 S., R. 8 W., Willamette Meridian, Oregon</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">(Restoring the survey by Dennis Hathorn in 1856 and the resurvey by Floyd A. Brooks and James E. Jelley in 1963-65)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of DLC Nos. 48, 49, and 58, in the SW 1/4 of sec. 7, remonumented by Brooks and Jelley in 1963-65; monumented</p>

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 49,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 8 W S 7</p>  <p>C 48 C 58 1963</p> </div> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears N. 33° W., 31.3 ft. dist., with a healed blaze. (Record, 33.0 ft. dist.)</p> <p>and a bearing tree mkd. by Byron in 1958 and reported by Brooks and Jelley in 1963-65</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 36° E., 59.4 ft. dist., with a healed blaze.</p> <p>An iron rod, 3/4 ins. diam., projecting 6 ins. above ground, reset alongside the cor. by Brooks and Jelley in 1963-65, is alongside the cor.</p> <p>N. 39° 23' 09" E., on the NW. bdy. of DLC No. 49, in sec. 7.</p>
2935.42	<p>Point selected for a witness point on the NW. line of DLC No. 49.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p>  <p>S 7 C 49 2008</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 29° E., 13.9 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 57° W., 10.5 ft. dist., mkd. WP S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
6225.51	<p>The closing cor. of secs. 6 and 7 at intersection with the line bet. secs. 6 and 7, hereinbefore described.</p> <hr style="width: 30%; margin: 10px auto;"/>

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 49,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	N 39° 23' 30" E., beginning new measurement, in section 6.
864.15	The closing cor. of secs. 5 and 6 at intersection with the line bet. secs. 5 and 6, hereinbefore described.

	N 39° 21' 32" E., beginning new measurement, in section 5.
2530.22	The closing cor. at the intersection of the E. and W. center line of sec. 5, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.
	from which new bearing trees
	A double fir, 24 ins. diam. at base, bears S. 18° E., 33.3 ft. dist., mkd. X BT.
	A fir, 24 ins. diam., bears N. 84° W., 14.3 ft. dist., mkd. CC S5 BT.
	A steel fence post is onside the cor.

	N 39° 26' 29" E., beginning new measurement.
1674.72	The closing cor. at the intersection with the E. and W. center line of the NW 1/4 of sec. 5, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.
	from which bearing trees mkd. by Brooks and Jelley in 1963-65
	A fir, 26 ins. diam., bears S. 82° W., 134.0 ft. dist., with a healed blaze.
	A fir, 30 ins. diam., bears N. 87 1/2° W., 128.0 ft. dist., with a healed blaze.

	N 38° 25' 07" E., beginning new measurement.
63.23	The closing cor. at the intersection of the N. and S. center line of sec. 5, established by Brooks and Jelley in 1963-65;


Dependent Resurvey of Certain Lines of
 Donation Land Claim No. 49,
 T. 22 S., R. 8 W., Willamette Meridian, Oregon

<p>FEEET</p>	<p>monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> </div> <p>from which bearing trees mkd by Brooks and Jelley in 1963-65</p> <p>A fir stump, 35 ins. diam., bears N. 24 1/2° E., 71.3 ft. dist., with scribe marks S5 CC BT visible under a healed blaze.</p> <p>A fir, 29 ins. diam., bears S. 83° W., 222.0 ft. dist., with a healed blaze. (Record, S. 82° W., 224.4 ft. dist.)</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears N. 26° E., 19.1 ft. dist., mkd. S5 CC BT.</p> <hr/> <p>N 39° 36' 55" E., beginning new measurement.</p>
<p>220.67</p>	<p>The N. cor. of DLC No. 49, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> </div> <p>from which bearing trees mkd by Brooks and Jelley in 1963-65</p> <p>A fir, 39 ins. diam., bears N. 34° E., 36.3 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 14° W., 4.6 ft. dist., with a healed blaze.</p> <hr/> <p>S 40° 43' 19" E., on the NE. bdy. of Claim No. 49.</p>
<p>2001.53</p>	<p>The closing cor. at the intersection with the E. and W. center line of sec. 5, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p>

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 48, T. 22 S., R. 8 W.,
and DLC No. 45, T. 22 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	(Restoring the survey by Dennis Hathorn, in 1856)

	From the cor. of DLC Nos. 48, 49, and 58, in the SW 1/4 of sec. 7, hereinbefore described.
	N 68° 19' 43" W., on the NE. bdy. of DLC No. 48
716.96	The closing cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

	N. 68° 14' 42" W., on the NE. bdy. of DLC No. 45, in sec. 12, T. 22 S., R. 9 W., beginning new measurement.
777.43	Point for the N. corner. of DLC No. 45, in the SE 1/4 of sec. 12 in T. 22 S., R. 9 W., determined at proportionate distance by Compass Rule Adjustment utilizing the survey by Wilcox in 1991, there is no remaining evidence of the original corner. The controlling corners utilized in establishing this position are the Cor. of DLC Nos. 48, 49, and 58, in the SW 1/4 of sec. 7 of T. 22 S., R. 8 W., and the 1914 Cole cor. established 1110 ft. dist., SW. of the N. cor. of DLC 45 on the NW. bdy. of DLC 45, recovered and perpetuated by Wilcox in 1991, hereinafter described.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	
	from which
	A fir, 17 ins. diam., bears S. 9 1/2° W., 19.9 ft. dist., mkd. X BT.
	A fir, 21 ins. diam., bears S. 53° W., 7.4 ft. dist., mkd. X BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

	S. 70° 40' 47" W., on the NW. bdy. of DLC No. 45, beginning new measurement.
1109.00	A point established by Cole in 1914, on the NW. bdy. of DLC No. 45, subsequently perpetuated by Wilcox, in 1991, and is accepted as a witness point on the line; monumented with a steel reinforcing bar, 30 ins. long, 5/8 ins. diam., firmly set,

**Dependent Resurvey of Certain Lines of
Donation Land Claim No. 48, T. 22 S., R. 8 W.,
and DLC No. 45, T. 22 S., R. 9 W., Willamette Meridian, Oregon**

FEET	<p>projecting 5 ins. above ground, with a yellow plastic cap mkd. STUNTZNER ENGR LS2244, from which the remains of a bearing tree mkd. by Cole</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 69° E., 65.5 ft. dist., with scribe marks 45 visible.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 82° E., 14.5 ft. dist., with a healed blaze at base and a X at breast height.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 88° W., 25.1 ft. dist., painted red, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground directly over the steel reinforcing bar, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivision-of-Section Lines of Section 5, T. 22 S., R. 8 W., Willamette Meridian, Oregon</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">(Restoring the survey by Floyd A. Brooks and James E. Jelley, in 1963-65)</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the closing cor. on the N. and S. center line of sec. 5 at the intersection with the NW. bdy. of DLC No. 49, hereinbefore described.</p> <p>N. 2° 18' 22" E., on the N. and S. center line of sec. 5.</p>
1292.64	<p>The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the closing cor. on the E. and W. center line of the NW 1/4 of sec. 5, at the intersection with the NW. bdy. of DLC No. 49, hereinbefore described.</p>

**Dependent Resurvey of a Portion of the
Subdivision-of-Section Lines of Section 5,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
2655.06	<p>N. 89° 55' 27" W., on the E. and W. center line of the NW 1/4 of sec. 5.</p> <p>The N 1/16 sec. cor. of secs. 5 and 6, hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 11, T. 22 S., R. 8 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">S 11 1/4 ——— S 14 T 22 S R 8 W 1967</p> <p>from which bearing trees mkd. by Brooks and Peterson in 1965-67</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 39° E., 4.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 82° W., 11.9 ft. dist., with a healed blaze.</p>
2625.29	<p>N. 0° 42' 46" E., on the N. and S. center line of sec. 11.</p> <p>Point for the center 1/4 sec. cor. of sec. 11, at the intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 8 W C 1/4 S 11 2008</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 81° E., 25.5 ft. dist., mkd. C 1/4 S11 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 1° W., 4.0 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 11,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET	
3925.66	<p>Point for the center N 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ \ S\ 11 \\ C \\ 2008 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 89 3/4° W., 12.5 ft. dist., mkd. CN 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 44 3/4° W., 19.6 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
5226.03	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the 1/4 sec. cor of secs. 11 and 12.</p> <p>N. 89° 33' 56" W., on the E. and W. center line of sec. 11.</p>
2682.13	<p>The center 1/4 sec. cor. of sec. 11.</p>
4044.14	<p>Point for the center W 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W\ 1/16 \\ C\ \text{-----}\ C \\ S\ 11 \\ 2008 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 51 1/2° E., 38.5 ft. dist., mkd. CW 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 87° W., 4.9 ft. dist., mkd. CW 1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
5406.15	<p>The 1/4 sec. cor. of secs. 10 and 11, perpetuated by Smith in 1999; monumented with an angle iron, 1 1/2 X 1 1/2 ins., loosely set, projecting 48 ins. above ground, from which the remains of an original bearing tree</p>

Subdivision of Section 11,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>A decayed fir stump, 34 ins. diam., bears S. 52 3/4° E., 119.6 ft. dist., no marks visible. (Record, S. 54° E., 116.8 ft. dist.)</p> <p>and the bearing trees mkd. by Godfrey in 1962-63 and reported by Brooks and Peterson in 1965-67</p> <p>A fir, 34 ins. diam., bears S. 9° E., 58.1 ft. dist., with a healed blaze. (Record, S. 7° E.)</p> <p>A fir, 33 ins. diam., bears S. 15 3/4° W., 72.6 ft. dist., with a healed blaze. (Record, S. 18° W.)</p> <p>and reference monuments set by Monrean in 1989</p> <p>A steel reinforcing bar, 5/8 ins. diam., firmly set, leaning, with top 2 ins. below the surface of the ground, with an aluminum cap mkd. DOUGLAS CO SURVEYOR B01 1989, bears N. 24° 28' 07" E., 92.76 ft. dist.</p> <p>A steel reinforcing bar, 5/8 ins. diam., firmly set, with top 2 ins. below the surface of the ground, with an aluminum cap mkd. DOUGLAS CO SURVEYOR B02 1989, bears N. 65° 35' 31" W., 125.18 ft. dist.</p> <p>and the B.L.M. monument originally set by Brooks and Peterson in 1956-67 and reset by Smith in 1999 as a reference monument</p> <p>An iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd. DCSO 1999 S10 S11 SOUTH 14 FT T22S R8W TO COR 1967, bears North, 14.00 ft. dist.</p> <p>Corner is located in a creek. No further monumentation deemed necessary.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the W 1/16 sec. cor. of secs. 11 and 14, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px auto;"> <p>S 11 W 1/16— S 14 1967</p> </div> <p>from which bearing trees mkd. by Brooks and Peterson in 1965-67</p> <p>A fir, 45 ins. diam., bears N. 35° E., 128.7 ft. dist., with a healed blaze.</p>
------	---

Subdivision of Section 11,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">A fir, 27 ins. diam., bears N. 44° W., 56.8 ft. dist., no marks visible.</p>
2614.40	<p>N. 0° 38' 47" E., on the N. and S. center line of the SW 1/4 of sec. 11</p> <p>The center W 1/16 sec. cor. of sec. 11.</p> <hr/>
1313.44	<p>N. 0° 38' 42" E., on the N. and S. center line of the NW 1/4 of sec. 11.</p> <p>Point for the NW 1/16 sec. cor. of sec. 11, at the intersection with the E. and W. center line of the NW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 11 2008</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 21 1/2° E., 17.5 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 82 1/2° W., 18.8 ft. dist., mkd. NW 1/16 S11 BT.</p>
2627.67	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The W 1/16 sec. cor. of secs. 2 and 11.</p> <hr/>
1363.48	<p>From the center N 1/16 sec. cor. of sec. 11.</p> <p>N. 89° 01' 10" W., on the E. and W. center line of the NW 1/4 of sec. 11</p> <p>The NW 1/16 sec. cor. of sec. 11.</p>
2728.60	<p>The N 1/16 sec. cor. of secs. 10 and 11, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 10 S 11 1967</p> <p>from which bearing trees mkd. by Brooks and Peterson in 1965-67</p>

Subdivision of Section 11,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 31 ins. diam., bears S. 72° E., 148.3 ft. dist., with a healed blaze. (Record S. 72 1/2° E., 149.8 ft. dist.)</p> <p>A fir, 30 ins. diam., bears N. 5 3/4° W., 182.5 ft. dist., with a healed blaze. (Record N. 5° W., 183.5 ft. dist.)</p> <hr/>