

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE
SOUTH BOUNDARY (SIXTH STANDARD PARALLEL SOUTH),

AND SUBDIVISIONAL LINES,

AND SUBDIVISION OF SECTIONS 20, 28, 29, 30, AND 32

TOWNSHIP 27 SOUTH, RANGE 2 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated July 14, 2003, approved July 25, 2003,
and Supplemental Special Instructions dated February 26, 2004,
approved February 27, 2004, which provided for
the surveys included under Group No. 1968, and Assignment
Instructions dated August 5, 2003, and April 12, 2004.

Survey commenced August 5, 2003

Survey completed July 8, 2004

T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>The following field notes are those of the dependent resurvey of a portion of the south boundary (sixth standard parallel south), and subdivisional lines, and subdivision of sections 20, 28, 29, 30, and 32, Township 27 South, Range 2 West, of the Willamette Meridian, Oregon.</p> <p>The history of Federal Surveys pertaining to this survey is as follows:</p> <p>In 1882, Samual C. Flint, U.S. Deputy Surveyor, surveyed the South Boundary (Sixth Standard Parallel South).</p> <p>In 1882, Samual C. Flint, U.S. Deputy Surveyor, surveyed the north, east, and west boundaries and a portion of the subdivisional lines.</p> <p>In 1905-07, Charles E. Roberts, U.S. Deputy Surveyor, retraced a portion of the subdivisional lines and surveyed a portion of the subdivisional lines.</p> <p>In 1908, William C. Gibb, U.S. Deputy Surveyor, retraced portions of the north boundary and section 5 connections of Township 28 South, Range 2 West.</p> <p>In 1911, Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, resurveyed the south boundary (sixth standard parallel south), retraced portions of the subdivisional lines and completed the subdivisional lines.</p> <p>The history of Private Surveys pertaining to this survey is as follows:</p> <p>In 1980, Romanso E. Ware, Oregon Professional Land Surveyor No. 1005, and Ronald A. Quimby, Oregon Professional Land Surveyor No. 1654, resurveyed a portion of the subdivisions and subdivided section 32, Township 27 South, Range 2 West, as shown on map file M79-49, filed at the Douglas County Surveyors Office.</p> <p>In 1985, Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, resurveyed a portion of the west boundary and subdivisions and subdivided section 30, Township 27 South, Range 2 West, as shown on map file M90-71, filed at the Douglas County Surveyors Office.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the <u>Special Instructions</u> dated July 14, 2003, and <u>Supplemental Special Instructions</u> dated February 26, 2004, for Group No. 1968, Oregon.</p> <p>The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS</p>

T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET

measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO), version 1.61. The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.

The directions of the lines are based on the true meridian as determined by a combination of direct solar observations and GPS measurements and were carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by Cadastral Measurement Management for windows (WinCMM), computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control:

1. CAPE BLANCO CORS ARP, National Geodetic Survey.
42° 50' 09.93681" N.; 124° 33' 47.99046" W.; NAD 1983 (CORS 2000)
2. DODSON BUTTE CORS ARP, National Geodetic Survey.
43° 07' 07.62977" N.; 123° 14' 39.21270" W.; NAD 1983 (CORS 2002)

The geographic position (NAD 1983 (CORS 2000)) of the 1/4 section corner of sections 19 and 30, was determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95%

T. 27 S., R. 2 W., Willamette Meridian, Oregon

F E E T	<p>confidence level, relative to the National Spatial Reference System, noted above, is as follows: Latitude: 43° 11' 53.49" N. Longitude: 122° 58' 50.68" W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the South Boundary (Sixth Standard Parallel South), T. 27 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the 1882 survey by Samuel C. Flint, the 1908 retracement by William N. Gibb, and the 1911 resurvey by Zachariah M. Derrick and Morris Wygant)</p> <hr/> <p>Beginning at an Angle point bet. secs. 32 and 4, on the S. bdy. of the Tp., originally established as the Standard Cor. of secs. 32 and 33, in 1882, perpetuated by the Douglas County Surveyors Office in 1969 and remonumented by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 279100, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27S R2W AP S32 S4 T28S RLS1654 1980</p> </div> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears N. 45° E., 7.4 ft. dist., with scribe marks AP CS BT visible in the bark over a healed blaze. (Record, 5.9 ft.)</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 25° W., 3.3 ft. dist., with fragmentary scribe marks visible on an opened blaze.</p> <p>and a bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 18° W., 11.3 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 29 1/4° E., 11.2 ft. dist., with a healed blaze.</p> <p>From this corner, the original closing cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., perpetuated by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Record of</p>
---------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 300100, bears N. 86° 59' 44" E., 198.67 ft. dist.; monumented with a fir, 30 ins. diam., with healed blazes visible on north, east, and west faces, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 39° E., 23.1 ft. dist., with a healed blaze. (Record, N. 36° 50' E.)</p> <p style="padding-left: 40px;">A roothole, bears N. 63° W., 22.5 ft. dist., with fallen fir trunk, 34 ins. diam., lying alongside, fragmentary scribe marks visible on an unhealed blaze. (Record, N. 55° 40' W., 24.4 ft., rescribed by Ware and Quimby)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 73° W., 45.6 ft. dist., mkd. T27S R2W S32 BT.</p> <p>From this cor., a witness cor. for the closing cor. of secs. 32 and 33, established by Ware and Quimby in 1980, bears N. 0° 00' 01" W., 7.12 ft. dist., hereinafter described.</p> <p>N. 89° 52' 31" W., on the south bdy. of sec. 32; desc. S. slope.</p>
96.02	<p>From this point, the original closing cor. of secs. 4 and 5, T. 28 S., R. 2 W. bears south, 3.53 ft. dist.; perpetuated by the Douglas County Surveyors Office in 1969 and remonumented by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 277100, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T28S R2W</p> <hr style="width: 50px; margin: 0 auto;"/> <p>CC S5 S4</p> <p>RLS1654</p> <p>1980</p> </div> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A laurel, 18 ins. diam., bears S. 68° W., 11.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Rescribed by the Douglas County Surveyors Office.)</p> <p>and a bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 63° E., 35.1 ft. dist., with a healed blaze.</p>
2457.61	<p>The 1/4 sec. cor. of sec. 32 only, established at midpoint bet. the closing cors. of secs. 32 and 33, and secs. 31 and 32, by Ware and Quimby in 1980, recorded in the Douglas County</p>

T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<p>Surveyors Office, Map File No. 79-49 and Record of Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 240100, and is accepted as the cor.; monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W 1/4 S32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">RLS1654 1980</p> <p>from which the remains of bearing trees mkd. by Ware and Quimby</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 30 3/4° E., 27.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 7 ins. diam., bears N. 47 1/4° W., 23.2 ft. dist., with scribe marks 1/4 S32 BT visible on an unhealed double blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 52° W., 39.1 ft. dist., mkd. 1/4 S32 BT.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 89° 51' 10" W., beginning new measurement; asc. E. slope.</p>
170	<p>Gravel road, 16 ft. wide, bears N. 52° E. and S. 52° W.</p>
229.72	<p>Angle Point for secs. 32 and 5, on the S. bdy. of the Tp., originally established as the standard 1/4 sec. cor. of sec. 32, in 1882, perpetuated by the Douglas County Surveyors Office in 1969 and remonumented by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Office Map File No. 79-49 and Record of Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 239100, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W AP S32 / \ S5 T28S</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">RLS1654 1980</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed cedar stump, 18 ins. diam., bears S. 56 3/4° E., 6.0 ft. dist., with no scribe marks visible on chopped out blaze. (Record, S. 62° E., 5.3 ft.)</p>

**Dependent Resurvey of a Portion of the South Boundary
(Sixth Standard Parallel South)
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>and remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A roothole bears N. 30° E., 21.4 ft. dist., with fallen cedar trunk, 19 ins. diam., lying alongside, with scribe marks BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A decayed cedar stump, 21 ins. diam., bears S. 18° E., 6.4 ft. dist., with scribe marks S BT visible on a partially healed blaze.</p> <p>and remains of bearing trees mkd. Ware and Quimby</p> <p style="padding-left: 40px;">A cedar stump, 21 ins. diam., bears S. 1 1/4° W., 41.2 ft. dist., with scribe marks BT visible on a partially healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A cedar, 19 ins. diam., bears N. 21 1/2° E., 29.0 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 17' 17" W., beginning new measurement; continue asc. E. slope.</p>
1097.42	<p>The W 1/16 sec. cor. of sec 32 only, on the S. bdy. of the Tp., established by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Office, Map File No. 79-49, and is accepted as the cor.; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W 1/16 S32</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">RLS1654 1980</p> <p>from which bearing trees mkd. by Ware and Quimby</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N. 35 3/4° E., 17.8 ft. dist., with scribe marks W 1/16 S32 BT visible on a partially healed double blaze.</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears N. 59 1/2° E., 17.3 ft. dist., with scribe marks W 1/16 S32 BT visible on a partially healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 17' 24" W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the South Boundary
 (Sixth Standard Parallel South)
 T. 27 S., R. 2 W., Willamette Meridian, Oregon

<p>F E E T</p> <p>1327.98</p>	<p>The closing cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyors Office in 1962 and remonumented by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 200100, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;"> COUNTY SURVEYORS OFFICE T27S S31 S32 R ----- 2 T28S W 1968 </p> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;"> A decayed fir stump, size indeterminate, bears N. 25 1/4° E., 7.7 ft. dist., with no marks visible. (Record, N. 29° 30' E., 6.6 ft.) </p> <p style="margin-left: 40px;"> A fir stump, 28 ins. diam., bears N. 23° W., 57.5 ft. dist., with a partially healed blaze. (Record, N. 21° W., 56.1 ft.) </p> <p>and bearing trees mkd. by the Douglas County Surveyors Office in 1968</p> <p style="margin-left: 40px;"> A madrone, 8 ins. diam., bears N. 78° E., 20.9 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. </p> <p style="margin-left: 40px;"> A fir, 21 ins. diam., bears N. 12 3/4° W., 15.1 ft. dist., with a healed blaze. </p> <p>From this corner, the original closing cor. of secs. 5 and 6, T. 28 S., R 2 W., bears S. 89° 32' 15" W., 223.76 ft. dist.; remonumented by the Douglas County Surveyors Office in 1962, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed T. 27 S., R. 02 W., Point Identifier No. 177100, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> COUNTY SURVEYORS OFFICE T27S CC R ----- 2 S6 S5 W T28S 1968 </p>
-------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the South Boundary
(Sixth Standard Parallel South)
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

F E E T	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears S. 32 3/4° E., 55.6 ft. dist., with a healed blaze. (Record, S. 57° E., 53.5 ft.)</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears S. 36 1/4° W., 7.2 ft. dist., with a no marks visible on an opened, decayed blaze. (Record, S. 45° W., 5.94 ft.)</p> <p>and a bearing tree mkd. by the Douglas County Surveyors Office in 1968</p> <p style="padding-left: 40px;">A madrone, 8 ins. diam., bears S. 1 1/4° W., 43.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <hr/> <p align="center">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/> <p align="center">(Restoring the 1911 survey by Zachariah M. Derrick and Morris Wygant)</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34, remonumented by Thomas E. Shrum, Jr., Oregon Registered Engineer No. 4287, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 35, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 128, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with aluminum cap incorrectly mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>USPC PROPERTY COR</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T27S</td> <td style="padding: 0 10px;">R2W</td> <td></td> </tr> <tr> <td style="padding: 0 10px; text-align: center;">27</td> <td style="padding: 0 10px; text-align: center;">28</td> <td rowspan="2" style="padding: 0 10px; vertical-align: middle;">1962</td> </tr> <tr> <td style="padding: 0 10px; text-align: center;">33</td> <td style="padding: 0 10px; text-align: center;">34</td> </tr> <tr> <td colspan="3" style="padding: 0 10px;">RE 4287</td> </tr> <tr> <td colspan="3" style="padding: 0 10px;">DO NOT DISTURB</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed hemlock stump, 25 ins. diam., bears N. 56 1/4° E., 42.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, N. 57° 40' E.)</p> <p style="padding-left: 40px;">A sawed cedar stump, 32 ins. diam., bears S. 23 1/2° E., 25.7 ft. dist., with scribe marks S33 BT visible on an open blaze. (Record, S. 21° E., rescribed by Shrum)</p>	T27S	R2W		27	28	1962	33	34	RE 4287			DO NOT DISTURB		
T27S	R2W														
27	28	1962													
33	34														
RE 4287															
DO NOT DISTURB															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 30 ins. diam., bears S. 22° W., 11.9 ft. dist., with scribe marks S34 BT visible on an open blaze. (rescribed by Shrum)</p> <p>A sawed cedar stump, 27 ins. diam., bears N. 14 1/2° W., 10.0 ft. dist., with scribe marks S28 BT visible on an open blaze. (Record, N. 11° 30' W., 7.9 ft., rescribed by Shrum)</p> <p>from which the remains of an accessory mkd. by Shrum</p> <p>A sawed cedar stump, 38 ins. diam., bears N. 15 1/2° E., 50.0 ft. dist., with scribe marks S27 BT visible on an open blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A fir, 19 ins. diam., bears N. 24 1/2° E., 63.3 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 68 3/4° E., 31.7 ft. dist., with a healed double blaze.</p> <p>A fir, 20 ins. diam., bears N. 74 1/4° W., 4.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A hemlock, 12 ins. diam., bears S. 11° W., 13.0 ft. dist., mkd. T27S R2W S33 BT.</p> <p>N. 0° 20' 26" W., bet. secs. 27 and 28.</p> <p>Descend broken NW. slope.</p>
595	Gravel road, 10 ft. wide, bears N. 37° E. and S. 37° W.
2310	Gravel road, 16 ft. wide, bears S. 14° E. and N. 14° W.
2618.24	The 1/4 sec. cor. of secs. 27 and 28, remonumented by Thomas E. Shrum, Jr., Oregon Registered Engineer No. 4287, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 22, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 77, monumented with an iron post, 1 in. diam., firmly set, projecting 21 ins. above ground, with aluminum cap incorrectly mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	USPC PROPERTY COR T27S R2W 1/4 S27 28 RE 4287 DO NOT DISTURB
	from which the remains of an original bearing tree A sawed, decayed fir stump, 21 ins. diam., bears N. 84 1/2 E., 14.5 ft. dist., with fragmentary scribe marks visible on an opened blaze. and remains of an accessory mkd. by Shrum A decayed fir stump, size indeterminate, bears S. 22 1/4° W., 34.2 ft. dist., with fragmentary scribe marks visible on an open blaze. and remains of bearing trees mkd. by the Douglas County Surveyors Office A sawed fir stump, 43 ins. diam., bears N. 14 1/4° E., 26.1 ft. dist., with scribe marks 1/4 S27 CS BT visible on wood fragment lying alongside. A fir, 17 ins. diam., bears S. 3° W., 103.2 ft. dist., with a healed double blaze. and a new bearing tree A fir, 9 ins. diam., bears N. 86 3/4° E., 17.7 ft. dist., mkd. 1/4 S27 BT. From this corner, an iron pipe, set by person(s) unknown, 2 ins. diam., firmly set, projecting 14 ins. above the ground, bears south, 1.2 ft. dist., with no cap. <hr style="width: 20%; margin: auto;"/> N. 0° 03' 51" E., beginning new measurement. Continue desc. broken NW. slope.
475	Gravel road, 16 ft. wide, bears S. 83° E. and N. 83° W.
1309.47	Point for the N 1/16 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base, 12 ins. high, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<div style="text-align: center;"> <p>T27S R2W N 1/16 S28 S27 2004</p> </div> <p>from which</p> <p>A fir, 16 ins. diam., bears N. 74 1/4° E., 7.8 ft. dist., mkd. N 1/16 S27 BT.</p> <p>A fir, 11 ins. diam., bears N. 57° W., 26.6 ft. dist., mkd. N 1/16 S28 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, an iron rebar, set by person(s) unknown, 3/4 in. diam., firmly set, projecting 14 ins. above the ground, bears N. 1° 16' 51" E., 23.87 ft. dist., with no cap, from which the remains of a bearing tree mkd. by person(s) unknown</p> <p>A sawed fir stump, 26 ins. diam., bears S. 19 1/2° E., 12.2 ft. dist., with no marks visible.</p> <p>Begin posting and blazing.</p>
1475	Gravel road, 8 ft. wide, bears N. 70° E. and S. 70° W.
1615	Spur, slopes S. 60° E.; desc. broken NE. slope.
2100	Gravel road, 10 ft. wide, bears S. 20° E. and N. 20° W.
2618.94	<p>The cor. of secs. 21, 22, 27, and 28, perpetuated by the Douglas County Surveyors Office in 1977 from original evidence no longer in existence, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 2 W., Index No. 170, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE T27S R2W S21 S22 S28 S27 1977</p> </div> <p>from which bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A fir, 22 ins. diam., bears N. 4 1/4° E., 18.7 ft. dist., with a healed double blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET													
	<p>A fir, 21 ins. diam., bears S. 49° E., 21.1 ft. dist., with a healed double blaze.</p> <p>A fir, 15 ins. diam., bears S. 24 3/4° W., 49.1 ft. dist., with a healed double blaze.</p> <p>A fir, 16 ins. diam., bears N. 84 1/2° W., 52.0 ft. dist., with a healed double blaze.</p>												
	<p>From the original closing cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., hereinbefore described.</p>												
	<p>N. 0° 00' 01" W., bet. secs. 32 and 33.</p>												
	<p>Ascend SW. slope.</p>												
<p>7.12</p>	<p>The witness cor. for the original closing cor. of secs. 32 and 33, established by Ware and Quimby in 1980, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Point Identifier No. 300100, and is accepted as the cor.; monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p>												
	<div style="text-align: center;"> <p>T27S R2W</p> <p>WC</p> <p>CC</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> <td style="padding: 0 5px;">S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">7 0</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">↓</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;">S4</td> </tr> </table> <p>T28S R2W</p> <p>1980 RLS1005</p> </div>	S32	S33	S			7 0			↓			S4
S32	S33	S											
		7 0											
		↓											
		S4											
	<p>from which a bearing tree mkd. by Ware and Quimby</p>												
	<p>A fir, 16 ins. diam., bears S. 39° E., 11.9 ft. dist., with a healed blaze.</p>												
<p>825</p>	<p>Gravel road, 16 ft. wide, bears east, west.</p>												
<p>1125</p>	<p>Dirt road, 16 ft. wide, bears N. 32° E. and S. 32° W.</p>												
<p>1183.55</p>	<p>The S 1/16 sec. cor. of secs. 32 and 33, established by Harold L. Ball, Oregon Registered Civil Engineer No. 6025, in 1974, recorded in the Douglas County Surveyors Office, Map File No. M53-51, and is accepted as the cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, 1 1/2 ft. base, 6 ins. high, with brass cap mkd.</p>												

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<div style="text-align: center; margin-bottom: 10px;"> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">RCE</td> <td style="padding: 0 5px;">S32</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 1/16</td> </tr> <tr> <td style="padding: 0 5px;">60</td> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S33</td> </tr> <tr> <td style="padding: 0 5px;">25</td> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">1974</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">T27S</td> <td style="padding: 0 5px;">R2W</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Ball</p> <p style="margin-left: 40px;">A hemlock, 23 ins. diam., bears N. 20 3/4° E., 34.2 ft. dist., with scribe marks S 1/16 S33 visible on a partially healed blaze.</p> <p style="margin-left: 40px;">A hemlock snag, 12 ins. diam., bears S. 77 1/4° W., 20.6 ft. dist., with scribe marks S 1/16 S32 BT visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p style="margin-left: 40px;">A hemlock, 12 ins. diam., bears S. 77° W., 9.1 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 00' 01" W., beginning new measurement.</p> <p>1303.57 The 1/4 sec. cor. of secs. 32 and 33, remonumented by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 125, and perpetuated by Kristian DeGroot, Oregon Professional Land Surveyor No. 1941, in 1998, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 263, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T27S</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">1/4 S32</td> <td style="border-left: 1px solid black; padding: 0 5px;">S33</td> </tr> </table> <p>R2W</p> <p>1968</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed fir stump, 51 ins. diam., bears N. 53 1/2° E., 23.8 ft. dist., with scribe marks 1/4 S3 BT visible on an opened blaze. (Record, N. 53° 40' E.)</p> <p style="margin-left: 40px;">A sawed fir stump, 40 ins. diam., bears N. 25 3/4° W., 5.3 ft. dist., with scribe marks 1/4 S32 visible on an opened blaze. (Record, N. 30° 10' W.)</p>	RCE	S32	S 1/16	60		S33	25		1974	S	T27S	R2W	1/4 S32	S33
RCE	S32	S 1/16													
60		S33													
25		1974													
S	T27S	R2W													
1/4 S32	S33														

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>and remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A hemlock, 22 ins. diam., bears N. 79° E., 13.4 ft. dist., with a healed blaze.</p> <p>A hemlock snag, 15 ins. diam., bears S. 45° E., 22.4 ft. dist., with scribe marks 1/4 S33 CS BT visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by DeGroot</p> <p>A hemlock, 15 ins. diam., bears S. 36 3/4° W., 21.0 ft. dist., with scribe marks 1/4 S32 BT visible on a partially healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 12" W., beginning new measurement.</p> <p>Descend NW. slope; begin posting and blazing.</p>
1255	Spring branch, 2 ft. wide, course N. 22° W.
1311.37	<p>Point for the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T27S R2W</p> <p> N 1/16</p> <p> </p> <p> S 32 S 33</p> <p> 2003</p> </div> <p>from which</p> <p>A fir, 21 ins. diam., bears S. 1/2° W., 13.7 ft. dist., mkd. N 1/16 S32 BT.</p> <p>A fir, 14 ins. diam., bears N. 54 3/4° W., 25.5 ft. dist., mkd. N 1/16 S32 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, an iron rebar, set by person(s) unknown, 5/8 in. diam., firmly set, projecting 18 ins. above the ground, bears S. 45° 26' 13" E., 8.23 ft. dist., with no cap.</p> <p>Discontinue posting and blazing.</p>
1705	Spring branch, 1 ft. wide, course N. 15° W.; desc. SW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

<p>F E E T</p> <p>2622.74</p>	<p>The cor. of secs. 28, 29, 32, and 33, remonumented by Thomas E. Shrum, Jr., Oregon Registered Engineer No. 4287, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 21, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 76, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, driven into an iron pipe, 2 ins. diam., projecting 2 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;"> USPC PROPERTY COR T27S R2W 29 28 ———— 32 33 RE 4287 DO NOT DISTURB </p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole bears S. 26 3/4° W., 13.1 ft. dist., with fallen fir trunk, size indeterminate, lying alongside, no marks visible. (Record, S. 29° W., 11.9 ft.)</p> <p>and remains of bearing trees mkd. by Shrum</p> <p style="padding-left: 40px;">A cedar stump, 10 ins. diam., bears N. 24 1/4° E., 39.3 ft. dist., with scribe marks S28 BT visible on an unhealed double blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 44 ins. diam., bears S. 31 1/2° E., 61.1 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed cedar stump, 48 ins. diam., bears S. 1° W., 60.7 ft. dist., no marks visible.</p> <p>and bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A cedar stump, 35 ins. diam., bears N. 69 1/4° W., 41.4 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 21 3/4° E., 62.8 ft. dist., mkd. T27S R2W S28 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 13 1/2° E., 17.8 ft. dist., mkd. T27S R2W S33 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 31 1/2° W., 25.3 ft. dist., mkd. T27S R2W S32 BT.</p>
-------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
2625.59	<p>A fir, 7 ins. diam., bears N. 35 1/4° W., 17.0 ft. dist., mkd. T27S R2W S29 BT.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34. N. 89° 30' 53" W., bet. secs. 28 and 33. Ascend broken N. slope.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33 at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27S R2W S 28 1/4 ————— S 33 2004</p> </div> <p>from which</p> <p>A fir, 12 ins. diam., bears N. 24 1/2° E., 9.4 ft. dist., mkd. 1/4 S28 BT.</p> <p>A fir, 16 ins. diam., bears S. 49 1/4° E., 27.0 ft. dist., mkd. 1/4 S33 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend NE. slope then descend W. slope.</p>
5251.18	<p>The cor. of secs. 28, 29, 32, and 33.</p> <hr/>
	<p>N. 0° 40' 56" W., bet. secs. 28 and 29. Ascend broken SW. slope; begin posting and blazing.</p>
395	<p>Spur, slopes west; desc. broken NW. slope.</p>
945	<p>Gravel road, 16 ft. wide, bears N. 60° E. and S. 60° W.</p>
1265	<p>Dry creek, 3 ft. wide, course N. 68° W.; continue desc. NW. slope.</p>
2385	<p>Dry creek, 3 ft. wide, course N. 62° W.; asc. NW. slope.</p>
	<p>Ascend broken W. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
2613.74	<p>The 1/4 sec. cor. of secs 28 and 29, determined at record bearing and dist. from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 30 ins. diam., bears S. 60° 20' E., 10.6 ft. dist., with scribe marks 1/4 S28 B visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S R 2 W</p> <p>1/4</p> <p>S 29 S 28</p> <p>2003</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 16 1/2° E., 13.8 ft. dist., mkd. 1/4 S28 BT.</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears N. 77 1/4° W., 19.1 ft. dist., mkd. 1/4 S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 29' 02" E., beginning new measurement.</p> <p>Ascend broken SW. slope; continue posting and blazing.</p>
30	Spur, slopes N. 60° W.; desc. broken NW. slope.
205	Ravine, drains S. 75° W.; asc. broken SW. slope.
875	Spur, slopes S. 70° W.; desc. broken NW. slope.
1306.24	<p>Point for the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<div style="text-align: center; margin-bottom: 10px;"> T27S R2W N 1/16 S29 S28 2004 </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 12 ins. diam., bears N. 34 1/4° E., 23.7 ft. dist., mkd. N 1/16 S28 BT.</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 16 3/4° W., 19.3 ft. dist., mkd. N 1/16 S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <p>2450 Gravel road, 16 ft. wide, bears N. 61° E. and W., in a curve.</p> <p>2612.48 The cor. of secs. 20, 21, 28, and 29, remonumented by the Douglas County Surveyors Office in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 48, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> COUNTY SURVEYORS OFFICE T27S <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S20</td> <td style="padding: 0 5px;">S21</td> <td style="padding: 0 5px;">2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S29</td> <td style="padding: 0 5px;">S28</td> <td style="padding: 0 5px;">W</td> </tr> </table> 1964 </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed cedar stump, 25 ins. diam., bears N. 56° E., 31.7 ft. dist., no marks visible on a decayed blaze. (Record, N. 56° 40' E.)</p> <p style="margin-left: 40px;">A sawed cedar stump, 40 ins. diam., bears S. 22° E., 40.3 ft. dist., no marks visible. (Record, S. 22° 18' E.)</p> <p style="margin-left: 40px;">A cedar, 31 ins. diam., bears N. 30° W., 69.5 ft. dist., with a healed blaze. (Record, N. 28° 30' W., 61.4 ft.)</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="margin-left: 40px;">A cedar, 20 ins. diam., bears N. 21 1/2° E., 23.4 ft. dist., with a healed blaze.</p>	S20	S21	2	S29	S28	W
S20	S21	2					
S29	S28	W					

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A hemlock, 15 ins. diam., bears S. 19 3/4° E., 17.3 ft. dist., with fragmentary scribe marks visible on a mostly healed blaze.</p> <p>A cedar, 14 ins. diam., bears S. 51 1/4° W., 6.4 ft. dist., with fragmentary scribe marks visible on a mostly healed blaze.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89° 38' 10" W., bet. secs. 21 and 28.</p> <p>Descend broken NW. slope.</p>
175	Gravel road, 16 ft. wide, bears S. 34° E. and N. 34° W.
2380	Wolf Creek, 3 ft. wide, course N. 20° W.; asc. broken NE. slope.
2623.14	<p>Point for the 1/4 sec. cor. of secs. 21 and 28 at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. diam., to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27S R2W</p> <p>S 21</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4</p> <p>S 28</p> <p>2004</p> </div> <p>from which</p> <p>A fir, 15 ins. diam., bears N. 12 1/4° E., 6.1 ft. dist., mkd. 1/4 S21 BT.</p> <p>A fir, 14 ins. diam., bears S. 22° E., 23.3 ft. dist., mkd. 1/4 S28 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Continue asc. broken NE. slope; begin posting and blazing.</p>
3590	Spur, slopes N. 20° W.; desc. broken NW. slope.
3915	Spring branch, 1 ft. wide, course N. 6° E.; asc. broken NE. slope.
3934.71	Point for the W 1/16 sec. cor. of secs. 21 and 28.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>S 21 W 1/16 ————— S 28 2004</p> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 6 ins. diam., bears N. 78 1/2° E., 39.1 ft. dist., mkd. W 1/16 S21 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 39 3/4° E., 15.6 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>Discontinue posting and blazing.</p>
4305	Gravel road, 16 ft. wide, bears S. 14° E. and N. 14° W.
5246.28	<p>The cor. of secs. 20, 21, 28, and 29.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the closing cor. of secs. 31 and 32 only, on the S. bdy. of the Tp.</p> <p>N. 0° 41' 31" E., bet. secs. 31 and 32.</p> <p>Ascend E. slope.</p>
300	Spur, slopes S. 15° E.; desc. N. slope.
695	Gravel road, 12 ft. wide, bears N. 65° E. and S. 65° W.
970	Gravel road, 10 ft. wide, bears S. 60° E. and N. 60° W.; asc. S. slope.
1235.22	<p>Point for the S 1/16 sec. cor. of sec. 32 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T27S R2W S 1/16 S32 2003</p> </div> <p>from which</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 14 ins. diam., bears N. 77 1/4° E., 27.2 ft. dist., mkd. S 1/16 S32 BT.</p> <p>A fir, 10 ins. diam., bears S. 46 1/2° E., 43.9 ft. dist., mkd. S 1/16 S32 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend steep S. slope; begin posting and blazing.</p>
2085	Spur, slopes S. 54° E.; desc. steep NE. slope.
2395	Gravel road, 10 ft. wide, bears S. 64° E. and N. 64° W.
2525.24	<p>The 1/4 sec. cor. of sec. 32 only, remonumented by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 105, and perpetuated by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 207, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T27S 1/4 S32 R2W 1968</p> <p>from which the remains of the original bearing trees</p> <p>A tin-capped, sawed fir stump, 17 ins. diam., bears S. 41 1/4° E., 11.5 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, S. 44°10' E., 10.6 ft., rescribed by the Douglas County Surveyors Office)</p> <p>A roothole bears N. 3° 30' W., 12.5 ft. dist., no trunk remains.</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office</p> <p>A tin-capped fir stump, 30 ins. diam., bears N. 27° E., 20.2 ft. dist., with no marks visible on a decayed blaze.</p> <p>and remains of bearing trees mkd. by Ware and Quimby</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>A sawed fir stump, 29 ins. diam., bears S. 22° W., 33.2 ft. dist., with scribe marks 1/4 S32 visible on a partially healed blaze.</p> <p>A sawed fir stump, 20 ins. diam., bears N. 74 1/2° W., 42.7 ft. dist., with scribe marks 1/4 S32 BT visible on a partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 22 1/2° E., 6.0 ft. dist., mkd. 1/4 S32 BT.</p> <p>A fir, 10 ins. diam., bears S. 85° E., 10.5 ft. dist., mkd. 1/4 S32 BT.</p> <hr/> <p>N. 0° 38' 26" E., beginning new measurement.</p> <p>Continue desc. steep NE. slope; continue posting and blazing.</p>
1455	Ravine, drains N. 84° E.; asc. broken SE. slope.
2035	Spur, slopes N. 65° E.; desc. broken NE. slope.
2611.13	<p>The cor. of secs. 29, 30, 31, and 32, perpetuated by person(s) unknown in 1954, from original evidence no longer in existence, remonumented by Thomas E. Shrum, Jr., Oregon Registered Engineer No. 4287, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 24, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 120, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">USPC PROPERTY COR T27S R2W 30 29 31 32 RE 4287 DO NOT DISTURB</p> <p>from which the remains of a bearing tree mkd. by Shrum</p> <p>A sawed, decayed, burnt cedar stump, 29 ins. diam., bears S. 49 1/4° E., 14.9 ft. dist., no marks visible.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A fir snag, 16 ins. diam., bears N. 88 1/4° E., 118.0 ft. dist., with blazed face and axe marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed, decayed fir stump, 27 ins. diam., bears N. 7 3/4° W., 161.6 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 21 3/4° E., 30.5 ft. dist., mkd. T27S R2W S29 BT.</p> <p>A fir, 11 ins. diam., bears S. 74° E., 9.2 ft. dist., mkd. T27S R2W S32 BT.</p> <p>A fir, 7 ins. diam., bears S. 60 1/4° W., 5.0 ft. dist., mkd. T27S R2W S31 BT.</p> <p>A fir, 11 ins. diam., bears N. 82 1/2° W., 41.9 ft. dist., mkd. T27S R2W S30 BT.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89° 48' 19" W., bet. secs. 29 and 32.</p> <p>Descend broken NW. slope; begin posting and blazing.</p>
120	Gravel road, 12 ft. wide, bears S. 6° E. and N. 13° W., in a curve.
1115	Spring branch, 2 ft. wide, course N. 23° W.
1315.80	Point for the E 1/16 sec. cor. of secs. 29 and 32, not monumented.
1415	Spring branch, 2 ft. wide, course N. 50° E.
2280	West Fork Wolf Creek, 1 ft. wide, course N. 14° W.; asc. NW. slope.
2631.60	The 1/4 sec. cor. of secs. 29 and 32, remonumented by Thomas E. Shrum, Jr., Oregon Registered Engineer No. 4287, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 25, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 84, and further perpetuated by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 206, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	USPC PROPERTY COR T27S R2W $\frac{29}{32}$ RE 4287 DO NOT DISTURB
	from which the remains of the original bearing trees A roothole bears N. 50° E., 11.2 ft. dist., with fallen cedar trunk, 16 ins. diam., lying alongside, scribe marks 1/4 S29 BT visible on an unhealed blaze. (rescribed by Shrum) A cedar stump, 11 ins. diam., bears S. 36 1/2° W., 19.1 ft. dist., with fallen trunk lying alongside, with a healed blaze. and remains of a bearing tree mkd. by the Douglas County Surveyors Office A sawed hemlock stump, 9 ins. diam., bears S. 22° E., 30.2 ft. dist., with fallen trunk lying alongside, fragmentary scribe marks visible on a partially healed blaze. and bearing trees mkd. by Ware and Quimby A fir, 18 ins. diam., bears N. 13 1/4° E., 33.8 ft. dist., with a healed blaze. A fir, 17 ins. diam., bears S. 56 1/4° W., 42.7 ft. dist., with a healed blaze. <hr style="width: 20%; margin: 10px auto;"/> S. 89° 37' 14" W., beginning new measurement. Ascend E. slope; continue posting and blazing.
300	Gravel road, 12 ft. wide, bears S. 38° E. and N. 38° W.
1790	Gravel road, 16 ft. wide, bears N. 8° E. and S. 8° W.
2145	Gravel road, 12 ft. wide, bears N. 34° E. and S. 34° W.
2616.06	The cor. of secs. 29, 30, 31, and 32. <hr style="width: 80%; margin: 10px auto;"/> N. 89° 52' 39" W., bet. secs. 30 and 31. Ascend broken NE. slope; begin posting and blazing.
1830	Spur, slopes N. 30° W.; desc. SW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

<p>F E E T</p> <p>2630.30</p>	<p>The 1/4 sec. cor. of sec. 30 only, remonumented by Thomas E. Shrum, Jr., Oregon Registered Engineer No. 4287, in 1954, from original evidence no longer in existence, perpetuated by himself in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 29, further perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 109, further perpetuated by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 240, monumented with a truck axle, 1 3/8 ins. diam., firmly set, projecting 3 ins. above ground, with 5 1/2 ins. diam. flange on top, mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-bottom: 1px solid black; padding: 0 10px;">30</td> <td style="padding: 0 5px; text-align: center;">T 27 S</td> </tr> <tr> <td style="padding: 0 10px;">31</td> <td style="padding: 0 5px; text-align: center;">R 2 W</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed stump, size and species indeterminate, bears N. 46° W., 12.5 ft. dist., no marks visible.</p> <p>and remains of a bearing tree mkd. by Shrum in 1962</p> <p style="padding-left: 40px;">A fir stump, size indeterminate, bears N. 49° E., 35.6 ft. dist., with scribe marks /4 S30 BT visible on decayed face.</p> <p>and a bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 54 1/2° E., 35.3 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 47° W., 14.9 ft. dist., with a healed double blaze.</p> <p>(Note: Marginal comments in Wygant's 1911 field notes indicate "This cor. refers to Sec. 30 only".)</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0° 08' 38" W., bet. secs. 29 and 30.</p> <p>Descend broken NE. slope; begin posting and blazing.</p>	30	T 27 S	31	R 2 W
30	T 27 S				
31	R 2 W				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
620	Gravel road, 15 ft. wide, bears S. 82° E. and N. 82° W.
1050	Spring branch, 1 ft. wide, course N. 65° E.
2620.78	<p>The 1/4 sec. cor. of secs. 29 and 30, remonumented by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 91, and perpetuated by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 236, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T27S 1/4 S30 S29 R2W 1968</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole bears N. 33° E., 15.2 ft. dist., no trunk remains.</p> <p style="padding-left: 40px;">A roothole bears N. 10° W., 7.9 ft. dist., no trunk remains.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears S. 39 1/2° E., 7.2 ft. dist., with scribe marks /4 S29 CS BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 50° W., 37.5 ft. dist., with a partially healed blaze.</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears N. 47 3/4° W., 50.4 ft. dist., with scribe marks /W S30 CS BT visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 83 3/4° W., 14.9 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 47° E., 6.4 ft. dist., mkd. 1/4 S29 BT.</p> <hr style="width: 60%; margin-left: 40px;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of secs. 20 and 29, determined at record bearing and dist. from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A cedar stump, 27 ins. diam., bears N. 21° E., 25.7 ft. dist., with scribe marks BT visible on fragmentary remains of the reverse scribe of a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S R 2 W</p> <p>S20</p> <p>1/4 —————</p> <p>S29</p> <p>2004</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 27° E., 3.9 ft. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 69 1/4° E., 11.2 ft. dist., mkd. 1/4 S29 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established at proportionate dist. (overlooking existing original evidence) as the 1/4 sec. cor. of secs. 20 and 29 by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is not accepted as the cor. and not utilized in the course of this survey, bears N. 9° 27' 28" W., 18.52 ft. dist., monumented with an aluminum post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. CHAMPION INTL CORP T27S R2W S20 1/4 S29 1985 PLS 1988.</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 33 3/4° W., 18.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 22 3/4° W., 16.3 ft. dist., with a healed blaze.</p> <p>N. 89° 31' 20" W., bet. secs. 20 and 29.</p> <p>Ascend broken NE. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEEET 1315.44	<p>Point for the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>T27S</td> <td>R2W</td> </tr> <tr> <td></td> <td>S 20</td> <td></td> </tr> <tr> <td>W 1/16</td> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td></td> <td>S 29</td> <td></td> </tr> <tr> <td></td> <td>2004</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 54 3/4° W., 23.7 ft. dist., mkd. W 1/16 S29 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 14 3/4° W., 22.1 ft. dist., mkd. W 1/16 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>From this corner, a point established using improper control as the W 1/16 sec. cor. of secs. 20 and 29, by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is not accepted as the cor. and not utilized in the course of this survey, bears N. 10° 11' 40" W., 9.39 ft. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. T27S R2W 20 W 1/16 29 1985 PLS 1988 DO NOT DISTURB.</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 21 ins. diam., bears N. 75 1/4° E., 22.5 ft. dist., no marks visible and a steel spike driven in the center.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 62 1/2° W., 35.4 ft. dist., with a healed blaze.</p> <p>Continue asc. broken NE. slope; begin posting and blazing.</p>		T27S	R2W		S 20		W 1/16				S 29			2004	
	T27S	R2W														
	S 20															
W 1/16																
	S 29															
	2004															
2290	Gravel road, 16 ft. wide, bears S. 44° E. and N. 44° W.															
2630.88	<p>The cor. of secs. 19, 20, 29, and 30, remonumented by the Douglas County Surveyors Office in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 49, perpetuated by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 231, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>															

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">COUNTY SURVEYORS OFFICE</p> <p style="text-align: center;">T27S <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S19</td> <td style="padding: 0 5px;">S20</td> <td style="padding: 0 5px;">R 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S30</td> <td style="padding: 0 5px;">S29</td> <td style="padding: 0 5px;">W</td> </tr> </table> 1964</p> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A cedar, 23 ins. diam., bears N. 48° E., 24.4 ft. dist., with a healed blaze. (Record, N. 48° 10' E.)</p> <p style="margin-left: 40px;">A cedar, 27 ins. diam., bears S. 65 1/2° E., 17.8 ft. dist., with a healed blaze. (Record, S. 64° 10' E.)</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears S. 62 1/2° W., 24.9 ft. dist., with scribe marks 27S R2W S19 BT on a partially healed double blaze. (Record, S. 62° 10' W., 26.4 ft.)</p> <p>and bearing tree mkd. by Geisler</p> <p style="margin-left: 40px;">A cedar, 13 ins. diam., bears N. 29° W., 31.8 ft. dist., with scribe marks 27S R2W S19 BT visible on a partially healed double blaze.</p> <hr/> <p>N. 0° 12' 12" W., bet. secs. 19 and 20.</p> <p>Descend broken NE. slope; continue posting and blazing.</p> <p>200 Gravel road, 16 ft. wide, bears S. 62° E. and N. 62° W.</p> <p>645 Spring branch, 2 ft. wide, course N. 65° E.; asc. broken SE. slope.</p> <p>1125 Gravel road, 12 ft. wide, bears N. 56° E. and S. 66° W.</p> <p>1306.10 Point for the S 1/16 sec. cor. of secs. 19 and 20.</p> <p style="margin-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="margin-left: 80px;">T27S R2W <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">S 1/16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S19</td> <td style="padding: 0 5px;">S20</td> </tr> </table> 2004</p> <p>from which</p>	S19	S20	R 2	S30	S29	W	S 1/16	S19	S20
S19	S20	R 2								
S30	S29	W								
S 1/16										
S19	S20									

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<p>A fir, 14 ins. diam., bears N. 89 1/2° E., 16.9 ft. dist., mkd. S 1/16 S20 BT.</p> <p>A fir, 8 ins. diam., bears S. 5 1/4° W., 17.1 ft. dist., mkd. S 1/16 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing; desc. broken NE. slope.</p>		
2612.20	<p>The 1/4 sec. cor. of secs. 19 and 20, remonumented by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 116, and perpetuated by Thomas E. Shrum, Jr., Oregon Professional Land Surveyor No. 1706, in 1977, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 168, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T27S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">1/4 S19</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S20</td> </tr> </table> <p>R2W</p> <p>1968</p> </div> <p>from which the remains of the original bearing trees</p> <p>A burned, decayed cedar stump, size indeterminate, bears S. 40 3/4° E., 32.3 ft. dist., no marks visible. (Record, S. 41° 30' E.)</p> <p>A cedar stump, 19 ins. diam., bears S. 33 3/4° W., 13.9 ft. dist., no marks visible on an opened blaze. (Record, S. 33° 20' W.)</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office</p> <p>A tin-capped, sawed hemlock stump, 16 ins. diam., bears S. 25 3/4° W., 28.8 ft. dist., with scribe marks 1/4 S19 CS BT visible on an open double blaze.</p> <p>and remains of a bearing tree mkd. by Shrum</p> <p>A tin-capped, sawed cedar stump, 6 ins. diam., bears N. 71° E., 9.2 ft. dist., with scribe marks 1/4 S20 T27S R2W BT visible on an open double blaze.</p> <p>and new bearing trees</p>	1/4 S19	S20
1/4 S19	S20		

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

F E E T	<p>A fir, 9 ins. diam., bears N. 26° E., 23.4 ft. dist., mkd. 1/4 S20 BT.</p> <p>A fir, 7 ins. diam., bears S. 87 1/2° W., 11.0 ft. dist., mkd. 1/4 S19 BT.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20, remonumented by the Douglas County Surveyors Office in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 46, and perpetuated by the Douglas County Surveyors Office in 1981, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 220, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T27S S18 S17 S19 S20 R2W 1964</p> <p>from which the remains of the original bearing trees</p> <p>A tin-capped fir stump, 36 ins. diam., bears N. 22° E., 33.7 ft. dist., no marks visible. (Record, N. 19° 30' E.)</p> <p>A tin-capped cedar stump, 40 ins. diam., bears N. 19° W., 11.2 ft. dist., with a healed blaze. (Record, N. 25° 0' W.)</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1964</p> <p>A tin-capped fir stump, 42 ins. diam., bears S. 70 1/4° W., 24.2 ft. dist., no marks visible.</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1981</p> <p>A cedar snag, 13 ins. diam., bears S. 11 3/4° E., 7.1 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 42 1/2° E., 13.8 ft. dist., mkd. T27S R2W S17 BT.</p> <p>A fir, 5 ins. diam., bears S. 69 3/4° E., 11.3 ft. dist., mkd. X BT.</p>
---------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 6 ins. diam., bears S. 19 1/4° W., 12.8 ft. dist., mkd. T27S R2W S19 BT.</p> <p>A fir, 6 ins. diam., bears N. 57 3/4° W., 3.5 ft. dist., mkd. T27S R2W S18 BT.</p> <p>S. 89° 39' 15" W., bet. secs. 18 and 19.</p> <p>Ascend broken N. slope.</p>
2625.97	<p>The 1/4 sec. cor. of secs. 18 and 19, determined at record bearing and dist. from the remains of the original bearing trees</p> <p>A sawed hemlock stump, 38 ins. diam., bears S. 24° 20' W., 25.7 ft. dist., with blazed face and axe marks visible on opened blaze.</p> <p>A stumphole, size indeterminate, bears N. 81° 10' W., 17.2 ft. dist., with decayed remains of a hemlock stump, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S R 2 W</p> <p>S18</p> <p>1/4 —————</p> <p>S19</p> <p>2003</p> </div> <p>from which new accessories</p> <p>An aluminum rod, 72 ins. long, 3/4 in. diam., driven 71 ins. in the ground, bears N. 6° 47' 44" E., 20.15 ft. dist., with aluminum cap mkd. RM T27S R2W S18 20.15 FT TO COR 2003 and an arrow pointing toward the cor.</p> <p>A fir, 4 ins. diam., bears S. 65 1/2° W., 16.3 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 36' 29" W., beginning new measurement.</p>
2818.51	<p>Intersect the E. bdy. of sec. 24, T. 27 S., R. 3 W., true point for the closing cor. of secs. 18 and 19.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T 27 S	
R 3 W	R 2 W
	S 18
	----- CC
	S 19

2003

from which

A fir, 20 ins. diam., bears N. 29 1/4° E., 27.5 ft. dist., mkd. T27S R2W S18 CC BT.

A fir, 11 ins. diam., bears S. 64 3/4° E., 28.3 ft. dist., mkd. T27S R2W S19 CC BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, the original closing cor. of secs. 18 and 19, established by Wygant in 1911, remonumented by the Douglas County Surveyors Office in 1966, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700373, bears N. 89° 36' 29" W., 58.35 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. COUNTY SURVEYORS OFFICE T27S R CC S18 R 3 2 W S19 W 1966

from which the remains of the original bearing trees

A sawed and decayed fir stump, 17 ins. diam., bears N. 62 1/2° E., 4.2 ft. dist., with fragmentary scribe marks visible on a partially opened blaze. (Record, 3.3 ft.)

A decayed fir stump, size indeterminate, bears S. 16 1/4° E., 6.9 ft. dist., with fragmentary scribe marks T BT visible on a partially opened blaze. (Record, S. 8 1/2° W., 7.9 ft.)

There is no remaining evidence of the bearing trees mkd. by the Douglas County Surveyors Office in 1966, due to logging activity in this area.

Add the marks AM on the brass cap.

Subdivision of Section 20,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0° 56' 15" E., on the N. and S. centerline of sec 20.</p> <p>Descend broken E. slope.</p>
1317.62	<p>Point for the center S 1/16 sec. cor. of sec. 20, not monumented.</p> <p>Ascend broken SE. slope</p>
2635.24	<p>Point for the center 1/4 sec. cor. of sec. 20 at the intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W C 1/4 . S20 2004</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 9 1/4° E., 10.3 ft. dist., mkd. C 1/4 S20 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 65 1/2° E., 11.8 ft. dist., mkd. C 1/4 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue asc. broken SE. slope.</p>
5232.61	<p>The 1/4 sec. cor. of secs. 17 and 20, remonumented by the Douglas County Surveyors Office in 1964, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 45, perpetuated by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 126, and further perpetuated by the Douglas County Surveyors Office in 1981, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 219, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>

Subdivision of Section 20,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	COUNTY SURVEYORS OFFICE T27S 1/4 <u> S17 </u> S20 R2W 1964
	from which the remains of the original bearing trees A roothole, bears S. 32° W., 22.7 ft. dist., with fallen hemlock trunk, size indeterminate, lying alongside, no marks visible. (Record, S. 29° 50' W., 21.1 ft.)
	and remains of bearing trees mkd. by the Douglas County Surveyors Office in 1981 A cedar, 17 ins. diam., bears N. 76 1/2° E., 8.0 ft. dist., with a healed double blaze.
	A decayed fir stump, size indeterminate, bears S. 32 1/2° E., 13.1 ft. dist., no marks visible.
	A fir snag, 28 ins. diam., bears N. 24 1/4° W., 46.2 ft. dist., with scribe marks 1/4 S17 CS BT visible on a partially healed double blaze.
	and new bearing tree A fir, 4 ins. diam., bears S. 16 3/4° W., 11.6 ft. dist., mkd. X BT.
	<hr/> From the 1/4 sec. cor. of secs. 20 and 21, determined at record bearing and dist. from the remains of the original bearing trees A sawed fir stump, 45 ins. diam., bears N. 85 1/2° E., 5.9 ft. dist., with scribe marks 1/4 S21 B visible on fragmentary remains of the reverse of a healed blaze. (Record, N. 85° 30' W.) Note: Blaze faces S. 85 1/2° W.
	A sawed cedar stump, 12 ins. diam., bears S. 40° W., 18.5 ft. dist., no marks visible.
	At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

Subdivision of Section 20,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	T 27 S R 2 W 1/4 S 20 S 21 2004
	from which
	A fir, 7 ins. diam., bears S. 17 3/4° E., 19.3 ft. dist., mkd. 1/4 S21 BT.
	A fir, 12 ins. diam., bears S. 60° W., 14.5 ft. dist., mkd. 1/4 S20 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	S. 89° 59' 01" W., on the E. and W. centerline of sec. 20.
	Descend broken W. slope and asc. broken SE. slope.
2657.30	The center 1/4 sec. cor. of sec. 20.
3998.73	Point for the center W 1/16 sec. cor. of sec. 20, not monumented.
5340.16	The 1/4 sec. cor. of secs. 19 and 20.

	From the W 1/16 sec. cor. of secs. 20 and 29.
	N. 0° 22' 11" W., on the calculated N. and S. centerline of the SW 1/4 of sec. 20.
	Descend broken NE. slope; begin posting and blazing.
145	Gravel road, 12 ft. wide, bears N. 65° E. and S. 65° W.
1160	Creek, 3 ft. wide, course N. 45° E.; asc. broke S. slope.
1311.79	Point for the SW 1/16 sec. cor. of sec. 20 at its calculated position.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T27S R2W SW 1/16 . S20 2004

**Subdivision of Section 20,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 75° E., 35.0 ft. dist., mkd. SW 1/16 S20 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 16 1/2° W., 18.9 ft. dist., mkd. SW 1/16 S20 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr/> <p>N. 89° 46' 18" W., on the calculated E. and W. centerline of the SW 1/4 of sec. 20.</p> <p>Ascend broken E. slope; continue posting and blazing.</p>
1240	Gravel road, 12 ft. wide, bears N. 4° E. and S. 10° W., in a curve.
1328.42	The S 1/16 sec. cor. of secs. 19 and 20.
	<hr/> <p>Subdivision of Section 28, T. 27 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 0° 07' 07" W., on the N. and S. centerline of sec. 28.</p> <p>Descend broken NE. slope.</p>
2615.75	<p>Point for the center 1/4 sec. cor. of sec. 28 at the intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W</p> <p style="text-align: center;">C 1/4 · S28</p> <p style="text-align: center;">2004</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 48° E., 16.5 ft. dist., mkd. C 1/4 S28 BT.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 1 3/4° W., 8.9 ft. dist., mkd. C 1/4 S28 BT.</p>

Subdivision of Section 28,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue desc. broken NE. slope.</p>
3923.65	<p>Point for the center N 1/16 sec. cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27S R2W</p> <p> C</p> <p>N 1/16 S28</p> <p> C</p> <p> 2004</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 54 3/4° E., 15.9 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 62 3/4° W., 15.8 ft. dist., mkd. CN 1/16 S28 BT.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue desc. broken NE. slope; begin posting and blazing.</p>
4300	<p>Gravel road, 10 ft. wide, bears N. 20° E. and S. 8° W., in a curve.</p>
4510	<p>Gravel road, 16 ft. wide, bears S. 38° E. and N. 38° W.</p>
4710	<p>Enter excavation, edge bears east and west.</p>
5035	<p>Leave excavation; desc. steep NW. slope.</p>
5231.55	<p>The 1/4 sec. cor. of secs 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>N. 89° 33' 59" W., on the E. and W. centerline of sec. 28.</p> <p>Descend W. slope and ascend NE. slope.</p>
2615.12	<p>The center 1/4 sec. cor. of sec. 28.</p>
3940.60	<p>Point for the center W 1/16 sec. cor. of sec. 28, not monumented.</p>

Subdivision of Section 28,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
5266.08	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>N. 89° 36' 05" W., on the E. and W. centerline of the NE 1/4 of sec. 28.</p> <p>Ascend broken SW. slope; begin posting and blazing.</p>
70	Spur, slopes S. 20° E.; desc. broken SW. slope.
1490	Creek, 2 ft. wide, course N. 16° W.; asc. broken NW. slope.
1640	Spur, slopes N. 63° W.; desc. broken SW. slope.
1875	Creek, 3 ft. wide, course N. 20° W.; asc. broken NE. slope.
2140	Spur, slopes N. 10° W.; desc. broken NW. slope.
2255	Creek, 2 ft. wide, course north; asc. broken NE. slope.
2619.13	<p>The center N. 1/16 sec. cor. of sec. 28.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>S. 89° 36' 04" E., on the calculated E. and W. centerline of the NW 1/4 of sec. 28.</p> <p>Ascend broken NW. slope; begin posting and blazing.</p>
760	Spur, slopes North; desc. broken NE. slope.
1318.52	<p>Point for the NW 1/16 sec. cor. of sec. 28 at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W NW 1/16 · S28</p> <p style="text-align: center;">2004</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 69° E., 20.6 ft. dist., mkd. NW 1/16 S28 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 35 1/4° W., 29.2 ft. dist., mkd. NW 1/16 S28 BT.</p>

**Subdivision of Section 28,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 0° 10' 57" E., on the calculated N. and S. centerline of the NW 1/4 of sec. 28.</p> <p>Descend broken NE. slope; continue posting and blazing.</p> <p>495 Creek, 1 ft. wide, course N. 14° W.; asc. broken SW. slope.</p> <p>625 Spur, slopes N. 20° W.; desc. broken NE. slope.</p> <p>650 Gravel road, 12 ft. wide, bears S. 80° E. and N. 80° W.</p> <p>1307.06 The W 1/16 sec. cor. of secs 21 and 28.</p> <p>Discontinue posting and blazing.</p> <hr/> <p style="text-align: center;">Subdivision of Section 29, T. 27 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 0° 02' 05" W., on the N. and S. centerline of sec. 29.</p> <p>Descend broken N. slope; begin posting and blazing.</p> <p>840 Gravel road, 16 ft. wide, bears N. 80° E. and S. 80° W.</p> <p>2604.03 Point for the center 1/4 sec. cor. of sec. 29 at the intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27S R2W C 1/4 . S 29 2003</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 39 3/4° E., 17.6 ft. dist., mkd. C 1/4 S29 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 66 1/2° W., 15.2 ft. dist., mkd. C 1/4 S29 BT.</p>
------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Subdivision of Section 29,
T. 27 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Discontinue posting and blazing; continue desc. broken NE. slope.
5202.44	The 1/4 sec. cor. of secs. 20 and 29.

	From the 1/4 sec. cor. of secs. 28 and 29.
	S. 89° 59' 14" W., on the E. and W. centerline of sec. 29.
	Descend broken NW. slope and ascend NE. slope.
2601.73	The center 1/4 sec. cor. of sec. 29.
	Continue asc. broken NE. slope; begin posting and blazing.
3515	Spur, slopes N. 30° E.; desc. broken NW. slope.
3870	Ravine, drains N. 40° E.; asc. broken SE. slope.
4495	Spur, slopes N. 40° E.; desc. broken NW. slope.
4840	Spur, slopes north; desc. broken W. slope.
4985	Spring branch, 1 ft. wide, course N. 35° W.; asc. NE. slope.
5222.43	The 1/4 sec. cor. of secs. 29 and 30.

	Subdivision of Section 30, T. 27 S., R. 2 W., Willamette Meridian, Oregon

	From the 1/4 sec. cor. of sec. 30 only.
	N. 0° 05' 05" E., on the N. and S. centerline of sec. 30.
	Descend broken NW. slope; begin posting and blazing.
885	Gravel road, 15 ft. wide, bears N. 40° E. and S. 40° W.
2565	Gravel road, 15 ft. wide, bears N. 33° E. and S. 33° W.
2648.87	The center 1/4 sec. cor. of sec. 30, established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 2 W., Index No. 235, and is accepted as the cor., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.

Subdivision of Section 30,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	T27S R2W C 1/4 S30 . 1985 PLS 1988
	from which bearing trees mkd. by Geisler A fir, 11 ins. diam., bears N. 15° E., 12.2 ft. dist., with a healed double blaze. A cedar, 9 ins. diam., bears S. 79 1/4° E., 4.6 ft. dist., with fragmentary scribe marks visible on a partially healed double blaze. Discontinue posting and blazing. <hr style="width: 20%; margin: auto;"/> N. 0° 04' 14" E., beginning new measurement. Ascend SW. slope.
1296.60	The center N 1/16 sec. cor. of sec. 30, established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, and recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is accepted as the cor., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. <div style="text-align: center;"> PLS 1988 C N 1/16 S30 C 1985 DO NOT DISTURB </div> from which bearing trees mkd. by Geisler A cedar, 16 ins. diam., bears N. 11 1/2° E., 12.5 ft. dist., with scribe marks CN S16 S30 visible on a partially healed blaze. A fir, 17 ins. diam., bears S. 55 1/4° E., 15.8 ft. dist., with a healed blaze. <hr style="width: 20%; margin: auto;"/> N. 0° 07' 26" E., beginning new measurement. Descend NW. slope.
1296.57	The 1/4 sec. cor. of secs. 19 and 30, remonumented by the Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Index No. 112, monumented with an iron post,

Subdivision of Section 30,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<p>1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T27S R2W S19 1/4 ————— S30 1968</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 1/2° E., 20.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 31° W., 14.5 ft. dist., with a healed blaze. (Rescribed by the Douglas County Surveyors Office)</p> <p>and bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 39° E., 27.3 ft. dist., with a healed blaze.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89° 14' 49" W., on the E. and W. centerline of sec. 30.</p> <p>Descend NW. slope and asc. E. slope.</p>
1309.81	<p>The center E 1/16 sec. cor. of sec. 30, established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, and recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is accepted as the cor., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">1985 E 1/16 C ————— C S30 PLS 1988</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 31 3/4° E., 27.8 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 51 3/4° W., 41.8 ft. dist., with a healed double blaze.</p>

Subdivision of Section 30,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>From this corner, an iron rebar, set by person(s) unknown, 5/8 in. diam., firmly set, projecting 18 ins. above the ground, bears S. 43° 42' 28" W., 18.17 ft. dist., with no cap, from which the remains of bearing trees mkd. by person(s) unknown</p> <p>A sawed fir stump, 56 ins. diam., bears N. 47° E., 16.0 ft. dist., no marks visible.</p> <p>A cedar snag, 20 ins. diam., bears S. 17 1/2° E., 14.7 ft. dist., with smoothed face and fragmentary scribe marks visible.</p>
	<hr/> <p>N. 89° 16' 42" W., beginning new measurement.</p>
	<p>Continue asc. broken NW slope; begin posting and blazing.</p>
60	<p>Gravel road, 15 ft. wide, bears N. 20° E. and S. 20° W.</p>
535	<p>Spur, slopes N. 10° E.; desc. broken NE. slope.</p>
1165	<p>Gravel road, 15 ft. wide, bears N. 30° E. and S. 30° W.</p>
1309.90	<p>The center 1/4 sec. cor. of sec. 30.</p>
	<p>Discontinue posting and blazing.</p>
	<hr/> <p>N. 89° 14' 41" W., beginning new measurement.</p>
	<p>Continue desc. broken NW. slope.</p>
1321.46	<p>The center W 1/16 sec. cor. of sec. 30, established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, and recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is accepted as the cor., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd.</p>
	<p>PLS 1988 W 1/16 C———C S30 1985 DO NOT DISTURB</p>
	<p>from which bearing trees mkd. by Geisler</p>
	<p>A fir, 14 ins. diam., bears N. 9 3/4° E., 24.3 ft. dist., with a healed double blaze.</p>
	<p>A fir, 21 ins. diam., bears N. 61 1/4° W., 2.4 ft. dist., with a healed double blaze.</p>
	<hr/>

Subdivision of Section 30,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	<p>N. 89° 16' 38" W., beginning new measurement.</p> <p>Continue desc. broken NW. slope; begin posting and blazing.</p>
260	<p>Creek, 4 ft. wide, course N. 10° W.; asc. broken NE. slope.</p>
890	<p>Spur, slopes N. 30° W.; desc. broken W. slope.</p>
1551.79	<p>The 1/4 sec. cor. of sec. 30 only, on the W. bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the east boundary, T. 27 S., R. 3 W., executed concurrently under this same group.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 30.</p> <p>N. 0° 06' 51" W., on the N. and S. centerline of the NE 1/4 of sec. 30.</p> <p>Descend broken NE. slope; begin posting and blazing.</p>
1303.40	<p>True point for the NE 1/16 sec. cor. of sec. 30, established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, and recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is accepted as the cor., falls on a toppled stump, impracticable to monument.</p> <p>From this point, a point established by Geisler as a witness cor. bears S. 89° 33' 49" E., 3.80 ft. dist. This point now functions as a reference monument; monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">WC NE 1/16 S30</p> <p style="text-align: center;">1985 1988</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 41° E., 15.5 ft. dist., with scribe mark X visible at breast height and a healed blaze at base.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 23° E., 15.6 ft. dist., with a healed blaze.</p> <hr/> <p>N. 89° 33' 49" W., on the E. and W. centerline of the NE 1/4 of sec. 30.</p> <p>Ascend broken E. slope; continue posting and blazing.</p>

Subdivision of Section 30,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
918	Gravel road, 12 ft. wide, bears N. 43° E. and S. 43° W.
1305.56	<p>The center N 1/16 sec. cor. of sec. 30.</p> <hr/> <p>N. 89° 07' 25" W., on the E. and W. centerline of the NW 1/4 of sec. 30.</p> <p>Descend broken W. slope; continue posting and blazing.</p>
1318.33	<p>The NW 1/16 sec. cor. of sec. 30, established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, and recorded in the Douglas County Surveyors Office, Map File No. 90-71, and is accepted as the cor., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S30</p> <p style="text-align: center;">1985 PLS 1988 DO NOT DISTURB</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S. 5° E., 14.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears S. 73 3/4° W., 31.2 ft. dist., with scribe marks NW 1/16 S30 BT visible on a partially healed double blaze.</p> <p>From this corner, an iron rebar, set by person(s) unknown, 3/4 in. diam., firmly set, projecting 12 ins. above the ground, bears S. 33° 30' 57" E., 13.30 ft. dist., with no cap, from which the remains of bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A hemlock, 25 ins. diam., bears N. 79 1/4° W., 14.1 ft. dist., with no marks visible on a partially healed blaze.</p> <hr/> <p>S. 0° 12' 25" W., on the N. and S. centerline of the NW 1/4 of sec. 30.</p> <p>Descend broken SW. slope; continue posting and blazing.</p>
1125	Creek, 2 ft. wide, course N. 65° W.; asc. broken N. slope.
1299.35	<p>The center W 1/16 sec. cor. of sec. 30.</p> <hr/>

Subdivision of Section 32,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	From the 1/4 sec. cor. of sec. 32 only, on the S. bdy. of the Tp.
	N. 0° 14' 43" E., on the N. and S. centerline of sec. 32.
	Ascend broken E. slope.
150	Gravel road, 16 ft. wide, bears N. 82° E. and S. 82° W.
	Continue asc. broken SE. slope.
940	Spur, slopes east; desc. steep NE. slope.
1165	Ravine, drains N. 84° E.; asc. steep SE. slope.
1195.98	The center S 1/16 sec. cor. of sec. 32, established by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Office, Map File No. 79-49, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.
	T27S R2W S1/16 · S32 RLS1654 1980
	from which bearing trees mkd. by Ware and Quimby
	A hemlock, 17 ins. diam., bears N. 47 3/4° E., 63.2 ft. dist., with scribe marks S 1/16 S32 BT visible on a partially healed double blaze.
	A cedar, 31 ins. diam., bears N. 27 1/4° W., 52.6 ft. dist., with scribe marks CS 1/16 S32 BT visible on a partially healed double blaze.

	N. 0° 14' 52" E., beginning new measurement.
	Continue asc. steep SE. slope; begin posting and blazing.
720	Spur, slopes east; desc. steep NE. slope.
1297.51	The center 1/4 sec. cor. of sec. 32, established by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Office, Map File No. 79-49, and is accepted as the cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 in. above ground, with brass cap mkd.
	T27S R2W C 1/4 · S32 RLS1654 1980

Subdivision of Section 32,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>from which bearing trees mkd. by Ware and Quimby</p> <p>A fir, 19 ins. diam., bears S. 42 1/2° E., 34.6 ft. dist., with a healed double blaze.</p> <p>A hemlock, 12 ins. diam., bears S. 42 1/4° W., 15.0 ft. dist., with scribe marks C 1/4 S32 visible on a partially healed double blaze.</p> <hr/>
	<p>N. 0° 13' 54" E., beginning new measurement.</p>
	<p>Continue desc. broken NE. slope; continue posting and blazing.</p>
1315.20	<p>Point for the center N 1/16 sec. cor. of sec. 32, not monumented.</p>
1730	<p>Gravel road, 20 ft. wide, bears N. 88° E. and S. 88° W.</p>
2415	<p>Gravel road, 16 ft. wide, bears S. 50° E. and N. 50° W.</p>
2630.40	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 89° 58' 20" W., on the E. and W. centerline of sec. 32.</p> <p>Descend broken NW. slope; begin posting and blazing.</p>
1322.48	<p>Point for the center E 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T27S R2W E 1/16 C ————— C S32 2003</p>
	<p>from which</p> <p>A fir, 16 ins. diam., bears N. 13 1/4° E., 13.5 ft. dist., mkd. CE 1/16 S32 BT.</p> <p>A fir, 8 ins. diam., bears S. 44° E., 16.0 ft. dist., mkd. CE 1/16 S32 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

Subdivision of Section 32,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	Discontinue posting and blazing.
1910	Dirt road, 20 ft. wide, bears N. 10° E. and S. 10° W.
1940	West Fork Wolf Creek, 2 ft. wide, course N. 4° E.; asc. NE. slope.
2644.96	The center 1/4 sec. cor. of sec. 32. <hr/>
	N. 89° 57' 17" W., beginning new measurement.
	Ascend broken NE. slope.
2634.86	The 1/4 sec. cor. of sec. 32 only. <hr/>
	From the center E 1/16 sec. cor. of sec. 32.
	N. 0° 05' 21" E., on the calculated N. and S. centerline of the NE 1/4 of sec. 32.
	Descend gentle NW. slope; begin posting and blazing.
1285	Gravel road, 10 ft. wide, bears S. 36° E. and N. 36° W.
1313.28	Point for the NE 1/16 sec. cor. of sec. 32 at its calculated position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	NE 1/16 . S32 2003
	from which
	A fir, 18 ins. diam., bears N. 85 1/4° E., 11.6 ft. dist., mkd. NE 1/16 S32 BT.
	A fir, 15 ins. diam., bears N. 38 3/4° W., 10.8 ft. dist., mkd. NE 1/16 S32 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post. <hr/>
	S. 89° 53' 20" E., on the calculated E. and W. centerline of the NE 1/4 of sec. 32.
	Ascend gentle NW. slope; continue posting and blazing.

Subdivision of Section 32,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEET	
190	Spur, slopes S. 10° E.; desc. SE. slope.
365	West edge of beaver pond, bears N. 26° E. and S. 26° W.
495	East edge of same pond, bears S. 35° E. and N. 45° W.; asc. NW. slope.
1319.14	The N 1/16 sec. cor. of secs. 32 and 33. <hr/>
	From the center S 1/16 sec. cor. of sec. 32. N. 89° 47' 17" W., on the E. and W. centerline of the SW 1/4 of sec. 32. Ascend SE. slope; begin posting and blazing.
1323.03	The SW 1/16 sec. cor. of sec. 32, established by Ware and Quimby in 1980, recorded in the Douglas County Surveyors Office, Map File No. 79-49, and is accepted as the cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T27S R2W SW 1/16 · S32 RLS 1654 1980 from which bearing trees mkd. by Ware and Quimby A hemlock, 16 ins. diam., bears S. 37 1/4° W., 17.7 ft. dist., with scribe marks SW 1/16 S32 BT visible on a partially healed double blaze. A hemlock, 17 ins. diam., bears N. 70 1/2° W., 21.8 ft. dist., with scribe marks SW 1/16 S32 BT visible on a partially healed double blaze. and new bearing trees A cedar, 7 ins. diam., bears N. 44 3/4° E., 14.8 ft. dist., mkd. SW 1/16 S32 BT. A fir, 4ins. diam., bears N. 52° W., 22.7 ft. dist., mkd. X BT. From this corner, an iron pipe, set by person(s) unknown, 2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 85°08'39" E., 3.63 ft. dist., with no cap. <hr/>
	N. 89° 47' 37" W., beginning new measurement.

Subdivision of Section 32,
T. 27 S., R. 2 W., Willamette Meridian, Oregon

FEEET	Continue asc. SE. slope; continue posting and blazing.
696	Gravel road, 10 ft. wide, bears N. 16° E. and S. 16° W.
1123	Spur, slopes south; desc. SW. slope.
1321.97	The S 1/16 sec. cor. of sec. 32 only.
<hr/> <p>GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in mountainous terrain, approx. 9.0 miles southeasterly from the community of Glide, Oregon.</p> <p>The elevation ranges from approximately 1800 feet above sea level near the 1/4 section corner of sections 20 and 21 to approximately 3800 feet above sea level near the 1/4 section corner of section 32 only.</p> <p>The area is drained by Evarts Creek which flows northwesterly to Cavitt Creek and Wolf Creek which flows northerly to Little River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>Access to the survey was made by graveled roads branching from Cavitt Creek Road.</p>	