

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY

AND SUBDIVISIONAL LINES,

TOWNSHIP 27 SOUTH, RANGE 3 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated July 14, 2003,
approved July 25, 2003, which provided for the surveys
included under Group No. 1968, and Assignment Instructions
dated August 5, 2003.

Survey commenced August 5, 2003

Survey completed July 8, 2004

T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the east boundary and subdivisional lines, Township 27 South, Range 3 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1882, Samual C. Flint, U.S. Deputy Surveyor, surveyed the north and west boundaries and a portion of the subdivisional lines, T. 27 S., R. 2 W.

In 1882, Samual C. Flint, U.S. Deputy Surveyor, surveyed the subdivisional lines, T. 27 S., R. 3 W.

In 1911, Morris Wygant, a Compassman working under the direction of Zachariah Derrick, U.S. Deputy Surveyor, retraced a portion of the east boundary, T. 27 S., R. 3 W.

In 1985, Boyd W. Peterson and Mark D. Dixon, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, and subdivided sections 23 and 35.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 14, 2003, for Group No. 1968, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO), version 1.61. The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements and carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The

T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET

adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control:

1. CAPE BLANCO CORS ARP, National Geodetic Survey.
42° 50' 09.93681" N.; 124° 33' 47.99046" W.; NAD 1983
(CORS 2000)
2. DODSON BUTTE CORS ARP, National Geodetic Survey.
43° 07' 07.62977" N.; 123° 14' 39.21270" W.; NAD 1983
(CORS 2002)

The geographic position (NAD 1983 (CORS 2000)) of the corner of sections 25 and 36 only, on the east boundary of the township, was determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System, noted above, is as follows:

Latitude: 43° 11' 03.80" N. Longitude: 122° 59' 29.85" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

(Restoring the surveys by Samuel C. Flint in 1882,
and the resurvey by Morris Wygant, in 1911)

Beginning at the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., reestablished by proportionate measurement by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700200, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with an aluminum cap mkd.

**Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET

CHAMPION INTL. CORP.

T 27 S T 27 S

S 25	S30
S 36	

R 3 W R 2 W

1985

PLS 1988

from which bearing trees mkd. by Geisler

A fir, 20 ins. diam., bears S. 13 3/4° W., 10.9 ft. dist.,
with healed double blazes.

A fir, 12 ins. diam., bears N. 44 1/4° W., 18.8 ft. dist.,
with healed double blazes.

From this corner, the closing corner of secs. 30 and 31, T. 27 S., R. 2 W., established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700178, and is accepted as the cor., bears S. 0° 27' 13" W., 130.19 ft. dist.; monumented with an aluminum post, 2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.

CHAMPION INT CORP

T 27 S

R 3 W	R 2 W
	S 30
S 36	CC
	S 31

1985

PLS 1988

from which the remains of bearing trees mkd. by Geisler

A fir, 19 ins. diam., bears N. 63 1/2° E., 6.2 ft. dist.,
with a healed blaze.

A roothole bears S. 12 1/2° E., 19.3 ft. dist., with
hemlock trunk, 9 ins. diam., lying alongside, with
illegible scribe marks visible on a partially healed
blaze.

and a new bearing tree

A fir, 19 ins. diam., bears S. 32 3/4° E., 30.8 ft. dist.,
mkd. T27S R2W S31 CC BT.

From this corner, the original closing cor. of secs. 30 and 31, T. 27 S., R. 2 W., remonumented by the Douglas County Surveyors Office in 1962, amended by Ronald G. Geisler, Oregon

**Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	<p>Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700178, bears S. 88° 04' 19" E., 17.57 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins., above the ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 27 S CC S 30 AM S 31 R 2 W 1962</p> <p>from which the remains of the original bearing trees</p> <p>A roothole bears N. 50° E., 18.5 ft. dist., with fir trunk, 36 ins. diam., lying alongside, no marks visible.</p> <p>A sawed fir stump, 31 ins. diam., bears S. 75° E., 19.1 ft. dist., no marks visible</p> <p>and the remains of bearing trees mkd. by person(s) unknown</p> <p>A fir, 12 ins. diam., bears N. 66 1/2° E., 20.1 ft. dist., with a healed double blaze.</p> <p>A fir, 14 ins. diam., bears S. 23° E., 26.9 ft. dist., with a healed double blaze.</p> <p>A fir snag, 6 ins. diam., bears S. 63 1/4° W., 21.0 ft. dist., with a healed double blaze.</p> <p>From this corner, an iron pipe, set by person(s) unknown, 1 3/4 ins. diam., firmly set, projecting 2 ins. above the ground, bears N. 72° 07' 02" W., 1.54 ft. dist., with no cap.</p> <p>N. 0° 34' 20" E., on the E. bdy. of sec. 25.</p> <p>Descend broken NE. slope, through second growth timber and dense undergrowth; begin posting and blazing.</p>
2360	Creek, 1.5 ft. wide, course N. 20° W., continue desc. over broken NW. slope.
2475.76	The 1/4 sec. cor. of sec. 30 only, T. 27 S., R. 2 W., established by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700237, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly

**Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>set, projecting 12 ins. above a collar of stone, 1 1/2 ft. base, 1 ft. high, with aluminum cap mkd.</p> <p style="text-align: center;">CHAMPION INTL. CORP. T 27 S R 2 W</p> <p style="text-align: center;"> 1/4 S 30</p> <p style="text-align: center;">1985 PLS 1988</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N. 43° E., 21.8 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 86° E., 45.5 ft. dist., with a healed double blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 37' 06" E., beginning new measurement.</p> <p>Continue desc. broken NW. slope, through second growth timber and dense undergrowth.</p>
220.78	<p>The 1/4 sec. cor. of sec. 25 only, reestablished by proportionate measurement by Ronald G. Geisler, Registered Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700240, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">CHAMPION INTL. CORP. T 27 S R 2 W</p> <p style="text-align: center;">1/4 S25 </p> <p style="text-align: center;">1985 PLS 1988</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 16 1/2° W., 19.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A hemlock, 5 ins. diam., bears N. 89 1/4° W., 10.9 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET	
	<p>N. 0° 38' 34" E., beginning new measurement.</p>
	<p>Continue desc. broken NW. slope, through second growth timber and dense undergrowth.</p>
600	<p>Graveled road, 20 ft. wide, bears N. 80° E. and S. 85° W.</p>
1440	<p>Evarts Creek, 3.0 ft. wide, course N. 60° W.; asc. SW. slope.</p>
2385.48	<p>The closing cor. of secs. 19 and 30, T. 27 S., R. 2 W. established by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 02 W., Point Identifier No. 100300, and is accepted as the cor., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">CHAMPION INTL. CORP. T 27 S R 3 W R 2 W S 19 S 25 -----CC S 30 1985 PLS 1988</p>
	<p>from which bearing trees mkd. by Geisler</p>
	<p>A fir snag, 12 ins. diam., bears N. 52 3/4° E., 15.1 ft. dist., with scribe marks T27S R2W S19 CC BT visible on a partially healed double blaze.</p>
	<p>A fir, 9 ins. diam., bears S. 30 1/2° E., 20.9 ft. dist., with scribe marks 7S R2 visible on a partially healed blaze.</p>
	<p>and a new bearing tree</p>
	<p>A fir, 20 ins. diam., bears N. 44 1/2° E., 23.4 ft. dist., mkd. T27S R2W S19 CC BT.</p>
	<p>From this corner, the original closing cor. of secs. 19 and 30, T. 27 S., R. 2 W. remonumented by the Douglas County Surveyors Office in 1969, amended by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700277, bears S. 88° 59' 02" E., 14.31 ft. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 27 S R S 19 R 3 CC ————— 2 W S 30 W AM 1969</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 65 1/2° E., 22.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, size indeterminate, bears S. 64° E., 48.8 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 76 3/4° E., 10.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 25 1/2° E., 15.1 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 35' 20" E., beginning new measurement.</p> <p>Continue asc. broken SW. slope, through second growth timber and dense undergrowth.</p> <p>140 Spur, slopes N. 55° W., desc. over NW. slope.</p> <p>215.09 The cor. of secs. 24 and 25 only, remonumented by the Douglas County Surveyors Office in 1969, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 03 W., Point Identifier No. 700300, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 27 S R S 24 R 3 ——— 2 W S 25 W 1969</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 51 ins. diam., bears S. 65° E., 29.0 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p>
------	--

Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET	<p>A hemlock, 10 ins. diam., bears N. 82° E., 33.4 ft. dist., with a healed blaze.</p> <p>A fir, 23 ins. diam., bears S. 8° W., 2.0 ft. dist., with a healed blaze.</p> <p>A cedar, 15 ins. diam., bears N. 71° W., 51.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A hemlock, 8 ins. diam., bears N. 24 1/4° W., 31.8 ft. dist., mkd. T27S R3W S24 BT.</p> <hr/> <p>N. 1° 14' 11" E., on the E. bdy. of sec. 24.</p> <p>Descend steep N. slope, through second growth timber and dense undergrowth; begin posting and blazing.</p> <p>255 Creek, 4 ft. wide, course N. 50° W., asc. over SW. slope.</p> <p>1005 Spur, slopes S. 20° W., desc. over NW. slope.</p> <p>2376.85 Point for the 1/4 sec. cor. of sec. 19 only, T. 27 S., R. 2 W., determined at midpoint latitudinally bet. the closing cor. of secs. 19 and 30, and the closing cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 27 S</p> <p>R3W R2W</p> <p>1/4 S19</p> <p>2003</p> </div> <p>from which</p> <p>A cedar, 9 ins. diam., bears N. 59 1/4° E., 30.2 ft. dist., mkd. 1/4 S19 BT.</p> <p>A fir, 16 ins. diam., bears S. 53 1/2° E., 30.2 ft. dist., mkd. 1/4 S19 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located 17.0 ft. E. of an overgrown graveled road, 20 ft. wide, which bears N. 35° E. and S. 55° W.</p>
------	---

**Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET	
	Continue desc. gentle NW. slope, through second growth timber and dense undergrowth.
2400	Overgrown graveled road, 20 ft. wide, bears N. 35° E. and S. 35° W.
2642.13	Point for the 1/4 sec. cor. of sec. 24 only, determined by the Broken Boundary Method. There is no remaining evidence of the original cor.
	Drive a finned aluminum rod, 72 ins. long, 3/4 ins. diam., 68 ins. in the ground, with aluminum cap mkd.
	<pre> T 27 S R 3 W R 2 W 1/4 S 24 2003 </pre>
	from which
	An alder, 8 ins. diam., bears S. 45 3/4° W., 8.7 ft. dist., mkd. 1/4 S24 BT in the bark.
	An alder, 6 ins. diam., bears N. 43 3/4° W., 5.7 ft. dist., mkd. 1/4 S24 BT in the bark.
	Deposit a magnet in a white plastic case alongside the finned aluminum rod.
	Corner is located in a wet marshy area.

	N. 0° 33' 26" E., beginning new measurement.
	Ascend broken N. slope, through second growth timber and dense undergrowth; continue posting and blazing.
230	Overgrown graveled road, 18 ft. wide, bears S. 60° E. and N. 60° W.
435	Graveled road, 20 ft. wide, bears N. 55° E. and S. 55° W.
560	Ridge, bears N. 70° E. and S. 75° W., desc. S. slope.
1695	Graveled road, 12 ft. wide, bears east and west.
2327.68	True point for the closing cor. of secs. 18 and 19, T. 27 S., R. 2 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 27 S., R. 2 W., executed concurrently under this same group.

**Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET	<p>The cor. of secs. 13 and 24 only, remonumented by the Douglas County Surveyors Office in 1966, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 2 W., Point Identifier No. 700400, monumented with an iron post, 1 1/2 ins. diam., projecting 30 ins. above ground, loosely set in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>																				
2757.78	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T27S</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">S</td> <td style="border-left: 1px solid black; padding: 0 5px;">13</td> <td style="padding: 0 10px;"> </td> <td style="padding: 0 5px;">R</td> </tr> <tr> <td style="padding: 0 5px;">3</td> <td style="padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 10px;"> </td> <td style="padding: 0 5px;">2</td> </tr> <tr> <td style="padding: 0 5px;">W</td> <td style="padding: 0 5px;">S</td> <td style="border-left: 1px solid black; padding: 0 5px;">24</td> <td style="padding: 0 10px;"> </td> <td style="padding: 0 5px;">W</td> </tr> <tr> <td colspan="5" style="text-align: center; padding: 5px 0 0 0;">1966</td> </tr> </table> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 38 ins. diam., bears S. 38° E., 19.1 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 69 3/4° W., 6.3 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 66 1/2° W., 15.9 ft. dist., with a healed double blaze.</p> <p>Reset the iron post, 36 ins. long, in place, 24 ins. in the ground, and deposit two Mag-Nails at the base of the iron post.</p> <hr style="width: 60%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W., Willamette Meridian, Oregon</p> <hr style="width: 60%; margin: 20px auto;"/> <p style="text-align: center;">(Restoring the survey by Samuel C. Flint, in 1882)</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp. S. 87° 21' 11" W., bet. secs. 25 and 36.</p> <p>Ascend broken NE. slope, through second growth timber and dense undergrowth; begin posting and blazing.</p>	R	S	13		R	3				2	W	S	24		W	1966				
R	S	13		R																	
3				2																	
W	S	24		W																	
1966																					
235	Graveled road, 15 ft. wide, bears S. 55° E. and N. 55° W.																				
625	Spur, slopes N. 10° E., desc. over SW. slope.																				
835	Graveled road, 25 ft. wide, bears N. 10° E. and S. 10° E.																				

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET					
2502.55	<p>The 1/4 sec. cor. of secs. 25 and 36, determined at record bearing and dist. from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 41 ins. diam., bears N. 62° W., 20.5 ft. dist., with fragmentary scribe marks and axe marks visible on the bark.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. long, 28 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 27 S R 3 W</p> <p style="padding-left: 40px;">S 25</p> <p style="padding-left: 40px;">1/4 ———</p> <p style="padding-left: 40px;">S 36</p> <p style="padding-left: 40px;">2003</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 78 1/2° E., 17.7 ft. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 26 1/2° E., 13.4 ft. dist., mkd. 1/4 S36 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 23' 56" W., beginning new measurement.</p> <p>Continue asc. over SW. slope, through second growth timber and dense undergrowth.</p>				
2661.66	<p>The cor. of secs. 25, 26, 35, and 36, remonumented by the Douglas County Surveyors Office, in 1970, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 3 W., Index No. 117, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p style="padding-left: 40px;">T 27 S</p> <table style="margin-left: 40px; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table> <p style="padding-left: 40px;">R 3 W</p> <p style="padding-left: 40px;">1970</p> </div> <p>from which the remains of the original bearing trees</p>	S 26	S 25	S 35	S 36
S 26	S 25				
S 35	S 36				

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET	
	<p>A laurel, 22 ins. diam., bears N. 80° E., 29.7 ft. dist., no marks visible. (Record, N. 65° E., 31.0 ft.)</p> <p>A laurel stump, 25 ins. diam., bears S. 55 3/4° E., 42.9 ft. dist., no marks visible. (Record, S. 53° E., 43.6 ft.)</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p>A laurel, 10 ins. diam., bears N. 28 1/2° E., 10.6 ft. dist., with a healed double blaze.</p> <p>A sawed fir stump, 44 ins. diam., bears S. 76° E., 64.7 ft. dist., with scribe marks T27S R3W S36 CS BT visible on a partially healed double blaze.</p> <p>A fir, 14 ins. diam., bears S. 58° W., 8.3 ft. dist., with a healed double blaze.</p> <p>A laurel, 7 ins. diam., bears N. 49° W., 4.6 ft. dist., with scribe marks T27S R3W S26 CS BT visible on a partially healed double blaze.</p> <p>and a bearing tree mkd. by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1984, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 3 W., Index No. 137</p> <p>An oak, 8 ins. diam., bears S. 71° E., 24.4 ft. dist., with scribe marks 27S W 5 BT visible on a partially healed blaze.</p>
	<hr/> <p>N. 1° 26' 02" E., bet. secs. 25 and 26.</p> <p>Ascend over SW. slope; continue posting and blazing.</p>
1705	Dirt road, 15 ft. wide, bears S. 60° E. and N. 60° W.
1960	Ridge, bears N. 30° E. and S. 50° W., desc. over NW. slope.
2616.41	The 1/4 sec. cor. of secs. 25 and 26, remonumented by Thomas E. Shrum, Jr., Registered Professional Engineer, No. 4287, in 1969, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 27 S., R. 3 W., Index No. 109, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET

U.S.P.C. PROPERTY COR.

T 27 S R 3 W

S		S
26		25

1/4

RE 4287

1969

from which the remains of the original bearing trees

A fir snag, 40 ins. diam., bears N. 35° E.,
52.8 ft. dist., no marks visible.

A roothole, bears S. 74 1/4° W., 27.6 ft. dist., with
decayed and burnt cedar trunk, size indeterminate, lying
alongside, no marks visible. (Record S. 85° W.,
28.4 ft.)

and the remains of bearing trees mkd. by Shrum

A sawed cedar stump, 13 ins. diam., bears S. 60 3/4° E.,
29.7 ft. dist., with fragmentary scribe marks 1/4 S25
visible on a partially healed blaze.

A fir, 15 ins. diam., bears S. 22 3/4° W., 4.5 ft. dist.,
with a healed double blaze.

and a new bearing tree

A cedar, 10 ins. diam., bears S. 57 1/2° E.,
37.4 ft. dist., mkd. 1/4 S25 BT

T. 27 S., R. 3 W., Willamette Meridian, Oregon

FEET

GENERAL DESCRIPTION

The lands included in the foregoing survey are located about 9 miles southeasterly from Glide, Oregon. The area is drained by Cavitt Creek, and a number of small seasonal streams. Elevations range from about 2355 feet above mean sea level, near the corner of sections 25, 26, 35, and 36, to about 2850 feet above mean sea level near the corner of sections 25, and 36 only, on the east boundary of the tp.

Access is gained by way of Little River Road, Cavitt Creek Road, paved roads which extend southeasterly from Glide, also by numerous other graveled logging and private roads.

Soil consists of rock, clay, and Gravelly soils. There were a number of rock outcroppings and bluffs throughout the area.

Timber in this area consists of fir, cedar, hemlock, oak, alder, madrone, maple, and chinquapin. Undergrowth consists of vine maple, hazel, ceanothus, fern, poison oak, salal, Oregon grape, arrowwood, huckleberry, salmonberry, and rhododendron.

There were no mineral deposits along the lines resurveyed. The lands are used primarily for timber production.
