

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY

AND SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 24 AND 26,

**TOWNSHIP 21 SOUTH, RANGE 8 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

***Edith M. Forkner, Cadastral Surveyor***

Under Special Instructions dated July 11, 2005, approved July 13, 2005,

which provided for the surveys included under Group No. 2115,

and Assignment Instructions dated January 24, 2007

***Survey commenced January 24, 2007***

***Survey completed May 1, 2007***

## T. 21 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines and the subdivision of sections 24 and 26, Township 21 South, Range 8 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the north boundary of Township 22 South, Range 7 West.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed the north boundary and a portion of the subdivisional lines of Township 22 South, Range 8 West.

In 1883, Laban H. Wheeler, U.S. Deputy Surveyor, surveyed the west boundary of Township 21 South, Range 7 West.

In 1883, William P. Wright, U.S. Deputy Surveyor, surveyed the subdivisional lines.

In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines of Township 21 South, Range 7 West.

In 1952-54, Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, resurveyed the east boundary, a portion of the south and north boundaries of the township, and a portion of the subdivisional lines.

In 1999-2000, Aaron M. Graham, Cadastral Surveyor, remonumented certain corner points and rehabilitated certain corner points without survey.

In 2005-06, Edith M. Forkner, Cadastral Surveyor, resurveyed a portion of the west boundary of Township 21 South, Range 7 West.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 11, 2005, for Group No. 2115, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

## T. 21 S., R. 8 W., Willamette Meridian, Oregon

FEET

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management (CMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 22, 23, 26, and 27, as determined by a direct tie from a Global Positioning System (GPS) observation on a temporary monument processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43° 43' 16.46" N.      Longitude: 123° 37' 21.60" W.

The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of section 35 only, on the south boundary of the township, as determined by a tie to the corner of sections 22, 23, 26, and 27, is as follows:

Latitude: 43° 41' 36.55" N.      Longitude: 123° 36' 46.88" W.

---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

---

(Restoring the survey by William H. Byars in 1881 and  
the resurvey by Marvin J. Lytle, et al., in 1952-54)

---

Beginning at the cor. of Tps. 21 and 22 S., Rgs. 7 and 8 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|---------|---|--|--------|--|-------|-------|--|------|------|--|-------|--|--|-----|-----|--|--|--------|--|--|------|--|
|         | <table style="margin: auto;"> <tr><td></td><td style="text-align: center;">T 21 S</td><td></td></tr> <tr><td style="text-align: center;">R 8 W</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">R 7 W</td><td></td></tr> <tr><td style="text-align: center;">S 36</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 31</td><td></td></tr> <tr><td colspan="3" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 1</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;">S 6</td><td></td></tr> <tr><td></td><td style="text-align: center;">T 22 S</td><td></td></tr> <tr><td></td><td style="text-align: center;">1952</td><td></td></tr> </table> |  | T 21 S |  | R 8 W | R 7 W |  | S 36 | S 31 |  | ----- |  |  | S 1 | S 6 |  |  | T 22 S |  |  | 1952 |  |
|         | T 21 S  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| R 8 W   | R 7 W   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| S 36    | S 31  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| -----   |   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| S 1     | S 6   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | T 22 S  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | 1952  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | from which the remains of the original bearing trees  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | A cedar, 56 ins. diam., bears S. 30° E., 18.5 ft. dist., with a healed blaze.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | A roothole bears N. 30° W., 36.3 ft. dist., with a down cedar, 30 ins. diam., alongside, no marks visible.  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | and bearing trees mkd. by Lytle, et al., in 1952-54   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | A cedar, 27 ins. diam., bears N. 50 1/2° E., 28.4 ft. dist., with a healed blaze.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | A hemlock, 25 ins. diam., bears S. 34 1/2° W., 17.2 ft. dist., with a healed blaze.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | A fir, 30 ins. diam., bears N. 42 3/4° W., 58.7 ft. dist., with a healed blaze.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | A steel fence post is alongside the cor.  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | N. 88° 52' 58" W., bet. secs. 1 and 36.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
|         | Ascend over shallow E. slope through medium timber and light undergrowth.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 95      | Ascend over steep E. slope.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 400     | Spur, slopes N. 45° E.; desc. across N. slope.  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 610     | Bottom of descent, slopes NE.; asc. over steep E. slope.  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 885     | Ridge, bears N. 10° W. and S. 10° E.; desc. over steep W. slope.  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 1195    | Across broken, generally shallow S. slope.  |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 1405    | Graveled road, 12 ft. wide, bears N. 70° E. and S. 70° W.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |
| 2581.65 | The 1/4 sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.   |  |        |  |       |       |  |      |      |  |       |  |  |     |     |  |  |        |  |  |      |  |

Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

|       |  |
|-------|--|
| FEEET | <p style="text-align: center;">1/4 <u>S 36</u><br/>1952</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A burned and decayed fir stump, size indeterminate, bears N. 40° E., 19.0 ft. dist., no marks visible. (Record, 16.5 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Lytle, et al., in 1952-54</p> <p style="padding-left: 40px;">A burned fir stump, 50 ins. diam., bears N. 7° E., 30.4 ft. dist., with scribe marks 1/4 S36 BT visible on detached face.</p> <p>and a bearing tree mkd. by Milo Godfrey, Douglas Deputy County Surveyor, in 1963, on file in the Douglas County Surveyors Record of Government Corners Renewed, T. 21 S., R. 8 W., Point Identifier No. 640100</p> <p style="padding-left: 40px;">The northeasterly and largest of a clump of three maples, 21 ins. diam., bears N. 39° E., 78.1 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Graham in 1999-2000</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 69 1/2° E., 47.1 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 41° W., 19.6 ft. dist., with axe marks X at breast height and a healed blaze. (Record, N. 39° W., 10.6 ft. dist.)</p> <p>and a bearing tree mkd. by Gary T. Smither, Registered Land Surveyor No. 2485, in 2005, on file in the Douglas County Surveyor's Office, under CS File No. 65/54-21</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 50 1/2° E., 9.1 ft. dist., with illegible scribe marks visible on pitched-over partially healed blaze.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89° 53' 01" W., beginning new measurement.</p> <p>Across broken, generally shallow S. slope through medium timber and light undergrowth.</p> |
| 180   | Ascend over steep E. slope.  |

**Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET   |  |
|--------|--|
| 287.04 | <p>The 1/4 sec. cor. of sec. 1 only, on the N. bdy. of T. 22 S., R. 8 W., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">—————<br/>1/4 S 1<br/>1952</p> <p>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears S. 26 1/2° E., 36.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A roothole bears S. 49 1/2° W., 37.0 ft. dist., with a down fir, 54 ins. diam., alongside with axe marks on loose bark.</p> <p>and a bearing tree mkd. by Milo Godfrey, Douglas Deputy County Surveyor, in 1963, on file in the Douglas County Surveyors Record of Government Corners Renewed, T. 21 S., R. 8 W., Point Identifier No. 636100</p> <p style="padding-left: 40px;">A fir, 49 ins. diam., bears N. 53° E., 22.2 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Gary T. Smither, Registered Land Surveyor No. 2485, in 2005, on file in the Douglas County Surveyor's Office, under CS File No. 65/54-20</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 46° E., 16.7 ft. dist., with scribe marks T22 R8 1/4 S1 BT visible on pitched-over partially healed blaze, and a spike on the left side center.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 30° W., 7.7 ft. dist., with scribe marks T22 R8 1/4 S1 BT visible on pitched-over partially healed blaze, and a spike on the left side center.</p> <p>An aluminum fence post is alongside the cor.</p> <p>Corner is located 3 ft. downhill from the down Lytle SW. bearing tree.</p> <p style="text-align: center;">—————</p> <p>N. 89° 30' 12" W., beginning new measurement.</p> <p>Ascend over steep E. slope through medium timber and light undergrowth.</p> |
| 260    | <p>Spur, slopes S. 20° W.; desc. over SW. slope.</p>   |

**Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
| 715     | Creek, 1/2 ft. wide, course S. 45° W.; con. across S. slope.   |
| 970     | Creek, 1/2 ft. wide, course S. 40° E.; asc. over SE. slope.  |
| 1630    | Little Paradise Creek Road, asphalt surface, 15 ft. wide, bears N. 40° E. and S. 20° W.  |
| 1930    | Spur, slopes N. 35° E.; desc. across N. slope.   |
| 2300.49 | <p>The cor. of secs. 35 and 36 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 8 W<br/> <u>S 35   S 36</u><br/> S 1<br/> T 22 S R 8 W<br/> 1952</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir stump, 64 ins. diam., bears N. 20° E.,<br/> 14.9 ft. dist., no marks visible. (Record,<br/> 13.2 ft. dist.)</p> <p style="margin-left: 40px;">A fir stump, 50 ins. diam., bears N. 70° W.,<br/> 8.8 ft. dist., no marks visible. (Record, 6.6 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Lytle, et al., in 1952-54</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears<br/> N. 39 1/4° W., 28.8 ft. dist., no marks visible.<br/> (Record, 27.7 ft. dist.)</p> <p>and bearing trees mkd. by person(s) unknown, reported by Gary T. Smither, Registered Land Surveyor No. 2485, in 2005, on file in the Douglas County Surveyor's Office, under CS File No. 65/54-22</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 64 1/2° E., 12.6 ft. dist.,<br/> with a healed blaze with a nail and washer in face, and<br/> a spike on the left side center.</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S. 8 3/4° E., 30.1 ft. dist.,<br/> with a healed blaze with a nail and washer in face, and<br/> a spike on the left side center.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 79 3/4° W., 31.2 ft. dist.,<br/> with a healed blaze with a nail and washer in face, and<br/> a spike on the right side center.</p> |



**Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |
|---------|---|
|         | <p>A fir, 16 ins. diam., bears S. 85 1/4° E., 29.0 ft. dist., mkd. T22S R8W S1 CC BT.</p> <p>An iron rod with International Paper Co. property sign is alongside the cor.</p> <p>Corner is located on a W. slope in the middle of a bench, 100 ft. wide.</p> <p>From this corner, the point for the original closing cor. of secs. 1 and 2, bears South, 5.9 dist., not monumented, determined at record bearing and distance from the remains of an original bearing tree</p> <p>A decayed fir stump, 20 ins. diam., bears S. 20 1/2° W., 28.4 ft. dist., with no marks visible on open blaze and axe marks in a diamond on the east side.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 43' 05" W., bet. secs. 2 and 35.</p> <p>Descend over SW. slope through medium timber and moderate undergrowth.</p> |
| 45      | Descend over steep W. slope.  |
| 385     | Descend over broken SW. slope.  |
| 875     | Creek, 1/2 ft. wide, course S. 60° W.; desc. over SW. slope.  |
| 1340    | Creek, 3 ft. wide, course N. 20° W.; asc. across steep N. slope.  |
| 1625    | Spur, slopes N. 30° W.; desc. over steep broken W. slope.   |
| 2024.23 | <p>The 1/4 sec. cor. of sec. 35 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in rocky soil with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 35<br/>—————<br/>1952</p> <p>from which the remains of the original bearing trees</p> <p>A yew, 13 ins. diam., bears S. 52° E., 19.0 ft. dist., with no scribe marks visible on partially healed blaze. (Record, 17.8 ft. dist.)</p> <p>A roothole bears N. 10° W., 13.2 ft. dist., with a down yew, size indeterminate, alongside, no marks visible.</p>  |

**Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

F E E T

and the remains of the bearing trees mkd. by Lytle, et al., in 1952-54

A decayed hemlock stump, size indeterminate, bears N. 57 3/4° E., 53.5 ft. dist., no marks visible.

A fir, 33 ins. diam., bears N. 1 1/4° W., 56.1 ft. dist., with a healed blaze.

An iron rod with International Paper Co. property sign is alongside the cor.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

---

(Restoring the survey by William P. Wright in 1883 and the resurvey by Marvin J. Lytle, et al., in 1952-54)

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

|        |       |
|--------|-------|
| T 21 S |       |
| R 8 W  | R 7 W |
| S 25   | S 30  |
| -----  |       |
| S 36   | S 31  |
| 1952   |       |

from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54

A fir, 38 ins. diam., bears N. 74 1/4° E., 53.5 ft. dist., no marks visible.

A decayed fir stump, 20 ins. diam., bears S. 65 1/2° W., 29.7 ft. dist., no marks visible.

A fir, 40 ins. diam., bears N. 60 3/4° W., 63.4 ft. dist., with a healed blaze.

and bearing trees mkd. by Forkner in 2005-06

A fir, 9 ins. diam., bears S. 64° E., 41.1 ft. dist., with scribe marks T21S R7W S31 BT visible on open blaze.

A fir, 6 ins. diam., bears S. 62 3/4° W., 33.5 ft. dist., with scribe marks T21S R8W S36 BT visible on open blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
|         | S. 89° 39' 26" W., bet. secs. 25 and 36.   |
|         | Across steep N. slope through medium timber and moderate undergrowth.  |
| 80      | Descend over steep NW. slope.  |
| 265     | Drainage, course N. 20° E.; asc. over steep E. slope.  |
| 435     | Spur, slopes N. 20° W.; desc. over broken SW. slope.   |
| 1440    | Top of rock bluff, 30 ft. high, faces W.   |
| 1810    | Top of rock bluff, 20 ft. high, faces W.   |
| 1910    | Creek, 3 ft. wide, course N. 60° W.; asc. across steep N. slope.   |
| 2230    | Top of ascent, slopes N.; desc. across steep N. slope.   |
| 2290    | Descend over steep W. slope.   |
| 2535    | Across bottom land.  |
| 2735    | Paradise Creek, 25 ft. wide, course S. 20° W.; con. across bottom land.  |
| 2762.79 | The 1/4 sec. cor. of secs. 25 and 36, perpetuated by Douglas Deputy County Surveyor's Office, in 1968, on file in the Douglas County Surveyors Record of Government Corners Renewed, T. 21 S., R. 8 W., Point Identifier No. 640200; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 2 ft. base, 24 ins. high, with brass cap mkd. |
|         | COUNTY SURVEYOR'S OFFICE<br>T 21 S<br>S 25<br>-----<br>S 36<br>R 8 W<br>1968   |
|         | from which the remains of a bearing tree mkd. by Lytle, et al., in 1952-54   |
|         | A decayed white fir stump, size indeterminate, bears S. 64° E., 48.8 ft. dist., no marks visible.  |
|         | and bearing trees mkd. by person(s) unknown  |
|         | An alder, 11 ins. diam., bears N. 20 3/4° E., 19.3 ft. dist., no marks visible.  |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |   |        |       |      |      |      |      |      |  |
|---------|---|--------|-------|------|------|------|------|------|--|
|         | <p>An alder, 12 ins. diam., bears S. 11 1/2° W., 9.3 ft. dist., with illegible scribe marks visible on bark.</p> <p>Drive a red Carsonite post alongside the cor.</p> <p>Corner is located at the bottom of the fill bank for Paradise Creek Road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 30' 27" W., beginning new measurement.</p> <p>Ascend over steep SE. slope through medium timber and moderate undergrowth.</p>   |        |       |      |      |      |      |      |  |
| 25      | Paradise Creek Road, asphalt surface, 15 ft. wide, bears N. 10° E. and S. 10° W.  |        |       |      |      |      |      |      |  |
| 340     | Top of ascent, slopes S.; desc. across steep S. slope.  |        |       |      |      |      |      |      |  |
| 505     | Drainage, course S. 20° E.; asc. over steep SE. slope.  |        |       |      |      |      |      |      |  |
| 850     | Ascend across steep S. slope.   |        |       |      |      |      |      |      |  |
| 1115    | Spur, slopes S.; desc. over steep SW. slope.  |        |       |      |      |      |      |      |  |
| 1580    | Creek, 2 ft. wide, course S. 25° E.; asc. over steep NE. slope.   |        |       |      |      |      |      |      |  |
| 2190    | Spur, slopes S. 45° E.; desc. across S. slope.  |        |       |      |      |      |      |      |  |
| 2735    | Graveled road, 10 ft. wide, bears N. 50° W. and S. 40° E.   |        |       |      |      |      |      |      |  |
| 2778.28 | <p>The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 21 S</td> <td style="padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 35</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1952</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A decayed fir stump, 36 ins. diam., bears N. 77 1/2° W., 23.8 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p style="margin-left: 40px;">A decayed fir stump, 30 ins. diam., bears N. 7 1/4° E., 81.8 ft. dist., no marks visible.</p> | T 21 S | R 8 W | S 26 | S 25 | S 35 | S 36 | 1952 |  |
| T 21 S  | R 8 W   |        |       |      |      |      |      |      |  |
| S 26    | S 25  |        |       |      |      |      |      |      |  |
| S 35    | S 36  |        |       |      |      |      |      |      |  |
| 1952    |   |        |       |      |      |      |      |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET |   |
|------|---|
|      | <p>A decayed fir stump, 23 ins. diam., bears S. 18° E., 50.2 ft. dist., no marks visible.</p> <p>A decayed fir stump, 42 ins. diam., bears S. 26 1/2° W., 27.7 ft. dist., no marks visible.</p> <p>A decayed fir stump, size indeterminate, bears N. 73 1/2° W., 62.0 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by person(s) unknown</p> <p>A fir, 12 ins. diam., bears S. 28° E., 20.9 ft. dist., with a healed blaze with a nail and washer in face, and a nail on the right side center.</p> <p>A fir, 14 ins. diam., bears S. 37 3/4° W., 16.7 ft. dist., with a healed blaze with a nail and washer in face, and a nail on the right side center.</p> <p>A fir, 15 ins. diam., bears S. 86 1/2° W., 17.2 ft. dist., with a healed blaze with a nail and washer in face, and a nail on the right side center.</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 24 1/2° E., 53.3 ft. dist., mkd. T21S R8W S25 BT.</p> <p>A fir, 19 ins. diam., bears N. 6° W., 85.3 ft. dist., mkd. T21S R8W S26 BT.</p> <p>A steel fence post is alongside the cor. and a fir, 2 ft. diam., bears N. 20° W., 20 ft. dist., with a BLM location tag.</p> <hr/> <p>N. 1° 24' 03" E., bet. secs. 25 and 26.</p> <p>Ascend over S. slope through medium timber and moderate undergrowth.</p> |
| 30   | Graveled road, 10 ft. wide, bears N. 65° W. and S. 50° E.   |
| 595  | Same graveled road, 12 ft. wide, bears N. 40° E. and S. 35° W.; asc. over SE. slope.  |
| 965  | Top of ascent, slopes E.; desc. across steep E. slope.  |
| 1165 | Graveled road, 10 ft. wide, bears N. 25° W. and S. 10° E.   |
| 1400 | Bottom of descent, slopes E.; asc. over SE. slope.  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
| 1595    | Abandoned graveled road, 8 ft. wide, bears N. 55° W. and S. 55° E.   |
| 1835    | Spur, slopes W.; desc. over steep NW. slope.   |
| 1945    | Top of rock cutbank, 40 ft. high, faces W.   |
| 2000    | Graveled road, 12 ft. wide, bears N. 20° E. and S. 30° W.  |
| 2170    | Same graveled road, 12 ft. wide, bears N. 20° W. and S. 20° E. at bottom of descent, slopes W.; asc. over cutbank, 30 ft. high, faces W.   |
| 2235    | Spur, slopes N. 20° W.; desc. across steep E. slope.   |
| 2444.30 | <p>The 1/4 sec. cor. of secs. 25 and 26, determined at intersection of the record bearing and distance from the NW. bearing tree and record bearing from the NE. bearing tree mkd. by Lytle, et al., in 1952-54</p> <p style="padding-left: 40px;">A broken top fir, 64 ins. diam., bears N. 62 1/4° E., 20.7 ft. dist., with no scribe marks visible on large partially healed blaze caused by falling debris. (Record, 25.1 ft. dist.)</p> <p style="padding-left: 40px;">A fir stump, 51 ins. diam., bears N. 80 1/4° W., 56.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 8 W</p> <p>1/4</p> <p>S 26   S 25</p> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 24 1/2° W., 20.4 ft. dist., mkd. X at breast height BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on a small bench in a steep E. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 14' 50" E., beginning new measurement.</p> <p>Descend across steep E. slope through medium timber and moderate undergrowth.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |   |
|---------|---|
| 520     | Creek, 1/2 ft. wide, course E.; asc. over steep rock face, bears SE.  |
| 670     | Rock spur, slopes S. 70° E.; desc. across steep E. slope.   |
| 950     | Drainage, course S. 55° E.; asc. over steep rocky S. slope.   |
| 1185    | Ascend over steep SE. slope.  |
| 1228.58 | Point for the N 1/16 sec. cor. of secs. 25 and 26.<br><br>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.<br><br><div style="text-align: center;">           N 1/16<br/>           S 26   S 25<br/>           2007         </div><br>from which<br><br><div style="margin-left: 40px;">             A fir, 14 ins. diam., bears S. 29 1/2° E., 11.7 ft. dist., mkd. N1/16 S25 BT.<br/><br/>             A chinquapin, 14 ins. diam., bears S. 24 1/4° W., 32.1 ft. dist., mkd. N1/16 S26 BT.           </div><br>Deposit a magnet in a white plastic case at the base of the stainless steel post.<br><br>Continue ascent over steep SE. slope through medium timber and moderate undergrowth. |
| 1575    | Top of knob; desc. over steep E. slope.   |
| 2457.16 | The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.<br><br><div style="text-align: center;">           T 21 S R 8 W<br/>           S 23   S 24<br/>           ————<br/>           S 26   S 25<br/>           1952         </div><br>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54<br><br><div style="margin-left: 40px;">             A fir stump, 35 ins. diam., bears N. 44° E., 111.0 ft. dist., no marks visible. (Record, N. 40 1/4° E., 113.5 ft. dist.)           </div>   |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET |   |
|------|---|
|      | <p>A fir stump, 30 ins. diam., bears S. 48° E., 62.7 ft. dist., no marks visible. (Record, S. 49 1/2° E.)</p> <p>A fir stump, 43 ins. diam., bears S. 35 1/2° W., 61.4 ft. dist., with scribe marks S 6 BT and other illegible scribe marks visible on partially healed blaze.</p> <p>A fir stump, 33 ins. diam., bears N. 28 1/2° W., 147.8 ft. dist., with illegible scribe marks visible on detached partially healed blaze. (Record, N. 31 1/4° W.)</p> <p>and new bearing trees</p> <p>A fir, 12 ins. diam., bears N. 68° E., 6.4 ft. dist., mkd. T21S R8W S24 BT.</p> <p>A fir, 11 ins. diam., bears S. 1/4° E., 8.8 ft. dist., mkd. T21S R8W S25 BT.</p> <p>A fir, 11 ins. diam., bears S. 14 1/4° W., 15.2 ft. dist., mkd. T21S R8W S26 BT.</p> <p>A fir, 11 ins. diam., bears N. 85 3/4° W., 29.7 ft. dist., mkd. T21S R8W S23 BT.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, with top flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">S 24<br/>1/4 ———<br/>S 25<br/>1952</p> <p>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p>A hollow burned decayed fir stump, size indeterminate, bears N. 58 1/2° E., 37.0 ft. dist., no marks visible. (Record, 35.0 ft. dist.)</p> <p>A roothole bears S. 28 1/2° E., 31.7 ft. dist., alongside of which is a down stump, 40 ins. diam., with a healed blaze.</p> <p>and bearing trees mkd. by Graham in 1999-2000</p> <p>A fir, 11 ins. diam., bears S. 74° E., 10.5 ft. dist., with a healed blaze.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |   |
|---------|---|
|         | <p>A fir, 16 ins. diam., bears N. 38° W., 14.6 ft. dist., with a healed blaze.</p> <p>S. 88° 33' 24" W., bet. secs. 24 and 25.</p> <p>Ascend over SE. slope through medium timber and moderate undergrowth.</p>   |
| 555     | Spur, slopes S. 25° E., desc. over SW. slope.   |
| 1030    | Paradise Creek Road, graveled surface, 20 ft. wide, bears N. 40° W. and S. 55° E.   |
| 1190    | Creek, 7 ft. wide, course S. 20° E.; con. across bottom land.   |
| 1240    | Creek, 1 ft. wide, course N. 85° E.; asc. over steep rocky E. slope.  |
| 1990    | Spur, slopes N. 55° E.; desc. across steep N. slope.  |
| 2475    | Creek, 2 ft. wide, course N. 40° E., asc. over steep rocky E. slope.  |
| 2685.67 | <p>The cor. of secs. 23, 24, 25, and 26.</p> <hr/> <p>N. 0° 09' 53" W., bet. secs. 23 and 24.</p> <p>Across steep rocky E. slope through medium timber and light undergrowth.</p>   |
| 535     | Spur, slopes N. 40° E.; desc. over steep NW. slope.   |
| 1060    | Creek, 4 ft. wide, course N. 75° E.; asc. across E. slope.  |
| 1575    | Top of ascent, slopes E.; desc. over broken NE. slope.  |
| 2320    | Creek, 6 ft. wide, course S. 45° E.; asc. over SW. slope.   |
| 2438.95 | <p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4<br/>S 23   S 24<br/>1954</p> <p>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p>A burned cedar stump, 26 ins. diam., bears N. 48° E., 11.2 ft. dist., with scribe marks 1/4 S24 BT visible on unhealed blaze and chainsaw marks BI.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET         |   |              |  |      |      |       |  |      |      |      |  |
|--------------|---|--------------|--|------|------|-------|--|------|------|------|--|
|              | <p>A burned cedar stump, 25 ins. diam., bears N. 4 1/4° W., 59.4 ft. dist., no marks visible. (Record, 58.1 ft. dist.) Tree is located on the easterly cut bank of an overgrown dirt road, 8 ft. wide, bears N. 35° W. and S. 50° E.</p> <p>and bearing trees mkd. by Graham in 1999-2000</p> <p>A fir, 17 ins. diam., bears N. 83 1/2° E., 9.1 ft. dist., with a healed blaze.</p> <p>A fir, 25 ins. diam., bears S. 34° W., 7.5 ft. dist., with a healed blaze.</p> <hr/> <p>N. 0° 18' 39" W., beginning new measurement.</p> <p>Ascend over SW. slope through medium timber and light undergrowth.</p>   |              |  |      |      |       |  |      |      |      |  |
| 585          | Ascend across steep W. slope.   |              |  |      |      |       |  |      |      |      |  |
| 1135         | Top of ascent, slopes W.; desc. over NW. slope.   |              |  |      |      |       |  |      |      |      |  |
| 1430         | Creek, 5 ft. wide, course S. 20° W.; asc. across E. slope.  |              |  |      |      |       |  |      |      |      |  |
| 1445         | Creek, 2 ft. wide, course S. 55° E.; asc. over S. slope.  |              |  |      |      |       |  |      |      |      |  |
| 1954         | Paradise Creek Road, graveled surface, 15 ft. wide, bears N. 85° E. and S. 65° W.   |              |  |      |      |       |  |      |      |      |  |
| 2438.27      | <p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T 21 S R 8 W</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2">1954</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A burned decayed fir stump, 41 ins. diam., bears S. 75° W., 19.5 ft. dist., no marks visible. (Record, 17.8 ft. dist.)</p> <p>A decayed fir stump, size indeterminate, bears N. 3° W., 20.2 ft. dist., with scribe marks 21S R8 visible on detached blaze. (Record, 17.8 ft. dist.)</p> <p>and the remains of a bearing tree mkd. by Lytle, et al., in 1952-54</p> | T 21 S R 8 W |  | S 14 | S 13 | <hr/> |  | S 23 | S 24 | 1954 |  |
| T 21 S R 8 W |   |              |  |      |      |       |  |      |      |      |  |
| S 14         | S 13  |              |  |      |      |       |  |      |      |      |  |
| <hr/>        |   |              |  |      |      |       |  |      |      |      |  |
| S 23         | S 24  |              |  |      |      |       |  |      |      |      |  |
| 1954         |   |              |  |      |      |       |  |      |      |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET |  |
|------|--|
|      | <p>A decayed hemlock stump, 14 ins. diam., bears S. 33 1/2° E., 66.7 ft. dist., no marks visible. (Record, S. 34 3/4° E.)</p> <p>and the remains of the bearing trees mkd. by Graham in 1999-2000</p> <p>A hemlock, 19 ins. diam., bears N. 33° E., 35.5 ft. dist., with scribe marks 21S R8W S13 BT visible on partially healed blaze.</p> <p>A fir snag, 15 ins. diam., bears S. 61 1/2° E., 20.9 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A cedar, 10 ins. diam., bears S. 58 1/2° W., 31.0 ft. dist., with scribe marks T21S R8W S23 BT visible on partially healed blaze.</p> <p>A fir, 11 ins. diam., bears N. 54° W., 9.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 19 ins. diam., bears S. 40 1/4° E., 47.9 ft. dist., mkd. T21S R8W S24 BT.</p> <p>A red metal fence post is alongside the cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, in a tractor front tire collar, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 13<br/>1/4 ———<br/>S 24<br/>1954</p> </div> <p>from which the remains of an original bearing tree</p> <p>A burned cedar stump, 33 ins. diam., bears S. 18° W., 27.7 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p>A roothole bears N. 37 3/4° E., 33.0 ft. dist., alongside of which is a down fir stump, 20 ins. diam., no marks visible.</p> <p>A roothole bears S. 34 1/4° W., 13.6 ft. dist., with a down decayed cedar snag, size indeterminate, alongside</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |  |
|---------|--|
|         | with no scribe marks visible on burned partially healed blaze.   |
|         | and bearing trees mkd. by Graham in 1999-2000  |
|         | A fir, 13 ins. diam., bears S. 70 1/4° W., 26.9 ft. dist., with a healed blaze.  |
|         | A fir, 13 ins. diam., bears N. 13 1/2° W., 12.7 ft. dist., with a healed blaze.  |
|         | N. 89° 51' 48" W., bet. secs. 13 and 24.   |
|         | Ascend over SW. slope through medium timber and light undergrowth.   |
| 490     | Creek, 2 ft. wide, over bedrock, course S. 15° E.; asc. over SE. slope.  |
| 600     | Across S. slope.   |
| 750     | Descend over SW. slope.  |
| 1210    | Descend across S. slope.   |
| 1455    | Spur, slopes S. 65° W., desc. over NW. slope.  |
| 1870    | Dry creek bed, drains S. 10° W.; con. over a ridge, 15 ft. high.   |
| 1910    | Creek, 2 ft. wide, course S. 65° W.; con. across S. slope.   |
| 2065    | Creek, 1 ft. wide, intermittently underground, course S.; con. across S. slope.  |
| 2688.86 | The cor. of secs. 13, 14, 23, and 24.  |
|         | <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4<br/>S 27   S 26<br/>1952</p> <p>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p>A fir snag, 37 ins. diam., bears S. 2 1/2° E., 24.4 ft. dist., with a healed blaze.</p> <p>A fir, 55 ins. diam., bears S. 30 1/2° W., 9.9 ft. dist., with a healed blaze.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |   |
|---------|---|
|         | and a new bearing tree  |
|         | A fir, 6 ins. diam., bears S. 8 1/4° E., 22.1 ft. dist.,<br>mkd. 1/4 S26 BT.  |
|         | N. 0° 23' 09" W., bet. secs. 26 and 27.   |
|         | Across E. slope through medium timber and light undergrowth.  |
| 95      | Descend across steep E. slope.  |
| 515     | Creek, 4 ft. wide, course S. 70° E.; asc. across W. slope.  |
| 1219.12 | Point for the N 1/16 sec. cor. of secs. 26 and 27.  |
|         | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,<br>25 ins. in the ground, with brass cap mkd.   |
|         | N 1/16<br>S 27   S 26<br>2007   |
|         | from which  |
|         | A fir, 10 ins. diam., bears N. 28 3/4° E., 27.2 ft. dist.,<br>mkd. N 1/16 S26 BT.   |
|         | A fir, 8 ins. diam., bears N. 53 1/2° W., 7.3 ft. dist.,<br>mkd. N 1/16 S27 BT.   |
|         | Deposit a magnet in a white plastic case at the base of the<br>stainless steel post.  |
|         | Con. ascent across W. slope through medium timber and light<br>undergrowth.   |
| 1900    | Creek, 1 ft. wide, course S. 45° W.; asc. over steep N. slope.  |
| 2438.24 | The cor. of secs. 22, 23, 26, and 27, monumented with an iron<br>post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above<br>ground, with brass cap mkd. |
|         | T 21 S R 8 W<br>S 22   S 23<br>-----<br>S 27   S 26<br>1999   |
|         | from which the bearing trees mkd. by Lytle, et al., in 1952-54  |
|         | A dead top fir, 66 ins. diam., bears N. 27° E.,<br>125.4 ft. dist., with a healed blaze.  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET |   |
|------|---|
|      | <p>A dead top fir, 35 ins. diam., bears S. 28 1/2° W., 84.5 ft. dist., with a healed blaze. (Record, S. 29 1/2° W.</p> <p>and the remains of the bearing trees mkd. by Graham in 1999-2000</p> <p>A roothole bears S. 75 3/4° E., 8.0 ft. dist., with a down fir, 7 ins. diam., alongside with scribe marks X BT visible on open blaze.</p> <p>A hemlock, 13 ins. diam., bears N. 54 1/2° W., 20.9 ft. dist., with scribe marks T21S R8W S22 BT visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Ronald Rice, Registered Land Surveyor No. 54633, in 2002, on file in the Douglas County Surveyor's Office, under CS File No .65/44-31 A and B.</p> <p>A fir, 11 ins. diam., bears N. 13 3/4° W., 26.2 ft. dist., with illegible scribe marks visible on partially healed blaze and an aluminum nail on the left side center.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 63 ins. diam., bears S. 3 3/4° E., 66.6 ft. dist., with axe marks visible.</p> <p>Aluminum fence post is alongside the cor.</p> <p>Corner is located on the SE. cor. of recently logged area, edge bears N. and W.</p> <hr/> <p>N. 0° 12' 18" E., bet. secs. 22 and 23.</p> <p>Descend across steep E. slope through medium timber and light undergrowth, along the E. edge recently logged area.</p> |
| 135  | Bottom of descent, slopes SE.; asc. over steep rocky S. slope.  |
| 545  | Devil's Graveyard Road, graveled surface, 10 ft. wide, bears N. 65° W. and S. 85° E. on ridge, bears same; desc. over steep N. slope.   |
| 905  | Bottom of descent, drains N. 30° E.; asc. across steep E. slope.  |
| 1435 | Spur, slopes N. 50° E.; desc. over steep NW. slope.   |
| 2095 | Creek, 3 ft. wide, course N. 55° W., at the NE. cor. of recently logged area, edge bears N. 55° W. and S.; leave recently logged area and asc. over broken SW. slope.   |

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |  |
|---------|--|
| 2424.04 | <p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} 1/4 \\ S\ 22 \quad   \quad S\ 23 \\ 1954 \end{array}</math> </div> <p>from which the reference monuments by Lytle, et al., in 1952-54</p> <p>An iron post, 1 in. diam., firmly set, with top flush with the surface of the ground, bears N. 89° 25' 10" E., 40.01 ft. dist., with brass cap mkd. 1/4 S23 RM 1954 and an arrow pointing to the corner. (Record, East, 39.6 ft. dist.)</p> <p>An iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, bears S. 89° 41' 30" W., 39.66 ft. dist., with brass cap mkd. 1/4 S22 RM 1954 and an arrow pointing to the corner. (Record, West, 39.6 ft. dist.)</p> <p>and bearing trees mkd. by Ronald Rice, Registered Land Surveyor No. 54633, in 2002, on file in the Douglas County Surveyor's Office, under CS File No. 65/44-32</p> <p>A fir, 27 ins. diam., bears S. 44 1/2° E., 24.6 ft. dist., with scribe marks S23 BT visible on partially healed blaze and an aluminum nail on the right side center.</p> <p>A fir, 19 ins. diam., bears N. 11 1/2° W., 14.7 ft. dist., with scribe marks 1/4 S22 B visible on partially healed blaze and an aluminum nail on the right side center.</p> <p>An aluminum fence post is alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 24' 55" E., beginning new measurement.</p> <p>Ascend over SW. slope through medium timber and light undergrowth.</p> |
| 985     | Graveled road, 12 ft. wide, bears N. 30° W. and S. 45° E., at the SE. cor. of recently logged area, edge bears N. and N. 30° W.; con. along E. edge recently logged area.  |
| 1100    | Spur, slopes N. 45° W.; desc. over very steep N. slope.  |
| 1430    | Drainage, course N. 25° W.; asc. across very steep W. slope.   |
| 1820    | Spur, slopes N. 25° W.; at the NE. cor. of recently logged area, edge bears S. and W.; leave recently logged area and desc. over very steep N. slope.  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |        |       |    |    |    |    |      |  |
|---------|---|--------|-------|----|----|----|----|------|--|
| 1960    | Creek, 5 ft. wide, course N. 45° W.; asc. over gentle SW. slope.  |        |       |    |    |    |    |      |  |
| 2433.31 | <p>The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 21 S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="padding: 0 10px;">15</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">14</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">22</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;">23</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1954</td> </tr> </table> </div> <p>from which the reference monuments by Lytle, et al., in 1952-54.</p> <p style="padding-left: 40px;">An iron post, 2 in. diam., firmly set, projecting 13 ins. above ground, bears N. 45° 41' 45" E., 32.17 ft. dist., with brass cap mkd. T21S R8W S14 RM 1954 and an arrow pointing to the corner. (Record, N. 45° E., 33.0 ft. dist.)</p> <p style="padding-left: 40px;">An iron post, 2 in. diam., firmly set, projecting 4 ins. above ground, bears S. 44° 53' 15" W., 33.68 ft. dist., with brass cap mkd. T21S R8W S22 RM 1954 and an arrow pointing to the corner. (Record, S. 45° W., 33.0 ft. dist.)</p> <p>and bearing trees mkd. by Troy Rambo, Registered Land Surveyor No. 2865, in 2001, on file in the Douglas County Surveyor's Office, under CS File No. 65/37-22 A.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 68° E., 10.5 ft. dist., with illegible scribe marks visible on pitched-over partially healed blaze and an aluminum nail on the left side center.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 33° W., 11.7 ft. dist., with illegible scribe marks visible on pitched-over partially healed blaze and an aluminum nail on the left side center.</p> <p>An aluminum fence post is alongside the cor.</p> <p>Corner is located on the SW. cor. of recently logged area, edge bears N. and E.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 88° 36' 06" W., bet. secs. 14 and 23.</p> <p>Ascend over SE. slope through medium timber and light undergrowth.</p> | T 21 S | R 8 W | 15 | 14 | 22 | 23 | 1954 |  |
| T 21 S  | R 8 W   |        |       |    |    |    |    |      |  |
| 15      | 14  |        |       |    |    |    |    |      |  |
| 22      | 23  |        |       |    |    |    |    |      |  |
| 1954    |   |        |       |    |    |    |    |      |  |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
| 250     | Across nearly level S. slope.  |
| 875     | Paradise Creek Road, graveled surface, 15 ft. wide, bears N. 30° W. and S. 35° E.; also bottom of descent, slopes S.; asc. over SE. slope.                             |
| 1060    | Spur, slopes S. 25° E.; desc. over SW. slope.  |
| 1250    | Creek, 1 ft. wide, course S. 5° W.; asc. over SE. slope.   |
| 1410    | Spur, slopes S. 65° E.; desc. over SW. slope.  |
| 1580    | Creek, 2 ft. wide, course S. 20° E.; asc. over SE. slope.  |
| 1680    | Across nearly level S. slope.  |
| 2335    | Ascend over SE. slope.   |
| 2470.20 | The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.                       |
|         | T<br><u>    S 14</u><br>S 23<br>1954   |
|         | from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54  |
|         | A decayed fir stump, size indeterminate, bears N. 44° E., 31.7 ft. dist., no marks visible.  |
|         | A fir stump, 70 ins. diam., bears S. 53 1/4° E., 36.3 ft. dist., no marks visible.   |
|         | and bearing trees mkd. by Graham in 1999-2000  |
|         | A fir, 17 ins. diam., bears N. 16° E., 11.9 ft. dist., with a healed blaze.  |
|         | A fir, 14 ins. diam., bears S. 40 1/2° E., 26.4 ft. dist., with a healed blaze.  |
|         | and bearing trees mkd. by Troy Rambo, Registered Land Surveyor No. 2865, in 2001, on file in the Douglas County Surveyor's Office, under CS File No. 65/37-22 A.       |
|         | A fir, 20 ins. diam., bears N. 74 3/4° E., 13.9 ft. dist., with illegible scribe marks visible on partially healed blaze and an aluminum nail on the left side center. |

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |  |
|---------|--|
|         | <p>A fir, 18 ins. diam., bears N. 88 3/4° W., 12.2 ft. dist., with illegible scribe marks visible on pitched-over partially healed blaze and an aluminum nail on the left side center.</p> <p>Aluminum fence post alongside the cor.</p> <p>Corner is located on a bench on a SE. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 03' 46" W., beginning new measurement.</p> <p>Ascend over SE. slope through medium timber and light undergrowth.</p> |
| 235     | Devil's Graveyard Road, graveled surface, 12 ft. wide, bears N. 45° E. and S. 10° W.; asc. over steep E. slope.  |
| 590     | Top of knob, spur slopes S.; desc. over steep SW. slope.   |
| 635     | SE. cor. recently logged area, edge bears N. 45° E. and W; con. along S. bdy. recently logged area.  |
| 2479.41 | The cor. of secs. 14, 15, 22, and 23.  |
|         | <hr style="width: 50%; margin: 10px auto;"/> <p><b>Subdivision of Section 24,<br/>T. 21 S., R. 8 W., Willamette Meridian, Oregon</b></p> <hr style="width: 50%; margin: 10px auto;"/>  |
|         | <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 11' 10" W., on the N. and S. center line of sec. 24.</p> <p>Ascend over nearly level S. slope through medium timber and moderate undergrowth.</p>   |
| 415     | Creek, 3 ft. wide, course S. 45° E., in gully, 40 ft. deep; con. asc. over nearly level S. slope.  |
| 1025    | Same creek, 2 ft. wide, course S. 50° W., in gully, 40 ft. deep; con. asc. over nearly level S. slope.   |
| 1905    | Same creek, 1 ft. wide, course S. 20° E., in gully, 20 ft. deep; con. asc. over nearly level S. slope.   |
| 2401.57 | <p>Point selected for a Witness Point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>   |

**Subdivision of Section 24,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon**

| FEET    |   |
|---------|---|
|         | <p>T 21 S R 8 W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 80px;">WP   S 24</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;">2007</p>   |
|         | <p>from which</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears S. 12 3/4° E., 47.4 ft. dist., mkd. WP S24 BT with a Mag Nail on the left side center.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 73 1/4° W., 15.2 ft. dist., mkd. WP S24 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located in a shallow bowl, 50 ft. across, drains E.</p> <p>Continue ascent over nearly level S. slope through medium timber and moderate undergrowth.</p> |
| 2915    | Creek, 1 ft. wide, course S. 55° E.; asc. over S. slope.  |
| 4135    | Graveled road, 12 ft. wide, bears N. 30° W. and S. 30° E.   |
| 4265    | Same graveled road, 12 ft. wide, bears S. 65° E. and S. 60° W.  |
| 4803.14 | The 1/4 sec. cor. of secs. 13 and 24.   |
|         | <hr/> <p style="margin: 0;"><b>Subdivision of Section 26,<br/>T. 21 S., R. 8 W., Willamette Meridian, Oregon</b></p> <hr/>  |
|         | <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">             S 26<br/>             1/4 ———<br/>             S 35<br/>             1952           </p> <p>from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54</p> <p style="margin-left: 40px;">A decayed cedar snag, size indeterminate, bears S. 32 1/2° E., 4.0 ft. dist., no marks visible.</p>                             |

Subdivision of Section 26,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

|         |   |
|---------|---|
| FEEET   | <p>A fir, 45 ins. diam., bears N. 73° W., 40.3 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Graham in 1999-2000</p> <p>A cedar, 42 ins. diam., bears S. 10° E., 51.1 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>Corner is located on a steep NE. slope.</p> <p>N. 0° 32' 10" E., on the N. and S. center line of sec. 26.</p> <p>Descend over steep NE. slope through medium timber and moderate undergrowth.</p>  |
| 350     | Creek, 4 ft. wide, course S. 30° E.; asc. over SE. slope.   |
| 2250    | Top of ascent, slopes E.; desc. over steep NE. slope.   |
| 2437.23 | <p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 8 W<br/>C 1/4 S 26<br/>2007</p> <p>from which</p> <p>A hemlock, 15 ins. diam., bears S. 78° E., 10.4 ft. dist., mkd. C1/4 S26 BT.</p> <p>A fir, 13 ins. diam., bears S. 67 1/2° W., 40.7 ft. dist., mkd. C1/4 S26 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on a steep NE. slope.</p> <p>Descend over steep NE. slope through medium timber and moderate undergrowth.</p> |
| 2600    | Creek, 1 ft. wide, course E.; asc. across steep E. slope.   |
| 3657.97 | <p>Point for the center N 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>   |

Subdivision of Section 26,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |  |
|---------|--|
|         | <p style="text-align: center;">C<br/>N 1/16   S 26<br/>C<br/>2007</p>  |
|         | <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 21° W., 6.0 ft. dist., mkd. CN1/16 S26 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 63 3/4° W., 15.6 ft. dist., mkd. CN1/16 S26 BT.</p> <p>Corner is located on a ledge in a series of several small rock faces, on a steep E. slope.</p> <p>Ascend over steep E. slope through medium timber and moderate undergrowth.</p> |
| 4545    | Creek, 1 ft. wide, course S. 25° E., asc. across steep W. slope.   |
| 4878.71 | The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.   |
|         | <p style="text-align: center;">S 23<br/>1/4 ———<br/>S 26<br/>1952</p>  |
|         | <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 4 3/4° E., 27.0 ft. dist., mkd. 1/4 S26 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 36° W., 37.0 ft. dist., mkd. 1/4 S23 BT.</p>   |
|         | <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 88° 22' 57" W., on the E. and W. center line of sec. 26.</p> <p>Ascend over steep W. slope through medium timber and moderate undergrowth.</p>   |
| 100     | Graveled road, 12 ft. wide, bears N. 20° W. and S. 20° E. on ridge, bears same; desc. over steep W. slope.   |
| 2000    | Creek, 2 ft. wide, course S. 20° E.; asc. over steep E. slope.   |
| 2467.01 | The center 1/4 sec. cor. of sec. 26.   |

Subdivision of Section 26,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

| FEET    |   |
|---------|---|
|         | Continue ascent over steep E. slope through medium timber and moderate undergrowth. |
| 2990    | Spur, slopes S. 20° E.; desc. over steep SW. slope.                                 |
| 4430    | Creek, 4 ft. wide, course S. 45° E.; asc. over E. slope.                            |
| 4928.81 | The 1/4 sec. cor. of secs. 26 and 27.   |
| <hr/>   |   |
|         | From the N 1/16 sec. cor. of secs. 25 and 26.                                       |
|         | N. 88° 34' 04" W., on the E. and W. center line of the NE 1/4 of sec. 26.           |
|         | Ascend over SE. slope through medium timber and light undergrowth.                  |
| 295     | Spur, slopes S. 25° W.; desc. over steep, rocky W. slope.                           |
| 350     | Graveled road, 10 ft. wide, bears N. 20° E. and S. 35° W.                           |
| 560     | Drainage, bears N. 40° W.; con. across rocky N. slope.                              |
| 710     | Descend over steep NW. slope.   |
| 1255    | Creek, dry, 2 ft. wide, course S. 45° W.; asc. over SE. slope.                      |
| 2080    | Top of ascent, slopes S.; desc. over W. slope.                                      |
| 2260    | Top of rock bluff, 50 ft. high, faces W.  |
| 2360    | Dry creek, 4 ft. wide, drains S.; asc. over steep E. slope.                         |
| 2481.98 | The center N 1/16 sec. cor. of sec. 26.   |
| <hr/>   |   |
|         | N. 88° 25' 55" W., on the E. and W. center line of the NW 1/4 of sec. 26.           |
|         | Ascend over steep E. slope through medium timber and light undergrowth.             |
| 965     | Spur, slopes S. 20° E.; desc. over steep, rocky SW. slope.                          |
| 1200    | Continue across broken S. slope.  |
| 2155    | Descend over steep W. slope.  |
| 2481.25 | The N 1/16 sec. cor. of secs. 26 and 27.  |
| <hr/>   |   |