

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE WEST
BOUNDARY, AND SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTIONS 7 AND 9
TOWNSHIP 26 SOUTH, RANGE 7 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated May 25, 2004, approved May 28, 2004,
which provided for the surveys included under Group No. 2075,
and Assignment Instructions dated March 14, 2005.

Survey commenced April 5, 2005

Survey completed June 23, 2005

T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines, and the subdivision of sections 7 and 9, Township 26 South, Range 7 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the township lines and a portion of the subdivisional lines.

In 1881, Addison R. and Samuel C. Flint, U.S. Deputy Surveyors, retraced a portion of north, south, and west boundaries, and completed the subdivisional lines.

In 1963, Donald R. Beck, Cadastral Surveyor, remonumented certain original corner points without survey.

In 1967, Lynn M. Roseberry, Cadastral Surveyor, and Albert J. Garrison, Surveying Technician, dependently resurveyed a portion of the subdivisional lines.

In 1969, Lynn M. Roseberry, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines.

In 1971, Peter A. Peterson and Daniel L. Berry, Cadastral Surveyors, dependently resurveyed a portion of the east boundary, T. 26 S., R. 8 W.

In 1971-74, Peter A. Peterson, Daniel L. Berry, Gurdon S. Popken, and Harvey E. Wofford, Cadastral Surveyors, dependently resurveyed a portion of the subdivisional lines.

In 2002, Timothy J. Moore, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, dependently resurveyed a portion of the west boundary and subdivisional lines.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 25, 2004, for Group No. 2075, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. Baselines were computed and adjusted by least squares analysis. The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of the Agriculture, Forest Service.

T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET																									
	<p>(Restoring the 1856 survey by Dennis Hathorn, and the 1881 resurvey by Addison R. and Samuel C. Flint, and the 1971 resurvey by Peter A. Peterson and Daniel L. Berry, and the 2002 resurvey by Timothy J. Moore and Robert H. Browning)</p> <hr/> <p>Beginning at the true point for the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., not monumented, determined at record bearing and distance from the witness corner by Peterson and Berry in 1971.</p> <p>N. 0° 07' 00" W., bet. secs. 7 and 12.</p>																								
33.00	<p>The witness cor. for the cor. of secs. 7, 12, 13, and 18, monumented with a brass tablet, 3 ins. diam., cemented firmly into solid bedrock, mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>T 26 S</td> <td></td> </tr> <tr> <td>R 8 W</td> <td> </td> <td>R 7 W</td> </tr> <tr> <td>S 12</td> <td> </td> <td>S 7</td> </tr> <tr> <td colspan="3"><hr/></td> </tr> <tr> <td>S 13</td> <td> </td> <td>S 18</td> </tr> <tr> <td></td> <td>\</td> <td>/</td> </tr> <tr> <td></td> <td>WC</td> <td></td> </tr> <tr> <td></td> <td>1971</td> <td></td> </tr> </table> </div> <p>from which bearing trees mkd. by Peterson and Berry</p> <p>A madrone, 11 ins. diam., bears N. 73 1/2° E., 36.4 ft. dist., with a healed double blaze.</p> <p>A madrone, 8 ins. diam., bears S. 59° W., 41.5 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 28 ins. diam., bears N. 45 1/4° W., 63.8 ft. dist., with a healed blaze.</p>		T 26 S		R 8 W		R 7 W	S 12		S 7	<hr/>			S 13		S 18		\	/		WC			1971	
	T 26 S																								
R 8 W		R 7 W																							
S 12		S 7																							
<hr/>																									
S 13		S 18																							
	\	/																							
	WC																								
	1971																								
	<hr/> <p>N. 0° 28' 30" W., bet. secs. 7 and 12, beginning new measurement, posting and blazing.</p> <p>Descend over steep Northerly rock face.</p>																								
5	Ravine, drains S. 80° E., asc. over Northerly slope.																								
50	Spur, slopes S. 80° E., continue asc. over steep Easterly slope, and rock outcroppings.																								
1145	Spur, slopes East, desc. over NE. slope.																								

**Dependent Resurvey of a Portion of the West Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1298.20	<p>The S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 12 S 7 1971</p> <p>from which bearing trees mkd. by Peterson and Berry</p> <p style="padding-left: 40px;">A chinquapin, 8 ins. diam., bears N. 58° E., 7.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A madrone, 11 ins. diam., bears S. 9° W., 11.2 ft. dist., with a healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 14' 55" W., beginning new measurement.</p> <p>Descend over broken NE. slope.</p>
1325.50	<p>The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above a mound of stone 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 26 S 1/4 S 12 S 7 R 8 W R 7 W 1971</p> <p>from which bearing trees mkd. by Peterson and Berry</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 85 3/4° E., 37.4 ft. dist., with a healed blaze. (Record, East, 39.6 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 49 ins. diam., bears S. 32° W., 33.7 ft. dist., with a healed blaze.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 11' 55" W., beginning new measurement.</p> <p>Descend over NE. slope changing to ascend over SW. slope.</p>
1339.66	<p>The N 1/16 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 12 S 7 1971</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET

from which the remains of bearing trees mkd. by Peterson and Berry

A fir, 40 ins. diam., bears N. 2° E., 24.4 ft. dist., with a healed blaze.

A chinquapin, 15 ins. diam., bears N. 53° W., 10.6 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Dennis Hathorn, and the 1888 survey by Addison R. and Samuel C. Flint, and the 1963 remonumentation of certain original corner points by Donald R. Beck, and the 1967 resurvey by Lynn M. Roseberry, and the 1971 resurvey by Peter A. Peterson and Daniel L. Berry, and the 1971-74 resurvey by Peterson, Berry, Popken, and Wofford)

From the cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 26 S	R 7 W
S 9	S 10
S 16	S 15
1963	

from which the remains of an original bearing tree reported by Beck

A sawed fir stump, 33 ins. diam., bears N. 78° E., 9.9 ft. dist., with a healed blaze.

and a bearing trees recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 7 W., Point Identifier 400500, reported by Beck

and bearing trees mkd. by the Douglas County Surveyors Office, in 1922, reported by Beck

A fir, 54 ins. diam., bears S. 18° E., 29.0 ft. dist., with a healed blaze.

and the bearing trees mkd. by the Douglas County Surveyors Office, in 1962-63, reported by Beck

A fir, 40 ins. diam., bears N. 59° E., 47.6 ft. dist., with a healed double blaze. (Record, 46.9 ft. dist.)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 36 ins. diam., bears S. 89° W., 24.4 ft. dist., with a healed double blaze.</p>
	<p>A fir, 20 ins. diam., bears N. 48° W., 7.3 ft. dist., with a healed double blaze.</p>
	<p>N. 0° 33' 23" W., bet. secs. 9 and 10, posting and blazing.</p>
	<p>Descend over broken NE. slope, through second growth timber and dense undergrowth.</p>
830	<p>Wire fence, bears N. 80° E. and S. 80° W.</p>
865	<p>Asphalt road, 25 ft. wide, bears N. 70° W. and S. 70° E.</p>
2182.12	<p>A local property corner, established by Herman A. Pieske, Registered Professional Land Surveyor, No. 1631, in 1988, recorded in the Douglas County Surveyors Office, Map File No. M106-25, monumented with an iron rod, 5/8 ins. diam, firmly set, projecting 1 in. above the ground, with yellow plastic cap, 1 1/2 ins. diam., affixed to top, with top mkd. AA SURVEYING INC. Not utilized during the course of this survey</p>
2485	<p>Creek 1 1/2 ft. wide, course N. 15° W., asc. over SE. slope.</p>
2585	<p>Spur, slopes West, desc. over NW. slope.</p>
2660.75	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 9 S 10 T 26 S R 7 W 1963</p>
	<p>from which the remains of a bearing tree mkd. by Beck</p>
	<p>A roothole, bears N. 85 1/2° W., 22.4 ft. dist., alongside of which is the displaced sawed cedar stump, 17 ins. diam., no marks visible.</p>
	<p>and the remaining bearing tree mkd. by Roseberry and Garrison</p>
	<p>A fir, 19 ins. diam., bears N. 11° W., 142.2 ft. dist., with a healed blaze.</p>
	<p>and a bearing tree mkd. by Thomas E. Shrum, Registered Professional Land Surveyor, No. 1706, in 1981, recorded in the Douglas County Surveyors Office, Map File No. M89-29</p>
	<p>A fir, 17 ins. diam., bears N. 62° E., 6.6 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>Corner is also located in a 5 strand barbed wire fence, extending north and south; also located east, 7.0 ft. dist. of a creek, 1 1/2 ft. wide, course N. 15° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 07" E., bet. secs. 9 and 10, continue posting and blazing.</p> <p>Descend over NW. slope.</p>				
35	<p>Creek 2 ft. wide, course N. 10° E., continue descending over NE. slope.</p>				
2651.06	<p>The cor. of secs. 3, 4, 9, and 10, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 26 S R 7 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> </table> <p>1959</p> </div> <p>from which accessories recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 7 W., Point Identifier No. 400600,</p> <p>the remains of the remaining bearing tree mkd. by the Douglas County Surveyors Office, in 1959, reported by Roseberry and Garrison</p> <p style="padding-left: 40px;">A fir snag, 11 ins. diam., bears S. 60° W., 32.0 ft. dist., with scribe marks T26S R7W S9 CS BT visible on open blaze.</p> <p>and a bearing tree mkd. by Roseberry and Garrison</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 63 1/4° E., 177.9 ft. dist., with a healed blaze. (Record, S. 62 1/2° E.)</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyors Office, in 1984,</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears N. 58 1/2° E., 139.8 ft. dist., with scribe marks BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 24 1/2° W., 28.9 ft. dist., with a healed double blaze.</p>	S 4	S 3	S 9	S 10
S 4	S 3				
S 9	S 10				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 23 ins. diam., bears S. 61 3/4° W., 33.6 ft. dist., with a healed double blaze.</p> <p>Corner is located, north, 0.5 ft. dist., of a fence cor., with woven wire fences extending, south and west.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89° 40' 25" W., bet. secs. 9 and 16, posting and blazing.</p> <p>Ascend over broken NE. slope changing to descend over NW. slope, through second growth timber and dense undergrowth.</p>
1345	Creek 1.5 ft. wide, course N. 5° W., asc. over NE. slope, changing to across Northerly slope.
2587.09	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 7 W</p> <p>S 9</p> <p>1/4 ———</p> <p>S 16</p> <p>1967</p> </div> <p>from which the remains of bearing trees mkd. by Roseberry and Garrison</p> <p style="text-align: center;">A fir, 24 ins. diam., bears S. 16 1/4° E., 29.6 ft. dist., with a healed blaze. (Record, S. 18° E., 31.7 ft. dist.)</p> <p style="text-align: center;">A fir, 22 ins. diam., bears N. 63 1/2° W., 35.0 ft. dist., with a healed blaze.</p> <p>From this corner, a point established as the 1/4 sec. cor. of secs. 9 and 16, by Hathorn in 1855, bears S. 47° 45' 17" W., 56.74 ft. dist., (record, S. 46° 30' 00" W., 55.44 ft. dist.), determined at record bearing and distance from the remaining original bearing tree: (the Hathorn position was superseded by the 1881 Flint survey)</p> <p style="text-align: center;">A sawed fir stump, 26 ins. diam., bears S. 85° E., 23.1 ft. dist., no marks visible.</p> <hr/> <p>N. 89° 48' 12" W., beginning a new measurement, continue posting and blazing.</p> <p>Across Northerly slope.</p>
20	Creek 1 ft. wide, course N. 55° E., asc. over NE. slope.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET									
515	Graveled road, 12 ft. wide, bears N. 45° W. and S. 40° E.								
1385	Graveled road, 12 ft. wide, bears N. 30° W. and S. 30° E.								
1700	Top of rock bluff, edge bears N. 45° W. and S. 45° E.								
2005	Ridge, bears N. 35° W. and S. 35° E., desc. over NW. slope.								
2592.97	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 26 S</td> <td>R 7 W</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td colspan="2">1967</td> </tr> </table> </div> <p>from which bearing trees mkd. by Roseberry and Garrison</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears N. 50 1/2° E., 70.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 54 ins. diam., bears S. 52 1/2° E., 16.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears S. 20° W., 41.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 36 1/4° W., 52.1 ft. dist., with a healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 17' 20" W., bet. secs. 8 and 9, beginning a new measurement.</p> <p>Descend over broken NW. slope, changing to broken NE. slope, through second growth timber and dense undergrowth.</p>	T 26 S	R 7 W	S 8	S 9	S 17	S 16	1967	
T 26 S	R 7 W								
S 8	S 9								
S 17	S 16								
1967									
1315	Graveled road, 15 ft. wide, bears N. 40° W. and S. 40° E.								
2638.93	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 26 S</td> <td>R 7 W</td> </tr> <tr> <td colspan="2">1/4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2">1967</td> </tr> </table> </div>	T 26 S	R 7 W	1/4		S 8	S 9	1967	
T 26 S	R 7 W								
1/4									
S 8	S 9								
1967									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>from which bearing trees mkd. by Roseberry and Garrison</p> <p style="padding-left: 40px;">A fir, 53 ins. diam., bears N. 46° E., 20.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 25° W., 21.1 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by the Douglas County Surveyors Office, in 1997, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 7 W., Point Identifier No. 300540</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 64 3/4° E., 12.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A double trunked cedar, 23 ins. diam., bears N. 67° W., 8.3 ft. dist., with fragmentary scribe marks 1/4 S8 CS visible on partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 21' 57" W., beginning a new measurement.</p> <p>Across nearly level Easterly slope.</p>
1285	Abandoned dirt road, 12 ft. wide, bears N. 30° E. and S. 30° W.
1318.24	<p>The N 1/16 sec. cor. of secs. 8 and 9, remonumented by Thomas E. Shrum, Registered Professional Land Surveyor, No. 1706, recorded in the Douglas County Surveyors Office, Map File No. M89-29, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T26S R7W PLS 1706 S 8 S 9 1981 1/16</p> <p>from which bearing trees mkd. by Roseberry and Garrison</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 43° E., 50.9 ft. dist., with a healed blaze. (Record, S. 40° E., 50.5 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 18° W., 32.5 ft. dist., with a healed blaze. (Record, N. 22° W., 34.0 ft. dist.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 04' 30" W., beginning new measurement, posting and blazing.</p> <p>Across nearly level Easterly slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET													
685	Top of ascent, slopes N. 15° W., desc. over NE. slope.												
1318.10	<p>The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 26 S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">R 7 W</td> </tr> <tr> <td style="padding: 0 5px;">S 5</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 8</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;"></td> <td style="border-top: 1px solid black; padding: 0 5px;">S 9</td> </tr> <tr> <td colspan="3" style="padding: 0 5px;">1967</td> </tr> </table> </div> <p>from which the remains of original bearing trees</p> <p style="margin-left: 40px;">A sawed fir stump, 25 ins. diam., bears N. 37 3/4° E., 31.7 ft. dist., with no scribe marks visible on opened blaze.</p> <p style="margin-left: 40px;">A fir, 38 ins. diam., bears N. 20° W., 9.2 ft. dist., with no scribe marks visible on opened blaze.</p> <p>and the remains of bearing trees mkd. by Roseberry and Garrison</p> <p style="margin-left: 40px;">A sawed fir stump, 24 ins. diam., bears N. 76 1/2° E., 36.0 ft. dist., with a healed blaze. (Record, N. 78 1/4 E.)</p> <p style="margin-left: 40px;">A cedar snag, 10 ins. diam., bears S. 78 1/2° E., 26.4 ft. dist., with scribe marks R7W S9 BT visible on partially healed blaze.</p> <p style="margin-left: 40px;">A cedar, 20 ins. diam., bears S. 72° W., 27.4 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A cedar, 7 ins. diam., bears N. 41 1/4° E., 39.2 ft. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears S. 36 1/2° E., 19.2 ft. dist., mkd. X BT.</p> <p>There is no longer any evidence of the corner established by Hathorn, in 1855.</p> <p>Corner is located on a NE. slope, with numerous large rock outcroppings.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>S. 89° 49' 30" W., bet. secs. 4 and 9, posting and blazing.</p>	T 26 S		R 7 W	S 5		S 4	S 8		S 9	1967		
T 26 S		R 7 W											
S 5		S 4											
S 8		S 9											
1967													

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	Descend over broken NW. slope.
790	Creek 5 ft. wide, course N. 20° E., asc. over NE. slope.
950	Creek 3 ft. wide, course N. 45° E., asc. over NE. slope.
1318.56	<p>The E 1/16 sec. cor. of secs. 4 and 9, established by Thomas E. Shrum, Registered Professional Land Surveyor, in 1981, recorded in the Douglas County Surveyors Office, Map File No. M89-29, and is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T26S R7W E 1/16 S 9 ——— S 16 PLS 1706 1981</p> <p>from which the remains of the remaining bearing trees mkd. by Shrum</p> <p style="padding-left: 40px;">A sawed fir stump, 12 ins. diam., bears N. 54° W., 18.8 ft. dist., with scribe marks 6 S4 BT visible on partially healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 38° E., 7.8 ft. dist., mkd. E1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 61° W., 23.8 ft. dist., mkd. E1/16 S4 BT.</p> <p>Corner is located West, 0.5 ft. dist., of a fence cor., with woven wire fence extending East.</p> <p style="text-align: center;">—————</p> <p>S. 89° 49' 01" W., beginning new measurement, continue posting and blazing.</p> <p>Continue ascending over broken NE. slope.</p>
1160	Creek 2 ft. wide, course S. 10° E., asc. over Easterly. slope.
1317.52	The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">T 26 S R 7 W S 4 1/4 ——— S 9 1967</p> <p>from which the remains of the bearing trees mkd. by Roseberry and Garrison</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears N. 16° E., 51.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A root hole, bears S. 12° E., 51.2 ft. dist., alongside of which is the fir trunk, 38 ins. diam., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 45° E., 10.4 ft. dist., mkd. 1/4 S4 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 14 1/4° E., 9.8 ft. dist., mkd. 1/4 S9 BT.</p> <p>From this corner, the corner of sections 4, 5, 8, and 9, bears S. 89° 52' 25" W., 2634.78 ft. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18, remonumented by Larry E. Monrean, Deputy County Surveyor, in 1981, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 26 S., R. 7 W., Point Identifier No. 200500, monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T 26 S R 7 W S 7 S 8 ——— ——— S 18 S 17 1981</p> <p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 37 ins. diam., bears N. 85° E., 15.2 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 85° W., 38.2 ft. dist., with fragmentary scribe marks visible on the bark.</p> <p>and the remains of bearing trees mkd. by Byron, reported by Roseberry</p>
------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>N. 88° 23' 51" W., beginning new measurement, continue posting and blazing.</p> <p>Continue descending over broken NW. slope.</p>
1331.77	<p>Point for the W 1/16 sec. cor. of secs. 7 and 18.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 7 W 1/16 ——— S 18 2005</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 67 1/4° E., 6.1 ft. dist., mkd. W1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 15 1/4° W., 23.6 ft. dist., mkd. W1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established by the BLM, in 1979, during the course of an unofficial Administrative Survey, recorded in the Douglas County Surveyors Office, Map File No. M80-80, and is not utilized during the course of this survey, bears N. 68° 11' 09" W., 12.74 ft. dist., monumented with an iron pipe, 3/4 ins. diam., 24 ins. long, firmly set, projecting 4 in. above the ground, from which the bearing trees referenced to, and not mkd.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 39 1/4° E., 23.6 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 78° E., 13.1 ft. dist., no marks visible.</p> <p>Remove the iron pipe, and place at the base of the stainless steel post.</p> <p>Continue descending over broken NW. slope.</p>
1845	Graveled road, 12 ft. wide, bears north and south.
1950	Hubbard Creek 2 ft. wide, course N. 10° E., asc. over NE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2710.16	<p>The true cor. of secs. 1, 12, 13, and 18, on the W bdy. of the Tp. Not monumented.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 35' 12" E., bet. secs. 7 and 8, posting and blazing.</p> <p>Descend over broken NE. slope, changing to ascend over broken SE. slope.</p>
1363.82	<p>The true point for the S 1/16 sec. cor. of secs. 7 and 8, falls on the root of a fir, 45 ins diam.</p> <p>At the corner point set a (MAG-NAIL) 3 1/2 in. X 1/4 in., flush in a root, 16 ins. diam.</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 14° E., 28.5 ft. dist., mkd. S1/16 S8 BT.</p> <p>and reference monument</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground for a reference monument, bears N. 72° 27' 15" W., 8.9 ft. dist. with brass cap mkd. RM S1/16 S7 8.9 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>From this corner, a point established by the BLM, in 1968, during the course of an unofficial Administrative Survey, and is not utilized during the course of this survey, bears N. 83° 41' 52" E., 1.20 ft. dist., monumented with an iron pipe, 3/4 ins. diam. X 60 ins. long, firmly set, projecting 18 ins. above the ground, from which the bearing trees referenced to, and not mkd.</p> <p style="padding-left: 40px;">A fir, 45 ins. diam., bears N. 58 3/4° E., 6.9 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears N. 47 1/2° W., 7.9 ft. dist., no marks visible.</p> <p>Remove the iron pipe, and place at the base of the stainless steel post.</p> <p>Continue ascending over broken SE. slope changing to SW. slope.</p> <p>Discontinue posting and blazing.</p>
2727.64	<p>The 1/4 sec. cor. of secs. 7 and 8, reestablished by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1983, recorded in the Douglas County Surveyors</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>Office, Map File No. M90-51, and is accepted as the corner, monumented with an iron pipe, 2 ins. diam., firmly set, flush with the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W 1/4 S 7 S 8 1983 PLS 1988</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 55 1/4° E., 25.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 25 1/4° W., 27.4 ft. dist., with a healed double blaze.</p> <p>From this corner, a point established by the BLM, in 1968, during the course of an unofficial Administrative Survey, and is not utilized during the course of this survey, bears N. 15° 38' 53" E., 1.07 ft. dist., monumented with an iron pipe, 3/4 ins. diam., firmly set, projecting 28 in. above the ground, from which the bearing trees referenced to, and not mkd.</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 35° E., 14.9 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A madrone, 11 ins. diam., bears N. 19 1/2° W., 16.3 ft. dist., no marks visible.</p> <p>Leave the iron pipe in place, as was tied to and referenced on the plat filed by Geisler.</p> <hr style="width: 30%; margin: 10px auto;"/>
N. 0° 34'	54" E., beg. new measurement, posting and blazing.
	Ascend over SW. slope.
700	Graveled road, 20 ft. wide, bears N. 30° W. and S. 30° E.
1364.10	Point for the N 1/16 sec. cor. of secs. 7 and 8.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	N 1/16 S 7 S 8 2005
	from which

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>A fir, 11 ins. diam., bears N. 20° E., 35.6 ft. dist., mkd. N1/16 S8 BT.</p> <p>A fir, 24 ins. diam., bears N. 80 1/4° W., 55.7 ft. dist., mkd. N1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this corner, a point established by the BLM, in 1968, during the course of an unofficial Administrative Survey, and is not utilized during the course of this survey, bears N. 15° 37' 40" E., 1.42 ft. dist., monumented with an iron pipe, 3/4 ins. diam. X 60 ins. long, firmly set, projecting 28 ins. above the ground, from which the bearing trees referenced to, and not mkd.</p> <p>A fir, 14 ins. diam., bears N. 52° E., 16.7 ft. dist., no marks visible.</p> <p>A madrone snag, 8 ins. diam., bears S. 0 1/4° E., 18.2 ft. dist., no marks visible.</p> <p>Remove the iron pipe, and place at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p> <p>Continue ascending over broken SW. slope.</p>				
2728.19	<p>The cor. of secs. 5, 6, 7, and 8, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 26 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>R 7 W</p> <p>1966</p> </div> <p>from which the remains of original bearing trees</p> <p>A decayed fir stump, 25 ins. diam., bears S. 85° E., 11.9 ft. dist., no marks visible.</p> <p>A sawed and decayed fir stump, 37 ins. diam., bears S. 80° W., 9.2 ft. dist., no marks visible.</p> <p>and a bearing tree of unknown origin, reported by Peterson</p>	S 6	S 5	S 7	S 8
S 6	S 5				
S 7	S 8				

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 21 ins. diam., bears S. 65° E., 35.6 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by the Douglas County Surveyors Office, reported by Peterson</p> <p>A fir, 12 ins. diam., bears N. 15° E., 34.3 ft. dist., with a healed blaze.</p> <p>A fir, 12 ins. diam., bears S. 22 3/4° W., 11.9 ft. dist., with a healed blaze. (Record, S. 27° W.)</p> <p>A chinquapin, 17 ins. diam., bears N. 57° W., 54.8 ft. dist., with a healed blaze.</p> <hr/> <p>N. 89° 39' 29" W., bet. secs. 6 and 7.</p> <p>Descend over broken SW. slope.</p>
1410	Graveled road, 16 ft. wide, bears N. 15° W. and S. 25° E.
1945	Dirt road, 9 ft. wide, bears N. 5° E. and S. 5° E.
2698.37	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 6</p> <p>1/4 ———</p> <p>S 7</p> <p>T 26 S R 7 W</p> <p>1974</p> </div> <p>from which the remains of bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p>A sawed and decayed fir stump, 25 ins. diam., bears S. 45° E., 61.4 ft. dist., with scribe marks 1/4 S6 BT visible on open blaze.</p> <p>A sawed and decayed fir stump, 25 ins. diam., bears N. 19° W., 26.4 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 9 ins. diam., bears N. 75 1/4° E., 27.1 ft. dist., mkd. 1/4 S6 BT.</p> <p>A fir, 6 ins. diam., bears S. 9 3/4° W., 12.3 ft. dist., mkd. 1/4 S7 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located south, 2.5 ft. dist., of a rock face, 6 ft. high, edge bears N. 80° W. and S. 80° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 42' 21" W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>
440	Creek 1 ft. wide, course S. 80° W., asc. over SE. slope.
615	Spur, slopes S. 25° W., desc. over SW. slope.
1349.15	<p>The W 1/16 sec. cor. of secs. 6 and 7, monumented with an iron post, firmly set, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 7 W 1/16 ——— S 18 1971</p> </div> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="margin-left: 40px;">A madrone, 12 ins. diam., bears S. 25° E., 2.6 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A madrone, 13 ins. diam., bears S. 55° W., 18.5 ft. dist., with a healed blaze.</p> <p>Corner is located on a steep southerly slope.</p> <hr style="width: 80%; margin: 10px auto;"/> <div style="text-align: center; margin: 10px auto;"> <p>Subdivision of Section 7, T. 26 S., R. 7 W., Willamette Meridian, Oregon</p> </div> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0° 12' 40" E., on the N. and S. centerline of sec. 7.</p> <p>Descend over broken NW. slope, changing to ascend over broken SW. slope.</p>
1345.90	Point for the center S 1/16 sec. cor. of sec. 7, not monumented
2665	Creek 2 ft. wide, course S. 45° W., asc. over SE. slope.
2691.79	<p>Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. centerline.</p> <p>At the cor. point</p>

**Subdivision of Section 7,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W C 1/4 S 7 2005</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 25° E., 18.9 ft. dist., mkd. C1/4 S7 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears West, 17.1 ft. dist., mkd. C1/4 S7 BT.</p> <p>Ascend over SE. slope.</p>
4043.97	Point for the center N 1/16 sec. cor. of sec. 7, not monumented.
5396.15	The 1/4 sec. cor. of secs. 6 and 7, hereinbefore described.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8, hereinbefore described.</p> <p>N. 89° 08' 56" W., on the E. and W. centerline of sec. 7.</p> <p>Descend over broken SW. slope, changing to broken NW. slope.</p>
2645	Creek 1.5 ft. wide, course S. 45° W., asc. over SE. slope.
2681.21	The center 1/4 sec. cor. of sec. 7.
	Ascend over SE. slope.
2780	Spur, slopes S. 60° W., desc. over NW. slope.
4024.03	<p>The center W 1/16 sec. cor. of sec. 7, established by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1983, recorded in the Douglas County Surveyors Office, Map File No. M90-51, and is accepted as the corner, monumented with an iron pipe, 1 ins. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">PLS 1988 W 1/16 C———C S 7 1983</p> <p>from which bearing trees mkd. by Geisler</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 34 1/2° E., 7.2 ft. dist., with a healed double blaze.</p>

**Subdivision of Section 7,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 19 ins. diam., bears S. 31 1/4° W., 7.1 ft. dist., with a healed double blaze.</p> <p>Continue descending over NW. slope.</p>
4640	Graveled road, 15 ft. wide, bears N. 45° W. and S. 45° E.
4680	Hubbard Creek 15 ft. wide, course N. 5° E., asc. over NE. slope.
5416.78	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy of the Tp., hereinbefore described.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy of the Tp.</p> <p>S. 88° 43' 20" E., on the E. and W. centerline of the SW. 1/4 sec. 7, posting and blazing.</p> <p>Descend over broken NE. slope.</p>
1385	Hubbard Creek 20 ft. wide, course N. 15° E., across creek bottom.
1388.10	<p>The true point for the SW 1/16 sec. cor. of sec. 7, at intersection with the N. and S. centerline of the SW 1/4 of sec. 7, where it is impractical to set a permanent monument.</p> <p>From this point, a witness corner established by Ronald G. Geisler, Registered Professional Land Surveyor, No. 1988, in 1983, recorded in the Douglas County Surveyors Office, Map File No. M90-51, for the SW 1/16 sec. cor. of sec. 7, bears S. 88° 43' 20" E., 30.18 ft. dist., and is accepted and utilized as control on the E. and W. centerline of the SW 1/4 of sec. 7, monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">30.0 FT WC ←----- SW 1/16 S 7 1983 PLS 1988</p> <p>from which bearing trees mkd. by Geisler</p> <p style="text-align: center;">An alder, 16 ins. diam., bears N. 15 1/4° E., 7.3 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 86 3/4° E., 17.7 ft. dist., with a healed blaze.</p> <hr/>

**Subdivision of Section 7,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>N. 0° 02' 09" W., on the N. and S. centerline of the SW 1/4 sec. 7, beginning new measurement, posting and blazing.</p> <p>Across creek bottom.</p>
170	<p>Begin asc., edge bears N. 10° E. and S. 5° W., asc. over SE. slope, changing to descend over NE. slope.</p>
565	<p>Hubbard Creek 15 ft. wide, course N. 55° W., asc. over SE. slope.</p>
695	<p>Graveled road, 12 ft. wide, bears N. 55° W. and S. 55° E.</p>
1335.74	<p>The center west 1/16 sec. cor. of sec. 7.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' 16" E., on the N. and S. centerline of the NW 1/4 sec. 7, beginning new measurement, posting and blazing.</p> <p>Ascend over broken SW. slope.</p>
1346.05	<p>Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. centerline of the NW 1/4 of sec. 7.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 7 2005</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 64 1/2° E., 9.5 ft. dist., mkd. NW1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 18 1/4° W., 17.2 ft. dist., mkd. NW1/16 S7 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 24' 46" W., on the E. and W. centerline of the NW 1/4 of sec. 7, beginning new measurement, posting and blazing.</p> <p>Descend over broken SW. slope.</p>
1398.90	<p>The N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr style="width: 20%; margin: 10px auto;"/>

**Subdivision of Section 9,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>From the 1/4 sec. cor. of secs. 9 and 16, hereinbefore described.</p> <p>N. 0° 41' 15" W., on the N. and S. centerline of sec. 9.</p> <p>Descend over NE. slope.</p>
2565	Graveled road, 20 ft. wide, bears N. 70° W. and S. 70° E.
2646.72	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. centerline of sec. 9.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W C 1/4 S 9 2005</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 73° E., 11.6 ft. dist., mkd. C1/4 S9 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 0 1/2° E., 28.1 ft. dist., mkd. C1/4 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue descending over broken NE. slope, changing to ascend over broken SE. slope.</p>
3967.94	<p>The center N 1/16 sec. cor. of sec. 9, established by Thomas E. Shrum, registered Professional Land Surveyor, No. 1706, in 1981, recorded in the Douglas County Surveyors Office, Map File No. M89-29, and is accepted as the cor., monumented with an iron pipe, 1 in. diam., loosely set, projecting 19 ins. above the ground, (reset the 1 X 36 ins. iron pipe in place, 28 ins. in the ground), with aluminum cap mkd.</p> <p style="text-align: center;">T29S R7W NC SEC 9 1/16 RLS 1706 1981</p> <p>from which bearing trees mkd. by Shrum</p>

**Subdivision of Section 9,
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 28 ins. diam., bears N. 54 1/2° E., 20.1 ft. dist., with a healed blaze.</p> <p>A hemlock, 10 ins. diam., bears S. 18 1/4° W., 7.6 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 1° 06' 14" W., beginning new measurement, posting and blazing.</p> <p>Ascend over Easterly slope.</p>
220	Spur, slopes S. 70° E., desc. over NE. slope.
1140	Creek 2 ft. wide, course N. 65° E., asc. over SE. slope.
1265	Spur, slopes S. 70° E., desc. over NE. slope.
1321.31	The 1/4 sec. cor. of secs. 4 and 9, hereinbefore described.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor of secs. 9 and 10, hereinbefore described.</p> <p>N. 89° 59' 10" W., on the E. and W. centerline of sec. 9, posting and blazing.</p> <p>Descend over broken NW. slope.</p>
5	Creek 1.5 ft. wide, course N. 15° W., asc. over NE. slope.
2592.66	The center 1/4 sec. cor. of sec. 9.
	Continue asc. over broken NE. slope.
5212.91	The 1/4 sec. cor. of secs. 8 and 9, hereinbefore described.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the center N 1/16 sec. cor. of sec. 9.</p> <p>S. 89° 56' 35" W., on the E. and W. centerline of the NW 1/4 sec. 9, posting and blazing.</p> <p>Ascend over broken Easterly slope, changing to asc. over broken NE. slope.</p>
1530	Graveled road, 15 ft. wide, bears N. 5° W. and S. 5° E.
2620	Dirt road, 15 ft. wide, bears N. 35° E. and S. 20° W.
2635.66	The 1/4 sec. cor. of secs. 8 and 9.
	<hr style="width: 80%; margin: 10px auto;"/>