

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
THE BOUNDARIES OF DONATION LAND CLAIM NO. 45,
AND THE SUBDIVISION-OF-SECTION LINES OF SECTIONS 32 AND 33,

TOWNSHIP 22 SOUTH, RANGE 8 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Aaron M. Graham, Cadastral Surveyor

Michael O. Jones, Surveying Technician

Under Special Instructions dated October 7, 2008, approved October 8, 2008,
which provided for the surveys included under Group No. 2241,
and Assignment Instructions dated October 8, 2008.

Survey commenced November 12, 2008

Survey completed April 29, 2009

T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the boundaries of Donation Land Claim No. 45, and the subdivision-of-section lines of sections 32 and 33, Township 22 South, Range 8 West, Willamette Meridian, Oregon.

The history of surveys pertinent to this survey is as follows:

In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the north and west boundaries and subdivisional lines and the meander lines of the Umpqua River, as shown on the official plat of survey, approved February 20, 1856.

In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the boundaries of Donation Land Claim No. 45, as shown on the official plat of survey, approved December 23, 1859.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed the north boundary and a portion of the east boundary and subdivisional lines, as shown on the official plat of survey, approved August 11, 1881.

In 1960, Floyd A. Brooks, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, as shown on the official plat of survey, accepted January 31, 1962.

In 1962, Floyd A. Brooks, Cadastral Surveyor, resurveyed a portion of the south boundary, (Fifth Standard Parallel South) and subdivisional lines, as shown on the official plat of survey, accepted September 24, 1963.

In 1963-65, Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, resurveyed a portion of the south boundary, (Fifth Standard Parallel South) and portions of the north and east boundaries, a portion of the subdivisional lines, and a portion of certain claim lines, remonumented certain original corners, and subdivided sections 32 and 33, as shown on the official plat of survey, accepted March 24, 1966.

In 1965-67, Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, resurveyed a portion of the west boundary, subdivisional lines, and certain claim lines, and subdivided section 29, as shown on the official plat of survey, accepted July 25, 1969.

In 1980, Harvey E. Wofford, Cadastral Surveyor, resurveyed a portion of the south boundary, (Fifth Standard Parallel South) and a portion of the west boundary, as shown on the official plat of survey, accepted April 14, 1983.

T. 22 S., R. 8 W., Willamette Meridian, Oregon

FEET

In 1983, Joel E. Robb, Cadastral Surveyor, resurveyed a portion of the subdivisional lines and subdivided section 31, as shown on the official plat of survey, accepted July 12, 1985.

The following plats and field notes filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name and year.

| <u>Date</u> | <u>Name and Registration Number</u> | <u>File Number</u> |
|-------------|--|--------------------|
| 1963 | Milo E. Godfrey Douglas Co. Surveyor | 52/14 |
| 1982 | Rockne R. Luckman PLS 1254 | M92-54 |
| 1997 | Mark Smalley PLS 2354 | 65/15-16 |
| 1980 | Randall W. Smith PLS 2469 | 61/11 |
| 2005 | Randall W. Smith PLS 2469 | 67/13-11 |
| 2005 | Randall W. Smith PLS 2469 | 67/13-12 |
| 2006 | Randall W. Smith PLS 2469 | 67/14-18 |
| 2006 | Randall W. Smith PLS 2469 | 67/14-24 |

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 7, 2008, for Group No. 2241, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines are based on the true meridian as determined by Global Positioning System (GPS) measurements and by direct solar observations and were carried forward by means of sustained angulation. All measurements on the lines were derived through the use of electronic measuring equipment.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS measurements utilized dual frequency carrier phase receivers and were executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", dated May of 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

Terrestrial distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

T. 22 S., R. 8 W., Willamette Meridian, Oregon

| | |
|------|---|
| FEET | <p>All new bearing trees have a 2 1/2 inch x 1/4 inch magnetic nail (MAG-NAIL TM) driven at the base on right side center, unless otherwise noted in the corner description.</p> <p>All new stainless steel corner post monuments have a magnet in a white plastic case at the base of the post, unless otherwise noted in the corner description.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of sections 28 and 29, as determined by direct occupation utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:</p> <p>Latitude: 43° 37' 42.376" N. Longitude: 123° 39' 57.332" W.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the corner of sections 19, 20, 29, and 30, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:</p> <p>Latitude: 43° 38' 06.75" N. Longitude: 123° 41' 01.98" W.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the W 1/16 section corner of sections 29 and 32, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:</p> <p>Latitude: 43° 37' 16.05" N. Longitude: 123° 40' 44.92" W.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the center 1/4 section corner of section 32, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:</p> <p>Latitude: 43° 36' 50.34" N. Longitude: 123° 40' 27.71" W.</p> <p>The geographic position (NAD 1983 (CORS 96)) of the center 1/4 section corner of section 33, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:</p> <p>Latitude: 43° 36' 49.81" N. Longitude: 123° 39' 16.27" W.</p> <hr style="width: 60%; margin-left: 0;"/> |
|------|---|

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

| | | | | | | | | | | | | | | | | | | | | | |
|--------|---|--------|-------|------|------|--|--|------|------|------|--|------|--|--|--|------|------|-----|--|------|--|
| FEET | <p>(Restoring the survey by William H. Byars, in 1881 and the resurvey by Floyd A. Brooks, in 1960 and Floyd A. Brooks and Peter A. Peterson, in 1965-67)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Beginning at the cor. of secs. 28, 29, 32, and 33, remonumented by Brooks in 1960; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">T 22 S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R 8 W</td> </tr> <tr> <td style="padding: 0 10px;">S 29</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 28</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; padding: 2px 0;"> </td> </tr> <tr> <td style="padding: 0 10px;">S 32</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 33</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1960</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A madrone, 33 ins. diam., bears S. 61° E., 33.0 ft. dist., no marks visible.</p> <p style="margin-left: 40px;">A madrone, 39 ins. diam., bears S. 52° W., 51.5 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Brooks</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears S. 35° W., 67.3 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A dead fir snag, 11 ins. diam., bears N. 35° W., 29.7 ft. dist., with a healed blaze. (Record, N. 38° W.)</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 40° W., 30.4 ft. dist., mkd. T22S R8W S29 BT.</p> <p>N. 8° 50' 06" W., bet. secs. 28 and 29</p> <p>1412.98 Point for the closing cor. of secs. 28 and 29, at intersection with the S. bdy. of Donation Land Claim No. 45.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2" style="padding: 0 10px;">C 45</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; padding: 2px 0;"> </td> </tr> <tr> <td style="padding: 0 10px;">S 29</td> <td style="padding: 0 10px;">S 28</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">C C</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2009</td> </tr> </table> </div> <p>from which</p> | T 22 S | R 8 W | S 29 | S 28 | | | S 32 | S 33 | 1960 | | C 45 | | | | S 29 | S 28 | C C | | 2009 | |
| T 22 S | R 8 W | | | | | | | | | | | | | | | | | | | | |
| S 29 | S 28 | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| S 32 | S 33 | | | | | | | | | | | | | | | | | | | | |
| 1960 | | | | | | | | | | | | | | | | | | | | | |
| C 45 | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| S 29 | S 28 | | | | | | | | | | | | | | | | | | | | |
| C C | | | | | | | | | | | | | | | | | | | | | |
| 2009 | | | | | | | | | | | | | | | | | | | | | |

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

| FEET | |
|---------|--|
| | <p>A maple, 16 ins. diam., bears N. 14° W., 66.0 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 14 ins. diam., bears S. 2° E., 26.3 ft. dist., mkd. E 1/16 S32 BT.</p> <p>A fir, 14 ins. diam., bears N. 87° W., 6.3 ft. dist., mkd. E 1/16 S29 BT.</p> <p>S. 89° 39' 58" W., bet. secs. 29 and 32</p> |
| 1301.84 | <p>The 1/4 sec. cor. of secs. 29 and 32, reestablished by Brooks in 1960; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">S 29 1/4 ——— S 32 T 22 S R 8 W 1960</p> <p>from which a bearing tree mkd. by Brooks</p> <p>A chinquapin, 17 ins. diam., bears N. 64° W., 58.1 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p>A fir, 20 ins. diam., bears S. 36° W., 9.9 ft. dist., mkd. 1/4 S32 BT.</p> <p>A fir, 26 ins. diam., bears N. 74° W., 15.9 ft. dist., mkd. 1/4 S29 BT.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89° 54' 56" W., beginning new measurement</p> |
| 1300.30 | <p>The W 1/16 sec. cor. of secs. 29 and 32, established by Brooks in 1960; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">S 29 W 1/16 ——— S 32 1960</p> <p>from which the bearing trees mkd. by Brooks</p> <p>A fir, 32 ins. diam., bears N. 86 1/2° E., 29.7 ft. dist., no marks visible.</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

| | | | | | | | | | | | | | | | |
|-------------|--|--------|-------|------|------|--|--|------|------|------|--|--------|-------------|------|------|
| FEET | <p>A fir, 33 ins. diam., bears S. 2 1/2° W., 30.0 ft. dist., no marks visible.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32, reestablished by Brooks in 1960; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 S</td> <td>R 8 W</td> </tr> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1960</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Brooks</p> <p>A fir, 38 ins. diam., bears N. 18° E., 26.4 ft. dist., with a healed blaze. (Record, N. 15 1/2° E.)</p> <p>A fir, 20 ins. diam., bears S. 19 1/2° E., 11.9 ft. dist., with a healed blaze.</p> <p>A fir, 24 ins. diam., bears S. 82° W., 44.2 ft. dist., with a healed blaze. (Record, S. 80 1/2° W.)</p> <p>A fir snag, 12 ins. diam., bears N. 67° W., 44.2 ft. dist., no marks visible (Record, N. 68° W.)</p> <p>and a new bearing tree</p> <p>A fir, 15 ins. diam., bears N. 23° W., 6.7 ft. dist., mkd. T22S R8W S30 BT.</p> <p>N. 0° 36' 50" E., bet. secs. 29 and 30</p> <p>1286.54 Point for the S 1/16 sec. cor. of secs. 29 and 30, at proportionate measurement; there is no remaining evidence of the corner; the iron post set by Brooks and Peterson in 1965-67 was found lying loose, approximately 20 ft. downhill of proportionate position.</p> <p>Reset the iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>S 1/16</td> </tr> <tr> <td>S 30 S 29</td> </tr> <tr> <td>2009</td> </tr> <tr> <td>1965</td> </tr> </table> </div> <p>from which</p> | T 22 S | R 8 W | S 30 | S 29 | | | S 31 | S 32 | 1960 | | S 1/16 | S 30 S 29 | 2009 | 1965 |
| T 22 S | R 8 W | | | | | | | | | | | | | | |
| S 30 | S 29 | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| S 31 | S 32 | | | | | | | | | | | | | | |
| 1960 | | | | | | | | | | | | | | | |
| S 1/16 | | | | | | | | | | | | | | | |
| S 30 S 29 | | | | | | | | | | | | | | | |
| 2009 | | | | | | | | | | | | | | | |
| 1965 | | | | | | | | | | | | | | | |

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

| FEET | |
|---------|---|
| | <p>A fir, 13 ins. diam., bears N. 21° E., 19.8 ft. dist., mkd. S 1/16 S29 BT.</p> <p>A fir, 11 ins. diam., bears S. 6° W., 5.5 ft. dist., mkd. S 1/16 S30 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <p>2573.08 The 1/4 sec. cor. of secs. 29 and 30, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 30 S 29 T 22 S R 8 W 1964</p> </div> <p>from which the bearing trees mkd. by Brooks and Peterson</p> <p>A dying fir, 21 ins. diam., bears N. 12° E., 24.2 ft. dist., with a healed blaze. (Record, N. 10° E., 25.1 ft. dist.)</p> <p>A decayed fir stump, 27 ins. diam., bears N. 70° W., 13.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 18 ins. diam., bears N. 63° E., 16.3 ft. dist., mkd. 1/4 S29 BT.</p> <p>A fir, 6 ins. diam., bears N. 13° W., 11.5 ft. dist., mkd. X BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 28' 29" E., beginning new measurement</p> |
| 2568.81 | <p>The cor. of secs. 19, 20, 29, and 30, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 8 W S 19 S 20 ----- S 30 S 29 1965</p> </div> <p>from which the remains of the bearing trees mkd. by Brooks and Peterson</p> |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A decayed fir stump, 17 ins. diam., bears N. 37° E., 15.2 ft. dist., no marks visible.

A decayed fir stump, 10 ins. diam., bears S. 39° E., 9.2 ft. dist., no marks visible. (Record, S. 34° E.)

A decayed fir stump, 12 ins. diam., bears S. 83° W., 17.3 ft. dist., no marks visible. (Record, 18.5 ft. dist.)

and the reference monuments set by Smalley, PLS No. 2354, in 1997

An iron rod, 5/8 ins. diam., firmly set, projecting 18 ins. above ground, bears North, 10.0 ft. dist. Set an aluminum cap, 2 1/4 ins. diam., mkd. RM T22S R8W 10.0 FT TO COR S20 2009, on top of the iron rod.

An iron rod, 5/8 ins. diam., firmly set, projecting 18 ins. above ground, bears S. 82° W., 9.8 ft. dist. Set an aluminum cap, 2 1/4 ins. diam., mkd. RM T22S R8W 9.8 FT TO COR S30 2009, on top of the iron rod.

and new bearing trees

A fir, 6 ins. diam., bears N. 41° E., 13.5 ft. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 56° E., 24.3 ft. dist., mkd. X BT.

A fir, 7 ins. diam., bears S. 12° W., 32.3 ft. dist., mkd. T22S R8W S30 BT.

A fir, 8 ins. diam., bears N. 53° W., 12.8 ft. dist., mkd. T22S R8W S19 BT.

**Dependent Resurvey of a Portion of the Boundaries of
Donation Land Claim No. 45,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

(Restoring the survey by Dennis Hathorn, in 1856
and the resurvey by Floyd A. Brooks and
Peter A. Peterson, in 1965-67)

From the SE. cor. of Donation Land Claim No. 45, in the SW 1/4 of sec. 28, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

Dependent Resurvey of a Portion of the Boundaries of
 Donation Land Claim No. 45,
 T. 22 S., R. 8 W., Willamette Meridian, Oregon

| FEET | |
|---------|---|
| | <p style="text-align: center;">T 22 S R 8 W</p> <p style="text-align: center;">C 45 S 28</p> <p style="text-align: center;">1965</p> <p>from which the bearing trees mkd. by Smith, PLS No. 2469, in 2006</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 10° E., 24.8 ft. dist., with scribe marks X BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 56° W., 19.2 ft. dist., with scribe marks Donation Land Claim 45 CS BT visible on partially healed blaze.</p> <p>A galvanized iron pipe, 1 in. diam. firmly set, projecting 14 ins. above ground, is on the W. side and a wood fence post is on the N. side of the iron post</p> <p>Corner is located NW., 3 ft., from the corner of dilapidated fences, extending N. and W.</p> <p>S. 89° 33' 30" W., on the S. bdy. of Donation Land Claim No. 45, in sec. 28.</p> |
| 99.97 | <p>The closing cor. of secs. 28 and 29, at intersection with the line bet. 28 and 29, hereinbefore described.</p> |
| | <p>Continue along the S. bdy. of Donation Land Claim No. 45, in sec. 29.</p> |
| 2546.38 | <p>The closing cor. at intersection with the N. and S. center line of sec. 29, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with a brass cap mkd.</p> |
| | <p style="text-align: center;">C 45</p> <p style="text-align: center;">C</p> <p style="text-align: center;">CC S 29</p> <p style="text-align: center;">C</p> |
| | <p style="text-align: center;">T 22 S R 8 W</p> <p style="text-align: center;">1965</p> |
| | <p>from which the bearing trees mkd. by Brooks and Peterson</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 56° E., 73.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 26° W., 48.2 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Smith, PLS No. 2469, in 2005</p> |

Dependent Resurvey of a Portion of the Boundaries of
 Donation Land Claim No. 45,
 T. 22 S., R. 8 W., Willamette Meridian, Oregon

| | |
|---------|--|
| FEET | <p>A fir, 14 ins. diam., bears N. 78° W., 21.0 ft. dist., with scribe marks CC DLC 45 CS BT visible on partially healed blaze.</p> <p>A galvanized iron pipe, 1 in. diam. firmly set, projecting 16 ins. above ground, bears S. 1° W., 2.75 ft. dist. of the iron post.</p> <p>Corner is located 2 ft. N. of an E. and W. fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 28' 28" W., beginning new measurement</p> |
| 1059.42 | <p>The SW. cor. of Donation Land Claim No. 45, remonumented by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">T 22 S R 8 W</p> <p style="text-align: center;">S 29 C 45</p> <p style="text-align: center;">1965</p> <p>from which a bearing tree mkd. by Brooks and Peterson</p> <p style="padding-left: 40px;">A hemlock, 27 ins. diam., bears N. 50° W., 33.7 ft. dist., with a healed blaze.</p> <p>and the bearing trees mkd. by Smith, PLS No. 2469, in 2006</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 74 1/2° E., 48.9 ft. dist., with scribe marks SW DLC 45 CS BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A maple, 11 ins. diam., bears S. 68° E., 23.0 ft. dist., with scribe marks SW DLC 45 CS BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears N. 65° W., 37.7 ft. dist., with scribe marks SW DLC 45 CS BT visible on partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 24' 38" W., on the W. bdy. of Donation Land Claim No. 45 in sec. 29; beginning new measurement</p> |
| 1211.58 | <p>The closing cor. at intersection with the E. and W. center line of sec. 29, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> |

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines of Section 32,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | <p>(Restoring the survey by Floyd A. Brooks and James E. Jelly, in 1963-65)</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 32 1964</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 7° E., 4.7 ft. dist., mkd. C 1/4 S32 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 87° E., 10.0 ft. dist., mkd. C 1/4 S32 BT.</p> <p>N. 0° 49' 25" E., on the N. and S. center line of sec. 32</p> |
| 1302.76 | <p>The center N 1/16 sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 32 C 1964</p> <p>from which the bearing trees mkd. by Brooks and Jelley</p> <p style="padding-left: 40px;">A fir stump, 14 ins. diam., bears S. 77 1/4° E., 7.3 ft. dist., no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 7° E., 11.4 ft. dist., mkd. CN 1/16 S32 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 51° E., 9.2 ft. dist., mkd. X BT.</p> <hr/> |
| 1280.64 | <p>From the center 1/4 sec. cor. of sec. 32</p> <p>N. 89° 27' 43" W., on the E. and W. center line of sec. 32.</p> <p>The center W 1/16 sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.</p> |

Dependent Resurvey of a Portion of the
 Subdivision of Section Lines of Section 32,
 T. 22 S., R. 8 W., Willamette Meridian, Oregon

| | |
|---------|--|
| F E E T | <p style="text-align: center;">W 1/16 C————C S 32 1964</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 17° E., 21.1 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 59° W., 11.9 ft. dist., mkd. CW 1/16 S32 BT.</p> <hr/> <p>From the NE 1/16 sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 32 1964</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 25° E., 10.4 ft. dist., mkd. NE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 7° E., 11.9 ft. dist., mkd. NE 1/16 S32 BT.</p> <p>N. 89° 41' 25" W., on the E. and W. center line of the NE 1/4 of sec. 32</p> <p>1307.26 The center N 1/16 sec. cor. of sec. 32</p> <hr/> <p>From the SW 1/16 sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 32 1964</p> <p>from which the remains of a bearing tree mkd. by Brooks and Jelley</p> <p style="padding-left: 40px;">A fir stump, 20 ins. diam., bears S. 67° W., 25.7 ft. dist., no marks visible.</p> <p>and new bearing trees</p> |
|---------|--|

**Dependent Resurvey of a Portion of the
Subdivision of Section Lines of Section 32,
T. 22 S., R. 8 W., Willamette Meridian, Oregon**

| | |
|---------|---|
| FEET | <p>A fir, 9 ins. diam., bears N. 11° E., 4.0 ft. dist., mkd. SW 1/16 S32 BT.</p> <p>A fir, 7 ins. diam., bears S. 75° W., 19.9 ft. dist., mkd. X BT.</p> <p>N. 0° 58' 09" E., on the N. and S. center line of the SW 1/4 of sec. 32</p> |
| 1324.55 | <p>The center W 1/16 sec. cor. of sec. 32</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C S 1/16 S 32 C 1964</p> </div> <p>from which the remains of a bearing tree mkd. by Brooks and Jelley</p> <p>A fir stump, 30 ins. diam., bears N. 36 1/2° W., 19.1 ft. dist., no marks visible. (Record, 17.8 ft. dist.)</p> <p>and new bearing trees</p> <p>A fir, 11 ins. diam., bears N. 80° E., 13.1 ft. dist., mkd. CS 1/16 S32 BT.</p> <p>A hemlock, 18 ins. diam., bears N. 45° W., 10.7 ft. dist., mkd. CS 1/16 S32 BT.</p> <p>N. 89° 14' 24" W., on the E. and W. center line of the SW 1/4 of sec. 32</p> |
| 1290.01 | <p>The SW 1/16 sec. cor. of sec. 32</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivision of Section Lines of Section 33, T. 22 S., R. 8 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the surveys by Floyd A. Brooks, in 1962 and Floyd A. Brooks and James E. Jelly, in 1963-65)</p> <hr/> |

Dependent Resurvey of a Portion of the
 Subdivision of Section Lines of Section 33,
 T. 22 S., R. 8 W., Willamette Meridian, Oregon

| FEET | |
|---------|---|
| | <p>From the center 1/4 sec. cor. of sec. 33, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 33 1964</p> <p>from which the bearing trees mkd. by Brooks and Jelley</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 41° E., 33.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 74 1/2° W., 23.1 ft. dist.,</p> <p>N. 89° 29' 53" W., on the E. and W. center line of sec. 33</p> |
| 1309.08 | <p>The center W 1/16 sec. cor. of sec. 33, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">W 1/16 C———C S 33 1964</p> <p>from which the remains of bearing trees mkd. by Brooks and Jelley</p> <p style="padding-left: 40px;">A roothole, size indeterminate, bears S. 19° W., 15.8 ft. dist.</p> <p style="padding-left: 40px;">A white fir, 36 ins. diam., bears N. 23° W., 16.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 9° W., 20.9 ft. dist., mkd. CW 1/16 S33 BT.</p> <hr/> <p>From the W 1/16 sec. cor. of sec. 33 only, on the south bdy. of the Tp., established by Brooks in 1962; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">W 1/16 S 33 ——— 1962</p> <p>from which a bearing tree mkd. by Brooks</p> |

Dependent Resurvey of a Portion of the
Subdivision of Section Lines of Section 33,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

| | |
|---------|---|
| FEET | <p>A fir, 13 ins. diam., bears N. 72° E., 128.0 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by Brooks and Jelley</p> <p>A fir, 31 ins. diam., bears N. 69° W., 48.9 ft. dist., with a healed blaze. (Record, 51.5 ft. dist.)</p> <p>N. 0° 16' 59" E., on the N. and S. center line of the SW 1/4 of sec. 33</p> |
| 2649.05 | <p>The center W 1/16 sec. cor. of sec. 33</p> <hr/> |