

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY AND SUBDIVISIONAL LINES,  
AND THE SUBDIVISION OF SECTION 13,  
**TOWNSHIP 30 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

*Kenneth W. Saveland, Cadastral Surveyor*

Under Special Instructions dated March 31, 2008, approved April 2, 2008,  
which provided for the surveys included under Group No. 2191,  
and Assignment Instructions dated April 9, 2008.

*Survey commenced April 14, 2008*

*Survey completed May 13, 2008*

## T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the east boundary and subdivisional lines, and the subdivision of section 13, Township 30 South, Range 7 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Addison R. Flint, U.S. Deputy Surveyor, surveyed the west boundary and subdivisional lines of T. 30 S., R. 6 W., as shown on the official plat of survey approved December 10, 1855.

In 1872, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on the official plat of survey approved October 1, 1872.

In 1963-64, John M. Jelley and C. Albert White, Cadastral Surveyors, resurveyed a portion of the west boundary and subdivisional lines, and subdivided section 7 of T. 30 S., R. 6 W., as shown on the official plat of survey accepted August 20, 1965.

In 1971-73, James E. Jelley and Charles E. Akin, Jr., Cadastral Surveyors, resurveyed a portion of the east boundary and subdivisional lines, and subdivided section 25, as shown on the official plat of survey accepted April 18, 1977.

In 1988-89, Wayne L. Rogers, Dale T. Bedell, and Boyd W. Peterson, Cadastral Surveyors, resurveyed a portion of the north boundary and subdivisional lines, and subdivided sections 6 and 11, as shown on the official plat of survey accepted August 26, 1992.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 31, 2008, for Group No. 2191, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the corner description field notes are given herein. Only those lines bounding public lands were blazed and posted.

The direction of the lines are based on the true meridian as determined by a combination of direct solar observations and Global Positioning System (GPS) measurements.

The survey was performed using a combination of GPS satellite techniques and terrestrial measurements. The GPS

**T. 30 S., R. 7 W., Willamette Meridian, Oregon**

FEET

measurements utilized dual frequency carrier phase receivers and were executed in accordance with the 'Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods', dated May 9, 2001, published by the U.S.D.A. Forest Service and U.S.D.I. Bureau of Land Management.

The static GPS measurements have been adjusted using computer software that incorporates a least squares adjustment routine. The maximum GPS Cadastral Measurement error ellipse at 95% confidence level is 0.06 feet based on local accuracy standards. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted using computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 11, 12, 13, 14, as determined by a tie from a GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference Continuously Operating Reference Station (CORS) "CAPE BLANCO CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:

Latitude: 42° 58' 16.67" N.      Longitude: 123° 29' 07.60" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

---

**Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon**

---

(Restoring the 1855 survey by Addison R. Flint, and the  
1971-73 resurvey by James E. Jelley and Charles E. Akin, Jr.)

---

Beginning at the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 30 S  
R 7 W    R 6 W  
      1/4  
      |  
S 13    S 18  
      |  
      1973

from which the remains of a bearing tree mkd. by Jelley and Akin

Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>A decayed fir stump, size indeterminate, bears S. 89° E., 38.3 ft. dist., with scribe marks 1/ and other fragmentary marks visible on a partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 87 3/4° E., 11.0 ft. dist., mkd. 1/4 S18 BT.</p> <p>A fir, 14 ins. diam., bears N. 15° W., 43.6 ft. dist., mkd. 1/4 S13 BT.</p> <p>From this cor., the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., perpetuated by Randall Smith, Deputy County Surveyor, in 1991, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 7 W., Point Identifier No. 700400, subsequently perpetuated by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 1999, filed in the Douglas County Surveyors Office, Map File No. M129-43, bears S. 0° 21' 23" W., 2618.73 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T 30 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R 7 W</td> <td style="padding: 2px 5px;">R 6 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 13</td> <td style="padding: 2px 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 24</td> <td style="padding: 2px 5px;">S 19</td> </tr> <tr> <td colspan="2" style="padding: 2px 5px;">1973</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A roothole, bears N. 76° E., 48.2 ft. dist., alongside of which is a down, decayed oak snag, 40 ins. diam., with no marks visible on a hollow, open blaze. (Record, N. 70° E., 46.2 ft. dist.)</p> <p>A sawed, decayed oak stump, 36 ins. diam., bears S. 47° E., 80.5 ft. dist., with no marks visible. (Record, S. 50° E.)</p> <p>A sawed, decayed oak stump, 44 ins. diam., bears S. 61 1/2° W., 215.8 ft. dist., with no marks visible. (Record, S. 60° W.)</p> <p>and the remains of bearing trees mkd. by Howard W. Johnstone, Oregon Professional Land Surveyor No. 498, in 1962, reported by Jelley and Akin</p> <p>A roothole, bears N. 51 1/2° E., 50.2 ft. dist., alongside of which is a down, decayed fir snag, 12 ins. diam., with no marks visible.</p>	T 30 S		R 7 W	R 6 W	S 13	S 18	S 24	S 19	1973	
T 30 S											
R 7 W	R 6 W										
S 13	S 18										
S 24	S 19										
1973											

Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p>A sawed, pine stump, 28 ins. diam., bears N. 51° W., 3.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze and a metal cap.</p> <p>and the remains of the bearing tree mkd. by Jelley and Akin</p> <p>A roothole, bears N. 13 1/2° E., 103.0 ft. dist., alongside of which is a down, decayed fir snag, size indeterminate, with no marks visible on an opened blaze.</p> <p>and a bearing tree mkd. by Smith</p> <p>A fir, 10 ins. diam., bears S. 66 3/4° E., 52.5 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by Smalley</p> <p>A fir, 8 ins. diam., bears N. 37° E., 29.2 ft. dist., with a healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 5 1/2° W., 22.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 7 ins. diam., bears N. 41 3/4° W., 36.2 ft. dist., mkd. T30S R7W S13 BT.</p> <p>Corner is located on a SW. slope, 35 ft. W. of a spur, slopes South.</p> <p>N. 0° 09' 30" E., bet. secs. 13 and 18, on the E. bdy. of the Tp., posting and blazing.</p>												
2385	Gravel road, 11 ft. wide, bears N. 45° E. and S. 50° W.												
2618.21	<p>The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., perpetuated by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 1995, filed in the Douglas County Surveyors Office, Map File No. M121-59, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 30 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">R</td> </tr> <tr> <td style="padding: 0 5px;">7</td> <td style="border-bottom: 1px solid black; padding: 0 5px;"></td> <td style="border-bottom: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">6</td> </tr> <tr> <td style="padding: 0 5px;">W</td> <td style="padding: 0 5px;">S 13</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">W</td> </tr> </table> <p>BLM 1964 1980</p> </div> <p>from which the remains of an original bearing tree</p>	R	S 12	S 7	R	7			6	W	S 13	S 18	W
R	S 12	S 7	R										
7			6										
W	S 13	S 18	W										

**Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon**

FEET

A roothole bears N. 89° W., 36.3 ft. dist., alongside of which is a down, decayed madrone, size indeterminate, with no marks visible.

and the remains of bearing trees mkd. by James Byron, Deputy County Surveyor, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 7 W., Index No. 700500, reported by Jelley and Akin

A sawed fir stump, 21 ins. diam., bears N. 20° E., 15.8 ft. dist., with a healed blaze.

A fir, 20 ins. diam., bears S. 29° E., 26.4 ft. dist., with a healed blaze.

A roothole bears S. 23° W., 17.8 ft. dist., alongside of which is a down, decayed fir snag, size indeterminate, with no marks visible.

A fir snag, 17 ins. diam., bears N. 18° W., 42.9 ft. dist., with a healed double blaze.

and a bearing tree mkd. by Smalley

A fir, 14 ins. diam., bears S. 89° W., 24.1 ft. dist., with a healed blaze.

and new bearing trees

A madrone, 10 ins. diam., bears N. 57 1/2° E., 94.2 ft. dist., mkd. T30S R6W S7 BT in the bark.

A fir, 12 ins. diam., bears N. 78 3/4° W., 21.9 ft. dist., mkd. T30S R7W S12 BT.

Corner is located on an E. slope and 60 ft. W. of a shallow ravine, drains South.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon**

---

(Restoring the 1872 survey by William H. Byars, the  
1963-64 resurvey by John M. Jelley and C. Albert White, the  
1971-73 resurvey by James E. Jelley and Charles E. Akin, Jr.,  
and the 1988-89 resurvey by Wayne L. Rogers,  
Dale T. Bedell, and Boyd W. Peterson)

---

From the cor. of secs. 13, 18, 19, and 24 on the E. bdy. of the Tp.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	N. 89° 12' 58" W., bet. secs. 13 and 24, posting and blazing.
40	Draw, drains S. 5° W., then asc. broken S. slope.
175	Spur, slopes South.
2516.50	<p>The 1/4 sec. cor. of secs. 13 and 24, perpetuated by Claude Kerr, Registered Professional Engineer No. 2125, in 1953, filed in the Douglas County Surveyors Office, C.S. File No. 41/160, subsequently perpetuated by Howard W. Johnstone, Oregon Professional Land Surveyor No. 498, in 1962, filed in the Douglas County Surveyors Office, C.S. File No. 51/163, monumented with an iron pipe, 31 ins. long, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed madrone stump, size indeterminate, bears N. 65° E., 25.7 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A decayed madrone stump, size indeterminate, bears S. 5° W., 46.9 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, size indeterminate, bears S. 73° W., 24.5 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, size indeterminate bears N. 17 1/2° W., 22.2 ft. dist., with no marks visible.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 30 S R 7 W</p> <p style="margin-left: 40px;">S 13</p> <p style="margin-left: 40px;">1/4 ———</p> <p style="margin-left: 40px;">S 24</p> <p style="margin-left: 40px;">2008</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears South, 16.1 ft. dist., mkd. 1/4 S24 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 67 3/4° W., 3.0 ft. dist., mkd. 1/4 S13 BT.</p> <p>Place iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>N. 88° 51' 37" W., beginning a new measurement.</p>
1200	<p>Gravel road, 10 ft. wide, bears N. 40° W. and S. 50° E., in curve.</p>
1224.90	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Drive a finned aluminum rod, 36 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>S 13  W 1/16 ———  S 24  2008</p> </div> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground for a reference monument, bears N. 68° 55' 40" E., 31.84 ft. dist., with aluminum cap mkd. RM W1/16 S13 31.8 FT TO COR 2008 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An iron rod, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground for a reference monument, bears S. 21° 33' 05" W., 16.00 ft. dist., with aluminum cap mkd. RM W1/16 S24 16.0 FT TO COR 2008 and an arrow pointing to the corner.</p> <p>Deposit a magnet in a white plastic case alongside the finned aluminum rod.</p> <p>Corner is located on a steep road bank, 20 ft. S. of a gravel road, 10 ft. wide, bears N. 55° W. and S. 55° E.</p> <p>Discontinue posting and blazing.</p> <p>From this corner, a point established by person(s) unknown bears S. 86° 03' 12" W., 14.32 ft. dist., not utilized in the course of this survey, monumented with an iron pipe, 1 in. diam., firmly set, projecting 15 ins. above ground, with a mushroomed top, from which remains of reference trees by person(s) unknown</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 34 ins. diam., bears S. 14° W., 12.9 ft. dist., with no marks visible on an open, decayed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, size indeterminate, bears N. 66° W., 5.0 ft. dist., with no marks visible on an open, decayed blaze.</p> <p>Along a broken NW. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon**

FEET									
2150	Gravel road, 10 ft. wide, bears N. 30° E. and S. 25° W.								
2449.80	<p>The cor. of secs. 13, 14, 23, and 24, perpetuated by John H. Markham, Jr., Registered Professional Engineer No. 2880, in 1951, subsequently perpetuated by the Douglas County Surveyors Office in 1966, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 7 W., Point Identifier No. 600400, determined at record bearing and distance from the remains of the orig. bearing trees</p> <p style="padding-left: 40px;">A roothole, bears S. 80° E., 18.5 ft. dist. (Record, 13.9 ft.)</p> <p style="padding-left: 40px;">A decayed madrone stump, size indeterminate, bears S. 48° W., 49.5 ft. dist., with no marks visible.</p> <p>and the remains of bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">A decayed madrone stump, size indeterminate, bears N. 1 1/2° E., 36.4 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A roothole, bears N. 70° W., 48.1 ft. dist.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A roothole, bears S. 35 1/2° E., 38.8 ft. dist., alongside of which is a down, decayed fir snag, 10 ins. diam., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T 30 S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 7 W</td> </tr> <tr> <td style="padding: 0 10px;">S 14</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 13</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 23</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 10px;">S 24</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">2008</td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 75 1/4° E., 9.9 ft. dist., mkd. T30S R7W S13 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 7 3/4° E., 15.9 ft. dist., mkd. T30S R7W S24 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 27 1/2° W., 18.6 ft. dist., mkd. T30S R7W S23 BT.</p>	T 30 S	R 7 W	S 14	S 13	S 23	S 24	2008	
T 30 S	R 7 W								
S 14	S 13								
S 23	S 24								
2008									

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 6 ins. diam., bears N. 18° W., 14.1 ft. dist., mkd. T30S R7W S14 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>An iron post, 29 ins. long, 1 1/4 ins. diam., with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R7W S14 S13 S23 S24 1966, was found disturbed and lying loose, and was placed inside the stainless steel post.</p> <hr/> <p>N. 2° 11' 23" W., bet. secs. 13 and 14.</p> <p>Descend a NW. slope.</p>
2540	<p>Spur, slopes N. 80° E.</p>
2596.68	<p>The 1/4 sec. cor. of secs. 13 and 14, perpetuated by Howard W. Johnstone, Oregon Professional Land Surveyor No. 498, in 1962, filed in the Douglas County Surveyors Office, C.S. File No. 51/163, monumented with an iron pipe, 24 ins. long, 1 3/4 ins. diam., firmly set, projecting 11 ins. above ground, from which the remains of the original bearing trees</p> <p>A decayed fir stump, 20 ins. diam., bears N. 60° E., 5.3 ft. dist., with no marks visible.</p> <p>A burnt, decayed fir stump, size indeterminate, bears S. 82° W., 11.9 ft. dist., downhill of which is a down fir snag, 12 ins. diam., with no marks visible on an open blaze.</p> <p>and the remains of bearing trees mkd. by Johnstone</p> <p>A roothole, bears S. 44 1/2° E., 20.1 ft. dist., alongside of which is a down fir snag, 12 ins. diam., with fragmentary scribe marks visible on a burnt, partially healed blaze.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 7 W</p> <p>1/4</p> <p>S 14   S 13</p> <p>2008</p> </div> <p>from which new bearing trees</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p>A pine, 9 ins. diam., bears N. 1 1/4° E., 23.7 ft. dist., mkd. 1/4 S13 BT.</p> <p>A fir, 13 ins. diam., bears S. 85 1/2° W., 32.7 ft. dist., mkd. 1/4 S14 BT.</p> <p>Place the iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 2° 31' 34" W., beginning a new measurement.</p>
1311.99	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>Drive a finned aluminum rod, 36 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">N 1/16 S 14   S 13 2008</p> <p>from which</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 44° 42' 50" E., 24.62 ft. dist., with aluminum cap mkd. RM N1/16 S13 24.6 FT TO COR 2008 and an arrow pointing to the corner.</p> <p>An iron rod, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 49° 40' 49" W., 28.36 ft. dist., with aluminum cap mkd. RM N1/16 S14 28.3 FT TO COR 2008 and an arrow pointing to the corner.</p> <p>Deposit a magnet in a white plastic case alongside the finned aluminum rod.</p> <p>Corner is located on a steep road bank.</p> <p>Begin posting and blazing.</p>
1345	<p>Gravel road, 10 ft. wide, bears N. 20° W. and S. 20° E.</p>
2623.98	<p>The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET

## COUNTY SURVEYORS OFFICE

T 30 S	
S 11	S 12
-----	
S 14	S 13
R 7 W	
1964	

from which the remains of an original bearing tree

A roothole, bears S. 70° W., 9.2 ft. dist., alongside of which is a burnt pine snag, size indeterminate, with no marks visible on a burnt, weathered blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1964, filed in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 7 W., Point Identifier No. 600500, reported by Rogers, Bedell, and Peterson

A sawed fir stump, 8 ins. diam., bears N. 87° E., 20.5 ft. dist., with no marks visible on burnt, partially healed double blaze.

A sawed, decayed fir stump, 15 ins. diam., bears S. 21° E., 16.5 ft. dist., with no marks visible.

A decayed fir stump, size indeterminate, bears S. 15° W., 6.6 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Jelley and Akin, reported by Rogers, Bedell, and Peterson

A fir stump, size indeterminate, bears N. 2° E., 11.2 ft. dist., alongside of which is a burnt, decayed down fir, size indeterminate, with no marks visible.

and the remains of bearing trees mkd. by Rogers, Bedell, and Peterson

A pine, 12 ins. diam., bears N. 74 1/2° E., 25.4 ft. dist., with no marks visible on a burnt, partially healed blaze. (Record, N. 78° E.)

A madrone stump, 4 ins. diam., bears N. 10 1/2° W., 24.4 ft. dist., alongside of which is a down madrone, 4 ins. diam., with scribe marks X BT visible on an open, weathered double blaze. (Record, N. 6° W.)

and new bearing trees

A pine, 6 ins. diam., bears S. 25 3/4° E., 19.2 ft. dist., mkd. T30S R7W S13 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 4 ins. diam., bears S. 50 1/2° W., 19.9 ft. dist., mkd. X BT.</p> <p>A cedar, 5 ins. diam., bears N. 54 1/2° W., 24.9 ft. dist., mkd. T30S R7W S11 BT.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 13, T. 30 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0° 41' 19" W., on the N. and S. centerline of sec. 13, posting and blazing.</p>
2560	Spur, bears slopes N. 60° W.
2614.34	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 7 W C 1/4 S 13 2008</p> <p>from which</p> <p>A fir, 7 ins. diam., bears N. 55° E., 8.3 ft. dist., mkd. X BT.</p> <p>A fir, 9 ins. diam., bears N. 32 3/4° W., 9.7 ft. dist., mkd. C 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p>
5233.74	The 1/4 sec. cor. of secs. 12 and 13, perpetuated by Mark F. Smalley, Oregon Professional Land Surveyor No. 2354, in 1995, filed in the Douglas County Surveyors Office, Map File No. M121-59, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

Subdivision of Section 13,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T 30 S R 7 W S 12 1/4 _____ S 13 1973</p>
	<p>from which bearing trees mkd. by Jelley and Akin</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 2° E., 31.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears N. 81° W., 16.5 ft. dist., with a healed double blaze.</p> <p>and bearing trees mkd. by</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 58 1/4° E., 23.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 42 1/2° W., 15.6 ft. dist., with a healed blaze.</p> <p>Corner is located on a SE. slope.</p> <p>From this cor., the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., bears S. 89° 19' 09" E., 2602.26 ft. dist., described on page 4.</p> <p>From this same cor., the cor. of secs. 11, 12, 13, and 14, bears N. 89° 18' 15" W., 2600.89 ft. dist., described on page 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., described on page 22128.</p> <p>N. 89° 19' 54" W., on the E. and W. centerline of sec. 13.</p>
2563.84	<p>The center 1/4 sec. cor. of sec. 13.</p> <p>Begin posting and blazing.</p>
5080.83	<p>The 1/4 sec. cor. of secs. 13 and 14, described on page 8.</p> <hr/>

T. 30 S., R. 7 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;"><b>GENERAL DESCRIPTION</b></p> <p>The lands embraced in the forgoing survey are located in mountainous terrain, approximately 6 miles westerly of Riddle, Oregon.</p> <p>The elevation ranges from about 1600 feet above sea level near the corner of sections 13, 14, 23, and 24, to about 2050 feet above sea level near the 1/4 section corner of sections 12 and 13.</p> <p>The area is drained by Doe Creek, which flows southwesterly into Cow Creek.</p> <p>Timber consists of alder, cedar, chinquapin, fir, madrone, maple, oak, and pine. Undergrowth consists of fern, Oregon grape, poison oak, salal, and vine maple.</p> <p>The soil is generally composed of rocky clay.</p> <p>Access to the survey was made by graveled roads branching from County Road No. 263.</p>
------	---