

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

**TOWNSHIP 19 SOUTH, RANGE 7 WEST,**

AND

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

**TOWNSHIP 20 SOUTH, RANGE 7 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

*Daniel N. Patterson, Cadastral Surveyor*

Under Special Instructions dated April 3, 2007, approved April 11, 2007,  
which provided for the surveys included under Group No. 2165,  
and Assignment Instructions dated July 19, 2007, October 12, 2007,  
and February 29, 2008.

*Survey commenced July 30, 2007*

*Survey completed September 8, 2008*

**T. 20 S., R. 7 W., Willamette Meridian, Oregon**

The following field notes are those of the dependent resurvey of a portion of the south boundary, Township 19 South, Range 7 West, and dependent resurvey of a portion of the subdivisional lines, Township 20 South, Range 7 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1874, Henry C. and Joseph Perkins, U.S. Deputy Surveyors, surveyed a portion of the south boundary of T. 19 S., R. 7 W., as shown on the official plat of survey approved October 16, 1874.

In 1891, Charles M. Collier, U.S. Deputy Surveyor, surveyed the remainder of the south boundary of T. 19 S., R. 7 W., as shown on the official plat of survey approved April 4, 1892.

In 1891, Thomas E. Todd, U.S. Deputy surveyor resurveyed a portion of the south boundary of T. 19 S., R. 7 W., and subdivisional lines in T. 20 S. R. 7 W., as shown on the official plat of survey approved November 9, 1892.

In 1949, Norman D. Price and Thomas A. Tillman, Cadastral Surveyors, resurveyed the south boundary and subdivisional lines in T. 19 S., R. 7 W., as shown on the official plat of survey accepted May 16, 1951.

In 1966-67, Lynn M. Roseberry and William W. Glenn, Cadastral Surveyors, resurveyed a portion of the west boundary of the township and subdivisional lines and remonumented certain original corners without resurvey, as shown on the official plat of survey accepted January 19, 1970.

In 1976-78, Harvey E. Wofford and Lester E. Fischer, Cadastral Surveyors, resurveyed a portion of the north boundary and subdivisional lines, as shown on the official plat of survey accepted January 28, 1980.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 3, 2007, for Group No. 2165, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

The direction of the lines are based on the true meridian as determined by direct solar observation.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

**T. 20 S., R. 7 W., Willamette Meridian, Oregon**

The geographic position (NAD 1983 (CORS 96)) of these corners as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

The 1/4 section corner of section 1 only on the north boundary of the township.

Latitude: 43° 51' 05.24" N.      Longitude: 123° 28' 48.44" W.

The 1/4 section corner of sections 2 and 11.

Latitude: 43° 51' 06.94" N.      Longitude: 123° 29' 58.61" W.

The corner of sections 4, 5, 8, and 9.

Latitude: 43° 51' 04.17" N.      Longitude: 123° 32' 54.59" W.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of sec. 1 only, T. 20 S., R. 7 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd.

T 19 S R 7 W

1/4 S 1  
T 20 S R 7 W  
1977

from which bearing trees mkd. by Wofford and Fischer in 1976-78

A fir, 47 ins. diam., bears S. 3° E., 47.5 ft. dist., with a healed blaze.

A cedar, 34 ins. diam., bears S. 65 1/2° W., 84.5 ft. dist., with a healed blaze.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 35 and 36 only, T. 19 S., R. 7 W., remonumented by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 19 S	R 7 W
S 35	S 36

S 1	
T 20 S	R 7 W
1977	

from which an original bearing tree

A fir , 63 ins. diam., bears N. 20° W., 44.9 ft. dist., with a healed blaze.

and a bearing tree mkd. by Wayne R. Tinglum, Engineering Technician, at the Eugene District Bureau of Land Management, in 1972, reported by Wofford and Fischer

A fir, 22 ins. diam., bears N. 82 1/2° E., 38.3 ft. dist., with a healed blaze.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The closing cor. of secs. 1 and 2, T. 20 S., R. 7 W., established by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

T 19 S	R 7 W
S 35	
-----	
S 2	S 1
T 20 S R 7 W	
CC	
1977	

from which bearing trees mkd. by Wofford and Fischer

A fir, 28 ins. diam., bears S. 59° E., 50.2 ft. dist., with a healed blaze.

A fir, 21 ins. diam., bears S. 64 1/2° W., 93.1 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 7 ins. diam., bears S. 48 3/4° W., 15.9 ft. dist., mkd. T20S R7W S2 CC BT.

From this corner, the original closing corner of secs. 1 and 2, bears S. 0° 19' 36" W., 4.37 ft. dist.; monumented with an iron rod, 3/4 in. diam., firmly set, top 6 ins. below the surface of the ground, from which the remains of an original bearing tree

A fir stump, 54 ins. diam., bears N. 77° E., 9.9 ft. dist., protected with a metal tin cover, with a scribe mark S visible on partially open blaze.

and a bearing tree mkd. by the County Surveyor and reported by Wofford and Fischer

A fir, 28 ins. diam., bears S. 8° W., 23.8 ft. dist., with a healed blaze.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of sec. 35 only, T. 19 S., R. 7 W., reestablished by Price and Tillman in 1949; monumented with an iron post, 1 in. diam, loosely set, projecting 24 ins. above the ground, with brass cap mkd.

1/4 S 35

1949

1977

At the corner point

I reset the iron post, 36 ins long, 32 ins. in the ground, and add the marks 2007.

from which the remains of a bearing tree mkd. by Price, reported by Wofford and Fischer in 1976-78

A decayed maple stump, size indeterminate, bears N. 61° W., 51.5 ft. dist., no marks visible.

and a bearing tree mkd. by Wofford and Fischer

An alder, 16 ins. diam., bears N. 9 3/4° E., 27.1 ft. dist., no marks visible.

and a new bearing tree

An alder, 15 ins. diam., bears N. 55 1/4° W., 12.8 ft. dist., mkd. 1/4 S35 BT on bark.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of sec. 2 only, T. 20 S., R. 7 W., established by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

T 19 S R 7 W

1/4 S 2  
 T 20 S R 7 W  
 1977

from which the remains of bearing trees mkd. by Wofford and Fischer

A decayed cedar stump, 34 ins. diam., bears S. 37 1/4° W., 16.8 ft. dist., with scribe marks 1/4 S2 BT visible on partially open blaze.

A maple, 21 ins. diam., bears S. 59° W., 106.3 ft. dist., with a healed blaze.

and new bearing trees

A fir, 11 ins. diam., bears S. 14 3/4° E., 6.7 ft. dist., mkd. 1/4 S2 BT.

A fir, 7 ins. diam., bears S. 61 1/2° W., 3.7 ft. dist., mkd. 1/4 S2 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The closing cor. of secs. 2 and 3, T. 20 S., R. 7 W., established by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

T 19 S		R 7 W	
S 34			
-----			
S 3		S 2	
T 20 S R 7 W			
CC			
1977			

from which the remains of bearing trees mkd. by Wofford and Fischer

A fir stump, 22 ins. diam., bears S. 66° E., 45.5 ft. dist., with a healed blaze.

A fir, 29 ins. diam., bears S. 5° W., 57.8 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 83° E., 22.3 ft. dist., mkd. T20S R7W S2 CC BT.

From this corner, the original closing cor. of secs. 2 and 3, bears N. 0° 18' 56" E., 13.86 ft., monumented with an iron rod, 1 1/2 ins. diam., firmly set, projecting 4 ins above the ground; alongside of which is the original sandstone, buried flush with surface of ground; from which the remains of bearing trees mkd. by the County Surveyor and reported by Wofford and Fischer

A decayed fir stump, 28 ins. diam., bears S. 10° E., 56.8 ft. dist., with no marks visible.

A fir snag, 36 ins. diam., bears S. 63 1/4° W., 54.1 ft. dist., with a healed blaze. (Record, S. 66 1/2° W.)

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The closing cor. of secs. 3 and 4, T. 20 S., R. 7 W., reestablished by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 19 S R 7 W	
S 33	
S 4	S 3
T 20 S R 7 W	
CC	
1977	

from which the remains of a bearing tree mkd. by W.F. Dailey, Resident Logging Engineer, in 1957, filed in Lane County Survey Restoration Index No. 1147

A decayed cedar stump, 48 ins. diam., bears S. 51 1/2° W., 94.3 ft. dist., no marks visible.

and bearing trees mkd. by Wofford and Fischer

A fir , 22 ins. diam., bears S. 82° E., 31.4 ft. dist., with a healed blaze.

An alder, 19 ins. diam., bears S. 52 1/2° W., 39.6 ft. dist., with a healed blaze.

and a bearing tree and reference monument mkd. by Kenneth Robert Ezell, Professional Land Surveyor No. 952, in 1998, filed in Lane County Survey Restoration Index No. 13233

A fir, 15 ins. diam., bears N. 72 1/2° E., 31.2 ft. dist. to PK nail at base, with a healed blaze.

An iron rod, 5/8 in. diam,; firmly set, projecting 2 ins. above the ground, bears N. 55 1/2° W., 48.7 ft. dist., with aluminum cap mkd. RP-1 1998

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The closing cor. of secs. 4 and 5, T. 20 S., R. 7 W., established by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

T 19 S R 7 W	
S 32	
S 5	S 4
T 20 S R 7 W	
CC	
1977	

from which the bearing trees mkd. by Wofford and Fischer

A fir, 20 ins. diam., bears S. 31 1/2° E., 9.9 ft. dist., with a healed blaze.

A fir, 17 ins. diam., bears S. 62° W., 6.6 ft. dist., with a healed blaze.

From this corner, the original closing cor. of secs. 4 and 5, bears N. 0° 09' 58" W., 1.32 ft., monumented with an iron rod, 1 in. diam., firmly set, projecting 2 ins above the ground; from which the remains of original bearing trees

A decayed fir stump, 48 ins. diam., bears N. 24° E., 14.5 ft. dist., with no marks visible.

A root hole, bears S. 8° W., 28.4 ft. dist., alongside of which is lying a decayed fir, size indeterminate, no marks visible.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of sec. 32 only, T. 19 S., R. 7 W., determined at record distance intersection from the remains of the original bearing trees

A fir, 79 ins. diam., bears S. 10° E., 33.0 ft. dist., with a healed blaze.

A decayed fir stump, size indeterminate, bears N. 30° W., 6.6 ft. dist., with no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T19S R7W  
1/4 S 32

---

T20S R7W  
2008

from which new bearing trees

A fir, 6 ins. diam., bears N. 83 1/4° W., 14.8 ft. dist., mkd. 1/4 S32 BT.

A fir, 5 ins. diam., bears N. 31° W., 12.5 ft. dist., mkd. X BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of sec. 5 only, T. 20 S., R. 7 W., established by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

T 19 S R 7 W

1/4 S 5

T 20 S R 7 W

1977

from which bearing trees mkd. by Wofford and Fischer

A fir, 19 ins. diam., bears S. 5° E., 23.8 ft. dist., with a healed blaze.

A fir, 27 ins. diam., bears S. 71 1/2° W., 21.1 ft. dist., with a healed blaze.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 20 S R 7 W  
 1/4  
 S 2 | S 1  
 1977

from which the remains of the original bearing trees, reported by Wofford and Fischer in 1976-78

A fir, 82 ins. diam., bears N. 70° E., 48.8 ft. dist., no marks visible.

A decayed fir stump, size indeterminate, bears S. 83° W., 72.6 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Wofford and Fischer

A fir stump, 12 ins. diam., bears S. 43° W., 11.9 ft. dist., with scribe marks 1/4 S2 BT visible on opened blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 76 1/4° W., 10.5 ft. dist., mkd. 1/4 S2 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

Point for the 1/16 80 sec. cor. of secs. 1 and 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

80  
1/16  
S 2 | S 1  
2007

from which

A fir, 12 ins. diam., bears N. 27 1/2° E., 11.3 ft. dist., mkd.  
80 1/16 S1 BT.

A fir, 10 ins. diam., bears N. 47 1/2° W., 18.7 ft. dist., mkd.  
80 1/16 S2 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd

T 20 S		R 7 W
S 10		S 11
S 15		S 14
1977		

from which the remains of original bearing trees reported by Wofford and Fischer in 1976-78

A burnt decayed fir snag, size indeterminate, bears N. 89 1/2° E., 59.4 ft. dist., with no marks visible.

A burnt decayed fir stump, size indeterminate, bears S. 5° E., 90.4 ft. dist., with no marks visible.

A burnt decayed fir snag, size indeterminate, bears N. 2° W., 5.9 ft. dist., with no marks visible.

and new bearing trees

An alder, 11 ins. diam., bears N. 24° E., 10.7 ft. dist., mkd. T20S R7W S11 BT on bark.

A maple, 18 ins. diam., bears S. 26 1/2° E., 3.7 ft. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 73 1/4° W., 33.7 ft. dist., mkd. T20S R7W S15 BT.

A fir, 13 ins. diam., bears N. 77° W., 38.5 ft. dist., mkd. T20S R7W S10 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 10 and 11, reestablished by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T 20 S R 7 W  
 1/4  
 S 10 | S 11  
 1977

from which the remains of a bearing tree mkd. by Wofford and Fischer

A cedar stump, 36 ins. diam., bears S. 32° E., 44.2 ft. dist., with scribe marks 1/4 S11 BT visible on open blaze. (Record, S. 32° W.)

and new bearing trees

A fir, 11 ins. diam., bears S. 59 1/2° E., 17.3 ft. dist., mkd. 1/4 S11 BT.

A fir, 13 ins. diam., bears S. 58 3/4° W., 15.6 ft. dist., mkd. 1/4 S10 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd

T 20 S		R 7 W
S 3		S 2
S 10		S 11
1967		

from which the remains of the original bearing trees reported by Wofford and Fischer in 1976-78

A burnt fir snag, 57 ins. diam., bears S. 64° W., 12.5 ft. dist., with scribe marks R S10 visible on opened blaze.

A burnt cedar snag, 20 ins. diam., bears N. 58° W., 6.6 ft. dist., with scribe marks T20S R7W S visible on partially open blaze.

and the remains of a bearing tree mkd. by Roseberry and Glenn in 1966-67, reported by Wofford and Fischer

A root hole, bears N. 65° E., 160.4 ft. dist., alongside of which is lying a decayed maple, size indeterminate, no marks visible.

and new bearing trees

A fir, 12 ins. diam., bears N. 67 1/4° E., 8.5 ft. dist., mkd. T20S R7W S2 BT.

A fir, 9 ins. diam., bears S. 34° E., 7.1 ft. dist., mkd. T20S R7W S11 BT.

An alder, 17 ins. diam., bears S. 39 3/4° W., 45.9 ft. dist., mkd. T20S R7W S10 BT.

A fir, 12 ins. diam., bears N. 44° W., 20.7 ft. dist., mkd. T20S R7W S3 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 2 and 11, remonumented by Roseberry and Glenn in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 20 S R 7 W  
 S 2  
 1/4 ———  
 S 11  
 1967

from which the remains of bearing trees mkd. by Roseberry and Glenn in 1966-67

A burnt fir stump, 24 ins. diam., bears N. 23° E., 28.4 ft. dist., with a healed blaze.

A burnt cedar, 28 ins. diam., bears S. 9° W., 31.7 ft. dist., with scribe marks 1/4 S visible on partially open blaze. (Record, S. 59° W.)

There are no suitable trees available within limits in sec. 2

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd

1/4  
S 3 | S 2  
T 20 S R 7 W  
1967

from which the remains of original bearing trees reported by Roseberry and Glenn in 1966-67

A decayed fir stump, size indeterminate, bears N. 29° E., 33.0 ft. dist., with a healed blaze.

A root hole, bears S. 46° W., 17.8 ft. dist., alongside of which is lying a decayed fir, size indeterminate, no marks visible.

and new bearing trees

A fir, 13 ins. diam., bears S. 43° E., 10.9 ft. dist., mkd. 1/4 S2 BT.

A fir, 11 ins. diam., bears S. 32 3/4° W., 23.8 ft. dist., mkd. 1/4 S3 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

Point for the 1/16 80 sec. cor. of secs. 2 and 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

80  
1/16  
S 3 | S 2  
2007

from which

A fir, 7 ins. diam., bears S. 76 1/2° E., 14.2 ft. dist., mkd.  
80 1/16 S2 BT.

A fir, 8 ins. diam., bears S. 32 1/2° W., 15.7 ft. dist., mkd.  
80 1/16 S3 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 15 and 16, remonumented by Roseberry and Glenn in 1966-67 and determined at record distance intersection from the remains of bearing trees mkd. by Roseberry and Glenn.

A root hole, bears N. 10° E., 13.9 ft. dist., alongside of which is lying a decayed maple, 14 ins. diam., with scribe marks 1/4 S BT visible on opened blaze.

A burnt decayed fir stump, size indeterminate, bears S. 59 3/4° W., 73.3 ft. dist., with no marks visible. (Record, S. 61° W.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
1/4  
S 16 | S 15  
2008

from which new bearing trees

A hemlock, 4 ins. diam., bears N. 49 1/4° E., 22.6 ft. dist., mkd. X BT.

An alder, 16 ins. diam., bears N. 4° W., 6.9 ft. dist., mkd. 1/4 S16 BT on bark.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd

T 20 S	R 7 W
S 9	S 10
S 16	S 15
1966	

from which the remains of an original bearing tree reported by Roseberry and Glenn in 1966-67

A burnt decayed fir stump, size indeterminate, bears S. 12° E., 48.8 ft. dist., with no marks visible.

and new bearing trees

A fir, 14 ins. diam., bears N. 89 3/4° E., 18.0 ft. dist., mkd. T20S R7W S10 BT.

A fir, 7 ins. diam., bears S. 68° E., 16.7 ft. dist., mkd. T20S R7W S15 BT.

A maple, 10 ins. diam., bears S. 27 1/4° W., 14.2 ft. dist., mkd. T20S R7W S16 BT.

A fir, 10 ins. diam., bears N. 0 3/4° W., 5.9 ft. dist., mkd. T20S R7W S9 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 10 and 15, remonumented by Wiljo E. Green, Professional Land Surveyor, No. 563, in 1967, filed in Lane County Restored Corner Index No. 3793; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

## OREGON STATE BOARD OF FORESTRY

1/4

S 10

S 15

RE 563

1967

from which the remains of an original bearing tree reported by Wofford and Fischer in 1976-78

A decayed fir snag, size indeterminate, bears N. 50 1/2° E., 11.2 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Green, reported by Wofford and Fischer

A decayed fir stump, size indeterminate, bears S. 73 1/4° E., 98.3 ft. dist., with no marks visible.

and new bearing trees

A fir, 12 ins. diam., bears N. 80 1/4° E., 53.2 ft. dist., mkd. 1/4 S10 BT.

A fir, 16 ins. diam., bears S. 45° E., 17.9 ft. dist., mkd. 1/4 S15 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The W 1/16 sec. cor. of secs. 10 and 15, established by Wiljo E. Green, Professional Land Surveyor, No. 563, in 1967, filed in Lane County Survey No. 14950, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd

## OREGON STATE BOARD OF FORESTRY

W 1/16

S 10

S 15

RE 563

1967

from which the remains of bearing trees mkd. by Green and reported by Wofford and Fischer in 1976-78

A burnt decayed hemlock stump, size indeterminate, bears N. 10° E., 22.1 ft. dist., with no marks visible.

A burnt decayed fir stump, size indeterminate, bears S. 52° E., 27.1 ft. dist., with no marks visible.

and new bearing trees

A fir, 12 ins. diam., bears S. 40° W., 8.9 ft. dist., mkd. W 1/16 S15 BT.

A fir, 10 ins. diam., bears N. 53° W., 6.4 ft. dist., mkd. W 1/16 S10 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 3 and 10, perpetuated by Wiljo E. Green, Professional Land Surveyor, No. 563, in 1967, filed in Lane County Restored Corner Index No. 3792; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with bronze cap mkd

## OREGON STATE BOARD OF FORESTRY

S 3  
 1/4 ———  
 S 10  
 1967  
 RS 563

from which an original bearing tree reported by Roseberry and Glenn in 1966-67

A burnt fir, 50 ins. diam., bears S. 28° E., 35.0 ft. dist., with no scribe marks visible on partially opened blaze.

and a bearing tree mkd. by Roseberry and Glenn

A fir, 20 ins. diam., bears S. 15° W., 40.6 ft. dist., with a healed blaze.

and a bearing tree mkd. by person (s) unknown

A fir, 63 ins. diam., bears S. 69 3/4° W., 28.0 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears N. 43° W., 17.6 ft. dist., mkd. 1/4 S3 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The W 1/16 sec. cor. of secs. 3 and 10, established by Wiljo E. Green, Professional Land Surveyor, No. 563, in 1967, filed in Lane County Survey No. 14950, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

## OREGON STATE BOARD OF FORESTRY

S 3  
W 1/16 ———  
S 10  
1967  
RS 563

from which a bearing tree mkd. by Green

A maple, 10 ins. diam., bears N. 2° W., 22.5 ft. dist., no marks visible.

and a new bearing tree

A cedar, 7 ins. diam., bears S. 30 3/4° E., 4.2 ft. dist., mkd. W1/16 S10 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 3, 4, 9, and 10, perpetuated by Wiljo E. Green, Professional Land Surveyor, No. 563, in 1967, filed in Lane County Restored Corner No. 3791; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

## OREGON STATE BOARD OF FORESTRY

T 20 S		R 7 W
S 4		S 3
S 9		S 10
1967		

from which the remains of the original bearing trees reported by Roseberry and Glenn in 1966-67

- A decayed burnt fir stump, 40 ins. diam., bears N. 76° E., 16.5 ft. dist., with illegible scribe marks visible on partially open blaze.
- A decayed burnt fir stump, 32 ins. diam., bears S. 12° E., 35.6 ft. dist., no marks visible.
- A decayed burnt fir stump, 35 ins. diam., bears S. 87° W., 35.6 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by Green and reported by Roseberry and Glenn

- A decayed burnt fir stump, 43 ins. diam., bears N. 27° E., 29.7 ft. dist., with illegible scribe marks visible on partially open blaze.
- A decayed burnt fir stump, 46 ins. diam., bears S. 66° E., 51.2 ft. dist., with illegible scribe marks visible on partially open blaze.
- A decayed burnt fir stump, 44 ins. diam., bears N. 59° W., 40.3 ft. dist., with illegible scribe marks visible on partially open blaze.

and new bearing trees

- A fir, 13 ins. diam., bears N. 35° E., 12.3 ft. dist., mkd. T20S R7W S3 BT.
- A fir, 11 ins. diam., bears S. 45 1/4° E., 9.7 ft. dist., mkd. T20S R7W S10 BT.
- A fir, 10 ins. diam., bears S. 15 1/4° W., 6.6 ft. dist., mkd. T20S R7W S9 BT.

**T. 20 S., R. 7 W., Willamette Meridian, Oregon**

A fir, 7 ins. diam., bears N.  $18\frac{1}{4}^{\circ}$  W., 16.1 ft. dist., mkd.  
T20S R7W S4 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
1/4  
S 4 | S 3  
2007

from which

A fir, 17 ins. diam., bears S. 33 3/4° E., 31.1 ft. dist., mkd.  
1/4 S3 BT.

A fir, 11 ins. diam., bears S. 84 3/4° W., 36.7 ft. dist., mkd.  
1/4 S4 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

Point for the 1/16 80 sec. cor. of secs. 3 and 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

80  
1/16  
S 4 | S 3  
2007

from which

A fir, 11 ins. diam., bears N. 2° E., 6.9 ft. dist., mkd. 80 1/16 S3  
BT.

A fir, 11 ins. diam., bears N. 66 1/4° W., 19.7 ft. dist., mkd.  
80 1/16 S4 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T	20	S	R	7	W
S	5	S	4		
S	8	S	9		
1967					

from which the remains of an original bearing tree reported by Roseberry and Glenn in 1966-67

A burnt decayed hemlock snag, size indeterminate, bears S. 58 1/2° W., 43.6 ft. dist., with no marks visible.

and the remains of bearing trees by Roseberry and Glenn

A burnt decayed fir stump, 50 ins. diam., bears N. 19 1/4° E., 41.6 ft. dist., with scribe marks T20S R7W S4 BT visible on open blaze. (Record, N. 23 1/2° E.)

A burnt decayed fir stump, 45 ins. diam., bears N. 71° W., 27.1 ft. dist., with no marks visible.

and new bearing trees

A fir, 13 ins. diam., bears N. 13° E., 16.4 ft. dist., mkd. T20S R7W S4 BT.

A fir, 9 ins. diam., bears S. 28 1/2° E., 41.3 ft. dist., mkd. T20S R7W S9 BT.

A fir, 10 ins. diam., bears S. 30° W., 14.7 ft. dist., mkd. T20S R7W S8 BT.

A fir, 11 ins. diam., bears N. 62 3/4° W., 9.1 ft. dist., mkd. T20S R7W S5 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 4 and 5, remonumented by Wofford and Fischer in 1976-78; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.

T 20 S R 7 W  
 1/4  
 S 5 | S 4  
 1977

from which the remains of an original bearing tree

A root hole, bears S. 88° W., 10.6 ft. dist., alongside of which is lying a decayed fir, size indeterminate, no marks visible.

and new bearing trees

A fir, 11 ins. diam., bears S. 79° E., 14.4 ft. dist., mkd. 1/4 S4 BT.

A fir, 13 ins. diam., bears N. 15 1/4° W., 9.0 ft. dist., mkd. 1/4 S5 BT.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

Point for the 1/16 80 sec. cor. of secs. 4 and 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

80  
1/16  
S 5 | S 4  
2008

from which

A fir, 14 ins. diam., bears N. 56 1/2° E., 9.8 ft. dist., mkd.  
80 1/16 S4 BT.

A fir, 12 ins. diam., bears N. 48 1/2° W., 19.4 ft. dist., mkd.  
80 1/16 S5 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
           S 5  
 1/4 ———  
           S 8  
           2008

from which

A fir, 12 ins. diam., bears S. 15° W., 10.7 ft. dist., mkd. 1/4 S8 BT

A fir, 12 ins. diam., bears N. 85 1/4° W., 21.3 ft. dist., mkd. 1/4 S5 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 20 S	R 7 W
S 6	S 5
S 7	S 8
1967	

from which the remains of original bearing trees reported by Roseberry and Glenn in 1966-67

A burnt decayed fir stump, size indeterminate, bears S. 84° E., 32.3 ft. dist., with no marks visible.

A burnt decayed fir snag, 32 ins. diam., bears S. 35° W., 6.6 ft. dist., with no marks visible on decayed opened blaze.

and the remains of bearing trees mkd. by Roseberry and Glenn

A burnt decayed fir stump, size indeterminate, bears N. 21 1/2° E., 43.6 ft. dist., with no marks visible.

A burnt decayed fir stump, size indeterminate, bears N. 28 1/2° W., 61.1 ft. dist., with no marks visible.

and new bearing trees

A fir, 9 ins. diam., bears N. 23 3/4° E., 5.4 ft. dist., mkd. T20S R7W S5 BT.

A fir, 12 ins. diam., bears S. 38 3/4° E., 5.3 ft. dist., mkd. T20S R7W S8 BT.

A fir, 9 ins. diam., bears S. 18° W., 21.1 ft. dist., mkd. T20S R7W S7 BT.

A fir, 7 ins. diam., bears N. 62 3/4° W., 10.7 ft. dist., mkd. T20S R7W S6 BT.

From this corner, a point established in 1967 for an electronic survey control point, ABC-2, during the Aerial Electronic Cadastral Resurvey in the Oxbow Ridge Fire Area, bears N. 50° 42' 25" E.; 504.27 ft. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

ABC-2
—
1967

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

from which the remains of bearing trees mkd. by Aerial Electronic Cadastral Resurvey

A burnt decayed fir stump, size indeterminate, bears N. 41° E., 67.7 ft. dist., with no marks visible.

A burnt decayed fir stump, size indeterminate, bears S. 14° W., 47.2 ft. dist., with no marks visible.

and new bearing trees

A fir, 9 ins. diam., bears N. 64 1/4° W., 6.6 ft. dist., mkd. ABC 2 BT.

A fir, 13 ins. diam., bears N. 28 1/2° E., 3.0 ft. dist., mkd. ABC 2 BT.