

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

PORTIONS OF CERTAIN CLAIM LINES,

AND PORTIONS OF THE SUBDIVISION OF SECTION LINES

IN SECTIONS 18 AND 19,

**TOWNSHIP 22 SOUTH, RANGE 8 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

***Edith M. Forkner, Cadastral Surveyor***

Under Special Instructions dated March 16, 2007, approved March 21, 2007,

which provided for the surveys included under Group No. 2300,

and Assignment Instructions dated May 11, 2007,

also Special Instructions dated July 3, 2007, approved July 5, 2007,

which provided for the surveys included under Group No. 2180,

and Assignment Instructions dated July 5, 2007.

***Survey commenced May 24, 2007***

***Survey completed October 16, 2007***

**T. 22 S., R. 8 W., Willamette Meridian, Oregon**

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, portions of certain claim lines, and portions of the subdivision of section lines in sections 18 and 19, Township 22 South, Range 8 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines and meandered the Umpqua River, as shown on official plat of survey approved February 20, 1856.

In 1856, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the boundaries of Donation Land Claim Nos. 46, 47, 49, 51, and 57, as shown on official plat of survey approved December 23, 1859.

In 1874, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on official plat of survey approved August 20, 1875.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines, as shown on official plat of survey approved August 11, 1881.

In 1931, George F. Rigby, U.S. Cadastral Engineer, dependently resurveyed a portion of the west boundary and subdivisional lines, subdivided section 18, and surveyed the patented portion of Lot 7 in section 18, as shown on official plat of survey accepted August 15, 1933.

In 1960, Floyd A. Brooks, Cadastral Surveyor, resurveyed a portion of the subdivisional lines, as shown on official plat of survey accepted January 31, 1962.

In 1963-65, Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, resurveyed a portion of the south boundary, (Fifth Standard Parallel South), a portion of the east and north boundaries, a portion of the subdivisional lines, and a portion of certain claim lines, and remonumented certain original corner points without survey, as shown on official plat of survey accepted March 24, 1966.

In 1965-67, Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, resurveyed a portion of the west boundary, a portion of certain claim lines, and a portion of the subdivisional lines, and subdivided sections 19 and 29, as shown on official plat of survey accepted July 25, 1969.

In 2006, Edith M. Forkner, Cadastral Surveyor, resurveyed a portion of the east boundary of T. 22 S., R. 9 W., as shown on official plat of survey accepted April 16, 2009.

The following Map files (M.F.), County Surveys (C.S.), Corner Records (C.R.), and field notes filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by surveyor's last name and year.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

<u>Date</u>	<u>Name</u>	<u>Registration Number</u>	<u>File Number</u>
1917	F. C. Frear	Deputy Co. Surveyor	Field Bk. 43, p. 9-14, Vol. 3, page 1, "old" corner bk. p. 26
1941	Ben B. Irving	Co. Surveyor	C.S. 16/55
1962-63	Milo E. Godfrey	Deputy Co. Surveyor	C.S. 52/14
1966	Wilford N. Haines	PLS 239	M.F. M31-30
1970	Douglas Co. Surveyor's Office		C.R. 047020
1977	Romanso E. Ware	PLS 1005	M.F. 68-73
1979	Wilford N. Haines	PLS 239	M.F. M77-19
1980	Leslie D. Roberts	PLS 1039	M.F. M83-34
1991	Douglas Co. Surveyor's Office		C.S. 64/17
1996	Bruce A. Shaner	PLS 430	M.F. M125-25
1996	Bruce A. Shaner	PLS 430	C.S. 65/8-1 A and C
1997	Leslie D. Roberts	PLS 1039	M.F. M126-32
1997	Douglas Co. Surveyor's Office		C.S. 64/74-19
1998	Russell D. Hendricks	PLS 688	M.F. M130-77
2002	Robert B. Ward, Jr.	PLS 1091	C.S. 65/44-29 C.S. 65/44-30

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 16, 2007, for Group No. 2300, and the Special Instructions dated July 3, 2007, for Group No. 2180, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

The direction of the lines are based on the true meridian as determined by direct solar observation.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 19, 24, 25, and 30, on the west boundary of the township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43° 38' 10.28" N.      Longitude: 123° 42' 18.39" W.

The cor. of secs. 8, 9, 16, and 17, identical with the W-NW cor. of Donation Land Claim No. 47, perpetuated by Frear in 1917, and by Godfrey in 1962-63, and accepted by Brooks and Jelley in 1963-65; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

		SURVEYORS					
		T. 22 S.					
COUNTY	B	S	8		S	9	OFFICE
	L						
	M	S	17		S	16	
		BLM					
		R. 8 W.					
		1962		1963			

from which the remains of an original bearing tree

A roothole bears N. 60° E., 3.3 ft. dist., alongside of which is a down fir stump, 47 ins. diam., with no scribe marks visible on open blaze.

and the remains of the bearing trees mkd. by Godfrey and reported by Brooks and Jelley as being mkd. by Fred Darby, Douglas County Surveyor, in 1962

A white fir, 28 ins. diam., bears N. 47 1/2° E., 53.5 ft. dist., with a healed blaze.

A decayed white fir snag, size indeterminate, bears S. 57° E., 69.3 ft. dist., no marks visible.

and the bearing trees mkd. by Roberts in 1997

A fir, 20 ins. diam., bears S. 9 3/4° E., 3.7 ft. dist., with a healed blaze.

A fir, 21 ins. diam., bears S. 88 3/4° W., 47.7 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 13 ins. diam., bears N. 43° W., 67.4 ft. dist., mkd. T22S R8W S8 BT.

An axle, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, and a steel fence post are alongside the cor.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

Corner is located alongside roots of original fir stump, on a flat at the W. end of a knob on an E. slope, and SE., 20 ft., from a abandoned dirt road, 8 ft. wide, extending S. 20° W. and N. 30° E., 50 ft. to tank trap, on the other side of which is a lightly maintained dirt road, 8 ft. wide, extending N. 50° E. and S. 85° W.

The 1/4 sec. cor. of secs. 8 and 9, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.

1/4  
S 8 | S 9  
T 22 S R 8 W  
1963

from which the remains of the bearing trees mkd. by Brooks and Jelley

A fir, 34 ins. diam., bears N. 82 1/4° E., 108.2 ft. dist., with a healed blaze. (Record, N. 83° E.)

A decayed white fir stump, size indeterminate, bears S. 51 1/4° W., 60.1 ft. dist., no marks visible.

and a new bearing tree

A fir, 9 ins. diam., bears S. 44 3/4° W., 60.2 ft. dist., mkd. 1/4 SEC9 BT.

A BLM location tag dated 1973 is on a hemlock, 4 ft. diam., E., 15 ft., from the cor.

Corner is located on a gentle S. slope, and S., 1100 ft. from a ridge, extending N. 35° E. and S. 60° W.

Point for the crossing closing corner of secs. 8 and 9, determined at intersection with the S. bdy. of Donation Land Claim No. 49.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

C 49  
-----  
S 8 | S 9  
CCC  
2007

from which

A hemlock, 10 ins. diam., bears S. 42 1/2° E., 14.3 ft. dist., mkd. CCC S9 BT.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A hemlock, 14 ins. diam., bears N.  $69\frac{3}{4}^{\circ}$  W., 31.1 ft. dist., mkd. CCC C49 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a very steep N. slope, and N., 5 ft., from an alder, 2 ft. diam.

From this corner, a point established as the intersection of the line bet. secs. 8 and 9 with the north boundary of Donation Land Claim No. 49, by Hendricks in 1998, and was not accepted for control in this survey due to improper procedure, bears N.  $0^{\circ} 16' 47''$  E., 15.75 ft. dist.; monumented with an iron rod,  $\frac{5}{8}$  ins. diam., firmly set, projecting 8 ins. above ground, with red plastic cap mkd. GEOMAX INC.

---

The cor. of secs. 4, 5, 8, and 9, perpetuated by Brooks and Jelley in 1963-65; monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, with brass cap mkd.

T 22 S		R 8 W
S 5		S 4
S 8		S 9
1963		

from which the remains of an original bearing tree

A decayed fir stump, 48 ins. diam., bears S.  $66^{\circ}$  W., 86.5 ft. dist., no marks visible. Stump is behind a white fir, 6 ins. diam., 60 ft. from the cor.

and a bearing tree mkd. by Brooks and Jelley

A hollow fir, 17 ins. diam., bears N.  $75^{\circ}$  W., 56.1 ft. dist., with reverse scribe marks T visible inside the hollow. (Record, dead.) Tree has a broken top and has grown a new one.

and the remains of the bearing trees mkd. by the Douglas County Surveyor's Office in 1997

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A white fir, 18 ins. diam., bears N.  $2\ 1/2^\circ$  E., 48.0 ft. dist., with a healed double blaze.

An alder, 13 ins. diam., bears S.  $62\ 1/4^\circ$  E., 28.5 ft. dist., with scribe marks 22S R8W S9 CS and other illegible scribe marks visible on partially healed double blaze.

A fir, 15 ins. diam., bears S.  $49^\circ$  W., 54.0 ft. dist., with a healed double blaze.

A maple, 14 ins. diam., bears S.  $76\ 1/4^\circ$  W., 12.5 ft. dist., with a healed double blaze.

Corner is located on a steep rocky N. slope, N., 280 ft. from an asphalt road, 10 ft. wide, extending N.  $60^\circ$  W. and S.  $85^\circ$  E., and S., 50 ft. from the N. edge of timber, bears E. and W., and S., 200 ft. from the S. edge of open field, bears E. and W., with fir reproduction and brush in between.

---

The E 1/16 sec. cor. of secs. 19 and 30, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

S 19  
E 1/16 ———  
S 30  
1965

from which the bearing trees mkd. by Brooks and Peterson

A fir, 30 ins. diam., bears S.  $57^\circ$  W., 15.2 ft. dist., with a healed blaze.

A fir, 17 ins. diam., bears N.  $25^\circ$  W., 32.7 ft. dist., with a healed blaze.

An aluminum fence post is alongside the cor.

Corner is located on a SW. slope, alongside roots of a down fir, 1 ft. diam., at the SE. cor. of timber, edge bears N. and W., with fir reproduction to E. and S., and E., 300 ft. from a creek, 3 ft. wide, course N.  $40^\circ$  W.

---

The 1/4 sec. cor. of secs. 19 and 30, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

S 19  
1/4 ———  
S 30  
T 22 S R 8 W  
1965

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

from which the remains of the bearing trees mkd. by Brooks and Peterson

A fir snag, 15 ins. diam., bears S. 29 1/2° W., 20.4 ft. dist., with a healed blaze. (Record, 21.5 ft. dist.)

A roothole, bears N. 18° W., 24.8 ft. dist., alongside of which is a down fir stump, 24 ins. diam., with a healed blaze.

and new bearing trees

A fir, 7 ins. diam., bears N. 58 1/2° E., 3.1 ft. dist., mkd. 1/4 S19 BT.

A fir, 5 ins. diam., bears S. 9 1/4° E., 18.5 ft. dist., mkd. 1/4 S30 BT.

Corner is located in young timber on a very broad spur, slopes gently N., and W., 110 ft. from a graveled road, 15 ft. wide, extending N. 10° E. and S. 10° W., and E., 765 ft. from another graveled road, 12 ft. wide, extending N. 50° E. and S. 60° W.

The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S	
R 9 W	R 8 W
S 24	S 19
-----	
S 25	S 30
1965	

from which the remains of the bearing trees mkd. by Brooks and Peterson

A decayed fir stump, 19 ins. diam., bears N. 78 1/4° E., 47.5 ft. dist., no marks visible.

A fir stump, 21 ins. diam., bears S. 43° E., 24.4 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 38° W., 14.9 ft. dist., with a healed blaze and snow blaze.

A fir, the westerly of two growing together, 24 ins. diam., bears N. 19° W., 13.9 ft. dist., with a healed blaze.

No suitable bearing trees available to the E.

Corner is located on a SE. slope on the W. edge of fir reproduction, edge bears N. and S.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

The S 1/16 sec. cor. of secs. 19 and 20, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

S 1/16  
S 19 | S 20  
1965

from which the remains of the bearing trees mkd. by Brooks and Peterson

A fir stump, 25 ins. diam., bears S. 42 3/4° E., 22.4 ft. dist., to a Mag Nail set in the top center of stump, with a healed blaze. (Record, S. 45° E., 23.8 ft. dist.)

A roothole, bears S. 67 1/2° W., 25.3 ft. dist., alongside of which is a down fir, 18 ins. diam., no marks visible. (Record, 62.7 ft. dist.) Tree has fallen on face but bearing tree tag is visible.

No suitable bearing trees available.

An aluminum fence post is alongside the cor.

Corner is located on a N. slope in blown down timber, in hole sawed out of fallen SW. bearing tree, near the SE. cor. of standing timber, edge bears N. and W., with fir reproduction to the S. and E., and S., 165 ft. from a creek, 2 ft. wide, course S. 50° W.

---

The 1/4 sec. cor. of secs. 19 and 20, perpetuated by Brooks in 1960; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

1/4  
S 19 | S 20  
T 22 S R 8 W  
1960

from which the remains of an original bearing tree

A pile of fir duff, 2 ft. across, bears N. 45° E., 13.2 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Brooks

A white fir stump, 36 ins. diam., bears S. 16° E., 63.4 ft. dist., with a healed blaze.

A fir snag, 12 ins. diam., bears N. 44° W., 15.8 ft. dist., no marks visible. (Record, N. 46 1/2° W.)

and a bearing tree mkd. by Godfrey in 1962-63 and reported by Brooks and Peterson in 1965-67 as being mkd. by the Douglas County Surveyor in 1963

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A white fir, 36 ins. diam., bears S. 60° W., 24.8 ft. dist., with a healed blaze.

and a new bearing tree

A white fir, 19 ins. diam., bears S. 43 3/4° E., 5.7 ft. dist., mkd. 1/4 S20 BT.

Corner is located on a SW. slope on the E. edge of timber, bears N. and S., with newly logged area to the E.

---

The cor. of secs. 17, 18, 19, and 20, perpetuated by Rigby in 1931, by establishing a monument at record bearing and distance from the remaining original bearing tree and alongside the original 1874 Byars corner tree which he found in poor condition. The Rigby monument was accepted by Brooks and Jelley in 1963-65, Brooks and Peterson in 1965-67, and by private surveyors as the cor. and is accepted as the best available evidence of the position of the original corner tree; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S	R 8 W
S 18	S 17
S 19	S 20
1931	

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears N. 74 1/2° W., 38.9 ft. dist., with illegible scribe marks visible on partially healed blaze. (Record, N. 70° W.)

and the remains of the bearing trees mkd. by Rigby and reported by Brooks and Jelley

A decayed fir stump, size indeterminate, bears S. 50 1/2° E., 50.2 ft. dist., no marks visible.

A decayed fir stump, size indeterminate, bears S. 16 1/4° W., 37.0 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Godfrey in 1962-633 and reported by Brooks and Jelley as being mkd. by Fred Darby, Douglas County Surveyor, in 1963

A decayed fir stump, 15 ins. diam., bears N. 48 1/4° E., 46.2 ft. dist., with scribe marks BT visible on open blaze. Stump is behind a white fir, 1 ft. diam.

A fir, 28 ins. diam., bears N. 49° W., 20.8 ft. dist., with a healed blaze. (Record, N. 46 1/2° W., 22.4 ft. dist.)

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

and the remains of the bearing trees mkd. by Brooks and Peterson

- A white fir, 19 ins. diam., bears N. 22° E., 35.3 ft. dist., with a healed blaze.
- A white fir stump, 36 ins. diam., bears S. 58° E., 46.2 ft. dist., no marks visible.
- A white fir, 28 ins. diam., bears S. 63° W., 21.8 ft. dist., with scribe marks S19 BT visible on pitched-over, partially healed blaze and an aluminum nail on the right side center added by Ward in 2002.
- A white fir, 22 ins. diam., bears N. 10 3/4° W., 32.0 ft. dist., with a healed blaze.

and a bearing tree mkd. by Ward in 2002

- A white fir, 21 ins. diam., bears S. 19 1/2° E., 10.2 ft. dist., with scribe marks R8W S20 BT and other illegible scribe marks visible on pitched-over partially healed blaze and an aluminum nail on the right side center.

An aluminum fence post is alongside the cor.

Corner is located on a SW. slope, at the NW. cor. of recently logged area, edge bears S. and E., and W., 825 ft. from Hedden Ridge Road, graveled surface, 12 ft. wide, extending N. 20° W. and S. 35° E.

---

The cor. of secs. 16, 17, 20, and 21, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top 25 ins. below the surface of the ground, with brass cap mkd.

T 22 S	R 8 W
S 17	S 16
-----	
S 20	S 21
1963	

No suitable accessories available. Deposit Mag Nails below the ground, to the north and south alongside the cor.

Corner is located in the southeasterly portion of an open field, and W., 100 ft. and N., 350 ft. of woven wire fences.

---

The witness point on the line bet. secs. 17 and 20, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with brass cap mkd.

WP  
S17

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

S20  
1963

Corner is located in a woven wire fence, bears N. 30° E. and S. 30° W., and E., 20 ft. from Henderer Road, asphalt surface, 20 ft. wide, extending N. 30° E. and S. 30° W.

Point for the crossing closing corner of secs. 17 and 20, determined at intersection with the W. bdy. of Donation Land Claim No. 51.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

$$\begin{array}{r} \text{C S 17} \\ \text{C} \text{-----} \text{C 51} \\ \text{C S 20} \\ \text{2007} \end{array}$$

from which

A fir, 17 ins. diam., bears S. 4° W., 41.1 ft. dist., mkd. CCC C51 BT.

A fir, 10 ins. diam., bears N. 27 3/4° W., 3.8 ft. dist., mkd. CCC S17 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on an E. slope.

From this corner, S. 8° 37' 39" W., on the W. bdy. of Donation Land Claim No. 51, at:

707.55 ft. dist, to a point, from which a point, established by Haines in 1966, and not accepted for control in this survey, bears N. 81° 22' 21" W., 30.75 ft. dist.; monumented with a T-iron, firmly set, projecting 3 ins. above ground. Point is located on an E. slope in dense blackberries near the E. edge of timber, edge bears N. 10° E. and S. 10° W.

716.71 ft. dist, to a point established by Haines in 1979; monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 12 ins. above ground, with a steel fence post, 10 ft. long, alongside. Point is located in dense blackberries on an E. slope near the toe.

946.11 ft. dist, to a point established by Haines in 1979; monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 17 ins. above ground, with a steel fence post, 10 ft. long, alongside. Point is located on the toe of an E. slope.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

1175.19 ft. dist, to a point established by Ware in 1977; monumented with an iron rod, 5/8 ins. diam., firmly set, with top flush with the surface of the ground, with a steel fence post, 10 ft. long, alongside. Point is located on nearly level land, near the toe of an E. slope.

1329.20 ft. dist, to a point established by Ware in 1977; monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 1 in. above ground, with a steel fence post, 6 ft. high, alongside. Point is located on nearly level land.

---

The 1/4 sec. cor. of secs. 17 and 20, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

S 17  
1/4 ———  
S 20  
T 22 S R 8 W  
1963

from which the bearing trees mkd. by Brooks and Jelley

A fir, 27 ins. diam., bears S. 79 1/2° W., 169.6 ft. dist., with a healed blaze. (Record, S. 82° W.)

An oak, 13 ins. diam., bears N. 45° W., 143.9 ft. dist., no marks visible. (Record, N. 42 1/2° W.)

and the bearing trees mkd. by Ward in 2002

A fir, 27 ins. diam., bears S. 37 1/2° W., 24.9 ft. dist., with no scribe marks visible on a pitched-over nearly healed blaze.

A fir, 20 ins. diam., bears N. 28° W., 7.4 ft. dist., with no scribe marks visible on a pitched-over nearly healed blaze.

An aluminum fence post is alongside the cor. and a BLM location tag is on a fir, 6 ins. diam., bears S. 30° E., 25 ft. from the cor.

Corner is located on a SE. slope, and E., 285 ft. of a sharp spur ridge, slopes N. 65° E.

---

The 1/4 sec. cor. of secs. 17 and 18, reestablished by Rigby in 1931, and recovered by Brooks and Jelley in 1963-65, who report recovering the Rigby monument but not remonumenting the cor; monumented with a BLM iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

1/4  
S 18 | S 17  
T 22 S R 8 W  
1963

from which the remains of the bearing trees mkd. by Rigby

A decayed fir stump, size indeterminate, bears N. 48 1/4° E., 11.9 ft. dist., no marks visible. Stump is partially uprooted.

A decayed fir stump, size indeterminate, bears S. 56° W., 21.1 ft. dist., with scribe marks 1/4 S18 BT visible on detached blaze.

and the remains of the bearing trees mkd. by John M. Phillips, Registered Land Surveyor No. 307, in 1954, not recorded, and reported by Brooks and Jelley

A decayed fir stump, 30 ins. diam., bears S. 61° E., 20.5 ft. dist., no marks visible.

A fir stump, 40 ins. diam., bears S. 87° W., 77.2 ft. dist., with partially healed axe marks. (Record, down fir.)

and the bearing trees mkd. by Brooks and Jelley

A white fir, 29 ins. diam., bears N. 15° E., 136.6 ft. dist., with a healed blaze and on N. side axe marks X at head height.

A white fir, 22 ins. diam., bears S. 39° W., 120.8 ft. dist., with a healed blaze. (Record, S. 40° W.)

An iron rod with International Paper Company sign is alongside the cor.

Corner is located on nearly level land, and S., 365 ft. from a graveled road, 10 ft. wide, extending N. 80° E. and S. 80° W.

---

The N-N 1/64 sec. cor. of secs. 17 and 18, established by Roberts in 1980, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with brass cap mkd.

PLS 1039  
S 18 | S 17  
N-N 1/64  
T 22 S R 8 W  
1980

from which the remains of the bearing trees mkd. by Roberts

A hemlock, 20 ins. diam., bears S. 19° W., 15.4 ft. dist., with illegible scribe marks visible on partially healed double blaze.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A roothole bears N.  $75^{\circ}$  W., 27.0 ft. dist., downhill past the monument of which is a down fir, 59 ins. diam., with scribe marks BT visible on partially healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S.  $59 \frac{3}{4}^{\circ}$  E., 11.6 ft. dist., mkd. N-N  $\frac{1}{64}$  S17 BT.

An iron rod,  $\frac{3}{8}$  in. diam., is alongside the cor.

Corner is located on a steep E. slope.

The cor. of secs. 7, 8, 17, and 18, perpetuated by Rigby in 1931, and recovered by Brooks and Jelley in 1963-65; monumented with a rusted iron pipe, 2 ins. diam., firmly set, with concrete core projecting 3 ins. above ground, in a mound of stone, 3 ft. base, to top, from which the original bearing trees

A fir, 49 ins. diam., bears S.  $9^{\circ}$  E., 4.6 ft. dist., with axe marks and a healed blaze.

A fir, 33 ins. diam., bears N.  $53 \frac{3}{4}^{\circ}$  W., 28.4 ft. dist., with a healed blaze. (Record, N.  $56^{\circ}$  W.)

and the bearing trees mkd. by Rigby

A fir, 27 ins. diam., bears N.  $86 \frac{1}{4}^{\circ}$  E., 21.8 ft. dist., with a healed blaze. (Record, N.  $83^{\circ}$  E.)

A fir, 72 ins. diam., bears S.  $19^{\circ}$  E., 50.2 ft. dist., with a healed blaze. Tree is behind the original SE. bearing tree.

A fir, 21 ins. diam., bears S.  $8 \frac{1}{4}^{\circ}$  W., 15.2 ft. dist., with a healed blaze. Tree is partially behind the original SE. bearing tree.

A fir, 46 ins. diam., bears N.  $81 \frac{3}{4}^{\circ}$  W., 21.8 ft. dist., no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long,  $2 \frac{1}{2}$  ins. diam., 22 ins. in the ground, directly over the rusted iron pipe and concrete core, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S	R 8 W
S 7	S 8
S 18	S 17
2007	

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a W. slope in young timber, near the northerly point of a stand of large timber, and W., 375 ft. of a dirt road, 6 ft. wide, extending N. 5° W. and S. 60° E.

The 1/4 sec. cor. of secs. 8 and 17, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., loosely set, projecting 16 ins. above ground, with brass cap mkd.

S 8  
1/4 ———  
S 17  
T 22 S R 8 W  
1963

from which the remains of the bearing trees mkd. by Brooks and Jelley

A decayed fir stump, 47 ins. diam., bears N. 62° E., 73.9 ft. dist., with a healed blaze.

A maple, 40 ins. diam., with several sprouts beginning from a burl, bears S. 48 1/2° E., 24.4 ft. dist., with scribe marks S17 visible on partially healed decayed blaze fallen off the tree.

and a new bearing tree

A white fir, 11 ins. diam., bears N. 78 1/4° W., 15.1 ft. dist., mkd. 1/4 S8 BT.

Add collar of stone to the cor. to stabilize the monument.

Corner is located on a steep N. slope, W., 60 ft. from a drainage, course N. 45° W., and W., 510 ft. of a ridge, extending N. 40° E. and S. 20° W.

The SW. cor. of Donation Land Claim No. 46, on the N. bdy. of Donation Land Claim No. 51, in sec. 17, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
S 17 | C 46  
———  
C 51  
1963

from which the remains of the bearing trees mkd. by Frear and reported by Brooks and Jelley

A decayed fir stump, size indeterminate, bears S. 79 1/4° W., 6.6 ft. dist., no marks visible.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A roothole bears N. 9° W., 3.3 ft. dist., alongside of which is a down fir, 28 ins. diam., no marks visible.

and the bearing trees mkd. by Brooks and Jelley

An oak, 16 ins. diam., bears N. 7° E., 75.2 ft. dist., with a healed blaze.

A white fir, 37 ins. diam., bears S. 57° E., 27.1 ft. dist., with a healed blaze.

A fir, 26 ins. diam., bears N. 50° W., 51.5 ft. dist., no marks visible.

Corner is located on a spur ridge, slopes E.

A point established on the W. bdy. of Donation Land Claim No. 46, in sec. 17, by Shaner, in 1996, and is accepted as a witness point for the W. bdy. of Donation Land Claim No. 46; monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. SHANER ENGR RLS 430, from which the bearing trees mkd. by Shaner

A maple, the smallest and southwesterly of a clump of three, 19 ins. diam., bears N. 31° E., 23.6 ft. dist., with scribe marks PC BT visible on bark.

A fir, 61 ins. diam., bears S. 73 3/4° W., 27.5 ft. dist., with scribe marks PC BT visible on bark.

A steel fence post is alongside the cor.

Corner is located on a NE. slope, and S., 105 ft. from a creek, 3 ft. wide, course S. 55° E.

The NW. cor. of Donation Land Claim No. 46, in sec. 17, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
S 17 | C 46  
1963

from which the remains of the original bearing trees

A decayed fir stump, 48 ins. diam., bears N. 67° E., 55.4 ft. dist., with a healed blaze.

A roothole bears S. 70° E., 100.3 ft. dist., alongside of which is a down decayed fir, size indeterminate, no marks visible.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

from which the remains of a bearing tree mkd. by Frear and reported by Brooks and Jelley

A decayed fir stump, size indeterminate, bears S. 57° E., 29.0 ft. dist., no marks visible. (Record, down fir.)

and the bearing trees mkd. by Brooks and Jelley

A white fir, 34 ins. diam., bears S. 15° E., 44.9 ft. dist., with a healed blaze.

A white fir, 26 ins. diam., bears N. 41° W., 38.9 ft. dist., with a healed blaze. Tree falls behind two firs, each 4 ins. diam.

The Frear iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, as reset by Brooks and Jelley, and a steel fence post are alongside the cor.

Corner is located on a broad spur, slopes S. 45° E., in hole cut in decayed fir log, 36 ins. diam., at the NW. cor. of timber, edge bears S. and E., with older fir reproduction to N. and W., and N., 600 ft. from a creek, 2 ft. wide, course S. 80° E.

---

The True Point for the SW. cor. of Donation Land Claim No. 47, on the N. bdy. of Donation Land Claim No. 46, on the line bet. secs. 16 and 17, perpetuated by Frear in 1917, and subsequently perpetuated by Godfrey in 1962-63 by establishing a witness corner to reference the true point monumented by Frear that had been destroyed by a creek, accepted by Brooks and Jelley in 1963-65, determined at record bearing and distance from the witness corner; the true point is located in a natural ditch, 3 ft. deep, 1 ft. wide, course S. 40° E., where it is impractical to establish a permanent monument, from which the remains of the bearing trees mkd. by Frear and reported by Brooks and Jelley

A roothole bears N. 71 1/2° E., 53.5 ft. dist., alongside of which is a down oak, 14 ins. diam., with axe marks visible on open decayed blaze with a woven wire fence grown into the tree.

An oak, 19 ins. diam., bears N. 82° E., 59.4 ft. dist., with a healed blaze.

From this point, the witness corner established by Godfrey and accepted by Brooks and Jelley, bears East, 15.18 ft. dist.; monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T. 22 S., R. 8 W., Willamette Meridian, Oregon

	SURVEYORS		
	T. 22 S.		
COUNTY	W.	DLC	R.
	C.	47	
		S.W.	W.
		15 FT. W.	OFFICE
		TO COR.	
		1962	

from which the remains of the bearing trees mkd. by Godfrey and reported by Brooks and Jelley

A decayed fir stump, size indeterminate, bears S. 71° E., 61.4 ft. dist., no marks visible. (Record, S. 74° E.)

A fir stump, 33 ins. diam., bears S. 78° W., 6.9 ft. dist., with a healed blaze.

and the bearing trees mkd. by Shaner in 1996

A fir, 8 ins. diam., bears N. 22 1/4° E., 21.8 ft. dist., with a healed blaze.

A fir, 12 ins. diam., bears S. 67 3/4° E., 49.6 ft. dist., with a healed blaze.

A steel fence post is alongside the witness corner.

Corner is located on a gentle SE. slope, at the SE. cor. of fir reproduction, edge bears N. and W., with young timber to the S. and E.

The interior NW. cor. of Donation Land Claim No. 47, on the line bet. secs. 9 and 16, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

	T 22 S	R 8 W
	S 9	
	C 47	
	1963	

from which the bearing trees mkd. by Frear and reported by Brooks and Jelley

A fir, 50 ins. diam., bears N. 54 1/4° E., 44.2 ft. dist., with a healed blaze. (Record, dead.) Tree has a broken top and has grown a new one.

A fir, 52 ins. diam., bears N. 79 1/2° W., 18.8 ft. dist., with a healed blaze.

and a bearing tree mkd. by Brooks and Jelley

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A fir, 20 ins. diam., bears S. 23 1/2° W., 27.7 ft. dist., with a healed blaze.

The Frear iron pipe, 1 1/2 ins. diam., firmly set, projecting 1 in. above ground, as reset by Brooks and Jelley, and a steel fencepost are alongside the cor.

Corner is located on a SE. slope, near the toe, and S., 340 ft. of a spur ridge, slopes E., and S., 555 ft. from a creek, 2 ft. wide, course S. 65° E.

---

The N-NW cor. of Donation Land Claim No. 47, in sec. 9, perpetuated by Frear in 1917, remonumented by Brooks and Jelley in 1963-65, found disturbed and reset by the Douglas County Surveyor's Office in 1970 and further perpetuated by the Douglas County Surveyor's Office in 1991; monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

## DOUGLAS COUNTY SURVEYORS OFFICE

T 22 S R 8 W

S 9	C 47
1991	

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears S. 7° E., 69.3 ft. dist., no marks visible.

A double fir, 49 ins. diam., bears S. 75° W., 11.9 ft. dist., with a healed blaze and axe marks X at breast height.

and the remains of a bearing tree mkd. by Frear and reported by Brooks and Jelley

A decayed fir stump, size indeterminate, bears N. 40° W., 9.9 ft. dist., no marks visible.

and the bearing trees mkd. by the Douglas County Surveyor's Office in 1991

A fir, 11 ins. diam., bears N. 79 3/4° E., 27.8 ft. dist., with a healed blaze.

A fir, 12 ins. diam., bears S. 33 3/4° W., 53.2 ft. dist., with a healed blaze.

The Frear iron pipe, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with bent top, reset by the Douglas County Surveyor's Office in 1991, and a steel fence post are alongside the cor.


Corner is located on a broad spur, slopes S. 45° E., in the NW. cor. of fir reproduction, edge bears S. and E., and S., 10 ft. from an overgrown dirt

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

spur road, 8 ft. wide, extending N. 45° W. and S. 45° E., 20 ft. from the end of the road.

The interior cor. on the S. bdy. of Donation Land Claim No. 49 in sec. 8, perpetuated by Irving in 1941, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
C 49  
S 8  
1963



from which the bearing trees mkd. by Irving in 1941 and reported as marked by Frear in 1935 by Brooks and Jelley

A white oak, 23 ins. diam., bears N. 54° E., 33.7 ft. dist., with a healed blaze.

A maple, 21 ins. diam., bears S. 68 1/2° W., 52.1 ft. dist., with a healed blaze. (Record, S. 72° W.)


The Irving iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, reset Brooks and Jelley, is alongside the cor.

From this corner, a point established by person(s) unknown, and was not utilized for control in this survey, bears S. 33 3/4° E., 11.4 ft. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground.

Corner is located on the right bank of the Umpqua River, 500 ft. wide, course S. 55° W., and SE., 40 ft., from the top of the bank and beginning of bottomlands, and NW., 40 ft., of the edge of bedrock.

The NW. cor. of Donation Land Claim No. 51, in sec. 17, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
S 17 C 51  
1963



from which the remains of the bearing trees mkd. by Frear and reported by Brooks and Jelley

A roothole bears N. 46 1/2° E., 33.3 ft. dist., alongside of which is a down fir, 35 ins. diam., no marks visible.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A decayed fir stump, 24 ins. diam., bears S. 42 1/2° E., 21.1 ft. dist., with a healed blaze.

and the remains of the bearing trees mkd. by Brooks and Jelley

A roothole bears S. 51° E., 38.3 ft. dist., alongside of which is a down decayed double cascara, 24 ins. diam., with a healed blaze.

A fir, 45 ins. diam., bears N. 59° W., 31.7 ft. dist., with a healed blaze.

and a new bearing tree

A white fir, 42 ins. diam., bears S. 80° E., 41.3 ft. dist., mkd. X at breast height BT.

Corner is located on an E. slope.

From this corner, S. 8° 37' 39" W., on the W. bdy. of Claim No. 51, at 633.17 ft. dist., to a point, from which a point established by Haines, in 1966, and was not accepted for control in this survey, bears N. 81° 22' 21" W., 5.39 ft. dist.; monumented with a T-iron, firmly set, projecting 6 ins. above ground. Point is located on an E. slope.

A point established by Frear in 1917, as a point on the W. bdy. of Donation Land Claim No. 51, in sec. 20, accepted by Hains in 1964, and perpetuated by Ware in 1977, and is accepted as a Witness Point on the W. bdy. of Donation Land Claim No. 51; monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
 |  
 WP  
 |  
 WEST  
 |  
 LINE  
 |  
 DLC  
 |  
 51  
 |  
 RPLS 1005 1977

from which a bearing tree mkd. by Frear

An oak, 30 ins. diam., bears S. 69° W., 19.5 ft. dist., no marks visible on large sawed open face.

and a bearing tree mkd. by Ware

A maple, 40 ins. diam., bears N. 22° W., 20.1 ft. dist., no marks visible on a very knobby burl.

A steel fence post is alongside the cor.

Corner is located on a SE. slope, SE., 70 ft. from Henderer Road, asphalt surface, 25 ft. wide, extending N. 35° E. and S. 35° W., and NW., 60 ft. from the left bank of the Umpqua River, 500 ft. wide, course N. 35° E.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

The SW. cor. of Donation Land Claim No. 57, in sec. 9, on the N. bdy. of Donation Land Claim No. 47, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
 S 9 | C 57  
 C 47  
 1963

from which the remains of a bearing tree mkd. by Frear and reported by Brooks and Jelley

A decayed fir stob, size indeterminate, bears N. 14° W., 20.5 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Brooks and Jelley

A maple, 22 ins. diam., bears N. 71° E., 25.7 ft. dist., with a healed blaze.

A fir stump, 16 ins. diam., bears S. 5° E., 37.0 ft. dist., no marks visible.

A fir, 36 ins. diam., bears N. 22° W., 15.8 ft. dist., with a healed blaze.

The Frear iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, reset by Brooks and Jelley, and a steel fence post are alongside the cor.

Corner is located on nearly level ground near the toe of a steep E. slope, and E., 170 ft. from a lightly maintained graveled road, 15 ft. wide, extending N. 15° W. and S.

The W-NW cor. of Donation Land Claim No. 57, in sec. 9, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

T 22 S R 8 W  
 S 9 | C 57  
 1963

from which the remains of an original bearing tree

A decayed fir stump, 59 ins. diam., bears N. 18° E., 82.5 ft. dist., no marks visible. Tree is behind a white fir, 6 ins. diam., 10 ft. dist.

and the remains of a bearing tree mkd. by Frear and reported by Brooks and Jelley

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A leaning decayed stump, 10 ins. diam., bears S. 24 1/2° E., 7.9 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Brooks and Jelley

A fir, 28 ins. diam., bears N. 41 1/2° E., 37.6 ft. dist., with a healed blaze.

A fir stump, 35 ins. diam., bears S. 39° E., 51.5 ft. dist., with a healed blaze.

and a bearing tree mkd. by person(s) unknown and reported by Roberts in 1997

A fir, 29 ins. diam., bears S. 67° E., 24.6 ft. dist., with a healed blaze.

A steel fence post is alongside the cor.

Corner is located on a nearly level bench on a generally SE. slope, and N., 140 ft. from a creek, 1 ft. wide, in a gully, course S. 30° E.

---

The interior NW. cor. of Donation Land Claim No. 57, in sec. 9, perpetuated by Frear in 1917, and remonumented by Brooks and Jelley in 1963-65; monumented with an iron post, 1 in. diam., firmly set, in solid rock, with top flush with the surface of the ground, with brass cap mkd.

T 22 S R 8 W  
S 9 | C 57  
 1963

from which the remains of the bearing trees mkd. by Brooks and Jelley

A fir, 37 ins. diam., bears S. 13 1/2° W., 71.3 ft. dist., with a healed blaze.

A fir, 39 ins. diam., bears N. 44° W., 34.2 ft. dist., with a healed blaze. (Record, 36.3 ft. dist.)

and a bearing tree mkd. by person(s) unknown and reported by Roberts in 1997

A maple, 20 ins. diam., bears S. 71° E., 9.9 ft. dist., with a healed blaze.

A steel fence post is alongside the cor.

Corner is located on an E. slope, near the top.

---

The N-NW cor. of Donation Land Claim No. 57, in sec. 9, on the S. bdy. of Donation Land Claim No. 49, perpetuated by Frear in 1917, and remonumented

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

T	22	S	R	8	W
			C	49	
		S	9		C 57
					1963

from which the remains of a bearing tree mkd. by Frear and reported by Brooks and Jelley

A roothole bears N. 67 1/4° W., 63.4 ft. dist., alongside of which is a down decayed stump, 19 ins. diam., no marks visible.

and the remains of the bearing trees mkd. by Brooks and Jelley

A decayed fir stump, 23 ins. diam., bears S. 45 3/4° E., 35.3 ft. dist., no marks visible. (Record, S. 50° E.)

A roothole bears S. 37 1/2° W., 59.4 ft. dist., alongside of which is a down decayed fir, 20 ins. diam., with no scribe marks visible on opened blaze.

A fir, 31 ins. diam., bears N. 66° W., 35.3 ft. dist., with a healed blaze.

and a bearing tree mkd. by Roberts in 1997

An alder, 10 ins. diam., bears N. 49 1/2° E., 7.2 ft. dist., with scribe marks T22S R8W C49 BT visible on bark and a healed blaze over a washer below the scribe marks.

The Frear iron pipe, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground, reset by Brooks and Jelley, and a steel fence post are alongside the cor.

Corner is located on nearly level land on a generally NE. slope.

The CE 1/16 sec. cor. of sec. 18, established by Roberts in 1980, and is accepted as the corner; monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

PLS	1039
	CE 1/16
S	18 T 22 S
	R 8 W
	1980

from which the bearing trees mkd. by Roberts in 1980

A hemlock, 27 ins. diam., bears S. 14 3/4° W., 34.4 ft. dist., with no scribe marks visible on nearly healed blaze.

## T. 22 S., R. 8 W., Willamette Meridian, Oregon

A fir, 72 ins. diam., bears N. 89 1/2° W., 38.5 ft. dist., with a healed blaze.

An iron rod with International Paper company sign is alongside the cor.

Corner is located on a steep N. slope, and N., 35 ft. from a flat-topped ridge, extending E. and W.

The center 1/4 sec. cor. of sec. 18, established by Rigby in 1931, and perpetuated by Brooks and Jelley in 1963-65; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

C 1/4 S 18  
1963

from which the remains of a bearing tree mkd. by Rigby

A decayed fir stump, 40 ins. diam., bears S. 66° W., 16.5 ft. dist., with remains of a healed blaze.

and the bearing trees mkd. by Brooks and Jelley

A fir, 29 ins. diam., bears S. 16 1/2° E., 59.4 ft. dist., with a healed blaze. Tree is behind a fir, 12 ins. diam., 2 ft. dist., add location tag to the S. side of this tree.

A fir, 31 ins. diam., bears N. 33° W., 98.3 ft. dist., with a healed blaze. (Record and to face, N. 34° W., 97.0 ft. dist.)

Corner is located on knife-edged spur ridge, slopes steeply N. 35° W.

The SE 1/16 sec. cor. of sec. 19, established by Brooks and Peterson in 1965-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

SE 1/16 S 19  
1965

from which the remains of the bearing trees mkd. by Brooks and Peterson

A fir stump, 23 ins. diam., bears S. 85° E., 62.7 ft. dist., with a healed blaze.

A fir, 14 ins. diam., bears S. 17° W., 7.9 ft. dist., with a healed blaze.

and the remains of a bearing tree mkd. by person(s) unknown

A fir, 24 ins. diam., bears N. 36 1/4° W., 37.6 ft. dist., with a healed blaze.

**T. 22 S., R. 8 W., Willamette Meridian, Oregon**

An aluminum fence post is alongside the cor.

Corner is located on a NE. slope, on the NW. cor. of fir reproduction, edge bears S., E., and W., 250 ft. from a creek, 1 ft. wide, course N. 30° W.

---