

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
A PORTION OF
THE SUBDIVISIONAL LINES

TOWNSHIP 29 SOUTH, RANGE 9 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated July 21, 2004, approved July 22, 2004,
which provided for the surveys included under Group No. 2092,
and Assignment Instructions dated September 8, 2004.

Survey commenced September 27, 2004

Survey completed May 19, 2005

T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, Township 29 South, Range 9 West, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855-56, Dennis Hathorn, U.S. Deputy Surveyor, surveyed a portion of the north boundary and subdivisional lines, as shown on the official plat of survey approved July 7, 1856.

In 1875, William S. Chapman, U.S. Deputy Surveyor, surveyed a portion of the north boundary and subdivisional lines, as shown on the official plat of survey approved December 17, 1875.

In 1907, William M. Porter, U.S. Deputy Surveyor, retraced a portion of the subdivisional lines and completed the survey of the subdivisional lines, as shown on the official plat of survey approved March 19, 1909.

In 1966, John M. Jelley, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey, accepted January 23, 1969.

In 1968, Peter A. Peterson, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines, as shown on the official plat of survey, accepted March 12, 1971.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 21, 2004, for Group No. 2092, Oregon.

The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO), version 1.62. The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods", version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.

The directions of the lines refer to the true meridian as determined by a combination of direct solar observations and GPS measurements and carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been

T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET

adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition, the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The following published stations from the National Spatial Reference System Continuously Operating Reference Station (CORS) were used for control: "CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP".

The geographic positions (NAD 1983 (CORS)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above.

The corner of sections 2, 3, 10, and 11:

Latitude: 43° 04' 08.54" N. Longitude: 123° 44' 29.45" W.

The 1/4 section corner of sections 15 and 16:

Latitude: 43° 02' 49.20" N.; Longitude: 123° 45' 41.14" W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

(Restoring the 1855-56 survey by Dennis Hathorn,
the 1875 survey by William S. Chapman, the 1907 survey by
William M. Porter, the 1966 resurvey by John M. Jelley
and the 1968 resurvey by Peter A. Peterson)

Beginning at the 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<div style="text-align: center;"> <p>1/4</p> <p>S 16 S 15</p> <hr style="width: 10%; margin: 0 auto;"/> <p>T29S R9W</p> <p>1968</p> </div> <p>from which the remains of bearing trees mkd. by Peterson</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 57° E., 7.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 9 ins. diam., bears N. 49° W., 10.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 5 ins. diam., bears N. 14° W., 30.8 ft. dist., mkd. X BT.</p> <p>N. 0° 19' 26" E., bet. secs. 15 and 16.</p> <p>Descend broken NW. slope; begin posting and blazing.</p>
2415	Creek 5 ft. wide, course S. 67° W., asc. SW. slope.
2733.90	<p>The original closing cor. of secs. 15 and 16, monumented with the original sandstone stone, 20 x 15 x 8 ins, firmly set, with 4 grooves on S. and 3 grooves on E. faces.</p> <p>At the corner point</p> <p>Drive an iron rebar, 5/8 ins. diam., 30 ins. long, 30 ins. in the ground and bury the original stone inverted alongside the rebar.</p>
2750.20	<p>The closing cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T29S R9W</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S10</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S16 S15</p> <p style="margin-left: 40px;">C C</p> <p>1968</p> </div> <p>from which the remaining bearing tree mkd. by Peterson</p> <p style="padding-left: 40px;">A chinquapin, 9 ins. diam., bears S. 70° E., 54.1 ft. dist., with a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

F E E T

and new bearing trees

A fir, 16 ins. diam., bears S. 45 1/2° E., 11.6 ft. dist.,
mkd. T29S R9W S15 CC BT.

A fir, 17 ins. diam., bears S. 22° W., 9.1 ft. dist., mkd.
T29S R9W S16 CC BT.

From this point, the cor. of secs. 9 and 10 only, bears
N. 89°04' 33 W., 35.70 ft. dist., monumented with an iron post,
2 1/2 ins. diam., firmly set, projecting 6 ins. above ground,
with brass cap mkd.

T29S	R9W
S9	S10
S16	
1968	

from which the remains of bearing trees mkd. by Peterson

A burned, decayed hemlock snag, 31 ins. diam., bears
N. 63° E., 15.2 ft. dist., with scribe marks T29S R9W
S10 BT visible on an open blaze. (Record, fir stump)

A burned, fir snag, 54 ins. diam., bears N. 38° W., 46.2
ft. dist., with scribe marks 9S R9W S9 BT visible on an
open blaze.

and new bearing trees

A fir, 8 ins. diam., bears N. 79 1/2° E., 19.5 ft. dist.,
mkd. T29S R9W S10 BT.

A fir, 9 ins. diam., bears N. 61 1/2° W., 13.1 ft. dist.,
mkd. T29S R9W S9 BT.

From the cor. of secs. 10, 11, 14, and 15, monumented with an
iron post, 1 1/4 ins. diam., firmly set, projecting 20 ins.
above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T29S	R9W
S10	S11
S15	S14
1959	

BLM1966

from which bearing trees mkd. by Porter, reported by Jelley

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>A fir, 48 ins. diam., bears N. 5° E., 34.3 ft. dist., with a healed blaze.</p> <p>A fir, 36 ins. diam., bears S. 45° E., 22.4 ft. dist., with fragmentary scribe marks visible on an opened blaze.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959, filed in the Douglas County Surveyor's Office under C.S. No. 49/100, and reported by Jelley</p> <p>A fir, 22 ins. diam., bears N. 52° E., 12.5 ft. dist., with a healed double blaze.</p> <p>A fir, 16 ins. diam., bears S. 29° W., 3.6 ft. dist., with a healed double blaze.</p> <p>A fir, 12 ins. diam., bears N. 55° W., 14.5 ft. dist., with a healed double blaze.</p>
	<p>N. 89° 06' 12" W., bet. secs. 10 and 15.</p>
	<p>Ascend broken E. and S. slope; begin posting and blazing.</p>
1915	<p>Spur, slopes S. 65° W.; desc. broken SW. slope.</p>
2235	<p>Paved road, 16 ft. wide, bears N. 40° E. and S. 40° W.</p>
2632.29	<p>Point for the 1/4 sec. cor. of sec. 15 only, on the N. bdy. of sec 15.</p> <p>Drive a finned alum. rod, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with alum. cap mkd.</p>
	<p style="text-align: center;">T 29 S R 9 W</p>
	<p style="text-align: center;">1/4 S 15</p>
	<p style="text-align: center;">2005</p>
	<p>from which</p>
	<p>A hemlock, 12 ins. diam., bears S. 58 1/4° E., 5.0 ft. dist., mkd. 1/4 S15 BT.</p>
	<p>A hemlock, 6 ins. diam., bears S. 27 1/2° W., 6.7 ft. dist., mkd. 1/4 S15 BT.</p>
	<p>Deposit a magnet in a white plastic case alongside the alum. rod.</p>
2638.22	<p>The 1/4 sec. cor. of sec. 10 only, on the S. bdy. of sec. 10, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>COUNTY SURVEYORS OFFICE T29S R9W</p> <p>SOUTH 1/4 S10</p> <p>1959</p> <p>from which the remains of a bearing tree mkd. by J.N. Gearhart, Coos County Surveyor, in 1950, filed in the Douglas County Surveyors Office under C.S. No. 40/253, and reported by Peterson as marked by Byron</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears S. 3 1/2° W., 20.5 ft. dist., with no marks visible. (Record, South)</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959, filed in the Douglas County Surveyors Office under C.S. No. 49/100, and reported by Peterson</p> <p style="padding-left: 40px;">A hemlock, 22 ins. diam., bears N. 72 3/4° E., 59.4 ft. dist., with a healed blaze and X mkd. in the bark. (Record, N. 67° E., 58.7 ft.)</p> <p style="padding-left: 40px;">A burned cedar snag, 60 ins. diam., bears N. 62° W., 54.1 ft. dist., with a healed blaze and X mkd. in the bark. (Record, N. 60° W.)</p> <p>and remains of bearing trees mkd. by Wayne L. Rogers, Professional Land Surveyor No. 2137, in 2001, filed in the Douglas County Surveyors Office under Map File No. 136-62</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 61 1/4° E., 8.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fallen fir snag, 7 ins. diam., bears N. 7 3/4° W., 30.7 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 33' 01" W., beginning new measurement.</p> <p>Continue desc. broken SW. slope, posting and blazing</p>
10	Creek, 3 ft. wide, course S. 28° W.; asc. broken S. slope.
525	Spur, slopes south; desc. broken SW. slope.
1470	Ravine, drains S. 5° W.; asc. broken SE. slope.
1615	Spur, slopes S. 5° W.; desc. broken SW. slope.
2626.12	The closing cor. of secs. 15 and 16.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET													
	<p>From the cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p>												
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T29S</td> <td style="text-align: center;">R9W</td> <td></td> </tr> <tr> <td style="text-align: center;">S3</td> <td style="text-align: center;">S2</td> <td></td> </tr> <tr> <td style="text-align: center;">S10</td> <td style="text-align: center;">S11</td> <td style="text-align: center;">BLM1966</td> </tr> <tr> <td colspan="2" style="text-align: center;">1959</td> <td></td> </tr> </table>	T29S	R9W		S3	S2		S10	S11	BLM1966	1959		
T29S	R9W												
S3	S2												
S10	S11	BLM1966											
1959													
	<p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 45° E., 38.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 60° E., 19.1 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959, filed in the Douglas County Surveyor's Office under C.S. No. 49/100, and reported by Jelley</p> <p style="padding-left: 40px;">A hemlock, 17 ins. diam., bears S. 1° W., 22.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears N. 50° W., 5.6 ft. dist., with a healed blaze.</p> <p>S. 89° 09' 13" W., bet. secs. 3 and 10.</p> <p>Ascend broken E. slope; begin posting and blazing.</p>												
920	Dirt road, 12 ft. wide, bears N. 26° E. and S. 22° W.												
990	Ridge, bears N. 20° E. and S. 20° W.; desc. broken SW. slope.												
1343.20	<p>The E 1/16 sec. cor. of secs. 3 and 10, established without authority by Floyd Meyer during a 1978 Bureau of Land Management administrative survey, filed in the Douglas County Surveyors Office, under Map File No. M81-13, subsequently recovered and utilized for the subdivision of section 10 by Wayne L. Rogers, Professional Land Surveyor No. 2137, in 2001, filed in the Douglas County Surveyors Office, Map File No. M136-62A/B, and is accepted as the cor.; monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 7 ins. above ground, with no cap,</p> <p>from which bearing trees mkd. by Meyer</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears N. 5 1/4° E., 14.9 ft. dist., with a healed double blaze.</p>												

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>A hemlock, 11 ins. diam., bears S. 51° W., 18.0 ft. dist., with a healed double blaze.</p> <p>and remains of bearing trees mkd. by person(s) unknown</p> <p>A sawed hemlock stump, 14 ins. diam., bears S. 9° W., 33.5 ft. dist., with a healed blaze and Rex Timber Inc. tag mkd. APPROX N. 09° 45' E. 33.4 FT RP LaFlamme 1977.</p> <p>A fir, 19 ins. diam., bears N. 34° W., 22.8 ft. dist., with a healed blaze and Rex Timber Inc. tag mkd. APPROX S. 33° 15' E. 22.7 FT RP LaFlamme 1977.</p> <p>At the corner point</p> <p>Drive an iron rebar, 30 ins. long, 5/8 in. diam., 25 ins. in the ground, inside the iron pipe, with alum. cap, 2 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>S 3</p> <p>E 1/16 —————</p> <p>S10</p> <p>2005</p> <hr style="width: 30%; margin: 0 auto;"/> </div> <p>S. 89° 10' 25" W., beginning new measurement.</p>
415	Paved road, 16 ft. wide, bears S. 4° E. and N. 4° W.
670	Ravine, drains N. 20° W.; asc. broken NE. slope.
1045	Paved road, 16 ft. wide, bears S. 8° E. and N. 7° W.
1340	Paved road, 10 ft. wide, bears S. 42° E. and N. 47° W.
1342.71	<p>The 1/4 sec. cor. of secs. 3 and 10, reestablished without authority by Floyd Meyer during a 1978 Bureau of Land Management administrative survey, filed in the Douglas County Surveyors Office, under Map File No. M81-13, subsequently recovered and utilized for the subdivision of section 10 by Wayne L. Rogers, Professional Land Surveyor No. 2137, in 2001, filed in the Douglas County Surveyors Office, Map File No. M136-62A/B, and is accepted as the cor.; monumented with a spike and washer, driven flush with surface of paved road, from which new reference monuments</p> <p>An iron rebar, 30 ins. long, 5/8 in. diam., driven 24 ins. in the ground as a reference monument, bears S. 0°29' 02" W., 19.3 ft. dist., with alum. cap, 2 1/2 ins. diam., mkd. RM T29S R9W S10 19.3 FT TO COR 2005, and an arrow pointing to the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>An iron rebar, 30 ins. long, 5/8 in. diam., driven 27 ins. in the ground as a reference monument, bears N. 81°53'10" W., 24.2 ft. dist., with alum. cap, 2 1/2 ins. diam., mkd. RM T29S R9W S3 24.2 FT TO COR 2005, and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89° 08' 56" W., beginning new measurement.</p>
	<p>Continue asc. broken E. slope, posting and blazing.</p>
<p>64.94</p>	<p>The witness cor. to the 1/4 sec. cor. of secs. 3 and 10, established without authority Floyd Meyer during a 1978 Bureau of Land Management administrative survey, filed in the Douglas County Surveyors Office, under Map File No. M81-13, subsequently recovered and utilized for the subdivision of section 10 by Wayne L. Rogers, Professional Land Surveyor No. 2137, in 2001, filed in the Douglas County Surveyors Office, under Map File No. M136-62A/B, and is accepted as the cor.; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 2 ins. above ground, with no cap, from which bearing trees mkd. by Meyers</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears North, 13.1 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 30° W., 29.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set an alum. cap, 3 1/2 ins. diam., on top of the iron pipe, mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>W.C. T29S R9W S 3 1/4 → S10 2005</p> </div>
<p>65</p>	<p>Spur, slopes N. 63° E.; desc. broken SW. slope.</p>
<p>595</p>	<p>Graveled road, 16 ft. wide, bears N. 2° E. and S. 11° E.</p>
<p>1342.53</p>	<p>The W 1/16 sec. cor. of secs 3 and 10, established by Wayne L. Rogers, Professional Land Surveyor No. 2137, in 2001, filed in the Douglas County Surveyors Office, under Map File No. M136-62A/B, and is accepted as the cor.; monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with yellow plastic cap mkd. I E ENG, from which bearing trees mkd. by Rogers</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET																					
	<p>A fir, 17 ins. diam., bears S. 3° W., 39.4 ft. dist., with a healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 58 3/4° W., 16.8 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears N. 49 3/4° W., 35.1 ft. dist., with a healed blaze.</p> <p>A fir, 7 ins. diam., bears N. 1/4° W., 30.6 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set an alum. cap, 3 1/2 ins. diam., on top of the iron rebar, mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto;"> <tr> <td></td> <td style="text-align: center;">S 3</td> <td></td> </tr> <tr> <td style="text-align: center;">W 1/16</td> <td style="text-align: center;">_____</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S10</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">2005</td> <td></td> </tr> </table> <hr style="width: 30%; margin: 10px auto;"/> </div> <p>S. 89° 09' 13" W., beginning new measurement.</p>		S 3		W 1/16	_____			S10			2005									
	S 3																				
W 1/16	_____																				
	S10																				
	2005																				
917.47	Ravine, drains N. 55° W.; asc. broken NE. slope.																				
1342.17	The cor. of secs 3, 4, 9, and 10, monumented with an iron post, 1 3/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.																				
	<table style="margin: auto;"> <tr> <td></td> <td colspan="2" style="text-align: center;">DOUG CO.</td> <td></td> </tr> <tr> <td style="vertical-align: middle;">COOS COUNTY</td> <td style="text-align: center;">T29S</td> <td style="text-align: center;">R9W</td> <td style="vertical-align: middle;">SURVEYOR OFF</td> </tr> <tr> <td></td> <td style="text-align: center;">S4</td> <td style="text-align: center;">S3</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S9</td> <td style="text-align: center;">S10</td> <td></td> </tr> <tr> <td></td> <td colspan="2" style="text-align: center;">1959</td> <td></td> </tr> </table>		DOUG CO.			COOS COUNTY	T29S	R9W	SURVEYOR OFF		S4	S3			S9	S10			1959		
	DOUG CO.																				
COOS COUNTY	T29S	R9W	SURVEYOR OFF																		
	S4	S3																			
	S9	S10																			
	1959																				
	<p>from which the remains of the original bearing trees</p> <p>A sawed, decayed fir stump, 62 ins. diam., bears S. 28 1/2° E., 31.7 ft. dist., with a healed blaze. (Record, S. 25° E.)</p> <p>A cedar, 30 ins. diam., bears S. 58° W., 17.2 ft. dist., with a healed blaze.</p> <p>A decayed fir root crown bears N. 45° W., 4.0 ft. dist., with no marks visible.</p>																				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	and remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1959, filed in the Douglas County Surveyors Office under C.S. No. 49/100, and reported by Peterson
	A roothole bears N. 89° W., 42.2 ft. dist., with fallen, decayed hemlock snag, 29 ins. diam., lying alongside, with a healed blaze.
	and bearing trees mkd. by Peterson
	A hemlock, 25 ins. diam., bears N. 18° E., 23.1 ft. dist., with a healed blaze.
	A hemlock, 21 ins. diam., bears S. 37 1/2° E., 49.5 ft. dist., with a healed blaze.
	and a new bearing tree
	A hemlock, 17 ins. diam., bears N. 10 1/2° W., 42.9 ft. dist., mkd. T29S R9W S4 BT.
	<hr/>
	N. 0° 05' 53" W., bet. secs. 3 and 4.
	Descend broken N. slope; continue posting and blazing.
345	Creek, 3 ft. wide, course N. 85° W.; asc broken SW. slope.
740	Spur, slopes N. 60° W.; desc. broken N. slope.
1125	Ravine, drains N. 65° W.; asc. broken SW. slope.
1495	Graveled road, 12 ft. wide, bears N. 80° E. and S. 85° W.
1560	Spur, slopes N. 85° W.; desc. broken NW. slope.
2155	Creek, 2 ft. wide, course N. 68° W.; asc. broken SW. slope.
2330	Spur, slopes N. 70° W.; desc. NW. slope.
2487.77	The 1/4 sec. cor. of secs. 3 and 4, perpetuated by Claude Kerr, Registered Logging Engineer No. 2125, in 1960, filed in the Douglas County Surveyors Office under C.S. File No. 51/76, and remonumented by the Douglas County Surveyors Office in 1976, filed in the Douglas County Surveyors Office under C.S. File No. 59/8, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET	<p style="text-align: center;">DOUGLAS CO SURVEYOR T29S R9W COR 1/4 S 4 S 3</p> <p style="text-align: center;">1976</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 36° E., 19.1 ft. dist., with scribe marks rescribed by Kerr S30 BT visible on a decayed, partially healed blaze. (Record, N. 41° E.)</p> <p>and remains of a bearing tree mkd. by Kerr</p> <p style="padding-left: 40px;">A hemlock snag, 25 ins. diam., bears S. 55 1/4° W., 43.1 ft. dist., with a healed blaze.</p> <p>and remains of a bearing tree mkd. by the Douglas County Surveyors Office</p> <p style="padding-left: 40px;">A decayed hemlock snag, 20 ins. diam., bears S. 2° W., 17.1 ft. dist., with scribe marks 1/4 S4 CS BT visible on a partially healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S. 46 1/2° W., 45.5 ft. dist., mkd. 1/4 S4 BT.</p> <hr/>
------	--

T. 29 S., R. 9 W., Willamette Meridian, Oregon

FEET

GENERAL DESCRIPTION

The lands included in the foregoing survey are located in mountainous terrain, approx. 4.5 miles northwesterly from the community of Camas Valley, Oregon.

The elevation ranges from approximately 2200 feet above sea level near the corner of sections 10, 11, 14, and 15, to approximately 2700 feet above sea level near the 1/4 section corner of sections 3 and 10.

The area is drained by Wildcat Creek and Deep Creek which flow southeasterly to the Middle Fork of the Coquille River and Rock Creek which flows southwesterly to the Middle Fork of the Coquille River.

Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

Access to the survey was made by graveled roads branching from Signal Tree Road.