

TOWNSHIP 30 SOUTH, RANGE 9 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 3 OF 3

FILED

Date: 12/17/2010 By: JC
 This survey consists of:
 Map: BLMPLAT 2010-1
 Narrative: VOL. 56
 Corner Rpt.: PAGE 22256-8
 DOUGLAS COUNTY
 SURVEYOR

(H) The N 1/16 sec. cor. of secs. 20 and 21, established by Gary T. Smither, Professional Land Surveyor No. 2485, in 2001, filed in the Douglas County Surveyor's Office, under Map No. M136-54, and is accepted as the corner; monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.

T 30 S R 9 W
 N 1/16
 S 20 | S 21
 2001
 LS 2485

from which the bearing trees mkd. by Smither

A fir, 16 ins. diam., bears N. 49 1/4° E., 16.6 ft. dist., with a healed blaze.
 A fir, 30 ins. diam., bears S. 25 1/4° E., 14.9 ft. dist., with a healed blaze.

(I) The cor. of secs. 16, 17, 20, and 21, perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1964, filed in the Douglas County Surveyor's Office, under CS file No. 53/53, subsequently perpetuated by Gary T. Smither, Registered Land Surveyor No. 2485, in 2001, filed in the Douglas County Surveyor's Office, under Map No. M136-54; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 30 S
 S 17 | S 16
 S 20 | S 21
 R 9 W
 1964

from which the remains of the original bearing trees

A cedar, 40 ins. diam., bears S. 37 1/2° W., 19.1 ft. dist., with scribe marks 30 9 visible on partially healed blaze.

A decayed fir stump, size indeterminate, bears N. 55° W., 16.2 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Tracy

A roothole bears N. 54° E., 16.9 ft. dist., alongside of which is a down fir, 8 ins. diam., with scribe marks T30S R9W S16 CS visible on partially healed blaze.

A fir stump, 9 ins. diam., bears S. 80 1/2° E., 13.4 ft. dist., with illegible scribe marks visible on partially healed blaze.
 and the remains of a bearing tree mkd by person(s) unknown

A fir snag, 38 ins. diam., bears S. 18° E., 3.1 ft. dist., with scribe marks S20 BT 378 visible on partially healed blaze.

and the bearing trees mkd. by Smither

A fir, 15 ins. diam., bears N. 15 3/4° E., 20.6 ft. dist., with scribe marks R9W S16 BT visible on partially healed blaze.

A fir, 9 ins. diam., bears N. 86° W., 31.4 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 9 ins. diam., bears S. 64 1/2° E., 28.2 ft. dist., mkd. T30S R9W S21 BT.

D.C.W.

DEPENDENT RESURVEY

(L) The 1/4 sec. cor. of secs. 7 and 18, perpetuated by Bruce A. Shaner, Registered Engineer No. 4906, in 1974, filed in the Douglas County Surveyor's Office, under Map No. M49-54; monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 30 S R 9 W
 S 7
 1/4 S — S 18
 S 18
 1973

from which the remains of the original bearing trees

A fir stump, 36 ins. diam., bears N. 15° E., 32.7 ft. dist., with illegible scribe marks visible on partially healed blaze.

A decayed fir stump, size indeterminate, bears S. 87 3/4° W., 14.7 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Shaner

A fir, 16 ins. diam., bears S. 1 1/2° W., 44.4 ft. dist., with a healed blaze.

A cedar stump, 6 ins. diam., bears N. 22 1/2° W., 18.8 ft. dist., with scribe marks 4 S7 visible on open blaze.

and a new bearing tree

A fir, 15 ins. diam., bears N. 53 1/4° W., 22.2 ft. dist., mkd. 1/4 S7 BT.

(M) The 1/4 sec. cor. of secs. 7 and 8, perpetuated by Jelley in 1962; monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4
 S 7 | S 8
 T 30 S R 9 W
 1962

from which the bearing trees mkd. by Jelley

A cedar, 41 ins. diam., bears N. 50 1/2° E., 63.0 ft. dist., with a healed blaze. (Record, N. 49 1/2° E., 64.7 ft. dist.)

A fir, 30 ins. diam., bears S. 40 3/4° W., 65.9 ft. dist., with a healed blaze. (Record, S. 40° W., 66.7 ft. dist.)

UNITED STATES DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

Portland, Oregon

This plat, which constitutes the entire record of this survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

John F. Guernsey, Acting

Chief Cadastral Surveyor of Oregon

September 27, 2010
 Date

THERE ARE NO LINE NOTES TO GO WITH THIS RETRACEMENT -
 ALL OF THE AVAILABLE INFORMATION IS ON THIS PLAT