7464

ORIGINAL

22264

FILED
Date: 4/25/2011 By: JC
This survey consists of:
Map: T21-8 2011-01; 2011-02; 2011-03
~~Narrative~~: VOL 56
~~Corner Rpt~~: 22263-22265

DOUGLAS COUNTY SURVEYOR

TOWNSHIP 21 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 3

DEPENDENT RESURVEY AND SUBDIVISION OF SECTION 4

(A) The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, utilized by Tillman in 1950, rehabilitated by Glenn, et al., in 1967, and by Stuntzner, PE No. 6245, in 1968; monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.

T 20 S R 8 W
S 33 | S 34
S 4 | S 3
T 21 S
1945

from which the remains of the original bearing trees

A burned decayed fir stump, size indeterminate, bears S. 44 3/4° E., 23.8 ft. dist., no marks visible.

The remains of a fir stump, size indeterminate, bears S. 24 1/2° W., 16.5 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Price and Rigby

A burned decayed fir stump, 25 ins. diam., bears S. 70° W., 28.4 ft. dist., no marks visible.

A burned decayed fir stump, 25 ins. diam., bears N. 61° W., 39.6 ft. dist., with scribe marks 3 BT and other illegible scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Glenn, et al.

The remains of a fir stump, size indeterminate, bears N. 4° E., 31.7 ft. dist., no marks visible. (Record, N. 11° E.)

and the remains of the bearing trees mkd. by Stuntzner, PE No. 6245

A decayed fir stump, 26 ins. diam., bears N. 37 3/4° E., 50.0 ft. dist., no marks visible.

A decayed fir stump, 47 ins. diam., bears S. 46 1/2° E., 88.9 ft. dist., with scribe marks S3 R8W visible on bark.

and new bearing trees

A fir, 11 ins. diam., bears N. 49° E., 54.4 ft. dist., mkd. T20S R8W S34 BT.

A fir, 14 ins. diam., bears S. 13 1/2° E., 15.0 ft. dist., mkd. T21S R8W S3 BT.

A fir, 13 ins. diam., bears S. 44 1/4° W., 26.3 ft. dist., mkd. T21S R8W S4 BT.

A fir, 9 ins. diam., bears N. 66° W., 24.4 ft. dist., mkd. T20S R8W S33 BT.

A steel fence post with a BLM bearing tree tag is alongside the cor.

Corner is located in young timber, on the W. edge near the S. end of a strip of land with no timber and dense undergrowth, 50 ft. wide, bears N.

(B) Point for the E 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

E 1/16 S 33 / S 4
2009

from which

A fir, 15 ins. diam., bears S. 26° W., 1.5 ft. dist., mkd. E1/16 S4 BT.

A fir, 10 ins. diam., bears N. 42 1/2° W., 12.3 ft. dist., mkd. E1/16 S33 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located in the root, 6 ins. diam., of the SW. bearing tree, at the bottom of descent of a S. facing slope.

(C) The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, rehabilitated by Glenn, et al., in 1967, and by Graham in 2005; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

1/4 S 33 / S 4
1945

from which the remains of the bearing trees mkd. by Price and Rigby

A decayed burned fir snag, 62 ins. diam., bears N. 18 3/4° E., 36.3 ft. dist., no marks visible.

A burned fir stump, 62 ins. diam., bears S. 43 1/2° W., 66.0 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Glenn, et al.

An alder root collar, 33 ins. diam., bears N. 49 1/2° W., 34.0 ft. dist., no marks visible.

and the bearing trees mkd. by Graham

A fir, 13 ins. diam., bears N. 1/4° E., 20.0 ft. dist., with a healed blaze. (Record, N. 1 1/2° W.)

A fir, 13 ins. diam., bears S. 64 3/4° E., 15.8 ft. dist., with a healed blaze. (Record, S. 67° E.)

A steel fence post is alongside the cor.

(D) Point for the W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 33 / S 4
2009

from which

A fir, 13 ins. diam., bears S. 41° W., 16.0 ft. dist., mkd. W 1/16 S4 BT.

A fir, 14 ins. diam., bears N. 5° W., 17.7 ft. dist., mkd. W 1/16 S33 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located N., 130 ft. from a spur, slopes E.

(E) The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, by Glenn, et. al., in 1967; and rehabilitated by Graham in 2005; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

T 20 S R 8 W
S 32 | S 33
S 5 | S 4
T 21 S
1967

from which the remains of an original bearing tree

A roothole bears S. 62° W., 4.0 ft. dist.

and the remains of a bearing tree mkd. by Price and Rigby

A burned fir snag, 54 ins. diam., bears S. 61° E., 43.6 ft. dist., with scribe marks T21S R8W visible on open blaze.

and the remains of the bearing trees mkd. by Glenn, et al.

A cedar stump, 42 ins. diam., bears N. 1/4° E., 73.3 ft. dist., with scribe marks T20S R8W S33 BT visible on open blaze.

A cedar stump, 57 ins. diam., bears N. 56° W., 114.8 ft. dist., with scribe marks T20S R8W S32 BT visible on open blaze. (Record, stump, 47 ins. diam.)

and the bearing trees mkd. by Graham

A fir, 10 ins. diam., bears S. 82° E., 29.7 ft. dist., with a healed blaze and a Mag Nail on the right side center. (Record, 30.1 ft. dist.)

A fir, 18 ins. diam., bears S. 1/2° W., 14.6 ft. dist., with illegible scribe marks visible on partially healed blaze and a Mag Nail on the right side center.

A fir, 15 ins. diam., bears N. 56 1/2° W., 25.2 ft. dist., with a healed blaze and a Mag Nail on the right side center.

Corner is located S., 50 ft. from a draw, drains S. 75° E.

No suitable bearing trees within limits in sec. 33.

(F) The 1/4 sec. cor. of secs. 3 and 10, reestablished by Lytle, et al., in 1952-54, utilized by Glenn, et al., in 1967, and by Baker, PLS No. 1978, in 1984; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

1/4 S 3 / S 10
1954

from which the remains of the bearing trees mkd. by Lytle, et al.

A fir stump, 36 ins. diam., bears N. 7 3/4° E., 27.1 ft. dist., with a healed blaze at waist height.

A scarred fir, 15 ins. diam., bears S. 20 3/4° W., 19.8 ft. dist., with a healed blaze at knee height and other healed blazes. (Record, S. 22 1/4° W.)

and a reference established by person(s) unknown and reported by Baker, PLS No. 1978

A rusty iron post, 1 1/2 ins. diam., firmly set, projecting 13 ins. above ground, bears S. 40° 17' 52" E., 4.06 ft. dist.

and a new bearing tree

A fir, 12 ins. diam., bears N. 79° E., 36.3 ft. dist., mkd. 1/4 S3 BT.

A steel fence post with a U.S. Forest Service tag and two International Paper Company tags is alongside the cor.

Corner is located at the center of the N. edge of a triangular patch of a dozen mature fir trees in otherwise dense fir reproduction.

(G) The cor. of secs. 3, 4, 9, and 10, remonumented by Price and Rigby in 1945, utilized by Lytle, et al., in 1952-54, and by Glenn, et al., in 1967, rehabilitated by Baker, PLS No. 1978, in 1984, and by Graham in 1999-2000; monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap, oriented W., mkd.

T 21 S R 8 W
S 4 | S 3
S 9 | S 10
1945

from which the remains of the original bearing trees

A decayed fir stump, 37 ins. diam., bears N. 39° E., 14.5 ft. dist., with the bottom of a healed blaze.

A roothole bears S. 70° W., 25.7 ft. dist., alongside of which are decayed fir remains.

A decayed fir stump, 24 ins. diam., bears N. 80° W., 10.6 ft. dist., with scribe marks BT visible on open blaze.

and the remains of a bearing tree mkd. by Price and Rigby

A decayed fir stump, 30 ins. diam., bears S. 69° E., 26.4 ft. dist., with burned remains of a healed blaze.

and the bearing trees mkd. by Graham

A fir, 14 ins. diam., bears N. 70 1/2° E., 15.5 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 29° E., 30.2 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 68° W., 29.8 ft. dist., with a healed blaze.

A fir, 13 ins. diam., bears N. 31 1/2° W., 23.6 ft. dist., with a healed blaze.

A steel fence post with an International Paper Company tag is alongside the cor.

Corner is located on the flat top of a knob, N. 65° W., 25 ft. from the center, and E., 250 ft., from Paradise Creek Road, graveled surface, 15 ft. wide, bearing N. 30° W. and S. 30° E.

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

This plat, which constitutes the entire record of this survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

Mary J. M. Hartel

Chief Cadastral Surveyor of Oregon

February 22, 2011
Date

D.C.W.

OFFICIALLY FILED: 4/25/2011

THERE ARE NO LINE NOTES TO GO WITH THIS RETRACEMENT - ALL OF THE AVAILABLE INFORMATION IS ON THIS PLAT

7464

FILED
Date: 4/25/2011 By: JC
This survey consists of:
Map: T21-8 2011-01; 2011-02; 2011-03
~~Narrative~~: VOL 56
~~Corner Rpt~~: 22263-22265

DOUGLAS COUNTY SURVEYOR

ORIGINAL

TOWNSHIP 21 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 3

DEPENDENT RESURVEY AND SUBDIVISION OF SECTION 4

(A) The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, utilized by Tillman in 1950, rehabilitated by Glenn, et al., in 1967, and by Stuntzner, PE No. 6245, in 1968; monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.

T 20 S R 8 W
S 33 | S 34
S 4 | S 3
T 21 S
1945

from which the remains of the original bearing trees

A burned decayed fir stump, size indeterminate, bears S. 44 3/4° E., 23.8 ft. dist., no marks visible.

The remains of a fir stump, size indeterminate, bears S. 24 1/2° W., 16.5 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Price and Rigby

A burned decayed fir stump, 25 ins. diam., bears S. 70° W., 28.4 ft. dist., no marks visible.

A burned decayed fir stump, 25 ins. diam., bears N. 61° W., 39.6 ft. dist., with scribe marks 3 BT and other illegible scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Glenn, et al.

The remains of a fir stump, size indeterminate, bears N. 4° E., 31.7 ft. dist., no marks visible. (Record, N. 11° E.)

and the remains of the bearing trees mkd. by Stuntzner, PE No. 6245

A decayed fir stump, 26 ins. diam., bears N. 37 3/4° E., 50.0 ft. dist., no marks visible.

A decayed fir stump, 47 ins. diam., bears S. 46 1/2° E., 88.9 ft. dist., with scribe marks S3 R8W visible on bark.

and new bearing trees

A fir, 11 ins. diam., bears N. 49° E., 54.4 ft. dist., mkd. T20S R8W S34 BT.

A fir, 14 ins. diam., bears S. 13 1/2° E., 15.0 ft. dist., mkd. T21S R8W S3 BT.

A fir, 13 ins. diam., bears S. 44 1/4° W., 26.3 ft. dist., mkd. T21S R8W S4 BT.

A fir, 9 ins. diam., bears N. 66° W., 24.4 ft. dist., mkd. T20S R8W S33 BT.

A steel fence post with a BLM bearing tree tag is alongside the cor.

Corner is located in young timber, on the W. edge near the S. end of a strip of land with no timber and dense undergrowth, 50 ft. wide, bears N.

(B) Point for the E 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

E 1/16 S 33 / S 4
2009

from which

A fir, 15 ins. diam., bears S. 26° W., 1.5 ft. dist., mkd. E1/16 S4 BT.

A fir, 10 ins. diam., bears N. 42 1/2° W., 12.3 ft. dist., mkd. E1/16 S33 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located in the root, 6 ins. diam., of the SW. bearing tree, at the bottom of descent of a S. facing slope.

(C) The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, rehabilitated by Glenn, et al., in 1967, and by Graham in 2005; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

1/4 S 33 / S 4
1945

from which the remains of the bearing trees mkd. by Price and Rigby

A decayed burned fir snag, 62 ins. diam., bears N. 18 3/4° E., 36.3 ft. dist., no marks visible.

A burned fir stump, 62 ins. diam., bears S. 43 1/2° W., 66.0 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Glenn, et al.

An alder root collar, 33 ins. diam., bears N. 49 1/2° W., 34.0 ft. dist., no marks visible.

and the bearing trees mkd. by Graham

A fir, 13 ins. diam., bears N. 1/4° E., 20.0 ft. dist., with a healed blaze. (Record, N. 1 1/2° W.)

A fir, 13 ins. diam., bears S. 64 3/4° E., 15.8 ft. dist., with a healed blaze. (Record, S. 67° E.)

A steel fence post is alongside the cor.

(D) Point for the W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 33 / S 4
2009

from which

A fir, 13 ins. diam., bears S. 41° W., 16.0 ft. dist., mkd. W 1/16 S4 BT.

A fir, 14 ins. diam., bears N. 5° W., 17.7 ft. dist., mkd. W 1/16 S33 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located N., 130 ft. from a spur, slopes E.

(E) The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, by Glenn, et. al., in 1967; and rehabilitated by Graham in 2005; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

T 20 S R 8 W
S 32 | S 33
S 5 | S 4
T 21 S
1967

from which the remains of an original bearing tree

A roothole bears S. 62° W., 4.0 ft. dist.

and the remains of a bearing tree mkd. by Price and Rigby

A burned fir snag, 54 ins. diam., bears S. 61° E., 43.6 ft. dist., with scribe marks T21S R8W visible on open blaze.

and the remains of the bearing trees mkd. by Glenn, et al.

A cedar stump, 42 ins. diam., bears N. 1/4° E., 73.3 ft. dist., with scribe marks T20S R8W S33 BT visible on open blaze.

A cedar stump, 57 ins. diam., bears N. 56° W., 114.8 ft. dist., with scribe marks T20S R8W S32 BT visible on open blaze. (Record, stump, 47 ins. diam.)

and the bearing trees mkd. by Graham

A fir, 10 ins. diam., bears S. 82° E., 29.7 ft. dist., with a healed blaze and a Mag Nail on the right side center. (Record, 30.1 ft. dist.)

A fir, 18 ins. diam., bears S. 1/2° W., 14.6 ft. dist., with illegible scribe marks visible on partially healed blaze and a Mag Nail on the right side center.

A fir, 15 ins. diam., bears N. 56 1/2° W., 25.2 ft. dist., with a healed blaze and a Mag Nail on the right side center.

Corner is located S., 50 ft. from a draw, drains S. 75° E.

No suitable bearing trees within limits in sec. 33.

(F) The 1/4 sec. cor. of secs. 3 and 10, reestablished by Lytle, et al., in 1952-54, utilized by Glenn, et al., in 1967, and by Baker, PLS No. 1978, in 1984; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.

1/4 S 3 / S 10
1954

from which the remains of the bearing trees mkd. by Lytle, et al.

A fir stump, 36 ins. diam., bears N. 7 3/4° E., 27.1 ft. dist., with a healed blaze at waist height.

A scarred fir, 15 ins. diam., bears S. 20 3/4° W., 19.8 ft. dist., with a healed blaze at knee height and other healed blazes. (Record, S. 22 1/4° W.)

and a reference established by person(s) unknown and reported by Baker, PLS No. 1978

A rusty iron post, 1 1/2 ins. diam., firmly set, projecting 13 ins. above ground, bears S. 40° 17' 52" E., 4.06 ft. dist.

and a new bearing tree

A fir, 12 ins. diam., bears N. 79° E., 36.3 ft. dist., mkd. 1/4 S3 BT.

A steel fence post with a U.S. Forest Service tag and two International Paper Company tags is alongside the cor.

Corner is located at the center of the N. edge of a triangular patch of a dozen mature fir trees in otherwise dense fir reproduction.

(G) The cor. of secs. 3, 4, 9, and 10, remonumented by Price and Rigby in 1945, utilized by Lytle, et al., in 1952-54, and by Glenn, et al., in 1967, rehabilitated by Baker, PLS No. 1978, in 1984, and by Graham in 1999-2000; monumented with an iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap, oriented W., mkd.

T 21 S R 8 W
S 4 | S 3
S 9 | S 10
1945

from which the remains of the original bearing trees

A decayed fir stump, 37 ins. diam., bears N. 39° E., 14.5 ft. dist., with the bottom of a healed blaze.

A roothole bears S. 70° W., 25.7 ft. dist., alongside of which are decayed fir remains.

A decayed fir stump, 24 ins. diam., bears N. 80° W., 10.6 ft. dist., with scribe marks BT visible on open blaze.

and the remains of a bearing tree mkd. by Price and Rigby

A decayed fir stump, 30 ins. diam., bears S. 69° E., 26.4 ft. dist., with burned remains of a healed blaze.

and the bearing trees mkd. by Graham

A fir, 14 ins. diam., bears N. 70 1/2° E., 15.5 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 29° E., 30.2 ft. dist., with a healed blaze.

A fir, 16 ins. diam., bears S. 68° W., 29.8 ft. dist., with a healed blaze.

A fir, 13 ins. diam., bears N. 31 1/2° W., 23.6 ft. dist., with a healed blaze.

A steel fence post with an International Paper Company tag is alongside the cor.

Corner is located on the flat top of a knob, N. 65° W., 25 ft. from the center, and E., 250 ft., from Paradise Creek Road, graveled surface, 15 ft. wide, bearing N. 30° W. and S. 30° E.

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

This plat, which constitutes the entire record of this survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

Mary J. M. Hartel

Chief Cadastral Surveyor of Oregon

February 22, 2011
Date

D.C.W.

22264

OFFICIALLY FILED: 4/13/2011

THERE ARE NO LINE NOTES TO GO WITH THIS RETRACEMENT - ALL OF THE AVAILABLE INFORMATION IS ON THIS PLAT