

## TOWNSHIP 21 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 3 OF 3

## DEPENDENT RESURVEY AND SUBDIVISION OF SECTION 4

(H) The 1/4 sec. cor. of secs. 4 and 9, remonumented by Price and Rigby in 1945, utilized by Glenn, et al., in 1967, found lying loose and reset by Flause, Deputy Douglas County Surveyor, with the 1945 GLO monument in 1981; monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

RESET  
S 4

1/4 S 9

DCSO  
1981  
1945

from which the remains of the original bearing trees

A roothole bears North, 18.5 ft. dist., alongside of which is a down cedar, 4.5 ins. diam., no marks visible.

A fir, 56 ins. diam., bears S. 10° W., 12.5 ft. dist., with axe marks visible on open decayed blaze.

and the remains of a bearing tree mkd. by Price and Rigby

A roothole bears N. 41° W., 50.2 ft. dist., downhill of which is a fir rootwad, no marks visible.

and the bearing trees mkd. by Flause, Deputy Douglas County Surveyor

A fir, 28 ins. diam., bears N. 51 1/2° W., 37.4 ft. dist., with a heated blaze.

A hemlock, 19 ins. diam., bears N. 22° W., 14.0 ft. dist., with scribe marks 1/4 and other illegible scribe marks visible on bark.

A steel fence post is alongside the cor.

Corner is located W., 40 ft. from Blind Creek, 6 ft. wide, course N., on the W. side of bottom land, 30 ft. wide.

(I) The cor. of secs. 4, 5, 8, and 9, remonumented by Price and Rigby in 1945, and by Glenn, et al., in 1967; monumented with an iron post (Record, fiberglass), 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

T 21 S R 8 W  
S 5 | S 4  
S 8 | S 9  
1967

from which the remains of an original bearing tree

A burned decayed fir stump, size indeterminate, bears N. 57° W., 9.9 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Price and Rigby

A fir snag, 34 ins. diam., bears S. 46 1/2° W., 63.4 ft. dist., with scribe marks T21S R8W S8 BT visible on open blaze.

and a bearing object mkd. by Glenn and Jelley

A sandstone outcrop bears S. 27° E., 95.4 ft. dist., no marks visible on flaking surface. (Record, S. 28° E., 105.6 ft. dist.)

and new bearing trees

A fir, 17 ins. diam., bears N. 17 1/2° E., 9.4 ft. dist., mkd. T21S R8W S4 BT.

A fir, 7 ins. diam., bears S. 17° E., 1.9 ft. dist., mkd. X at breast height BT.

A fir, 8 ins. diam., bears S. 69 3/4° W., 12.8 ft. dist., mkd. T21S R8W S8 BT.

A fir, 11 ins. diam., bears N. 67 1/2° W., 13.8 ft. dist., mkd. T21S R8W S5 BT.

A steel fence post is 3 ft. downhill from the cor.

Corner is located on a steep E. slope, W., 50 ft. from a gully, drains W.

(J) The 1/4 sec. cor. of secs. 4 and 5, remonumented by Price and Rigby in 1945, and by Glenn, et al., in 1967; monumented with an iron post (Record, fiberglass), 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

1/4  
S 5 | S 4  
1967

from which the remains of an original bearing tree

A fir snag, splitting, 73 ins. diam., bears N. 22° E., 19.1 ft. dist., with a heated blaze.

and new bearing trees

A fir, 17 ins. diam., bears N. 77 1/2° E., 17.0 ft. dist., mkd. 1/4 S4 BT.

A fir, 16 ins. diam., bears S. 23 1/2° W., 17.0 ft. dist., mkd. 1/4 S5 BT.

A steel fence post is alongside the cor.

Corner is located W., 460 ft. from Big Creek Road, asphalt surface, 15 ft. wide, bearing S. 80° E. and S. 70° W., and N., 1045 ft. of same road, 20 ft. wide, bearing N. 55° E. and S. 65° W., and N., 1140 ft. from Big Creek, 15 ft. wide, course E., in bottom land 30 ft. wide.

(K) Point for the center 1/4 sec. cor. of sec. 4, at intersection of the N. and S., and E. and W. center lines.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 8 W  
C 1/4 S 4  
2009

from which

A fir, 14 ins. diam., bears N. 12° E., 12.7 ft. dist., mkd. C1/4 S4 BT.

A fir, 9 ins. diam., bears S. 28 3/4° W., 8.0 ft. dist., mkd. X at breast height BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on nearly level ground in young timber with no undergrowth.

(L) The 1/4 sec. cor. of secs. 3 and 4, reestablished by Price and Rigby in 1945, utilized by Glenn, et al., in 1967, and reestablished by Baker, PLS No. 1978, in 1984; monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

1/4  
S 4 | S 3  
1945

from which the remains of the bearing trees mkd. by Price and Rigby

A burned decayed fir stump, 37 ins. diam., bears S. 64 1/2° E., 31.7 ft. dist., no marks visible.

A burned decayed fir stump, size indeterminate, bears N. 47 1/2° W., 23.8 ft. dist., with a heated blaze fallen off stump.

and the remains of the bearing trees mkd. Baker, PLS 1978

A fir snag, 7 ins. diam., bears N. 68° E., 17.9 ft. dist., with scribe marks 1/4 S3 visible on open decayed blaze.

A fir snag, 8 ins. diam., bears N. 63° W., 14.5 ft. dist., with a heated blaze.

and new bearing trees

A fir, 13 ins. diam., bears S. 85° E., 9.0 ft. dist., mkd. 1/4 S3 BT.

A fir, 21 ins. diam., bears S. 55 1/2° W., 9.3 ft. dist., mkd. 1/4 S4 BT.

A steel fence post with a U.S. Forest Service tag is alongside the cor.

Corner is located S., 40 ft. from a sharp spur, 40 ft. wide, nearly level, slopes S. 70° W.

(M) Point for the center W 1/16 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

W 1/16  
C  
S 4  
2009

from which

A fir, 20 ins. diam., bears S. 70° E., 23.2 ft. dist., mkd. CW1/16 S4 BT.

A fir, 19 ins. diam., bears N. 3° W., 10.4 ft. dist., mkd. X at breast height BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located alongside the root wad of two down firs, both 1 1/2 ft. diam., and N., 10 ft., from another down fir, 1 1/2 ft. diam., and E., 115 ft., from a natural drainage ditch, 1 ft. wide, 2 ft. deep, course S. 15° E.

FILED

Date: 4/25/2011 By: JC

This survey consists of:

Map: T21-8 2011-01; 2011-02; 2011-03

Narrative: VOL 56

Corner Rpt: 22263-22265

DOUGLAS COUNTY  
SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Portland, Oregon

This plat, which constitutes the entire record of this survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

Mary A. W. Harts

Chief Cadastral Surveyor of Oregon

February 22, 2011

Date