

TOWNSHIP 29 SOUTH, RANGE 6 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 2

RETRACEMENT

- (A) The cor. of secs. 28, 29, 32, and 33, established by Hurlbert in 1878, perpetuated by Mensch in 1905, subsequently perpetuated by Thielsen and White in 1958, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 29 S R 6 W
S 29 | S 28
S 32 | S 33
1958

from which the remains of an orig. bearing tree

- A fir, 35 ins. diam., bears N. 50° E., 10.6 ft. dist., with no marks visible. (Record 13.9 ft.)

from which the remains of bearing trees mkd. by Mensch, reported by Thielsen and White

- A madrone, 24 ins. diam., bears N. 25° E., 29.0 ft. dist., with no marks visible.

- A madrone, 28 ins. diam., bears S. 26° E., 29.0 ft. dist., with no marks visible on a partially healed blaze.

- A sawed fir stump, size indeterminate, bears S. 62 3/4° W., 42.9 ft. dist., with scribe marks T29S R6W S32 BT visible on an open blaze. (Record S. 66° W., not reported by Thielsen and White)

- A chinquapin, 17 ins. diam., bears N. 46 3/4° W., 36.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record N. 44° W., 35.0 ft.)

and bearing trees mkd. by Thielsen and White

- A cedar, 24 ins. diam., bears N. 64 3/4° E., 40.9 ft. dist., with a healed blaze. (Record, N. 75° E.)

- A fir, 29 ins. diam., bears N. 37 1/2° W., 31.0 ft. dist., with scribe marks T29S R6W S29 BT visible on bark blaze.

and a new bearing tree

- A cedar, 10 ins. diam., bears S. 46 3/4° W., 33.6 ft. dist., mkd. T29S R6W S32 BT.

- (B) The 1/4 sec. cor. of secs. 29 and 32, established by Mensch in 1905, perpetuated by John H. Markham, Jr., Registered Engineer No. 2880, in 1956, filed in the Douglas County Surveyor's Office, C. S. File No. 42/190, subsequently perpetuated by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S R 6 W
S 29
1/4 | S 32
1962

from which the remains of an orig. bearing tree

- A sawed, decayed cedar stump, size indeterminate, bears S. 55° W., 26.4 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by Markham, Jr., Registered Engineer No. 2880

- A fir, 47 ins. diam., bears N. 78 1/4° E., 59.7 ft. dist., with no marks visible on bark blaze.

- A chinquapin, 22 ins. diam., bears S. 48 3/4° E., 15.4 ft. dist., with a healed double blaze.

- A sawed madrone stump, 12 ins. diam., bears S. 26 1/4° W., 32.2 ft. dist., with no marks visible.

- (C) The cor. of secs. 29, 30, 31, and 32, established by Mensch in 1905, perpetuated by John H. Markham, Jr., Registered Engineer No. 2880, in 1956, filed in the Douglas County Surveyor's Office, C. S. File No. 42/190, in 1956, subsequently perpetuated by Rogers in 1980, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, (alongside of which is the orig. basalt stone, 15 x 12 x 8 ins., loosely set, projecting 9 ins. above ground, with 5 notches on SE. edge and 1 notch on SW. edge) with brass cap mkd.

T 29 S R 6 W
S 30 | S 29
S 31 | S 32
1980

from which the remains of the orig. bearing trees

- A sawed, decayed fir stump, 26 ins. diam., bears N. 72° E., 17.8 ft. dist., with no marks visible.

- A decayed fir stump, size indeterminate, bears S. 42° E., 4.6 ft. dist., with no marks visible.

- A sawed fir stump, 5 ft. tall, 12 ins. diam., bears S. 86° W., 7.3 ft. dist., with a healed blaze.

and the remains of bearing trees mkd. by Markham, Jr., Registered Engineer No. 2880, reported by Rogers

- A sawed, decayed madrone stump, size indeterminate, bears S. 12° W., 23.8 ft. dist., with no marks visible.

- A sawed, decayed madrone stump, size indeterminate, bears N. 23° W., 35.0 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by Rogers

- A sawed fir stump, 5 ft. high, 16 ins. diam., bears N. 20 1/2° E., 19.1 ft. dist., with a healed blaze.

- A sawed cedar stump, 6 ft. high, 22 ins. diam., bears S. 29° W., 9.9 ft. dist., with a healed blaze.

- A sawed cedar stump, 6 ft. high, 21 ins. diam., bears N. 73 1/2° W., 16.2 ft. dist., with a healed blaze.

and new bearing trees

- A cedar, 11 ins. diam., bears N. 61 1/4° E., 44.5 ft. dist., mkd. T29S R6W S29 BT.

- A cedar, 10 ins. diam., bears S. 28 3/4° E., 16.0 ft. dist., mkd. T29S R6W S32 BT.

- A cedar, 22 ins. diam., bears S. 54° W., 91.1 ft. dist., mkd. T29S R6W S31 BT.

- A cedar, 10 ins. diam., bears N. 57° W., 48.9 ft. dist., mkd. T29S R6W S30 BT.

Bury the orig. stone alongside the iron post.

- (F) The center W 1/16 sec. cor. of sec. 31, established by Rogers in 1980, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

W 1/16
C | S 31
1980

from which bearing trees mkd. by Rogers

- A fir, 17 ins. diam., bears S. 18 3/4° E., 21.8 ft. dist., with a healed blaze.

- A cedar, 14 ins. diam., bears N. 17° W., 29.4 ft. dist., with a healed blaze.

- (D) The center E 1/16 sec. cor. of sec. 31, established by Rogers in 1980, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

E 1/16
C | S 31
1980

from which bearing trees mkd. by Rogers

- A fir, 14 ins. diam., bears N. 23 1/4° E., 4.3 ft. dist., with a healed blaze.

- A yew snag, 11 ins. diam., bears S. 64° W., 14.9 ft. dist., with scribe marks CE 1/16 S31 BT visible on a partially healed blaze.

and a new bearing tree

- A fir, 19 ins. diam., bears S. 81 3/4° E., 19.1 ft. dist., mkd. X BT.

From this corner, a point established by person(s) unknown bears N. 49° 43' 45" W., 6.53 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 13 ins. above ground, and was not utilized in the course of this survey.

- (E) The center 1/4 sec. cor. of sec. 31, established by Rogers in 1980, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

C | S 31
C
1980

from which the remaining bearing tree mkd. by Rogers

- A fir, 14 ins. diam., bears S. 30 1/4° E., 23.4 ft. dist., with a healed blaze.

and a new accessory

- A rebar, 30 ins. long, 5/8 in. diam., driven 28 ins. in the ground for a reference monument, bears N. 40° 11' 46" E., 15.06 ft. dist. with an alum. cap mkd. RM C1/4 S31 I5.1 FT TO COR and an arrow pointing to the corner.

From this corner, a point established by person(s) unknown bears S. 21° 47' 16" W., 2.98 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, and was not utilized in the course of this survey.

FILED

Date: 5/17/2011 By: JC

This survey consists of:

Map: T29S R6W 2011

Narrative: VOL 56

Corrctd Rpt: PGS 22275-76

DOUGLAS COUNTY
SURVEYORUNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The retracement represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

John P. Remonath, Acting

Chief Cadastral Surveyor of Oregon

March 2, 2011
Date