

TOWNSHIP 24 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 3

DEPENDENT RESURVEY

(A) The cor. of secs 25, 30, 31 and 36, on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1956 and 1960, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 7002000, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS T24S RBW 25 | 30 | 7W SEC 36 | 31 OFFICE 1956

from which the remaining orig. bearing trees

A fir, 59 ins. diam., bears N. 15° E., 89.1 ft. dist., with a healed blaze. A burnt, decayed fir snag, size indeterminate, bears S. 75° E., 83.8 ft. dist., with no marks visible. A fir, 73 ins. diam., bears N. 85° W., 28.4 ft. dist., with a healed blaze and marks DN visible in the bark. (Record, 132.0 ft.)

and bearing trees mkd. by the Douglas County Surveyors Office in 1960

A double trunk madrone, 37 ins. diam., bears S. 17° E., 10.6 ft. dist., with a healed double blaze. A fir, 37 ins. diam., bears S. 8 1/4° W., 58.2 ft. dist., with a healed double blaze. and bearing tree mkd. by person(s) unknown

A fir, 50 ins. diam., bears N. 13 3/4° W., 10.9 ft. dist., with mark X visible in the bark.

(B) The 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., determined at record bearing and dist. from the remains of the orig. bearing trees

A saved fir stump, 48 ins. diam., bears S. 2° E., 79.2 ft. dist., with scribe marks BT visible on opened blaze. A rosethe bears N. 70° W., 17.8 ft. dist., which follows fir trunk 49 ins. diam. lying alongside. Fragmentary scribe marks visible on bark blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T 24 S R 8 W 7 W 1/4 S 25 | S 30 OFFICE 2005

from which

A fir, 14 ins. diam., bears S. 87 1/2° E., 18.0 ft. dist., mkd. 1/4 S30 BT.

A fir, 16 ins. diam., bears S. 33° W., 23.4 ft. dist., mkd. 1/4 S25 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

(C) The cor. of secs 19, 24, 25 and 30, on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1956, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 7003000, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS T24S R 24 | S19 R 8 SEC 25 | S30 W OFFICE 1956

from which the remains of bearing trees mkd. by Chandler in 1894

A maple, 33 ins. diam., bears N. 14 3/4° E., 45.8 ft. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, N. 17° E., 49.5 ft., rescribed by the Douglas County Surveyors Office in 1958.)

A maple, 22 ins. diam., bears S. 84 3/4° W., 37.6 ft. dist., with no marks visible. (Record, S. 88° W.)

A decayed fir stump, size indeterminate, bears N. 5° W., 45.3 ft. dist., with fragmentary scribe marks visible on blaze face lying alongside. (Record, 92.1 ft.)

and accessories mkd. by the Douglas County Surveyors Office

A chisel mark "x" on a vertical rock face, 5 ft. above ground, bears S. 48° E., 7.9 ft. dist., with chisel marks 80 alongside.

A cedar, 15 ins. diam., bears S. 9 1/4° W., 38.5 ft. dist., with a healed double blaze.

A fir, 27 ins. diam., bears N. 83 3/4° W., 61.3 ft. dist., with a healed double blaze.

(D) The 1/4 sec. cor. of secs. 25 and 36, reestablished by Mark F. Smalley, Oregon Professional Land Surveyor No. 23554, in 1999, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 640200, and is accepted as the cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, with alum. cap mkd.

ROSEBURG RESOURCES COMPANY T24S RBW 1/4 SEC 25 S36 1999 L.S.2354

from which bearing trees mkd. by Smalley

A fir, 13 ins. diam., bears N. 60 1/2° E., 28.4 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 20 ins. diam., bears S. 26 1/2° W., 16.6 ft. dist., with a healed blaze.

A fir, 26 ins. diam., bears N. 51 3/4° W., 25.1 ft. dist., with scribe marks 1/4 S visible on a partially healed blaze.

A fir, 17 ins. diam., bears N. 1/2° W., 33.9 ft. dist., with a healed blaze.

(E) The cor. of secs 25, 26, 35 and 36, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS T24S S26 | S25 S35 | S36 OFFICE 1958

from which the remaining orig. bearing trees

A fir, 41 ins. diam., bears N. 85° E., 35.0 ft. dist., with a healed blaze.

A fir, 38 ins. diam., bears S. 80° E., 27.7 ft. dist., with a healed blaze.

A decayed fir stump, size indeterminate, bears N. 73° W., 25.1 ft. dist., with no marks visible.

and bearing trees mkd. by the Douglas County Surveyors Office in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 600200, reported by Bedell

A cedar, 27 ins. diam., bears N. 73 1/2° E., 42.9 ft. dist., with a healed double blaze. (Record, N. 75° E.)

A fir, 20 ins. diam., bears S. 5° E., 18.8 ft. dist., with a healed double blaze.

A fir, 15 ins. diam., bears West, 19.8 ft. dist., with a healed double blaze.

A hemlock, 22 ins. diam., bears N. 72° W., 27.4 ft. dist., with a healed double blaze.

and bearing tree mkd. by person(s) unknown

A fir, 21 ins. diam., bears N. 44 1/4° E., 28.0 ft. dist., with a healed blaze.

(F) Point for the 1/4 sec. cor. of secs 25 and 26 at proportionate dist.; there is no remaining evidence of the orig. cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T24S RBW 1/4 SEC 25 S26 | S25 2005

from which

A fir, 18 ins. diam., bears N. 5 1/2° E., 30.4 ft. dist., mkd. 1/4 S25 BT.

A hemlock, 17 ins. diam., bears S. 57 1/2° W., 17.4 ft. dist., mkd. 1/4 S26 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

FILED

Date: 7/18/2011 By: JC This survey consists of: Map: VOL. 56 PAGES Narrative: 22310-22312

THIS RECORD IS THE DEPENDENT RESURVEY OF THE DOUGLAS COUNTY SURVEYOR

OFFICIALLY FILED: 6/8/11

THIS PLAT REPRESENTS THE ENTIRE RECORD OF THE DEPENDENT RESURVEY

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Portland, Oregon

This plat, which constitutes the entire record of this survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

John P. Parnsworth, Acting Chief Cadastral Surveyor of Oregon

April 8, 2011 Date