

TOWNSHIP 24 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

DEPENDENT RESURVEY

(G) The cor. of secs. 23, 24, 25 and 26, remonumented by the Douglas County Surveyors Office in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 600300, monumented with an iron post, 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS
T24S R8W
S23 | S24
S26 | S25
R8W
OFFICE 1958

from which the remains of bearing trees mkd. by Chandler

A sowed fir stump, 55 ins. diam., bears N. 35° E., 28.5 ft. dist., with a heeled blaze. (Record, 32.3 ft.)

A fir, 69 ins. diam., bears S. 45° E., 22.9 ft. dist., with a heeled blaze. (Record, 26.4 ft.)

A fir, 37 ins. diam., bears S. 6° W., 28.9 ft. dist., with a heeled blaze. (Record, 35.6 ft.)

A cedar, 33 ins. diam., bears N. 8 1/4° W., 20.5 ft. dist., with a heeled blaze. (Record, N. 11° W., 23.8 ft.)

and new bearing tree

A fir, 22 ins. diam., bears N. 64° E., 61.8 ft. dist., mkd. T24S R8W S24 BT.

(H) The E. 1/16 sec. cor. of secs. 24 and 25, established by Reald L. Rice, Oregon Professional Land Surveyor No. 54633, in 2003, recorded in the Douglas County Surveyors Office, Map File No. M42-47, and is accepted as the cor., monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with alum. cap mkd.

ROSEBURG RESOURCES
E 1/16 S24
S26
S4698LS
COMPANY

from which bearing trees mkd. by Rice

A fir, 17 ins. diam., bears S. 87 1/2° E., 33.7 ft. dist., with scribe marks E 1/16 S25 BT visible on an unhealed blaze.

A fir, 22 ins. diam., bears N. 56 3/4° W., 48.6 ft. dist., with scribe marks E 1/16 S24 BT visible on an unhealed blaze.

(I) The 1/4 sec. cor. of secs. 24 and 25, reestablished by Reald L. Rice, Oregon Professional Land Surveyor No. 54633, in 2003, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 640300, and is accepted as the cor., monumented with an iron rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with alum. cap mkd.

ROSEBURG RESOURCES
T24S R8W
S24
S26
S4633LS
COMPANY

from which bearing trees mkd. by Rice

A fir, 14 ins. diam., bears N. 76 1/2° E., 14.9 ft. dist., with scribe marks 1/4 S24 BT visible on an open blaze.

A fir, 14 ins. diam., bears S. 57 1/2° E., 20.4 ft. dist., with scribe marks S25 BT visible on an open blaze.

A fir, 15 ins. diam., bears S. 65° W., 13.3 ft. dist., with scribe marks 1/4 S25 BT visible on an open blaze.

A fir, 14 ins. diam., bears N. 12.3/4° W., 12.1 ft. dist., with scribe marks 1/4 S24 BT visible on an open blaze.

(J) Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T24S R8W
1/4 S23
S26
2005

from which

A fir, 13 ins. diam., bears N. 47 1/4° E., 24.4 ft. dist., mkd. 1/4 S23 BT.

A fir, 18 ins. diam., bears S. 50 1/2° E., 40.6 ft. dist., mkd. 1/4 S26 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

(K) The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T24S R8W
S22 | S23
S27 | S26
1959

from which the remains of the orig. bearing trees

A decayed fir snag, 52 ins. diam., bears N. 56 1/4° E., 58.7 ft. dist., with a heeled blaze. (Record, N. 55° E.)

A decayed fir stump, size indeterminate, bears S. 20° E., 46.2 ft. dist., with no marks visible.

A decayed fir stump, 61 ins. diam., bears S. 33° W., 73.3 ft. dist., with a heeled blaze. (Record, S. 34 1/2° W., 71.9 ft.)

and remains of bearing trees mkd. by Corbin

A fir, 24 ins. diam., bears N. 32° E., 12.5 ft. dist., with a heeled blaze.

A fir, 20 ins. diam., bears S. 62 1/2° E., 13.8 ft. dist., with a heeled blaze.

A dead fir, 9 ins. diam., bears S. 32° W., 17.2 ft. dist., with a heeled blaze.

and bearing tree mkd. by the Douglas County Surveyors Office in 1966, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 24 S., R. 08 W., Point Identifier No. 500300,

A fir, 22 ins. diam., bears N. 1 1/2° W., 18.8 ft. dist., with a heeled blaze.

and new bearing tree

A fir, 28 ins. diam., bears S. 53 1/4° W., 43.2 ft. dist., mkd. T24S R8W S27 BT.

FILED
Date: 7/18/2011 By: JC
This survey consists of:
Map: VOL. 56 PAGES
Narrative: 22310-22312
Corner Rpt: ENTIRE RECORD OF THE DEPENDENT RESURVEY

DOUGLAS COUNTY SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

This plat, which constitutes the entire record of this survey, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

John P. Farnsworth, Acting
Chief Cadastral Surveyor of Oregon

April 8, 2011
Date