

TOWNSHIP 29 SOUTH, RANGE 4 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 3

RETRACEMENT

FILED Date: 7/18/2011 By: JC. This survey consists of: Map: VOL. 56, PAGES Narrative: 22313-22315 Corner Rpt: ... DOUGLAS COUNTY SURVEYOR

(A) The cor. of secs. 6 and 7, T. 29 S., R. 3 W., on the E. bdy. of the Tp., remonumented by Jelley and Rogers in 1979-80, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.



from which the remains of an original bearing tree A sowed fir stump, 30 ins. diam., bears N. 40° E., 30.4 ft. dist., with no marks visible. and bearing trees mkd. by Jelley and Rogers

A fir, 19 ins. diam., bears N. 31 3/4° E., 67.3 ft. dist., with a healed blaze. A fir, 23 ins. diam., bears S. 29 1/2° E., 38.3 ft. dist., with a healed blaze.

(B) The 1/4 sec. cor. of sec. 1 only, established by Beck in 1964-65, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



from which the remains of bearing trees mkd. by Beck A sowed fir stump, 32 ins. diam., bears S. 48 1/2° W., 26.8 ft. dist., with a healed blaze and fallen trunk lying alongside. (Record S. 52° W., 28.4 ft.) A fir, 18 ins. diam., bears N. 36 1/2° W., 29.0 ft. dist., with a healed blaze. and new bearing tree A fir, 7 ins. diam., bears S. 64° W., 16.0 ft. dist., mkd. 1/4 SI BT.

(C) The 1/4 sec. cor. of sec. 6 only, T. 29 S., R. 3 W., monumented by Beck in 1964-65, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees A sowed fir stump, 26 ins. diam., bears S. 35 1/2° E., 17.2 ft. dist., with scribe marks 1/4 S / BT visible in the bark. A sowed fir stump, 40 ins. diam., bears S. 48 3/4° W., 17.2 ft. dist., with one marks visible.

and bearing trees mkd. by John H. Markham, Jr., Oregon Registered Engineer No. 2880, in 1962, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 04 W., Point Identifier No. 700663, reported by Beck

A decayed fir stump, 21 ins. diam., bears N. 57° E., 34.3 ft. dist., with no marks visible.

A sowed fir stump, 50 ins. diam., bears S. 64° E., 29.7 ft. dist., with fragmentary scribe marks visible in the bark.

and new bearing trees

A fir, 10 ins. diam., bears N. 54° E., 5.5 ft. dist., mkd. 1/4 S6 BT. A fir, 7 ins. diam., bears S. 12° E., 18.3 ft. dist., mkd. 1/4 S6 BT.

(D) The original closing cor. of Tps. 29 S., R. 3 and 4 W., amended by Beck in 1964-65, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees

A sowed fir stump, 43 ins. diam., bears S. 52° E., 40.3 ft. dist., with one marks visible around a healed blaze.

A root hole bears S. 35° W., 22.4 ft. dist., with fallen fir trunk, 32 ins. diam., lying alongside, with no marks visible.

and bearing trees mkd. by Byron in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 04 W., Point Identifier No. 700700, reported by Beck

A cedar, 26 ins. diam., bears S. 30° E., 28.9 ft. dist., with no marks visible.

A cedar, 30 ins. diam., bears S. 72 1/4° W., 54.8 ft. dist., with no marks visible.

(E) The closing cor. of Tps. 29 S., Rs. 3 and 4 W., established by Beck in 1964-65, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Byron in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 4 W., Point Identifier No. 700700, reported by Beck

A cedar, 26 ins. diam., bears S. 25° E., 35.6 ft. dist., with a healed blaze. and bearing tree mkd. by Beck

A fir, 19 ins. diam., bears N. 31 3/4° E., 67.3 ft. dist., with a healed blaze.

A fir, 23 ins. diam., bears S. 29 1/2° E., 38.3 ft. dist., with a healed blaze.

(F) The 1/4 sec. cor. of sec. 1 and 36, on the N. bdy. of the Tp., reestablished by Beck in 1964-65, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which the remains of bearing trees mkd. by Beck

A fir, 19 ins. diam., bears S. 18 1/2° E., 46.3 ft. dist., with a healed blaze. (Record 46.9 ft.)

A cedar snag, 14 ins. diam., bears N. 46 1/2° W., 7.3 ft. dist., with scribe marks 1 / visible on a partially healed blaze.

and new bearing tree

A fir, 12 ins. diam., bears N. 80 3/4° E., 18.8 ft. dist., mkd. 1/4 S36 BT.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Portland, Oregon

The retracement represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

John P. Farnsworth, Acting

Chief Cadastral Surveyor of Oregon

April 6, 2011 Date