

TOWNSHIP 29 SOUTH, RANGE 4 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 3 OF 3

(6) The cor. of secs. 1, 2, 35, and 36 on the N. by, of the Tp. remonumented by James W. Byron, Jr., Douglas County Surveyors Office, in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 04 W., Point Identifier No. 600600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS T285 R S35 | S36 R 4 S2 | S1 W T29S OFFICE 1958

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears S. 53° W., 11.9 ft. dist., with no marks visible.

A decayed fir stump, 19 ins. diam., bears N. 44 1/2° W., 19.8 ft. dist., with scribe marks T28 S3 visible on an opened blaze.

and bearing trees mkd. by Byron, reported by Beck

A cedar stump, 16 ins. diam., bears N. 61 1/2° E., 7.3 ft. dist., with scribe marks S36 T28S R4W CS BT visible on an unhealed double blaze.

A cedar, 23 ins. diam., bears S. 2° E., 17.2 ft. dist., with a healed blaze.

A decayed fir stump, 15 ins. diam., bears S. 80° W., 31.7 ft. dist., with a healed blaze.

A fir, 41 ins. diam., bears N. 3 1/2° W., 15.2 ft. dist., with a healed blaze.

and bearing tree mkd. by Beck

A fir, 16 ins. diam., bears N. 61 1/2° E., 64.7 ft. dist., with a healed blaze.

and new bearing tree

A fir, 7 ins. diam., bears S. 62 1/4° W., 28.0 ft. dist., mkd. T29S R4W S2 BT.

(H) The 1/4 sec. cor. of secs. 1 and 2, remonumented by James W. Byron, Jr., Douglas County Surveyors Office, in 1958, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 04 W., Point Identifier No. 600600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS T29S 1/4 S2 | S1 R4W OFFICE 1958

from which the remains of an original bearing tree

A roothole bears S. 29° E., 27.1 ft. dist., with decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

and bearing trees mkd. by Byron

A cedar, 44 ins. diam., bears N. 5 1/2° E., 20.9 ft. dist., with one mark visible on a partially healed blaze.

A fir, 41 ins. diam., bears S. 33° W., 26.7 ft. dist., with a healed blaze.

(I) The cor. of secs. 1, 2, 11, and 12, perpetuated by John M. Powell, Douglas County Surveyors Office, in 1969, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 04 W., Point Identifier No. 600600, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS T29S R4W OFFICE S2 | S1 S11 | S12 1969

from which the remains of the original bearing trees

A cedar, 22 ins. diam., bears S. 38 1/2° E., 21.4 ft. dist., with a healed blaze. (Record S. 45° E., 19.8 ft.)

A cedar, 30 ins. diam., bears S. 20° W., 18.3 ft. dist., with a healed blaze. (Record 15.8 ft.)

A root hole bears N. 30° W., 29.0 ft. dist., with no trunk remains.

and remains of bearing trees mkd. by Powell

A madrone, 25 ins. diam., bears N. 14 1/2° E., 23.6 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

A madrone stump, 10 ins. diam., bears N. 55 1/4° W., 2.0 ft. dist., with a healed blaze.

and new bearing tree

A fir, 12 ins. diam., bears N. 55 1/4° W., 21.5 ft. dist., mkd. T29S R4W S2 BT.

RETRACEMENT

FILED Date: 7/18/2011 By: JC This survey consists of: Map: VOL. 56, PAGES Narrative: 22313-22315 DOUGLAS COUNTY SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT Portland, Oregon

The retracement represented by this plot, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director John P. Farnsworth, Acting Chief Cadastral Surveyor of Oregon

Date April 6, 2011

THIS PLAT REPRESENTS THE ENTIRE RECORD OF THE DEPENDENT RESURVEY