

TOWNSHIP 30 SOUTH, RANGE 6 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 3

RETRACEMENT AND REHABILITATION

(A) The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 29 S R 6 W
S 5 | S 4
S 5 | S 4
T 30 S R 6 W
1958

from which the remains of bearing trees mkd. by Mensch, reported by Jelley and Rogers

A saved fir stump, 42 ins. diam., bears S. 66° E., 28.4 ft. dist., with fragmentary scribe marks visible on an healed blaze.

A decayed fir snag, 36 ins. diam., bears S. 7° W., 16.5 ft. dist., with no marks visible

and the remains of bearing trees mkd. by Thlesen and White, reported by Jelley and Rogers

A saved cedar stump, 20 ins. diam., bears S. 16 1/4° E., 71.3 ft. dist., with scribe marks 30 S 66W S4 visible on a partially healed blaze.

A saved, decayed fir stump, 46 ins. diam., bears S. 39 1/2° W., 62.0 ft. dist., with no marks visible.

and a bearing tree mkd. by Gary Langlitz, Deputy County Surveyor, in 1974, filed in the Douglas County Surveyor's Office, C.S. File No. 56-43, reported by Jelley and Rogers

A fir, 23 ins. diam., bears N. 48° W., 34.7 ft. dist., with a healed double blaze.

and the remains of bearing trees mkd. by Jelley and Rogers

A fir snag, 13 ins. diam., bears S. 18° E., 34.3 ft. dist., with a healed blaze.

A fir, 11 ins. diam., bears S. 47° W., 18.5 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 15 ins. diam., bears S. 34° E., 49.4 ft. dist., mkd. T30S R6W S4 BT.

(B) The E 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, buried 2 ins. below the surface of the ground, with brass cap mkd.

E 1/16 S 5
T 30 S R 6 W
1958
80

from which bearing trees mkd. by Thlesen and White

A cedar, 27 ins. diam., bears S. 22 1/4° E., 35.3 ft. dist., with a healed blaze. (Record, S. 21 1/2° E.)

A cedar, 21 ins. diam., bears S. 37° W., 149.8 ft. dist., with a healed blaze. (Record, S. 36 1/2° W.)

Corner is located 12.6 ft. S. of a groveled road, 12 ft. wide, bears N. 65° E. and S. 65° W.

(C) The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, 3 1/2 ft. base, 1 ft. high, with brass cap mkd.

T 30 S R 6 W
S 5 | S 4
S 5 | S 4
T 30 S R 6 W
1967

from which the remains of bearing trees mkd. by persons unknown, reported by Roseberry

A saved, decayed fir stump, 60 ins. diam., bears N. 2° E., 110.9 ft. dist., with a healed blaze.

A saved double fir stump, 62 ins. diam., bears S. 5 1/4° E., 261.4 ft. dist., with a healed blaze.

A fir, 45 ins. diam., bears S. 69 1/2° W., 217.8 ft. dist., with scribe marks S 58 visible on an opened blaze.

A saved, decayed fir stump, 54 ins. diam., bears N. E. 3/4° W., 77.2 ft. dist., with a healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears N. 68 1/2° E., 35.0 ft. dist., mkd. T30S R6W S4 BT.

A pine, 21 ins. diam., bears S. 41 3/4° E., 216.5 ft. dist., mkd. T30S R6W S9 BT.

A fir, 5 ins. diam., bears N. 31 1/4° W., 44.6 ft. dist., mkd. T30S R6W S5 BT.

From this cor., a point established by John H. Markham Jr., Oregon Registered Engineer No. 2880, in 1951, of the interference of old rail fences no longer in existence filed in the Douglas County Surveyor's Office, C.S. File No. 40-277, bears N. 6° 30' 00" E., 53.46 ft. dist., alongside of which is an iron pipe, 1 in. diam., lying loose on the ground, and is not utilized in the course of this survey, from which bearing trees mkd. by Markham Jr.

A saved fir stump, 65 ins. diam., bears N. 6 3/4° E., 46.2 ft. dist., with a healed blaze.

A saved fir stump, 34 ins. diam., bears N. 24 1/2° E., 77.2 ft. dist., with a healed blaze.

A fir, 31 ins. diam., bears N. 53° W., 64.7 ft. dist., with a healed double blaze.

Corner is located 120 ft. E. of a ridge top and a groveled road, 10 ft. wide, bears S. 15° E. and N. 25° W.

(D) The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.

1/4
S 5 | S 4
T 30 S R 6 W
1967

from which the remains of an original bearing tree

A rootless bears S. 7° E., 29.7 ft. dist., alongside of which is a fallen oak trunk, 30 ins. diam., with no marks visible on an open blaze.

and the remaining bearing trees mkd. by John H. Markham Jr., Oregon Registered Engineer No. 2880, in 1957, filed in the Douglas County Surveyor's Office, C.S. File No. 42-321, reported by Jelley and Rogers

An oak, 12 ins. diam., bears S. 72 1/2° E., 62.7 ft. dist., with a healed double blaze.

An oak, 13 ins. diam., bears S. 5 3/4° W., 56.4 ft. dist., with a healed blaze.

A decayed fir stump, 17 ins. diam., bears S. 84 3/4° W., 22.1 ft. dist., with no marks visible on a hollow blaze.

and a bearing tree mkd. by James W. Byron, Douglas County Surveyor, in 1962, filed in the Douglas County Surveyor's Office, C.S. File No. 49-139, reported by Jelley and Rogers

A cedar, 29 ins. diam., bears N. 47 1/2° E., 68.6 ft. dist., with a healed blaze.

A fir, 15 ins. diam., bears S. 73 3/4° W., 29.0 ft. dist., with a healed blaze.

(E) The N 1/16 sec. cor. of secs. 4 and 5, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

N 1/16
S 5 | S 4
1980

from which bearing trees mkd. by Jelley and Rogers

A fir, 19 ins. diam., bears S. 78 1/4° E., 4.3 ft. dist., with a healed blaze. (Record S. 5° E.)

A fir, 18 ins. diam., bears N. 43 1/2° W., 8.3 ft. dist., with a healed blaze. (Record N. 67° W.)

A history of surveys pertaining to this retracement and rehabilitation is as follows:

In 1855, Nathaniel Ford, U.S. Deputy Surveyor, surveyed the south boundary, T. 29 S., R. 6 W.

In 1855, Addison R. Flint, U.S. Deputy Surveyor, surveyed the subdivisional lines.

In 1905, Fred Mensch, U.S. Deputy Surveyor, resurveyed a portion of the south boundary and surveyed a portion of the subdivisional lines, T. 29 S., R. 6 W.

In 1958-59, Hans W. Thlesen and C. Albert White, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines, T. 29 S., R. 6 W.

In 1963-64, John M. Jelley and C. Albert White, Cadastral Surveyors, resurveyed a portion of the west boundary and subdivisional lines and subdivided section 7.

In 1967, Lynn M. Roseberry, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1980, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the north boundary and subdivisional lines and subdivided section 5.

FILED
Date: 7/18/2011 By: JC
This survey consists of:
Map: VOL. 56 PAGES
Narrative: 22316-22318
Corner Rpt.: SURVEY RECORDS OF THE
DOUGLAS COUNTY
SURVEYOR

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Portland, Oregon

The retracement and rehabilitation represented by this plat having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

May J. M. Hunt

Chief Cadastral Surveyor of Oregon

April 22, 2011

Date

6/18/11

OFFICIALLY FILED: