

THIS PLAT REPRESENTS THE ENTIRE RECORD OF THE DEPENDENT RESURVEY

OFFICIALLY FILED: 6/18/11

ORIGINAL

TOWNSHIP 30 SOUTH, RANGE 8 WEST, OF THE WILLAMETTE MERIDIAN, OREGON

SHEET 2 OF 2

FILED

Date: 7/18/2011 By: JC
This survey consists of:
Map: VOL 56 PAGES
Narrative: 22315-22320
Corner Rpt: UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT
DOUGLAS COUNTY SURVEYOR

RETRACEMENT

The 1/4 sec. cor. of secs. 33, and 34, remonumented by Vernon R. Tracy, Douglas County Surveyors Office, in 1964, recorded in Douglas County Surveyors Record of Government Corners, Renewed, T. 30 S., R. 8 W., Index No. 45, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 13 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

COUNTY SURVEYORS
T30S 1/4 S33 S34
R8W 1964 OFFICE

from which the remaining original bearing tree
A fir, 36 ins. diam., bears S. 76° W., 14.5 ft. dist., with a healed blaze,

and remaining bearing tree mkd. by Tracy
A fir, 23 ins. diam., bears S. 35 1/4° W., 35.6 ft. dist., with a healed blaze.

and new bearing tree

A fir, 7 ins. diam., bears N. 52 1/4° E., 22.2 ft. dist., mkd. 1/4 S34 BT.

The cor. of secs. 27, 28, 33 and 34, remonumented by James W. Byron, Douglas County Surveyors Office, in 1956, recorded in Douglas County Surveyors Record of Government Corners, Renewed, T. 30 S., R. 8 W., Index No. 12, perpetuated by L.E. Monroon, Douglas County Surveyors Office, in 1976, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 8 W., Index No. 119, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS
T30S R8W
S28 S27 OFFICE 1976
S33 S34

from which the remains of the original bearing trees

A roothole bears N. 4° E., 4.6 ft. dist., with an uprooted saved fir stump, 30 ins. diam., alongside, with no marks visible.

A fir snag, 21 ins. diam., bears S. 6° W., 13.2 ft. dist., with no marks visible.

A roothole bears N. 40° W., 31.0 ft. dist., with an uprooted saved fir stump, 48 ins. diam., alongside, with no marks visible.

and the remains of a bearing tree mkd. by Byron

A decayed fir stump, 14 ins. diam., bears N. 46 3/4° E., 70.6 ft. dist., with a healed blaze.

and bearing trees mkd. by Monroon

A fir, 19 ins. diam., bears S. 8 1/4° W., 30.7 ft. dist., with a healed blaze.

A saved fir stump, 31 ins. diam., bears N. 74 3/4° W., 9.2 ft. dist., with a healed blaze and steel spike driven into the top.

and new bearing trees

A fir, 7 ins. diam., bears N. 54 3/4° E., 14.2 ft. dist., mkd T30S R8W S27 BT.

A fir, 7 ins. diam., bears S. 23 1/2° E., 16.6 ft. dist., mkd T30S R8W S34 BT.

A fir, 6 ins. diam., bears N. 51 3/4° W., 16.0 ft. dist., mkd T30S R8W S28 BT.

The 1/4 sec. cor. of secs. 28 and 33, determined of record dist. from the remains of bearing trees mkd. by Beck and White in 1963-1964

A decayed fir stump, 17 ins. diam., bears S. 75 1/4° E., 68.6 ft. dist., with axe marks visible. (Record, S. 7° E.)

A saved decayed fir stump, 40 ins. diam., bears N. 56 1/2° W., 70.6 ft. dist., with a healed blaze. (Record, N. 54° W.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, with brass cap mkd.

T30S R8W
1/4 S28
S33
2006

from which new bearing trees

A fir, 10 ins. diam., bears S. 81° W., 37.3 ft. dist., mkd 1/4 S33 BT.

A fir, 7 ins. diam., bears N. 4 3/4° W., 26.0 ft. dist., mkd 1/4 S28 BT.

Deposit a magnet in a white plastic case of the base of the stainless steel post.

From this corner, a point established by John M. Powell, Douglas County Surveyors Office in 1968, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 8 W., Index No. 88, bears N. 89°25'03" W., 56.89 ft. dist., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR OFFICE T30S R8W WC 60 EAST TO S28 1/4 S33 1968

from which the remains of bearing trees mkd. by Powell

A tin-capped fir stump, 16 ins. diam., bears S. 27 3/4° W., 25.3 ft. dist., with scribe marks C 1/4 S33 visible on open blaze.

A decayed hemlock stump, size indeterminate, bears N. 63 1/2° W., 17.6 ft. dist., with scribe mark B visible on open decayed blaze.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Portland, Oregon

The retracement represented by this plat, having been correctly executed in accordance with the requirements of law and the regulations of this Bureau, is hereby accepted.

For the Director

Mary J. M. Hunt

Chief Cadastral Surveyor of Oregon

April 22, 2011

Date