

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

TOWNSHIP 20 SOUTH, RANGE 9 WEST,

AND THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

AND THE SUBDIVISION OF SECTION 2,

TOWNSHIP 21 SOUTH, RANGE 9 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Edith M. Forkner, Cadastral Surveyor

Under Special Instructions dated October 15, 2009,
approved October 21, 2009, which provided for the surveys included under
Group No. 2286, and Assignment Instructions dated October 21, 2009.

Survey commenced October 27, 2009

Survey completed June 29, 2010

Tps. 20 and 21 S., R. 9 W., Willamette Meridian, Oregon

The following field notes are those of the dependent resurvey of a portion of the south boundary, Township 20 South, Range 9 West, and the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 2, Township 21 South, Range 9 West, Willamette Meridian, Oregon.

The history of Federal authority surveys pertaining to this survey is as follows:

In 1877, William Thiel, U.S. Deputy Surveyor, surveyed a portion of the south boundary and subdivisional lines of T. 20 S., R. 9 W., as shown on the official plat of survey approved July 3, 1878.

In 1891, William Thiel, U.S. Deputy Surveyor, completed the survey of the south boundary of T. 20 S., R. 9 W., as shown on the official plat of survey approved May 6, 1893.

In 1893, Alonzo Gesner, U.S. Deputy Surveyor, retraced a portion of the south boundary of T. 20 S., R. 9 W., and surveyed the subdivisional lines of T. 21 S., R. 9 W., as shown on the official plat of survey approved September 21, 1896.

In 1953-54, Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, resurveyed the south boundary and a portion of the subdivisional lines of T. 20 S., R. 9 W., and the west boundary of T. 20 S., R. 8 W., as shown on the official plat of survey accepted March 23, 1960.

In 1957, Norman J. McDonald, Cadastral Surveyor, remonumented certain original corner points without survey, as shown in the official field notes approved July 15, 1964.

In 1966-67, Peter A. Peterson, Cadastral Surveyor, resurveyed portions of the north, east, and west boundaries of the township and subdivisional lines, as shown on the official plat of survey accepted February 20, 1970.

In 2006, Edith M. Forkner, Cadastral Surveyor, remonumented certain corner points on the south boundary of T. 20 S., R. 9 W., as shown in the official field notes approved January 15, 2010.

The following local surveys filed in the Douglas County Surveyor's Office are referred to in subsequent corner descriptions and are referenced by the surveyor's last name, official title or Professional Land Surveyor (PLS) No., and year.

Date	Surveyor and PLS No.	Map No.
1971	Douglas County Surveyor	CS 53/66 cor. desc. 500640
1984	Les Roberts PLS1039	M96-26 CS 58/280-6A and -6B
1984	L.E. Monrean Deputy Douglas County Surveyor	CS 62/18 cor. desc. 528700 cor. desc. 568700
1990	Daniel W. Baker PLS1978	M111-29
1997	Mark F. Smalley PLS2354	CS 65/13-9C

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions dated October 15, 2009, for Group No. 2286, Oregon.

Tps. 20 and 21 S., R. 9 W., Willamette Meridian, Oregon

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the corner description field notes are given herein.

The direction of the lines are based on the true meridian as determined by direct solar observation.

An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Each new bearing tree has a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 35 and 36, on the south boundary of T. 20 S., R. 9 W., as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43° 47' 00.15" N. Longitude: 123° 43' 39.38" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The closing cor. of secs. 2 and 3, on the S. bdy. of T. 20 S., R. 9 W., established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

T 20 S R 9 W
S 35

S 3 | S 2
T 21 S | R 9 W
CC
1967

from which the remains of the original bearing trees for the original closing cor., utilized by Peterson to reference this closing corner

- A decayed fir stump, 60 ins. diam., bears S. 13 1/2° E., 40.3 ft. dist., with a healed blaze.
- A decayed fir stump, 52 ins. diam., bears S. 32° W., 58.4 ft. dist., with a healed blaze. (Record, 60.7 ft. dist.)

and new bearing trees

- A fir, 17 ins. diam., bears S. 4 1/4° E., 39.8 ft. dist., mkd. T21S R9W S2 CC BT.
- A fir, 16 ins. diam., bears S. 69 1/4° W., 14.7 ft. dist., mkd. T21S R9W S3 CC BT.

Corner is located on the N. end of a natural bench in a W. slope, improved in the past for use as a road. Upper edge of bench follows the line bet. secs. 2 and 3 for 1000 ft. dist.

From this cor., a fir snag, 3 ft. diam., bears N. 25° W., 20 ft. dist., with a BLM location tag.

From this same cor., the original closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., recovered by Tillman and Gawron in 1953-54 and utilized by Peterson in 1966-67, bears N. 0° 12' 51" W., 8.91 ft. dist.; monumented with a sandstone, 10 x 8 x 7 ins., firmly set, with top flush with the surface of the ground, with marks CC on top, from which the remains of an original bearing tree

- A decayed fir snag, 34 ins. diam., bears N. 4 1/4° E., 19.8 ft. dist., no marks visible.

At the corner point

Set an iron rod, 35 ins. long, 1/2 ins. diam., 35 ins. in the ground, flush with the ground surface and bury the sandstone alongside the iron rod.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of sec. 35 only, on the S. bdy. of T. 20 S., R. 9 W., reestablished by proportionate measurement by Tillman and Gawron in 1953-54, rehabilitated by Peterson in 1966-67, utilized by Roberts, PLS No. 1039, in 1984, and rehabilitated by Monrean, Deputy Douglas County Surveyor, in 1984, and by Forkner in 2006-09; monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.

1/4 S 35

1954

from which the remains of the bearing trees mkd. by Peterson

A decayed fir stump, 75 ins. diam., bears N. 62° E., 79.2 ft. dist., no marks visible.

A decayed maple stump with sprouts, the largest of which is 7 ins. diam., bears N. 58 1/2° W., 25.7 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by person(s) unknown and reported by Roberts, PLS No. 1039

A burned cedar snag, 40 ins. diam., bears S. 35° W., 25.6 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Monrean, Deputy Douglas County Surveyor

A fir, 9 ins. diam., bears N. 71 1/2° E., 7.1 ft. dist., with a healed blaze.

A fir snag, 6 ins. diam., bears N. 21° W., 5.9 ft. dist., with a healed blaze.

and a bearing tree by Forkner

A hemlock, 15 ins. diam., bears N. 80° W., 42.8 ft. dist., with scribe marks 1/4 S35 BT visible on partially healed blaze and a Mag Nail on the right side center.

A steel fence post with USFS tag is alongside the cor.

Corner is located, E., 70 ft. dist., of the top of a knob, on the N. side; W., 205 ft. dist., of a dirt road, 8 ft. wide, extending S. 70° W. and E. for 95 ft. dist. before turning S. 50° E.; and W., 370 ft. dist., of another dirt road, 8 ft. wide, extending N. 15° W. and S., with a tank trap to N. and S.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of sec. 2 only, on the S. bdy. of T. 20 S., R. 9 W., established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top 1 in. below the surface of the ground, with a brass cap mkd.

1/4 S 2
T 21 S R 9 W
1967

from which the remains of the bearing trees mkd. by Peterson

- A roothole bears S. 65° E., 63.4 ft. dist., alongside of which is a down decayed cedar stump, size indeterminate, no marks visible.
- A burned decayed fir stump, 16 ins. diam., bears S. 86 1/2° W., 46.2 ft. dist., no marks visible.

and new bearing trees

- A fir, 15 ins. diam., bears S. 32° E., 20.7 ft. dist., mkd. 1/4 S2 BT. Tree is located behind a fir snag, 1/2 ft. diam., 10 ft. from cor.
- A fir, 11 ins. diam., bears S. 43 3/4° W., 11.8 ft. dist., mkd. X BT.

Corner is located on a steep NE. slope, W., 115 ft. dist., of a creek, damp, 1 ft. wide, course S. 40° E.

22331

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The E 1/16 sec. cor. of sec. 2 only, on the S. bdy. of T., established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.

E 1/16 S 2
1967

from which the remains of a bearing tree mkd. by Peterson

A decayed fir stump, size indeterminate, bears S. 81° W., 39.2 ft. dist., no marks visible. (Record, 40.3 ft. dist.)

and new bearing trees

A pistol-butt alder, 15 ins. diam., bears S. 12 1/2° E., 20.5 ft. dist., mkd. E1/16 S2 BT on bark.

A fir, 17 ins. diam., bears S. 50° W., 43.9 ft. dist., mkd. E1/16 S2 BT.

Corner is located on the inside edge of a flat on a steep W. slope.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The cor. of secs. 35 and 36 only, on the S. bdy. of T. 20 S., R. 9 W., remonumented by Tillman and Gawron in 1953-54, utilized by Peterson in 1966-67, and by Roberts, PLS No. 1039, in 1984, and rehabilitated by Monrean, Deputy Douglas County Surveyor, in 1984; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a brass cap mkd.

T 20 S	R 9 W
S 35	S 36
T 21 S R 9 W	
S 2	
1954	

from which the remains of the original bearing trees

- A root hole with fir remains, size indeterminate, bears N. 81 1/2° E., 153.1 ft. dist., no marks visible.
- A hollow decayed fir stump, 47 ins. diam., bears S. 81 1/2° E., 116.8 ft. dist., no marks visible.

and the remains of the bearing trees mkd. by Tillman and Gawron

- A decayed hemlock pile, size indeterminate, bears N. 53 1/2° E., 21.8 ft. dist., no marks visible. Tree is located behind an alder, 1 ft. diam., 4 ft. from bearing tree.
- A decayed hemlock pile, size indeterminate, bears N. 18° W., 9.2 ft. dist., no marks visible.

and the bearing trees mkd. by Monrean, Deputy Douglas County Surveyor

- A fir, 20 ins. diam., bears N. 83 1/2° E., 22.8 ft. dist., with a healed blaze.
- A fir, 12 ins. diam., bears N. 23 1/2° W., 32.3 ft. dist., with a healed double blaze.

A steel fence post with a USFS tag is alongside the cor.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The original closing cor. of secs. 1 and 2, on the S. bdy. of T. 20 S., R. 9 W., remonumented by Tillman and Gawron in 1953-54, utilized by Peterson in 1966-67, and by Baker, PLS No. 1978, in 1990; monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with a brass cap mkd.

```

T 20 S R 9 W
  S 36
  -----
  S 2 | S 1
T 21 S R 9 W
  1954

```

from which the remains of the original bearing trees

- A decayed fir stump, 60 ins. diam., bears N. 6° E., 45.5 ft. dist., no marks visible and tailhold notch at face.
- A fir, 59 ins. diam., bears S. 77 1/4° E., 37.0 ft. dist., no marks visible and small tailhold notch at face.
- A fir stump, 81 ins. diam., bears S. 9 3/4° W., 101.6 ft. dist., with a healed blaze.

and a new bearing tree

- A fir, 7 ins. diam., bears S. 47° W., 19.6 ft. dist., mkd. X BT.

An aluminum fence post with International Paper Company sign is alongside the cor.

Corner is located on the NE. cor. of older fir reproduction, edge bears S. and W., and W., 10 ft. dist., of a spur, slopes S. 5° E., and W., 95 ft. dist., of bottom of descent, slopes S.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of sec. 36 only, on the S. bdy. of T. 20 S., R. 9 W., remonumented by Tillman and Gawron in 1953-54, utilized by Peterson in 1966-67, and rehabilitated by Forkner in 2006-09; monumented with an iron post, 1 in. diam., firmly set in solid rock, projecting 4 ins. above the surface of the rock, with a brass cap mkd.

1/4 S 36

1954

from which the remains of the bearing trees mkd. by Tillman and Gawron

A decayed fir stump, 31 ins. diam., bears N. $9\ 3/4^\circ$ E., 47.5 ft. dist., with a healed blaze. (Record, 49.1 ft. dist.)

A decayed fir stump, 6 ins. diam., bears N. $70\ 1/2^\circ$ W., 17.2 ft. dist., with a healed blaze. (Record, 18.0 ft. dist.)

and the bearing trees mkd. by Forkner

A maple, 8 ins. diam., bears N. $8\ 1/2^\circ$ E., 46.8 ft. dist., with scribe marks 1/4 S36 BT visible on bark and a Mag Nail right side center. (Record, N. 9° E., 48.5 ft. dist.)

A fir, 11 ins. diam., bears N. $84\ 1/2^\circ$ W., 17.2 ft. dist., with illegible scribe marks visible on mostly healed double blaze and a Mag Nail right side center.

Corner is located E., 20 ft. dist., of a spur, slopes S., and W., 70 ft. dist., of a creek, 2 ft. wide, course S. Rock faces from spur to 100 ft. E. of creek.

22335

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of sec. 1 only, on the S. bdy. of T. 20 S., R. 9 W., established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.

1/4 S 1
1967

from which the remains of the bearing trees mkd. by Peterson

A fir snag, partially uprooted, leaning N, 28 ins. diam., bears S. 49 1/2° E., 25.4 ft. dist., no marks visible. (Record, S. 51° E., 24.1 ft. dist.)

A fir, 37 ins. diam., bears S. 62° W., 47.5 ft. dist., with a healed blaze.

and a new bearing tree

A white fir, 10 ins. diam., bears S. 32 3/4° E., 45.7 ft. dist., mkd. 1/4 S1 BT.

Corner is located on N. edge young second growth, edge bears N. 85° E. and S. 85° W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The closing cor. of Tps. 20 and 21 S., R. 9 W., on the W. bdy. of T. 20 S., R. 8 W., reestablished by proportionate measurement by Tillman and Gawron in 1953-54, and utilized by Peterson in 1966-67; monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

T 20 S		
R 9 W	T 20 S	
S 36	R 8 W	
CC ———		
S 1	S 31	
T 21 S		
1954		

from which the remains of the bearing trees mkd. by Tillman and Gawron

A fir, 40 ins. diam., bears S. $31\ 1/4^\circ$ W., 36.3 ft. dist., with a healed blaze.

A decayed cedar stump, 14 ins. diam., bears N. 65° W., 44.2 ft. dist., with a healed blaze. Stump is partially uprooted.

and a new bearing tree

A white fir, 8 ins. diam., bears N. $51\ 1/2^\circ$ W., 11.4 ft. dist., mkd. T20S R9W S36 CC BT.

A steel fence post is alongside the cor.

Corner is located E., 110 ft. dist., of a creek, 2 ft. wide, course N. 30° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The cor. of secs. 1, 2, 11, and 12, remonumented by Peterson in 1966-67, and rehabilitated by Smalley, PLS No. 2354, in 1997; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top 22 ins. below the surface of the ground, with a brass cap mkd.

T	21	S	R	9	W
	S	2		S	1
	S	11		S	12
	1966				

from which the bearing trees mkd. by Peterson

A fir, 24 ins. diam., bears N. 3° E., 58.7 ft. dist., with a healed blaze.

A fir, 37 ins. diam., bears S. 34° W., 54.8 ft. dist., with a healed blaze.

and the bearing trees mkd. by Smalley, PLS No. 2354

A fir, 10 ins. diam., bears S. 9° E., 20.3 ft. dist., with a healed blaze.

A fir, 7 ins. diam., bears N. 26 1/2° W., 17.9 ft. dist., with a healed blaze.

An aluminum fence post with International Paper Company sign is alongside the cor.

Corner is located in the fill bank of an overgrown graveled road, 6 ft. wide, extending N. 65° E. and S. 80° W., and E., 735 ft. dist., of Scare Creek, 15 ft. wide, course N. 5° W., near W. edge of bottom land, 200 ft. wide.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 1 and 2, remonumented by Peterson in 1966-67, and rehabilitated by Baker, PLS No. 1978, in 1990; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with a brass cap mkd.

1/4
S 2 | S 1
T 21 S R 9 W
1967

from which the remains of the original bearing trees

A decayed fir pile, size indeterminate, bears S. 85° E., 5.9 ft. dist., with scribe marks /4 S visible on detached remains.

A decayed fir pile, size indeterminate, bears S. 67° W., 7.3 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by Peterson

A shattered decayed fir stump, size indeterminate, bears S. 54° E., 15.2 ft. dist., no marks visible.

and the bearing trees mkd. by Baker, PLS No. 1978

A fir, 45 ins. diam., bears S. 15 1/2° E., 30.4 ft. dist., with a healed blaze and nail left side center.

A fir, 18 ins. diam., bears S. 88° W., 17.5 ft. dist., with a healed blaze and nail right side center. A second fir is growing from the same base to the S.

An aluminum fence post with International Paper Company sign is alongside the cor.

Corner is located N., 370 ft. dist., of a creek, 4 ft. wide, course W., on the N edge of bottom land, 20 ft. wide.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The N 1/16 sec. cor. of secs. 1 and 2, established by Peterson in 1966-67, and rehabilitated by Baker, PLS No. 1978, in 1990; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with a brass cap mkd.

N 1/16
S 2 | S 1
1967

from which the remains of a bearing tree mkd. by Peterson

A roothole bears N. 46° E., 11.2 ft. dist., alongside of which is a down fir, 22 ins. diam., with a healed blaze.

and the remains of the bearing trees mkd. by Baker, PLS No. 1978

A fir snag, 21 ins. diam., bears S. 64 3/4° E., 33.3 ft. dist., with a healed blaze.

A fir, 36 ins. diam., bears N. 78 1/2° W., 73.2 ft. dist., with a healed blaze.

and a new bearing tree

A hemlock, 26 ins. diam., bears S. 57 1/2° E., 26.0 ft. dist., mkd. N1/16 S1 BT.

An aluminum fence post with International Paper Company sign is alongside the cor.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/16-80 sec. cor. of secs. 1 and 2, established by Peterson in 1966-67, and utilized by Baker, PLS No. 1978, in 1990; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with a brass cap mkd.

1/16
S 2 | S 1
80
1967

from which the remains of the bearing trees mkd. by Peterson

A fir, 63 ins. diam., bears N. 85° E., 35.0 ft. dist., with a healed blaze.

A decayed fir high stump, 30 ins. diam., bears S. 75° W., 16.5 ft. dist., with a healed blaze on detached pieces of bark. Add scribe marks BT at breast height.

and a new bearing tree

A fir, 16 ins. diam., bears S. 82° W., 12.2 ft. dist., mkd. 1/16-80 S2 BT. Tree leans slightly S.

An aluminum fence post with International Paper Company sign is alongside the cor.

Corner is located S., 115 ft. dist., of a boulder, 30 x 30 x 30 ft.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/16-100 sec. cor. of secs. 1 and 2, established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, tilted N., with top 3 ins. below the surface of the ground, with a brass cap mkd.

1/16
S 2 | S 1
100
1967

from which the remains of a bearing tree mkd. by Peterson

A fir stump, 71 ins. diam., bears S. 21 1/2° W., 46.9 ft. dist., no marks visible.
(Record, S. 27° W.)

and new bearing trees

A cedar, 37 ins. diam., bears S. 58 1/2° E., 36.1 ft. dist., mkd. 1/16-100 S1 BT on root.

A fir, 7 ins. diam., bears S. 77 1/2° W., 30.5 ft. dist., mkd. X BT.

Corner is located N., 130 ft. dist., of creek, 2 ft. wide, course S. 55° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 2 and 11, reestablished by proportionate measurement by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with a brass cap mkd.

S 2
1/4 ———
S 11
T 21 S R 9 W
1967

from which the bearing tree mkd. by Peterson

A fir, 28 ins. diam., bears S. 61° E., 4.6 ft. dist., with a healed blaze.

and a new bearing tree

A fir, 25 ins. diam., bears N. 23° W., 11.9 ft. dist., mkd. 1/4 S2 BT.

Corner is located at the base of a boulder, 3 ft. high, 6 ft. wide.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The W 1/16 sec. cor. of secs. 2 and 11, established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, tilted W., projecting 8 ins. above ground, with a brass cap mkd.

S 2
W 1/16 ———
S 11
1967

from which the remains of the bearing trees mkd. by Peterson

A decayed fir stump, 36 ins. diam., bears S. 52° W., 66.2 ft. dist., no marks visible.
(Record, 68.0 ft. dist.)

A decayed fir stump, 17 ins. diam., bears N. 59° W., 97.7 ft. dist., with the bottom of a decayed healed blaze.

and new bearing trees

A fir, 20 ins. diam., bears S. 12 1/2° W., 30.7 ft. dist., mkd. W1/16 S11 BT.

A fir, 16 ins. diam., bears N. 14° W., 25.4 ft. dist., mkd. W1/16 S2 BT.

Corner is located in the steep cutbank on the E side of a graveled road, 15 ft. wide, extending N. and S.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The cor. of secs. 2, 3, 10, and 11, remonumented by McDonald in 1963, and rehabilitated by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a brass cap mkd.

T 21 S	R 9 W
S 3	S 2
S 10	S 11
1963	

from which the remains of the original bearing trees

- A roothole bears S. 41° E., 26.4 ft. dist., alongside of which is a down fir, 45 ins. diam., with a healed blaze.
- A decayed fir pile, size indeterminate, bears N. 44° W., 27.7 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by McDonald

- A very decayed shattered fir stump, size indeterminate, bears S. 72 1/2° E., 12.5 ft. dist., alongside of which is a down decayed fir, size indeterminate, with remains of a healed blaze on detached remains.

and new bearing trees

- A fir, 13 ins. diam., bears N. 9 1/4° E., 24.9 ft. dist., mkd. T21S R9W S2 BT.
 - A fir, 20 ins. diam., bears S. 60 1/4° E., 59.1 ft. dist., mkd. T21S R9W S11 BT.
 - A fir, 13 ins. diam., bears S. 76° W., 42.3 ft. dist., mkd. T21S R9W S10 BT. Mag Nail on left side center.
 - A fir, 27 ins. diam., bears N. 6 3/4° W., 50.1 ft. dist., mkd. T21S R9W S3 BT.
-

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The S 1/16 sec. cor. of secs. 2 and 3, established by Peterson in 1966-67; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top flush with the surface of the ground, with a brass cap mkd.

S 1/16
S 3 | S 2
1967

from which the remains of a bearing tree mkd. by Peterson

A decayed fir stump, 53 ins. diam., bears N. 65 1/2° W., 106.3 ft. dist., with a healed blaze. (Record, N. 69° W.)

and new bearing trees

A fir, 32 ins. diam., bears S. 68 1/2° E., 27.5 ft. dist., mkd. S1/16 S2 BT.

A fir, 24 ins. diam., bears N. 82° W., 26.9 ft. dist., mkd. S1/16 S3 BT.

Corner is located on N edge of overgrown skid road, 6 ft. wide, extending S. 85° E. and N. 85° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

The 1/4 sec. cor. of secs. 2 and 3, remonumented by McDonald in 1963, utilized by Peterson in 1966-67, and rehabilitated by the Douglas County Surveyor in 1971; monumented with an iron post, 2 1/2 ins. diam., firmly set, with top 2 ins. below the surface of the ground, with a brass cap, oriented NE., mkd.

T 21 S R 9 W
1/4
S 3 | S 2
1963

from which the remains of an original bearing tree

A decayed fir stump, 64 ins. diam., bears N. 20 1/4° W., 60.1 ft. dist., no marks visible.

and the remains of a bearing tree mkd. by the Douglas County Surveyor

A decayed maple stump, size indeterminate, bears S. 78 3/4° E., 38.7 ft. dist., no marks visible.

and new bearing trees

A fir, 20 ins. diam., bears S. 74 1/4° E., 34.0 ft. dist., mkd. 1/4 S2 BT.

A fir, 12 ins. diam., bears S. 85 1/2° W., 73.1 ft. dist., mkd. 1/4 S3 BT.

A steel fence post, broken off, found lying loose NE., 10 ft. dist.

Corner is located on the N. edge of a triangular shaped stand of alder, 150 ft. wide by 150 ft. long, bounded to the SE. by an abandoned graveled road, 10 ft. wide, extending N. 55° E. and S. 75° W., and to the SW. by a graveled road, 12 ft. wide, extending N. 35° W. and S. 10° E.

**Subdivision of Section 2,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

Point for the center 1/4 sec. cor. of sec. 2, at intersection of the N. and S. and the E. and W. center lines.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 21 S R 9 W
C 1/4 S 2
2010

from which

A fir, 12 ins. diam., bears N. 50 3/4° E., 29.0 ft. dist., mkd. C1/4 S2 BT.

A fir, 12 ins. diam., bears S. 63° W., 18.1 ft. dist., mkd. X BT, with Mag Nail left side center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located E., 1 1/2 ft. dist., of a fir, 1 ft. diam., and E., 60 ft. dist., of draw, drains N. 25° W.

From this cor., a point established by person(s) unknown, bears N. 63° 50' 04" W., 3.50 ft. dist., determined at record distances from the faces of the remains of the bearing trees mkd. by person(s) unknown utilizing information documented on a corner card held at the BLM Coos Bay District Office

A burned cedar stump, 42 ins. diam., bears N. 50 3/4° E., 27.2 ft. dist., no marks visible.

A burned fir stump with metal cap, 54 ins. diam., bears S. 14 1/2° W., 12.4 ft. dist., no marks visible.

There is no filed survey or other known record documenting who established this point or how it was established, therefore this point was not utilized for control during this survey.

**Subdivision of Section 2,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

Point for the center W 1/16 sec. cor. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{W 1/16} \\ \text{C} \text{-----} \text{C} \\ \text{S 2} \\ \text{2010} \end{array}$$

from which

A fir, 13 ins. diam., bears N. 86° E., 18.6 ft. dist., mkd. CW1/16 S2 BT.

A fir, 9 ins. diam., bears S. 3 1/4° W., 38.9 ft. dist., mkd. X BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located W., 495 ft. dist., of a spur, 15 ft. high, 35 ft. wide, slopes N. 20° E., between a creek to W., 2 ft. wide, course N. 30° E., and a creek to E., 2 ft. wide, course N.

From this cor., a point established by person(s) unknown, bears N. 41° 55' 56" W., 3.50 ft. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 7 ins. above ground, from which the remains of the bearing trees mkd. by person(s) unknown

A decayed fir stump, 27 ins. diam., bears N. 56 1/4° E., 37.4 ft. dist., no marks visible.

A decayed fir stump, 27 ins. diam., bears S. 1 1/4° W., 13.7 ft. dist., no marks visible.

There is no filed survey or other known record documenting who established this point or how it was established, therefore this point was not utilized for control during this survey.

**Subdivision of Section 2,
T. 20 S., R. 9 W., Willamette Meridian, Oregon**

Point for the SW 1/16 sec. cor. of sec. 2, at its calculated position.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

SW 1/16 S 2
2010

from which

A maple, 21 ins. diam., bears N. 71 1/2° E., 19.8 ft. dist., mkd. SW1/16 S2 BT.

A fir, 20 ins. diam., bears S. 76° W., 28.2 ft. dist., mkd. SW1/16 S2 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located E., 110 ft. dist., of a graveled road, 10 ft. wide, extending N. 40° E. and S. 25° W., and S., 110 ft. dist., of the same road, extending N. 50° E. 100 ft. to a three-way junction and S. 50° W.; also S., 220 ft. dist., of an abandoned dirt road, 8 ft. wide, extending N. 50° W. and S. 75° E. 100 ft. to the same three-way junction.

From this cor., a point established by person(s) unknown, bears S. 44° 17' 03" W., 5.04 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of a bearing tree mkd. by person(s) unknown

A very decayed metal-capped fir stump, 34 ins. diam., bears N. 15 3/4° W., 14.9 ft. dist., no marks visible.

There is no filed survey or other known record documenting who established this point or how it was established, therefore this point was not utilized for control during this survey.
